

1200 WALNUT STREET NEWTON, MASSACHUSETTS 02461-1267

STEPHEN J. BUCHBINDER
ALAN J. SCHLESINGER
LEONARD M. DAVIDSON
HEATHER G. MERRILL
PAUL N. BELL
KRISTINE H.P. HUNG
KATHERINE BRAUCHER ADAMS
AMY C. EGLOFF
FRANKLIN J. SCHWARZER
JONATHAN A. GOLDMAN

TELEPHONE (617) 965-3500 FACSIMILE (617) 965-6824

OF COUNSEL
ROBIN GORENBERG

Email: fschwarzer@sab-law.com

July 25, 2013

BY HAND

Alderman Ted Hess-Mahan Chairman, Land Use Committee Newton Board of Aldermen 1000 Commonwealth Avenue Newton, MA 02459-1449

Re: 20 Burrage Road, Petition #180-13

Dear Chairman Hess-Mahan,

I represent Ron and Diane Sostek, the owners of 41 Alderwood Road, the property that directly abuts and shares a driveway with 20 Burrage Road. At the public hearing on June 11, 2013, my clients expressed serious concerns about the development at 20 Burrage Road in relation to the location of the retaining walls abutting the shared driveway, the problem of snow removal, and the overall condition of the driveway. Because of those concerns, they opposed the petitioner's special permit application at that time.

Since then, my clients and I have met with the developer and members of the Inspectional Services Department in an attempt to reconcile these differences. Through these negotiations, the developer and my clients have agreed to a series of conditions which, if made part of the Board Order would assuage my clients' concerns. These conditions are:

- 1. The existing retaining wall abutting the shared driveway will be moved back so that it will curve around the existing footing under the deck. The outer edge of the retaining wall shall not extend more than 8 feet from the existing foundation wall of the house. A photo is enclosed showing the proposed location of the new retaining wall.
- 2. The location of the existing retaining wall at the bottom of the driveway will likewise be moved back so that it curves around the existing footing under the deck and goes back in a straight line toward the property line. The outer edge of this retaining wall shall not extend further into the driveway than 9 feet from the existing foundation wall. A photo is enclosed showing the proposed location of the new retaining wall.





55 Pend Street Waltham, MA 02454

Phone: (781) 894-8736 Fax: (978) 663-0993

Proposal

New Driveway Construction Remove all existing asphalt Remove any unsuitable base material such as roots, rock, clay ect. Add enusher run gravel to existing gravel so gravel base is 6-8 inches regrade & compact Lay 2 inches of finish asphalt & compact Compact Lay 2 inches of finish asphalt & compact Compact Lay 2 inches of finish asphalt & compact C	Dianc Sospek	
Specifications  Specifications  Total  New Driveway Construction  Remove all existing asphalt  Remove any unsuitable base material such as roots rock, clay ect.  Add crusher run gravel to existing gravel so gravel base is 6-8 inches regrade & compact  Lay 2 inches of finish asphalt & compact  6 Year Warranty Against Cracking & Peeling  Remove any unsuitable base material such as roots, rock, clay ect.  Add erusher run gravel to existing gravel so gravel base is 6-8 inches regrade & compact  1 Dinter solution (Scan)  Remove all existing asphalt  Remove any unsuitable base material such as roots, rock, clay ect.  Add erusher run gravel to existing gravel so gravel base is 6-8 inches regrade & compact  Lay 2 inches of finish asphalt & compact  Sand & emulsion seam with city sidewalk  6 Year Warranty Against Cracking & Peeling	41 Alderwood Rd	Commence of the Comment of the Comme
New Driveway Construction Remove all existing asphalt Remove any unsuitable base material such as roots.rock,clay ect. Add crusher run gravel to existing gravel so gravel base is 6-8 inches regrade & compact Lay 2 inches of binder asphalt & compact Lay 2 inches of linish asphalt & compact Lay 2 inches of finish asphalt & compact Sand & emulsion seam with city sidewalk 6 Year Warranty Against Cracking & Peeling	Newton Ma 02459	[7/11/2013] 2079
New Driveway Construction Remove all existing asphalt Remove any unsuitable base material such as roots.rock, clay ect. Add crusher run gravel to existing gravel so gravel base is 6-8 inches regrade & compact Lay 2 inches of binder asphalt & compact 6 Year Warranty Against Cracking & Peeling  Pearline of Compact Lay 2 inches of binder asphalt & compact Lay 2 inches of finish asphalt & compact Lay 2 inches of finish asphalt & compact Sand & emulsion seam with city sidewalk 6 Year Warranty Against Cracking & Peeling	617-965-3500	
Remove any unsuitable base material such as roots, rock, clay ect.  Add crusher run gravel to existing gravel so gravel base is 6-8 inches regrade & compact Lay 2 inches of finish asphalt & compact (6 Year Warranty Against Cracking & Peeling  Penurha of existing splant (Cracking & Peeling  Penurha of existing splant (Cracking & Peeling  Penurha of existing splant (Cracking & Peeling  Perurha of existing splant (Cracking & Peeling  Remove all existing asphalt Remove all existing asphalt Remove any unsuitable base material such as roots, rock, clay ect. Add crusher run gravel to existing gravel so gravel base is 6-8 inches regrade & compact Lay 2 inches of binder asphalt & compact Lay 2 inches of finish asphalt & compact Sand & emulsion seam with city sidewalk 6 Year Warranty Against Cracking & Peeling	Specifications	Total
The teveling coarse of asphale  New Driveway Construction (Scan)  Remove all existing asphalt  Remove any unsuitable base material such as roots, rock, clay ect.  Add crusher run gravel to existing gravel so gravel base is 6-8 inches regrade & compact  Lay 2 inches of binder asphalt & compact  Lay 2 inches of finish asphalt & compact  Sand & emulsion seam with city sidewalk  6 Year Warranty Against Cracking & Peeling	New Driveway Construction  Remove all existing asphalt  Remove any unsuitable base material such as roots.rock, clay ect.  Add crusher run gravel to existing gravel so gravel base is 6-8 inches regrade & compact  Lay 2 inches of binder asphalt & compact  Lay 2 inches of finish asphalt & compact  Of Year Warranty Against Cracking & Peeling	2,450,00
Remove all existing asphalt Remove any unsuitable base material such as roots, rock, clay ect. Add crusher run gravel to existing gravel so gravel base is 6-8 inches regrade & compact Lay 2 inches of binder asphalt & compact Lay 2 inches of finish asphalt & compact Sand & emulsion seam with city sidewalk 6 Year Warranty Against Cracking & Peeling	Them Bit existing asphalt  by a fevering goarse of asphalt  by B inches of limich asphalt as compact  and A million, sean	2,476,69
Balance due on completion	Remove all existing asphalt Remove any unsuitable base material such as roots,rock,clay ect. Add crusher run gravel to existing gravel so gravel base is 6-8 inches regrade & compact Lay 2 inches of finish asphalt & compact Lay 2 inches of finish asphalt & compact Sand & emulsion seam with city sidewalk	3,925,00
	Balance due on completion	
We propose to finish laker and material computation appared may with above specifications, and subject to the conditions found		

We propose to furnish labor and material -- complete in accordance with above specifications, and subject to the conditions found on this agreement for the total specified on this estimate.

Accepted. The above prices, specifications and conditions are satisfactory and are hereby accepted. You are authorized to do the work as specified. Payment will be made as outlined above.

	Respectfully submitted.	W.R. Walton Contracting, Inc.
		Linda Walton
Ву		