



NOTES

GENERAL CONSTRUCTION NOTES

1. THE 28 DAY COMPRESSIVE STRENGTH OF CONCRETE SHALL BE 4,000 PSI.
2. REINFORCING STEEL SHALL BE ASTM A630 GRADE 60 (60,000).
3. CONCRETE SHALL CONFORM TO STANDARD SPEC. MASS AS SECTION 210.
4. GRANULAR BACKFILL SHALL CONFORM TO STANDARD SPEC. SECTION 210.
5. ALL CONSTRUCTION SHALL BE DONE IN CONFORMANCE TO THE APPLICABLE SPECIFICATIONS FOR HIGHWAY AND BRIDGES.

PREPARED BY:
 HERRICK CONSULTING
 JAMES A. HERRICK, P.E.
 5 EVERGREEN CIRCLE
 LONDONDERRY, NH 03055
 603 434-9900
 NH REG. NO. 41121

PREPARED FOR:
 NITZAN GORODY & ZION YEHOSHUA
 72 NEWTONVILLE AVE.
 NEWTON, MA 02458

PROPERTY ID: 12021 0025C
 MIDDLESEX SOUTH DISTRICT DEEDS
 BOOK: 58883 PAGE: 387

SHEET 1 OF 1

DATE: 8/14/12

