Facility Name: Albemarle Field 'Russell J. Halloran Sports and Recreation Complex' Size (Ac): 24.9 acres Address: 250 Albemarle Road, Newtonville (Adjacent to Day Middle School and Horace Mann Elementary School) Ward: 2 General Facility Notes: Accessible playground area (3-5-yr & 5-12-yr), raised planters & gazebo near Horace-Mann (future Newton Early Childhood); ballfield bleachers, tennis courts, basketball courts, field house on accessible route; Albemarle Rd. sidewalk runs the length of the park; accessible on-street parking near playground and pool; contiguous to wooded Avery Estate (not accessible). Site Furnishings YES Tables & Benches Number of Benches Ther are 27 becnhes. Number of Tables yes There are 5 picnic tables Located adjacent to accessible paths There are 9 benches with backs and arm rests, there are 15 benches with backs and 3 backless Back and Arm Rests Grills Located adjacent to accessible paths no Trash Cans Located adjacent to accessible paths yes 7 bigbelly trash compactor; 7 bigbelly recycling unit; 1trash/1 recycling by field house Picnic Shelters Located adjacent to accessible paths yes Gazebo and 3 picnic tables are located next to playground Notes: Trails & Paths Surface (A=Asphalt, C=Concrete, SD= stone dust, NS= naturally surfaced, B=Boardwalk, BR=Bridge) yes Dimensions (width) Pathway is five feet wide, driveway is eight feet wide. N/A Signage for visually impaired N/A Notes: YES Aquatics - Refer to Harry Gath memorial Pool Play Areas YES Fibar safety surfacing, poured in place surfacing Facility Type (3-5 Yrs,5-12 Yrs) yes Same experience provided to all yes Access Routes Located adjacent to accessible paths yes Enough space between equipment for wheelchair Notes: There is a bubbler at the playground. Game Areas YES Facility Type (RF=Rectangular Fields, BF= Ballfields, BK=Basketball, TN=Tennis, BC=Bocce) 4 RF. 6 BF. 1 BK. 2 TN. 2 BK Standards Access Routes Located adjacent to accessible paths yes Spectator Seating yes There are 4 bleacher seating areas at the ball fields Notes: Athletic fields are irrigated with well water. There is athletic lighting for the football, baseball and softball field. There is a flagpole and scoreboard by Murphy little league. There is a snack shack and three double station bubblers on site. There are six bleacher sets. many of these amenities lack accessible paths N/A N/A N/A YES Boat Docks Fishing Facilities Community Gardens Parking Accessible Spaces **Total Spaces** 10 Spaces 180 Parking Amenities (L=lot, ST=street) L, ST yes Accessible space located closest to accessible entrance Yes Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft N/A Minimum width of 13 ft includes 8 ft space plus 5 ft access aisle Yes 1 Yes, 9 No Minimum of 1 van space for every accessible space, 8' wide + 8' aisle Yes 6 Yes, 4 No Sign with international symbol of accessibility at each space Yes Yes, 10 Sign 5'-8' to top of sign Yes 4 yes, 6 no Surface evenly paved or hard-packed (no cracks) Surface slope less than 1:20, 5% Yes Curbcut to pathway from parking lot at each space if sidewalk (curb) is present Some curb cuts are shared Curbcut is a minimum width of 3 ft, excluding sloped sides, has sloped sides, all slopes not to exceed 1:12, and textured or painted yellow 9 curb cuts are not painted yellow or textured Notes: N/A YES Site Access, Path of Travel, Entrances Site Access Accessible path of travel from passenger disembarking area and parking area to accessible entrance yes Surface evenly paved or hard-packed yes Disembarking area at accessible entrance yes not all spots have a disembarking area ath of Travel Description Comments

Path does not require the use of stairs	yes	
Path does not require the use of wheelchair ramp	yes	
Path is stable, firm and slip resistant	yes	
Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50).	yes	
Continuous common surface, no changes in level greater than ½ inch	yes	
Entrances	•	
Primary public entrances accessible to person using wheelchair, must be signed, gotten to independently, and not be the service entrance	Yes	
Level space extending 5 ft. from the door, interior and exterior of entrance doors	Yes	
Minimum 32" clear width opening (i.e. 36" door with standard hinge)	Yes	
At least 18" clear floor area on latch, pull side of door	Yes	
Door handle no higher than 48" and operable with a closed fist	No	
Vestibule is 4 ft plus the width of the door swinging into the space	N/A	
Entrance(s) on a level that makes elevators accessible	N/A	
Door mats less than ¼" thick are securely fastened	N/A	
Door mats more than ¾" thick are recessed	N/A	
Grates in path of travel have openings of X" maximum	Yes	
Signs at non-accessible entrance(s) indicate direction to accessible entrance	No	
Emergency egress – alarms with flashing lights and audible signals, sufficiently lighted	No	
Notes:		
Stairs and Doors	YES	
Doors Doors	1.20	
Minimum 32" clear opening	Yes	
At least 18" clear floor space on pull side of door	Yes	
Closing speed minimum 3 seconds to within 3" of the latch	No N/A	
Maximum pressure 5 pounds interior doors	N/A	
Threshold maximum ½" high, beveled on both sides	Yes	
Hardware operable with a closed fist (no conventional door knobs or thumb latch devices)	No	
Hardware minimum 36", maximum 48" above the floor	No	
Clear, level floor space extends out 5 ft from both sides of the door	Yes	
Door adjacent to revolving door is accessible and unlocked	N/A	
Doors opening into hazardous area have hardware that is knurled or roughened	N/A	
Notes:		
Restrooms	YES	
5 ft turning space measured 12" from the floor	Yes	
At least one Sink	'	
Clear floor space of 30" by 48" to allow a forward approach	Yes	
Mounted without pedestal or legs, height 34" to top of rim	Yes	
Extends at least 22" from the wall	Yes	
Open knee space a minimum 19" deep, 30" width, and 27" high	Yes	
Cover exposed pipes with insulation	No	
Faucets operable with closed fist (lever or spring activated handle)		
	No	-
At least one Stall		1
At least one Stall Accessible to person using wheelchair at 60" wideby 72" deep	No	
At least one Stall Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide	No No	
At least one Stall Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door swings out	No No Yes	
At least one Stall Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door swings out Stall door is self closing	No No Yes No	
At least one Stall Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door swings out Stall door is self closing Stall door has a pull latch	No No Yes No No	
At least one Stall Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door swings out Stall door is self-closing Stall door has a pull latch Lock on stall door is operable with a closed fist, and 32" above the floor	No No Yes No No	
At least one Stall Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door swings out Stall door is self closing Stall door is self closing Stall door has a pull latch Lock on stall door is operable with a closed fist, and 32" above the floor Coat hook is 54" high	No No Yes No No	NO hook
At least one Stall Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door swings out Stall door is self-closing Stall door has a pull latch Lock on stall door is operable with a closed fist, and 32" above the floor	No No Yes No No	NO hook
At least one Stall Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door swings out Stall door is self closing Stall door is self closing Stall door has a pull latch Lock on stall door is operable with a closed fist, and 32" above the floor Coat hook is 54" high	No No Yes No No	NO hook Comments
At least one Stall Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door swings out Stall door swings out Stall door sa self closing Stall door has a pull latch Lock on stall door is operable with a closed fist, and 32" above the floor Coat hook is 54" high	No No Yes No No	
At least one Stall Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door is self closing Stall door is self closing Stall door has a pull latch Lock on stall door is operable with a closed fist, and 32" above the floor Coat hook is 54" high Teilet Description	No No Yes No No No	
At least one Stall Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door is self closing Stall door has a pull latch Lock on stall door is operable with a closed fist, and 32" above the floor Coat hook is 54" high Description 18" from center to nearest side wall	No No Yes No No No No	
At least one Stall Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door is self closing Stall door is perable with a closed fist, and 32" above the floor Coat hook is 54" high Toilet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or floture	No No Yes No No No No Yes Yes Yes	
At least one Stall Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door swings out Stall door swings out Stall door has a pull latch Lock on stall door is operable with a closed fist, and 32" above the floor Coat hook is 54" high Toilet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor	No No Yes No No No No Yes Yes Yes	
At least one Stall Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door is self closing Stall door is self closing Stall door has a pull latch Lock on stall door is operable with a closed fist, and 32" above the floor Coat hook is 54" high Toilet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor Grab Bars	No No Yes No No No No Yes Yes Yes	Comments
At least one Stall Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door so self closing Stall door has a pull latch Lock on stall door is operable with a closed fist, and 32" above the floor Coat hook is 54" high Toilet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fisture Top of seat 17"-19" above the floor Grab Bars Description	No No No Yes No No No No Yes Yes Yes Yes	Comments
At least one Stall Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door is new food one stall door is self-closing Stall door has a pull latch Lock on stall door is perable with a closed fist, and 32" above the floor Cost hook is 54" high Toilet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or foture Top of seat 17"-19" above the floor Grab Bars Description On back and side wall closest to toilet	No No No Yes No No No No Yes Yes Yes Yes	Comments
At least one Stall Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door swings out Stall door swings out Stall door is self closing Stall door has a pull latch Lock on stall door is operable with a closed fist, and 32" above the floor Coat hook is 54" high Toilet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor Grab Bars Description On back and side wall closest to toilet 1%" diameter	No No Yes No No No No Yes Yes Yes Yes Yes	Comments
At least one Stall Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door is self closing Stall door has a pull latch Lock on stall door is operable with a closed fist, and 32" above the floor Coat hook is 54" high Toilet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor Grab Bars Description On back and side wall closest to toilet 1½" dearance to wall	No No No Yes No No No No Yes Yes Yes Yes Yes Yes	Comments
At least one Stall Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door is self closing Stall door is self closing Stall door has a pull latch Lock on stall door is operable with a closed fist, and 32" above the floor Coat hook is 54" high Toilet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor Stall Bars Description On back and side wall closest to toilet 1½" dearneter 1½" dearneter 1½" dearneter to wall Located 30" above and parallel to the floor	No No No No No No No No No Yes Yes Yes Yes Yes Yes Yes	Comments
At least one Stall Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door is self closing Stall door is self closing Stall door has a pull latch Lock on stall door is operable with a closed fist, and 32" above the floor Cost hook is 54" high Tollet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor Grab Bars Description On back and side wall closest to tollet 1½" diameter 1½" clearance to wall Located 30" above and parallel to the floor Acid-etched or roughened surface	No No No No No No No No No Yes	Comments
At least one Stall Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door so swings out Stall door is self closing Stall door has a pull latch Lock on stall door is operable with a closed fist, and 32" above the floor Coat hook is 54" high Toilet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor Grab Bars Description On back and side wall closest to toilet 1½" dearance to wall Located 30" above and parallel to the floor Acid-etched or roughened surface 42" long Fixtures	No No No No No No No No No Yes	Comments
At least one Stall Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door is self closing Stall door is self closing Stall door has a pull latch Lock on stall door is operable with a closed fist, and 32" above the floor Coat hook is 54" high Toilet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor Stab Bars Description On back and side wall closest to toilet 1½" dearneter 1½" dearneter 1½" dearneter to wall Located 30" above and parallel to the floor Acid etched or roughened surface 42" long Fixtures Description	No No No No No No No No No Yes Yes Yes Yes Yes Yes Yes Yes Yes	Comments
At least one Stall Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door is self closing Stall door is self closing Stall door has a pull latch Lock on stall door is operable with a closed fist, and 32" above the floor Coat hook is 54" high Toilet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor Grab Bars Description On back and side wall closest to toilet 1½" diameter 1½" clearance to wall Located 30" above and parallel to the floor Acid-etched or roughened surface 42" long Fixtures Description 1½" diameter	No No Yes No No No No No No No N	Comments
At least one Stall Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door so swings out Stall door si self closing Stall door has a pull latch Lock on stall door is operable with a closed fist, and 32" above the floor Coat hook is 54" high Toilet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor Grab Bars Description On back and side wall closest to toilet 1½" clearance to wall Lock on supplied to the floor Acid-etched or roughened surface 42" long Fixtures Description 1½" diameter 1½" diameter 1½" diameter	No No No No No No No No No Yes	Comments
At least one Stall Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door is 36" wide Stall door is self closing Stall door is self closing Stall door is self closing Stall door has a pull latch Lock on stall door is operable with a closed fist, and 32" above the floor Coat hook is 54" high Teilet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor Grab Bars Description On back and side wall closest to toilet 11%" diameter 11%" dearnace to wall Located 30" above and parallel to the floor Acid-etched or roughened surface 42" long Fixtures Description 11%" diameter 11%" dearnace to wall Located 30" above and parallel to the floor Acid-etched or roughened surface 42" long Fixtures Description 11%" diameter 11%" dearnace to wall Located 30" above and parallel to the floor	No No Yes No No No No No No No N	Comments
At least one Stall Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door so swings out Stall door si self closing Stall door has a pull latch Lock on stall door is operable with a closed fist, and 32" above the floor Coat hook is 54" high Toilet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor Grab Bars Description On back and side wall closest to toilet 1½" clearance to wall Lock on supplied to the floor Acid-etched or roughened surface 42" long Fixtures Description 1½" diameter 1½" diameter 1½" diameter	No No No No No No No No No Yes	Comments
At least one Stall Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door is 36" wide Stall door is self closing Stall door is self closing Stall door is self closing Stall door has a pull latch Lock on stall door is operable with a closed fist, and 32" above the floor Coat hook is 54" high Teilet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor Grab Bars Description On back and side wall closest to toilet 11%" diameter 11%" dearnace to wall Located 30" above and parallel to the floor Acid-etched or roughened surface 42" long Fixtures Description 11%" diameter 11%" dearnace to wall Located 30" above and parallel to the floor Acid-etched or roughened surface 42" long Fixtures Description 11%" diameter 11%" dearnace to wall Located 30" above and parallel to the floor	No No No No No No No No No Yes	Comments
At least one Stall Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door si self closing Stall door si self closing Stall door has a pull latch Lock on stall door is operable with a closed fist, and 32" above the floor Coat hook is 54" high Toilet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor Grab Bars Description On back and side wall closest to toilet 1½" clearance to wall Locket 30" above and parallel to the floor Acid-etched or roughened surface 42" long Fixtures Description 1½" clearance to wall Located 30" above and parallel to the floor Notes:	No No No No No No No No No Yes	Comments
At least one Stall Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door is self closing	No No No No No No No No No Yes	Comments
At least one Stall Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door is self closing Stall door is self closing Stall door is self closing Stall door has a pull latch Lock on stall door is operable with a closed fist, and 32" above the floor Coat hook is 54" high Toilet Toilet Toilet Toilet Toilet Toilet Toilet Too of seat 17"-19" above the floor Stab Bars Description On back and side wall closest to toilet 1½" dearnace to wall Located 30" above and parallel to the floor Acid-etched or roughened surface 42" long Fistures Description Description Tiv" dearnace to wall Located 30" above and parallel to the floor Notes: Floors, Drinking Fountains, Telephones	No No No No No No No No No Yes	Comments Comments Comments
At least one Stall Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door swings out Stall door is self closing Stall door is self closing Stall door is perable with a closed fist, and 32" above the floor Cost hook is 54" high Tollet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or foture Top of seat 17"-19" above the floor Grab Bars Description On back and side wall closest to toilet 1½" diameter 1½" clearance to wall Located 30" above and parallel to the floor Acid-etched or roughened surface 42" long Fixtures Description 1½" diameter 1½" clearance to wall Located 30" above and parallel to the floor Notes: Floors, Drinking Fountains, Telephones Floors, Drinking Fountains, Telephones Floors, Drinking Fountains, Telephones Floors	No Yes	Comments
At least one Stall Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door si self closing Stall door is deep closing Stall door is deep closing Stall door is deep closing Stall do	No Yes	Comments Comments Comments
At least one Stall Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door is self closing Stall door is self closed Stall doo	No N	Comments Comments Comments
Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door is 36" wide Stall door is 36" wide Stall door so self closing Stall door so perable with a closed fist, and 32" above the floor Cost hook is 54" high Toilet 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of sext 17"-19" above the floor Grab Bars Description On back and side wall closest to toilet 1½" clearance to wall Located 30" above and parallel to the floor Acid-etched or roughened surface 42" long Fixtures Description 1½" clearance to wall Located 30" above and parallel to the floor Notes: Floors, Drinking Fountains, Telephones Floors Description Notes:	No Yes	Comments Comments Comments
At least one Stall Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door is self closing Stall door is self closed Stall doo	No N	Comments Comments Comments
Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door is 36" wide Stall door is 36" wide Stall door so self closing Stall door so perable with a closed fist, and 32" above the floor Cost hook is 54" high Toilet 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of sext 17"-19" above the floor Grab Bars Description On back and side wall closest to toilet 1½" clearance to wall Located 30" above and parallel to the floor Acid-etched or roughened surface 42" long Fixtures Description 1½" clearance to wall Located 30" above and parallel to the floor Notes: Floors, Drinking Fountains, Telephones Floors Description Notes:	No Yes	Comments Comments Comments
Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door is 36" wide Stall door is self closing Stall door is self closing Stall door is operable with a closed fist, and 32" above the floor Coat hook is 54" high Tollet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor Grab Bars Description On back and side wall closest to toilet 11%" clearance to wall Located 30" above and parallel to the floor Acid-etched or roughened surface 42" long Tistures Description Statures Description Tistures Tistu	No Yes	Comments Comments Comments
Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door is 36" wide Stall door is self closing Stall door is self closing Stall door is operable with a closed fist, and 32" above the floor Coat hook is 54" high Tollet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor Grab Bars Description On back and side wall closest to toilet 11%" clearance to wall Located 30" above and parallel to the floor Acid-etched or roughened surface 42" long Tistures Description Statures Description Tistures Tistu	No Yes	Comments Comments Comments
Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 50" wide Stall door is 50" wide Stall door is 61" door is 61	No	Comments Comments Comments
Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door is 36" wide Stall door is 36" wide Stall door is self closing Stall door is operable with a closed fist, and 32" above the floor Coat hook is 54" high Toilea 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture 170 p of seat 17"-19" above the floor Grab Bars Description On back and side wall closest to toilet 11%" clearance to wall Located 30" above and parallel to the floor Acid-etched or roughened surface 42" long fixtures Description Stiff clearance to wall Located 30" above and parallel to the floor Notes: Floors, Drinking Fountains, Telephones Bloors Description Non-sip surface Carpeting is high-density, low pile, non-absorbent, stretched taut, securely anchored Cordor with minimum is 3 ft Objects (signs, ceiling lights, fixtures) can only protrude 4" into the path of travel from a height of 27" to 80" above the floor	No Yes	Comments Comments Comments
Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door is 96" vide Stall door is 96" closing Stall door is 94 pull tatch Lock on stall clor is operable with a closed fist, and 32" above the floor Coat hook is 54" high Toilet Description 13" from center to nearest side wall 42" milimium clear space from center to farthest wall or flature Top of seat 17"-19" above the floor Grab Bars Description On back and side wall closest to toilet 13" diameter 13" clearance to wall Located 30" above and parallel to the floor Acid etched or roughened surface 42" long Flatures Description 13" diameter 13" clearance to wall Located 30" above and parallel to the floor Notes: Floors, Drinking Fountains, Telephones Bloors Description Non-silp surface Carpeting is high-density, low pile, non-absorbent, stretched taut, securely anchored Cornidor width minimum is 3 ft Objects (signs, ceiling lights, fixtures) can only protrude 4" into the path of travel from a height of 27" to 80" above the floor Notes: Signs, Signals, and Switches Suitches, Controls and Sizes Suitches, Controls and Sizes Suitches, Controls and Sizes Suitches, Controls and Sizes	No	Comments Comments Comments Comments Comments
Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door is 36" wide Stall door is 96" wide Stall door is 96" wide Stall door is 96" closing Stall door is set Closing Stall door is set Closing Stall door is ap and litarch Lock on stall clore is operable with a closed fist, and 32" above the floor Coat hook is 54" high Tollet Description 13" from center to nearest side wall 42" minimum clear space from center to farthest wall or fluture Top of seal 17"-19" above the floor Grab Bars Description On back and side wall closest to tollet 13" clearance to wall Located 30" above and parallel to the floor Acid-etched for roughened surface 42" long Etaturas Description 13" diameter 13" clearance to wall Located 30" above and parallel to the floor Notes: Floors, Drinking Fountains, Telephones Boors Description Non-silp surface Carpeting is high-density, low pile, non-absorbent, stretched taut, securely anchored Corridor width minimum is 3 ft Objects (signs, ceiling lights, fixtures) can only protrude 4" into the path of travel from a height of 27" to 80" above the floor Notes: Signs, Signals, and Switches Switches, Controls and Signs Description Switches and controls for light, heat, ventilation, windows, fire alarms, thermostats, etc, must be a minimum of 36" and a maximum of 48" above the floor for a Switches and controls for light, heat, ventilation, windows, fire alarms, thermostats, etc, must be a minimum of 36" and a maximum of 48" above the floor for or Switches and controls for light, heat, ventilation, windows, fire alarms, thermostats, etc, must be a minimum of 36" and a maximum of 48" above the floor for a Switches and controls for light, heat, ventilation, windows, fire alarms, thermostats, etc, must be a minimum of 36" and a maximum of 48" above the floor for a	No	Comments Comments Comments
Accessible to person using wheelchair at 60° wideby 72" deep Stall door is 36° wide Stall door is 36° wide Stall door is 96° door is 9	No	Comments Comments Comments Comments

Electrical outlets centered no lower than 18" above the floor	Yes
Warning signals must be visual as well as audible	No
Notes:	
Swimming Pool/ Lake beach	N/A
Shower Rooms	N/A
Picknicking	N/A
Off Leash Dog Areas (OLA)	N/A

Facility Name: Angier School Playground Size (Ac): 4.7 acres Address: 1697 Beacon Street, Waban Ward: 5 General Facility Notes: Recent school rebuilt and accessible play equipment areas in 2016; no accessible pathways in the field area. Poured in place saefty surfacing. Site Furnishings YES Comments Tables & Benches Number of Benches yes 14 total - 6 have backs, 6 have no backs, 2 spectator benches with backs at little league Number of Tables Located adjacent to accessible paths yes no paths, large pad area at playground Back and Arm Rests yes 4 - 2 have backs, 2 have no backs Trash Cans Located adjacent to accessible paths 1 bigbelly trash compactor; 1 bigbelly recycling unit; 1trash/1 recycling by tennis court yes Picnic Shelters no paths, shellters are within large accessibe area at playground Located adjacent to accessible paths YES Notes: **Trails & Paths** YES Comments Surface (A=Asphalt, C=Concrete, SD= stone dust, NS= naturally surfaced, B=Boardwalk, BR=Bridge) Dimensions (width) no paths, large pad area at playground No Signage for visually impaired YES Play Areas Comments Facility Type (3-5 Yrs,5-12 Yrs) gaga pit Same experience provided to all yes Access Routes Located adjacent to accessible paths yes no paths, large pad area at playground Enough space between equipment for wheelchair yes Notes: Game Areas YES Comments 3 TN (2 benches w/ backs at tennis courts), 1 basketball court, 1 basketball standard, 1BF (w/ Facility Type (RF=Rectangular Fields, BF= Ballfields, BK=Basketball, TN=Tennis, BC=Bocce) yes backstop, benches, protective screens and shed) Access Routes Located adjacent to accessible paths No Spectator Seating 8 picnic tables w/ shade structure, Notes: require accessible route to non accessible amenities N/A **Boat Docks** Fishing Facilities N/A N/A Community Gardens Parking YES Total Spaces Accessible Spaces Description Comments Parking Amenities (L=lot, ST=street) yes Accessible space located closest to accessible entrance yes Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft N/A 12.5 ft wide Minimum width of 13 ft includes 8 ft space plus 5 ft access aisle No Minimum of 1 van space for every accessible space, 8' wide + 8' aisle. yes Sign with international symbol of accessibility at each space yes Sign 5'-8' to top of sign No Surface evenly paved or hard-packed (no cracks) yes Surface slope less than 1:20, 5% yes Curbcut to pathway from parking lot at each space if sidewalk (curb) is present yes Curbcut is a minimum width of 3 ft, excluding sloped sides, has sloped sides, all slopes not to exceed 1:12, and textured or painted yellow Notes: N/A YES Site Access, Path of Travel, Entrances Comments Accessible path of travel from passenger disembarking area and parking area to accessible entrance no paths, large pad area at playground Surface evenly paved or hard-packed Disembarking area at accessible entrance Path of Travel Description Comments Path does not require the use of stairs yes no paths, large pad area at playground

Path does not require the use of wheelchair ramp	yes	
Path is stable, firm and slip resistant	yes	
Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50).	yes	
Continuous common surface, no changes in level greater than ½ inch	yes	
Stairs and Doors	N/A	
Restrooms	N/A	
Floors, Drinking Fountains, Telephones	N/A	
Signs, Signals, and Switches	N/A	
Swimming Pool/ Lake beach	N/A	
Shower Rooms	N/A	
Picknicking	N/A	
Off Leash Dog Areas (OLA)	N/A	

Facility Name: Auburndale Park 'The Cove' Size (Ac): 29.9 acres Address: West Pine Street, Auburndale Ward: 4 General Facility Notes: Accessible asphalt pathway to picnic area, and fieldhouse. Portions of stone dust path through undeveloped wooded area to Waltham and Flowed Meadow are accessible; tot lot is accessible; 5-12 play aparatus required accessible path; fitness equipment stations on accessible route; accessible parking lot; acreage includes contiguous Lyons Park. Site Furnishings YES Yes Comments Tables & Benches Number of Benches YES Number of Tables YES 30 tables dispersed into 5 permitted picnic areas. Located adjacent to accessible paths 3 of the 5 picnic areas are along an accessible path, 2 benches are on an accessibe path. Back and Arm Rests City standard benches have backrest but no arm rests. Picnic tables do not have back rests YES Grills Located adjacent to accessible paths YES 3 of the 5 grilling areas are along an accessible path. Each picnic area has multiple grills Trash Cans Located adjacent to accessible paths YES Notes: YES Trails & Paths Comments Description Surface (A=Asphalt, C=Concrete, SD= stone dust, NS= naturally surfaced, B=Boardwalk, BR=Bridge) A; SD, NS; BR Dimensions (width) 6 feet minimum; paths range up to 12 feet in width Rails No Signage for visually impaired Notes: YES Play Areas Comments Facility Type (3-5 Yrs,5-12 Yrs) YES 3-5 Yrs; 5-12 Yrs Same experience provided to all No Access Routes Located adjacent to accessible paths YES Enough space between equipment for wheelchair YES Notes: YES **Game Areas** Comments Description Facility Type (RF=Rectangular Fields, BF= Ballfields, BK=Basketball, TN=Tennis, BC=Bocce) YES 1 BF; 1 BK; 2 TN Access Routes Located adjacent to accessible paths basketball and tennis courts are on accessible path; ball fieldis not on an accessible path Equipment YES spectator seating not on accessible route Spectator Seating **Boat Docks** N/A Fishing Facilities N/A **Community Gardens** N/A Parking YES Total Spaces Accessible Spaces 144 5 Space Description Comments Parking Amenities (L=lot, ST=street) YES Accessible space located closest to accessible entrance YES All 5 parking spaces are next to an accessible park entrance Minimum width of 13 ft includes 8 ft space plus 5 ft access aisle YES Minimum of 1 van space for every accessible space, 8' wide + 8' aisle. YES Sign with international symbol of accessibility at each space YES Surface evenly paved or hard-packed (no cracks) YES Surface slope less than 1:20, 5% YES Notes: Site Access, Path of Travel, Entrances YES Site Access Description Comments Accessible path of travel from passenger disembarking area and parking area to accessible entrance YES Surface evenly paved or hard-packed YES Ponding of water? No Path of Travel Description Comments Path does not require the use of stairs YES Path does not require the use of wheelchair ramp YES Path is stable, firm and slip resistant YES Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50). YES

Continuous common surface, no changes in level greater than ½ inch	YES	
Any objects protruding onto the pathway must be detected by a person with a visual disability using a cane	No	
<u>Entrances</u>		
Description		Comments
Primary public entrances accessible to person using wheelchair, must be signed, gotten to independently, and not be the service entrance	Yes	
Level space extending 5 ft. from the door, interior and exterior of entrance doors		
	Yes	
Minimum 32" clear width opening (i.e. 36" door with standard hinge)	Yes	
At least 18" clear floor area on latch, pull side of door	Yes	
Door handle no higher than 48" and operable with a closed fist	No	
Vestibule is 4 ft plus the width of the door swinging into the space	Yes	
Entrance(s) on a level that makes elevators accessible	N/A	
Door mats less than ½" thick are securely fastened	No	
	1	
Door mats more than ¾" thick are recessed	No	
Grates in path of travel have openings of ½" maximum	N/A	
Signs at non-accessible entrance(s) indicate direction to accessible entrance	No	
Emergency egress – alarms with flashing lights and audible signals, sufficiently lighted	No	
Notes:		
Chairmand Danie	VEC	
Stairs and Doors	YES	
<u>Doors</u>	1	
Description		Comments
Minimum 32" clear opening	Yes	
At least 18" clear floor space on pull side of door	Yes	
Closing speed minimum 3 seconds to within 3" of the latch	Yes	
Hardware operable with a closed fist (no conventional door knobs or thumb latch devices)	No	
Hardware minimum 36", maximum 48" above the floor	Yes	
Clear, level floor space extends out 5 ft from both sides of the door	Yes	
Door adjacent to revolving door is accessible and unlocked	N/A	
Doors opening into hazardous area have hardware that is knurled or roughened	N/A	
Notes:		
Restrooms	YES	
Description	123	Comments
	W	Commens
5 ft turning space measured 12" from the floor	Yes	
At least one Sink	1	
Description		Comments
Clear floor space of 30" by 48" to allow a forward approach	Yes	
Mounted without pedestal or legs, height 34" to top of rim	Yes	
Extends at least 22" from the wall	Yes	
Open knee space a minimum 19" deep, 30" width, and 27" high	Yes	
Cover exposed pipes with insulation		
	No	
Faucets operable with closed fist (lever or spring activated handle)	Yes	
At least one Stall		,
Description		Comments
Accessible to person using wheelchair at 60" wideby 72" deep	Yes	
Stall door is 36" wide	Yes	
Stall door swings out	Yes	
Stall door is self closing	No	
Stall door has a pull latch	Yes	
Lock on stall door is operable with a closed fist, and 32" above the floor	No	
Coat hook is 54" high	Yes	
Coat hook is 54" high Toilet	ies	
	ies .	Comments
Toilet	Yes	Comments
Toilet Description 18" from center to nearest side wall	Yes	Comments
Toilet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture	Yes Yes	Comments
Toilet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor	Yes	Comments
Toilet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor Grab Bars	Yes Yes	
Toilet Description 18' from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor Grab Bars Description	Yes Yes Yes	Comments
Toilet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor Grab Bars Description On back and side wall closest to toilet	Yes Yes Yes	
Toilet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor Grab Bars Description On back and side wall closest to toilet 1%" diameter	Yes Yes Yes	
Toilet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor Grab Bars Description On back and side wall closest to toilet	Yes Yes Yes	
Toilet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor Grab Bars Description On back and side wall closest to toilet 1%" diameter	Yes Yes Yes Yes Yes Yes	
Toilet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor Grab Bars Description On back and side wall closest to toilet 1½" diameter 1½" clearance to wall	Yes Yes Yes Yes Yes Yes Yes Yes Yes	
Toilet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor Grab Bars Description On back and side wall closest to toilet 1½" diameter 1½" clearance to wall Located 30" above and parallel to the floor Acid-etched or roughened surface	Yes	
Toilet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor Grab Bars Description On back and side wall closest to toilet 1½" clearance to wall Located 30" above and parallel to the floor Acid-etched or roughened surface 42" long	Yes	
Toilet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor Grab Bars Description On back and side wall closest to toilet 11%" diameter 11%" dearance to wall Located 30" above and parallel to the floor Acid-etched or roughened surface 42" long Fixtures	Yes	Comments
Toilet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the filoor Grab Bars Description On back and side wall closest to toilet 1½" dearance to wall Located 30" above and parallel to the floor Acid-etched or roughened surface 42" long Fixtures Description	Yes	
Toilet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor Grab Bars Description On back and side wall closest to toilet 1½" diameter 1½" clearance to wall Located 30" above and parallel to the floor Acid-etched or roughened surface 42" long Fixtures Description 1½" diameter	Yes	Comments
Toilet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor Grab Bars Description On back and side wall closest to toilet 1½" clearance to wall Located 30" above and parallel to the floor Acid-etched or roughened surface 42" long Fixtures Description 1½" diameter 1½" diameter	Yes	Comments
Toilet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor Grab Bars Description On back and side wall closest to toilet 1½" diameter 1½" clearance to wall Located 30" above and parallel to the floor Acid-etched or roughened surface 42" long Fixtures Description 1½" diameter	Yes	Comments
Toilet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor Grab Bars Description On back and side wall closest to toilet 1½" clearance to wall Located 30" above and parallel to the floor Acid-etched or roughened surface 42" long Fixtures Description 1½" diameter 1½" diameter	Yes	Comments
Toilet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor Grab Bars Description On back and side wall closest to toilet 1½" dearance to wall Located 30" above and parallel to the floor Acid-etched or roughened surface 42" long Fixtures Description 1½" dearance to wall Located 30" above and parallel to the floor	Yes	Comments
Toilet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor Grab Bars Description On back and side wall closest to toilet 1½" dearance to wall Located 30" above and parallel to the floor Acid-etched or roughened surface 42" long Fixtures Description 1½" dearance to wall Located 30" above and parallel to the floor	Yes	Comments
Toilet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor Grab Bars Description On back and side wall closest to toilet 1½" clearance to wall Located 30" above and parallel to the floor Acid-etched or roughened surface 42" long Fixtures Description 1½" diameter 1½" dearance to wall Located 30" above and parallel to the floor Notes:	Yes	Comments
Toilet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor Grab Bars Description On back and side wall closest to toilet 1½" diameter 1½" clearance to wall Located 30" above and parallel to the floor Acid-etched or roughened surface 42" long Fixtures Description 1½" diameter 1½" diameter 1½" diameter 1½" diameter 1½" description 1½" diameter 1½" clearance to wall Located 30" above and parallel to the floor Notes: Floors, Drinking Fountains, Telephones	Yes	Comments
Toilet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor Grab Bars Description On back and side wall closest to toilet 1½" diameter 1½" clearance to wall Located 30" above and parallel to the floor Acid-etched or roughened surface 42" long Eixtures Description 1½" diameter 1½" dearance to wall to the floor Notes: Floors, Drinking Fountains, Telephones Signs, Signals, and Switches	Yes	Comments
Tooliet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor Grab Bars Description On back and side wall closest to toilet 1½" diameter 1½" clearance to wall Located 30" above and parallel to the floor Acid-etched or roughened surface 42" long Fixtures Description 1½" diameter 1½" clearance to wall Located 30" above and parallel to the floor 1½" diameter 1½" clearance to wall Located 30" above and parallel to the floor Notes: Floors, Drinking Fountains, Telephones Signs, Signals, and Switches Swimming Pool / Lake beach Lake bea	Yes	Comments
Tooliet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor Grab Bars Description On back and side wall closest to toilet 11%" diameter 11%" clearance to wall Located 30" above and parallel to the floor Acid-etched or roughened surface 42" long Fixtures Description 11%" diameter 11%" signater 11%" diameter 11%" diameter 11%" diameter 11%" diameter 11%" diameter 11%" clearance to wall Located 30" above and parallel to the floor Notes: Floors, Drinking Fountains, Telephones Signals, and Switches Symmming Pool / Lake beach Shower Rooms Shower Rooms Shower Rooms Signals, and Switches Signals, and Switches Shower Rooms Signals, and Switches Si	Yes	Comments
Tooliet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor Grab Bars Description On back and side wall closest to toilet 11%" diameter 11%" clearance to wall Located 30" above and parallel to the floor Acid-etched or roughened surface 42" long Fixtures Description 11%" diameter 11%" signater 11%" diameter 11%" diameter 11%" diameter 11%" diameter 11%" diameter 11%" clearance to wall Located 30" above and parallel to the floor Notes: Floors, Drinking Fountains, Telephones Signals, and Switches Symmming Pool / Lake beach Shower Rooms Shower Rooms Shower Rooms Signals, and Switches Signals, and Switches Shower Rooms Signals, and Switches Si	Yes	Comments
Tooliet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor Grab Bars Description On back and side wall closest to toilet 1½" clearance to wall Located 30" above and parallel to the floor Acid-etched or roughened surface 42" long Fixtures Description 1½" diameter 1½" clearance to wall Located 30" above and parallel to the floor Notes: Floors, Drinking Fountains, Telephones Signs, Signals, and Switches Swimming Pool/ Lake beach Shower Rooms Picknicking	Yes	Comments Comments
Tooliet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor Grab Bars Description On back and side wall closest to toilet 11%" diameter 11%" clearance to wall Located 30" above and parallel to the floor Acid-etched or roughened surface 42" long Fixtures Description 11%" diameter 11%" signater 11%" diameter 11%" diameter 11%" diameter 11%" diameter 11%" diameter 11%" clearance to wall Located 30" above and parallel to the floor Notes: Floors, Drinking Fountains, Telephones Signals, and Switches Symmming Pool / Lake beach Shower Rooms Shower Rooms Shower Rooms Signals, and Switches Signals, and Switches Shower Rooms Signals, and Switches Si	Yes	Comments
Topic from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor Grab Bars Description On back and side wall closest to toilet 1½" diameter 1½" clearance to wall 1coated 30" above and parallel to the floor Acid-etched or roughened surface 42" long Fixtures Description 1½" diameter 1½" clearance to wall 1coated 30" above and parallel to the floor Notes: Floors, Drinking Fountains, Telephones Signs, Signals, and Switches Swimming Pool/ Lake beach Shower Rooms Picknicking Description A minimum of 5% of the total tables must be accessible with clear space under the table top not less than 30" mide and 19" deep per seating space and not less than 22" clear forther the grape under the table to provide as 12" clear space (totaling 48") must extend beyond the 19" clear space under the table to provide and 27" clear from the ground to the underside of the table. An additional 29" clear space (totaling 48") must extend beyond the 19" clear space under the table to provide	Yes	Comments Comments
Description	Yes	Comments Comments
Description	Yes	Comments Comments
Description	Yes	Comments Comments
To list Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor Grab Bars Description On back and side wall closest to toilet 1½" clearance to wall Located 30" above and parallel to the floor Acid-etched or roughened surface 42" long Fixtures Description 1½" diameter 1½" dearance to wall Located 30" above and parallel to the floor Notes: Floors, Drinking Fountains, Telephones Signs, Signals, and Switches Swimming Pool/ Lake beach Shower Rooms Picknicking Description A minimum of 5½ of the total tables must be accessible with clear space under the table top not less than 30" wide and 19" deep per seating space and not less than 27" clear from the ground to the underside of the table. An additional 29" clear space (totaling 48") must extend beyond the 19" clear space under the table to provide access For tables without toe clearance, the knee space under the table must be at least 28" high, 30" wide and 24" deep. Top of table no higher than 32" above ground	Yes	Comments Comments Comments
Top of seat 17"-19" above the floor Grab Bars Description On back and side wall closest to toilet 1½" diameter 1½" diameter 1½" diameter 1½" dearance to wall Located 30" above and parallel to the floor Acid-etched or roughened surface 42" long Fixtures Description 1½" dearance to wall Located 30" above and parallel to the floor Notes: Floors, Drinking Fountains, Telephones Signs, Signals, and Switches Swimming Pool/ Lake beach Shower Rooms Picknicking Description A minimum of 5% of the total tables must be accessible with clear space under the table top provide access For tables without toe clearance, the knee space under the table must be at least 28" high, 30" wide and 24" deep. Top of table no higher than 32" above ground Surface of the clear ground space under and around the table must be stable, firma nd slip-resistant, and evenly graded with a maximum slope of 2% in all directions Surface of the clear ground space under and around the table must be stable, firma nd slip-resistant, and evenly graded with a maximum slope of 2% in all directions	Yes	Comments Comments Comments
To possible to the following properties of the following p	Yes	Comments Comments
Top of seat 17"-19" above the floor ### from center to nearest side wall ### from center to nearest side wall or fixture ### Top of seat 17"-19" above the floor ### Grab Bars ### Description ### Glearance to wall ### Located 30" above and parallel to the floor ### Acid etched or roughened surface #### dameter ### dameter	Yes	Comments Comments
Toelet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor Grab Bass Description On back and side wall closest to toilet 1½" diameter 1½" clearance to wall Located 30" above and parallel to the floor Acid-etched or roughened surface 42" long Elatures Description 1½" dearance to wall Located 30" above and parallel to the floor Notes: Floors, Drinking Fountains, Telephones Signs, Signals, and Switches Swimming Pool/ Lake beach Shower Rooms Picknicking Description A minimum of 5% of the total tables must be accessible with clear space under the table top not less than 30" wide and 19" deep per seating space and not less than 27" clear from the ground to the underside of the table. An additional 29" clear space (totaling 48") must extend beyond the 19" clear space under the table top not less than 30" wide and 19" deep per seating space and not less than 27" clear from the ground to the underside of the table. An additional 29" clear space (totaling 48") must extend beyond the 19" clear space under the table top rovide access For tables without toe clearance, the knee space under the table must be at least 28" high, 30" wide and 24" deep. Top of table no higher than 32" above ground Surface of the clear ground space under and around the table must be stable, firm and slip-resistant, and evenly graded with a maximum slope of 2% in all directions Accessible tables, grills and fire rings must have clear ground space of at least 36" around the perimeter	Yes	Comments Comments

Off Leash Dog Areas (OLA)	N/A	

Facility Name: Officer Bobby Braceland Playground 'Upper Falls Playground' Size (Ac): 8.8 acres Address: Chestnut Street, Newton Upper Falls Ward: 5 General Facility Notes: Van accessible parking spaces, accessible park entry and route to tennis courts and benches constructed in 2012; no accessible pathways at ballfields, off-leash dog area, tot lot and basket ball court. Site Furnishings YES Comments Tables & Benches Number of Benches YES 6 BENCHES Number of Tables No Located adjacent to accessible paths YES 1 bench located along accessible path; remaning five are on lawn or mulch Back and Arm Rests YES 3 benches have backrest; no arm rest on any of the benches Trash Cans Located adjacent to accessible paths YES Trash, Recycling and dog waste bin are adjacent to accessible path Picnic Shelters N/A Located adjacent to accessible paths Notes: **Trails & Paths** YES Comments Description Surface (A=Asphalt, C=Concrete, SD= stone dust, NS= naturally surfaced, B=Boardwalk, BR=Bridge) YES Dimensions (width) N/A 6 feet minumum NO Signage for visually impaired Notes: YES **Play Areas** Comments Facility Type (3-5 Yrs,5-12 Yrs) YES Same experience provided to all No Access Routes Located adjacent to accessible paths No requires accessible route to play structure from Pennsylvania Ave. Enough space between equipment for wheelchair Yes Notes: Game Areas YES Description Comments Facility Type (RF=Rectangular Fields, BF= Ballfields, BK=Basketball, TN=Tennis, BC=Bocce) YES 1 RF; 1 BF; 1 BK; 2 TN Tennis courts are located adjacent to accessible path; all other amenities are not adjacent to Located adjacent to accessible paths YES Equipment Notes: **Boat Docks** N/A N/A Fishing Facilities N/A YES Community Gardens Parking Required Accessible Spaces 2 Space Description Comments Parking Amenities (L=lot, ST=street) YES Both accessible parking spaces are located at the entrance Accessible space located closest to accessible entrance YES YES Minimum width of 13 ft includes 8 ft space plus 5 ft access aisle Minimum of 1 van space for every accessible space, 8' wide + 8' aisle. YES Sign with international symbol of accessibility at each space YES Surface evenly paved or hard-packed (no cracks) YES YES Surface slope less than 1:20, 5% Curbcut to pathway from parking lot at each space if sidewalk (curb) is present . YES one curb cut for both parking spaces Curbcut is a minimum width of 3 ft, excluding sloped sides, has sloped sides, all slopes not to exceed 1:12, and textured or painted yellow YES N/A Ramps YÉS Site Access, Path of Travel, Entrances Description Comments Accessible path of travel from passenger disembarking area and parking area to accessible entrance YES Surface evenly paved or hard-packed YES Ponding of water? NO Disembarking area at accessible entrance YES Path of Travel Description Comments Path does not require the use of stairs YES Path does not require the use of wheelchair ramp YES

Path is stable, firm and slip resistant	YES	
Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50).	YES	
Continuous common surface, no changes in level greater than ½ inch	YES	
Any objects protruding onto the pathway that may not be detected by a person with a visual disability using a cane	NO	
Objects protruding more than 4" from the wall must be within 27" of the ground, or higher than 80"	NO	
Curb on the pathway must have curb cuts at drives, parking and drop-offs	YES	
Stairs and Doors	N/A	
Restrooms	N/A	
Floors, Drinking Fountains, Telephones	N/A	
Signs, Signals, and Switches	N/A	
Swimming Pool/ Lake beach	N/A	
Shower Rooms	N/A	
Picknicking	N/A	
Off Leash Dog Areas (OLA)	YES	
Description	Yes	Comments
Access Routes		
Located adjacent to accessible paths	No	
Area accesible	No	
Notes:		

Facility Name: Boyd Park Size (Ac): 4.8 acres Address: Jackson Road, Nonantum Ward: 1 General Facility Notes: Accessible parking at the Lincoln-Elliot School; Park disected by Watertown and Newton city lines; accessible pathway to courts; steep stairs down from Pearl St; playfield and softball field have no accessible pathways (including the portion in Watertown); 2-5 yr play structure; 5-12 yr Structure; play Site Furnishings YES Comments Tables & Benches Number of Benches YES 7 Benches Number of Tables YES Located adjacent to accessible paths YES 2 4 with Backs Back and Arm Rests YES Grills NA Located adjacent to accessible paths Trash Cans YES 1 Located adjacent to accessible paths Picnic Shelters Located adjacent to accessible paths Notes: Trails & Paths YES Comments Surface (A=Asphalt, C=Concrete, SD= stone dust, NS= naturally surfaced, B=Boardwalk, BR=Bridge) YES Dimensions (width) 6-ft Min Signage for visually impaired Notes: YES Play Areas Comments Facility Type (3-5 Yrs,5-12 Yrs) YES 2 Structures one acessible with ramp Same experience provided to all YES Access Routes Located adjacent to accessible paths YES Enough space between equipment for wheelchair Notes: YES **Game Areas** Comments Facility Type (RF=Rectangular Fields, BF= Ballfields, BK=Basketball, TN=Tennis, BC=Bocce) 2 BF ,1 BK, 1 RF Located adjacent to accessible paths YES Basketball acessible by path Berm cuts onto courts Spectator Seating No Notes: **Boat Docks** Fishing Facilities N/A N/A YES **Community Gardens** Parking Total Spaces Required Accessible Spaces 26 | 1 Space Description Comments Parking Amenities (L=lot, ST=street) YES lot Accessible space located closest to accessible entrance YES Minimum width of 13 ft includes 8 ft space plus 5 ft access aisle Yes Minimum of 1 van space for every accessible space, 8' wide + 8' aisle. No Sign with international symbol of accessibility at each space Yes Surface evenly paved or hard-packed (no cracks) Yes Surface slope less than 1:20, 5% Yes Curbcut to pathway from parking lot at each space if sidewalk (curb) is present . Yes Curbcut is a minimum width of 3 ft, excluding sloped sides, has sloped sides, all slopes not to exceed 1:12, and textured or painted yellow Yes Notes: N/A YES Site Access, Path of Travel, Entrances Comments Accessible path of travel from passenger disembarking area and parking area to accessible entrance YES Asphalt path to Hardpack around play structure Surface evenly paved or hard-packed Yes Disembarking area at accessible entrance Yes Path of Travel Description Comments Path does not require the use of stairs

Path does not require the use of wheelchair ramp	Yes	
Path is stable, firm and slip resistant	Yes	
Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50).	Yes	
Continuous common surface, no changes in level greater than ½ inch	No	
Notes:		
Stairs and Doors	YES	
Stairs	•	
Description		Comments
Open risers	No	
Nosings not projecting	Yes	
Treads no less than 11" wide	Yes	
Handrails on both sides	Yes	
Handrails 34"-38" above tread	Yes	
Handrail extends a minimum of 1' beyond top and bottom riser (if no safety hazard and space permits)	No	
Handgrip oval or round	Round	
Handgrip has a smooth surface	Yes	
Handgrip diam. 1¼" - 1½"	Yes	
1½" clearance between wall and handrail	NA	
Notes:		
Restrooms	N/A	
Floors, Drinking Fountains, Telephones	N/A	
Signs, Signals, and Switches	N/A	
Swimming Pool/ Lake beach	N/A	
Shower Rooms	N/A	
Picknicking	N/A	
Off Leash Dog Areas (OLA)	N/A	

Facility Name: Bullough's Pond Park Size (Ac): 1.4 acres (not including pond) Address: Bullough Park, Newton Centre General Facility Notes: On-street parking; sloped, perimeter park along pond shore; stone dust sidewalk running the length of the park on Bulloughs Park Rd. is not accessible in some sections; skating hut demolished in 2017. Sitting area is accessible with two benches and companion space on a concrete outlook constructed from the existing skating hut foundation in 2018. YES Site Furnishings Comments Tables & Benches YES Number of Tables NO 2 benches on the concrete outlook are accessible Located adjacent to accessible paths YES Back and Arm Rests YES 5 out of 7 benches have back and arm rest Located adjacent to accessible paths NO Notes: YES Trails & Paths Surface (A=Asphalt, C=Concrete, SD= stone dust, NS= naturally surfaced, B=Boardwalk, BR=Bridge) YES SD; A. Dimensions (width) 4 feet minimum NO Signage for visually impaired NO Notes: N/A Play Areas N/A N/A N/A N/A Game Areas Boat Docks Fishing Facilities Community Gardens N/A N/A YES Parking Site Access, Path of Travel, Entrances Site Access Comments Surface evenly paved or hard-packed YES Ponding of water? NA N/A Path of Travel Comments Description Path does not require the use of stairs YES Path does not require the use of wheelchair ramp YES Path is stable, firm and slip resistant YES Perimeter stone dust path has a number of obstructions due to erosion Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50). YES Continuous common surface, no changes in level greater than $\mbox{\ensuremath{\upred}{\%}}$ inch NO surface condition is fair but lacks continuity in some sections Any objects protruding onto the pathway that may not be detected by a person with a visual disability using a cane Stairs and Doors N/A N/A N/A N/A N/A Restrooms Floors. Drinking Fountains. Telephones Signs. Signals, and Switches Swimming Pool/ Lake beach Shower Rooms N/A N/A Picknicking Off Leash Dog Areas (OLA) N/A

Facility Name: Burr Playground Size (Ac): 5.1 acres Address: Waverly Ave. or Park Street, Newton Corner (across from Bigelow Middle School), Newton Corner General Facility Notes: Accessible pathways to the building and splash pad from both Park St. and Waverly Ave.; accessible splash pad constructed in 2017; Play structures are not accessible; Burr Playground serves Bigelow Middle School. YES Site Furnishings Comments Tables & Benches YES 8 Number of Tables Located adjacent to accessible paths Back and Arm Rests YES Located adjacent to accessible paths YES 1 Picnic Shelters Located adjacent to accessible paths Notes: YES Trails & Paths Description Comments Surface (A=Asphalt, C=Concrete, SD= stone dust, NS= naturally surfaced, B=Boardwalk, BR=Bridge) YES Dimensions (width) 8 FT NO Signage for visually impaired NO Benches Notes: YES Aquatics Comments Description Facility Type (P=Pool, L=Lake Beach, SP=Splash Pad) YES Accessible Entrance YES walkway from parking or ramp from street Location from accessible parking YES Safety features i.e. warning for visually impaired No Location from accessible path into water zero entry NA Shade provided (ST=Shade Trees, SS=Shade Shelter) Yes Trees Notes: YES Play Areas Description Comments Facility Type (3-5 Yrs,5-12 Yrs) no acessibility Same experience provided to all Access Routes Located adjacent to accessible paths no Enough space between equipment for wheelchair no YES Game Areas Comments Description Facility Type (RF=Rectangular Fields, BF= Ballfields, BK=Basketball, TN=Tennis, BC=Bocce) 1RF, 2BF, 4TN, 1 BK Access Routes Located adjacent to accessible paths Yes Basketball court NA Courts are open to path, no curb cut required Berm cuts onto courts quipment Spectator Seating No Notes: **Boat Docks** N/A N/A YES Fishing Facilities Community Gardens Parking Required Accessible Spaces otal Spaces 1 Space Description Comments YES Parking Amenities (L=lot, ST=street) L Accessible space located closest to accessible entrance Yes Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft $\,$ YES Minimum width of 13 ft includes 8 ft space plus 5 ft access aisle Yes Minimum of 1 van space for every accessible space, 8' wide + 8' aisle. No Sign with international symbol of accessibility at each space Yes Surface evenly paved or hard-packed (no cracks) NO concrete broken in multiple spots Surface slope less than 1:20, 5% Yes Notes: Ramps YES Comments Slope Maximum 1:12 No Ramp to Building not to code Minimum width 4 ft between handrails YES Handrails on both sides if ramp is longer than 6 ft YES

YES

Handrails at 34" and 19" from ramp surface

Handrails extend 12" beyond top and bottom	Yes	
Handgrip oval or round	Round	
Handgrip smooth surface	Yes	
Handgrip diameter between 1%" and 2"	Yes	
Clearance of 1½" between wall and wall rail Non-slip surface	NA Yes	
Level platforms (4ft x 4 ft) at every 30 ft, at top, at bottom, at change of direction	NA NA	
Notes:		
Site Access, Path of Travel, Entrances	YES	
<u>Site Access</u>		
Description Accessible path of travel from passenger disembarking area and parking area to accessible entrance	Yes	Comments
Surface evenly paved or hard-packed	Yes	
Ponding of water?	No	
Disembarking area at accessible entrance	Yes	
Path of Travel		
Description		Comments
Path does not require the use of stairs	Yes	
Path does not require the use of wheelchair ramp	Yes	
Path is stable, firm and slip resistant	Yes	
Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50). Continuous common surface, no changes in level greater than ½ inch	Yes No	
Entrances	110	
Description		Comments
Primary public entrances accessible to person using wheelchair, must be signed, gotten to independently, and not be the service entrance	Yes	No signage
Level space extending 5 ft. from the door, interior and exterior of entrance doors	Yes	
Minimum 32" clear width opening (i.e. 36" door with standard hinge)	Yes	
At least 18" clear floor area on latch, pull side of door	Yes	
Door handle no higher than 48" and operable with a closed fist Vertibular 4.6 plus the width of the door swinging into the case.	No No	
Vestibule is 4 ft plus the width of the door swinging into the space Entrance(s) on a level that makes elevators accessible	No	N/A
Entrance(s) on a level that makes elevators accessible Door mats less than '%" thick are securely fastened	Yes	N/A
Door mats more than %" thick are securely lastened	Yes	
Grates in path of travel have openings of ½" maximum		N/A
Signs at non-accessible entrance(s) indicate direction to accessible entrance	No	
Emergency egress – alarms with flashing lights and audible signals, sufficiently lighted	Yes	
Notes:		
Contract Decision	VEC	
Stairs and Doors	YES	
<u>Description</u>	l	Comments
Minimum 32" clear opening	Yes	
At least 18" clear floor space on pull side of door	Yes	
At least 18" clear floor space on pull side of door Threshold maximum %" high, beveled on both sides	Yes No	
At least 18" clear floor space on pull side of door Threshold maximum %" high, beveled on both sides Hardware operable with a closed fist (no conventional door knobs or thumb latch devices)	Yes No No	
At least 18" clear floor space on pull side of door Threshold maximum ½" high, beveled on both sides Hardware operable with a close off it no conventional door knobs or thumb latch devices) Hardware minimum 36", maximum 48" above the floor	Yes No No Yes	
At least 18" clear floor space on pull side of door Threshold maximum %" high, beveled on both sides Hardware operable with a closed fist (no conventional door knobs or thumb latch devices)	Yes No No	N/A
At least 18" clear floor space on pull side of door Threshold maximum %" high, beveled on both sides Hardware operable with a closed fist (no conventional door knobs or thumb latch devices) Hardware minimum 36", maximum 48" above the floor Clear, level floor space extends out 5 ft from both sides of the door	Yes No No Yes	N/A N/A
At least 18" clear floor space on pull side of door Treshold maximum ½" high, beveled on both sides Hardware operable with a closed fist (no conventional door knobs or thumb latch devices) Hardware minimum 36" maximum 48" above the floor Clear, level floor space extends out 5 ft from both sides of the door Door adjacent to revolving door is accessible and unlocked	Yes No No Yes	
At least 18" clear floor space on pull side of door Threshold maximum ½" high, beveled on both sides Hardware openable with a close offit (no conventional door knobs or thumb latch devices) Hardware minimum 36", maximum 48" above the floor Clear, level floor space extends out 5 ft from both sides of the door Door adjacent to revolving door is accessible and unicked Doors opening into hazardous area have hardware that is hunfed or roughened	Yes No No Yes	
At least 18" clear floor space on pull side of door Threshold maximum % "high, beveled on both sides Hardware operable with a closed fist (no conventional door knobs or thumb latch devices) Hardware minimum 36", maximum 48" above the floor Clear, level floor space extends out 5 ft from both sides of the door Door adjacent to revolving door is accessible and unlocked Doors opening into hazardous area have hardware that is knurled or roughened Notes:	Yes No No Yes Yes	
At least 18" clear floor space on pull side of door Threshold maximum 18" high, beveled on both sides Hardware operable with a cleared fits (no conventional door knobs or thumb latch devices) Hardware minimum 36", maximum 48" above the floor Clear, level floor space extends out 5 ft from both sides of the door Door adjacent to revolving door is accessible and unlocked Doors opening into hazardous area have hardware that is knurled or roughened Notes: Restrooms	Yes No No Yes	N/A
At least 18" clear floor space on pull side of door Threshold maximum W.* high, beveled on both sides Hardware operable with a closed fist (no conventional door knobs or thumb latch devices) Hardware minimum 36", maximum 48" above the floor Clear, level floor space extends out 5 ft from both sides of the door Door adjacent to revolving door is accessible and unlocked Doors opening into hazardous area have hardware that is knufed or roughened Notes: Restrooms Description	Yes No No Yes Yes Yes	
At least 18" clear floor space on pull side of door Threshold maximum 18" high, beveled on both sides Hardware operable with a cleared fits (no conventional door knobs or thumb latch devices) Hardware minimum 36", maximum 48" above the floor Clear, level floor space extends out 5 ft from both sides of the door Door adjacent to revolving door is accessible and unlocked Doors opening into hazardous area have hardware that is knurled or roughened Notes: Restrooms	Yes No No Yes Yes	N/A
At least 18" clear floor space on pull side of door Threshold maximum 18" high, beveled on both sides Hardware operable with a closed fist (no conventional door knobs or thumb latch devices) Hardware minimum 36", maximum 48" above the floor Clear, level floor space extends out 5 ft from both sides of the door Door adjacent to revolving door is accessible and unlocked Doors opening into hazardous area have hardware that is knurled or roughened Notes: Restrooms Description S ft turning space measured 12" from the floor	Yes No No Yes Yes Yes	N/A
At least 18" clear floor space on pull side of door Threshold maximum 18" high, beveled on both sides Hardware operable with a closed fist (no conventional door knobs or thumb latch devices) Hardware minimum 36", maximum 48" above the floor Clear, level floor space extends out 5 ft from both sides of the door Door adjacent to revolving door is accessible and unlocked Doors opening into hazardous area have hardware that is knurled or roughened Notes: Restrooms Description S ft turning space measured 12" from the floor At least one Sink Description Clear floor space of 30" by 48" to allow a forward approach	Yes No No Yes Yes Yes Yes	N/A Comments
At least 18" clear floor space on pull side of door Threshold maximum 18" high, beveled on both sides Hardware operable with a clear off it, for conventional door knobs or thumb latch devices) Hardware minimum 36", maximum 48" above the floor Clear, level floor space extends out 5 ft from both sides of the door Door adjacent to revolving door is accessible and unlocked Doors opening into hazardous area have hardware that is knurled or roughened Notes: Restrooms Description 5 ft turning space measured 12" from the floor At least one Sink Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim	Yes No No No Yes Yes Yes Yes Yes	Comments Comments
At least 18" clear floor space on pull side of door Threshold maximum 18" high, beveled on both sides Hardware operable with a close off it for conventional door knobs or thumb latch devices) Hardware minimum 36", maximum 48" above the floor Clear, level floor space extends out 5 ft from both sides of the door Door adjacent to revolving door is accessible and unlocked Doors opening into hazardous area have hardware that is knurled or roughened Notes: Restrooms Description 5 ft turning space measured 12" from the floor At least one Sisk Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedesta for legs, height 34" to top of rim Extends at least 22" from the wall	YES No No Yes Yes YES YES YES No	N/A Comments
At least 18" clear floor space on pull side of door Threshold maximum 18" high, beveled on both sides Hardware operable with a clear off it, for conventional door knobs or thumb latch devices) Hardware minimum 36", maximum 48" above the floor Clear, level floor space extends out 5 ft from both sides of the door Door adjacent to revolving door is accessible and unlocked Doors opening into hazardous area have hardware that is knurled or roughened Notes: Restrooms Description 5 ft turning space measured 12" from the floor At least one Sink Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim	Yes No No No Yes Yes Yes Yes	Comments Comments
At least 18" clear floor space on pull side of door Threshold maximum 18" high, beveled on both sides Hardware operable with a closed fist (no conventional door knobs or thumb latch devices) Hardware operable with a closed fist (no conventional door knobs or thumb latch devices) Hardware minimum 36", maximum 48" above the floor Clear, level floor space extends out 5 ft from both sides of the door Door adjacent to revolving door is accessible and unlocked Doors opening into hazardous area have hardware that is knurled or roughened Notes: Restrooms Description S ft turning space measured 12" from the floor At least one Sink Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high	YES NO NO YES	Comments Comments
At least 18" clear floor space on pull side of door Threshold maximum 18" high, beveled on both sides Hardware operable with a close off fit (no conventional door knobs or thumb latch devices) Hardware operable with a close off fit (no conventional door knobs or thumb latch devices) Hardware minimum 36", maximum 48" above the floor Clear, level floor space extends out 5 ft from both sides of the door Door adjacent to revolving door is accessible and unlocked Doors opening into hazardous area have hardware that is knufled or roughened Notes: Restrooms Description 5 ft turning space measured 12" from the floor At least one Sink Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucts operable with closed fist (lever or spring activated handle) At least one Stall —Single use restrooms	YES No No Yes	Comments Comments 17.5in
At least 18" clear floor space on pull side of door Threshold maximum 18" high, beveled on both sides Hardware openable with a close off its (no conventional door knobs or thumb latch devices) Hardware minimum 36", maximum 48" above the floor Clear, level floor space extends out 5 ft from both sides of the door Door adjacent to revolving door is accessible and unlocked Doors opening into hazardous area have hardware that is knurled or roughened Notes: Restrooms Description 5 ft turning space measured 12" from the floor At least one Sink Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucts openable with locked fist (lever or spring activated handle) At least one Sink Lestropies use restrooms Description	YES No Yes	Comments Comments
At least 18" clear floor space on pull side of door Threshold maximum 18" high, beveled on both sides Hardware operable with a clear off it (no conventional door knobs or thumb latch devices) Hardware minimum 36", maximum 48" above the floor Clear, level floor space extends out 5 ft from both sides of the door Door adjacent to revolving door is accessible and unlocked Doors opening into hazardous area have hardware that is knurled or roughened Notes: Restrooms Description 5 ft turning space measured 12" from the floor At least one 5ink Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Estends at least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucets operable with closed fist (lever or spring activated handle) At least one Stall —single use restrooms Description Accessible to person using wheelchair at 60" wideby 72" deep	YES No YES YES YES YES YES No YES YES No YES No No	Comments 17.Sin Comments
At least 18" clear floor space on pull side of door Threshold maximum 18" high, beveled on both sides Hardware operable with a close off it for conventional door knobs or thumb latch devices) Hardware minimum 36", maximum 48" above the floor Clear, level floor space extends out 5 ft from both sides of the door Door adjacent to revolving door is accessible and unlocked Doors opening into hazardous area have hardware that is knurled or roughened Notes: Restrooms Description 5 ft turning space measured 12" from the floor At least one Sisk Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedesta for legs, height 34" to top of rim Extends at least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucets operable with closed fist (lever or spring activated handle) At least one Sial — Single use restrooms Description Caccessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide	YES NO NO YES YES YES YES YES YES YES NO YES NO NO NO	Comments Comments 17.5in
At least 18" clear floor space on pull side of door Threshold maximum 18" high, beveled on both sides Hardware operable with a clear off it (no conventional door knobs or thumb latch devices) Hardware minimum 36", maximum 48" above the floor Clear, level floor space extends out 5 ft from both sides of the door Door adjacent to revolving door is accessible and unlocked Doors opening into hazardous area have hardware that is knurled or roughened Notes: Restrooms Description 5 ft turning space measured 12" from the floor At least one 5ink Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Estends at least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucets operable with closed fist (lever or spring activated handle) At least one Stall —single use restrooms Description Accessible to person using wheelchair at 60" wideby 72" deep	YES No YES YES YES YES YES No YES YES No YES No No	Comments 17.Sin Comments
At least 18" clear floor space on pull side of door Threshold maximum 18" high, beveled on both sides Hardware poemble with a close off it (no conventional door knobs or thumb latch devices) Hardware minimum 36", maximum 48" above the floor Clear, level floor space extends out 5 ft from both sides of the door Door adjacent to revolving door is accessible and unlocked Doors opening into hazardous area have hardware that is knurled or roughened Notes: Restrooms Description 5 ft turning space measured 12" from the floor At least one Sink Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall Open knees pace a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucets openable with closed fist (lever or spring activated handle) At least one Sall — Single use restrooms Description Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door is 36" wide Stall door is 36" wide	YES NO YES	Comments 17.Sin Comments
At least 18" clear floor space on pull side of door Threshold maximum 18" high, beveled on both sides Hardware porable with a close off its (no conventional door knobs or thumb latch devices) Hardware minimum 36", maximum 48" above the floor Clear, level floor space extends out 5 ft from both sides of the door Door adjacent to revolving door is accessible and unlocked Doors opening into hazardous area have hardware that is knurled or roughened Notes: Restrooms Description Sit turning space measured 12" from the floor At least one Sink Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucets operable with Cosed fist (lever or spring activated handle) At least one Sink—Single use restrooms Description Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 56" wide Stall door is 56" wide Stall door is 56" wide Stall door is 56" dide Stall door is 56" dide Stall door is operable with a closed fist, and 32" above the floor	YES NO NO YES YES YES YES NO NO YES YES YES YES YES YES YES YES	Comments 17.Sin Comments
At least 18" clear floor space on pull side of door Threshold maximum 18" high, beveled on both sides Hardware porable with a clear off it (no conventional door knobs or thumb latch devices) Hardware minimum 36", maximum 48" above the floor Clear, level floor space extends out 5 ft from both sides of the door Door adjacent to revolving door is accessible and unicked Doors opening into hazardous area have hardware that is knurled or roughened Notes: Restrooms Description Sh turning space measured 12" from the floor At least one Sink Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucts operable with closed fist, (lever or spring activated handle) At least one Stall —Single use restrooms Description Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 56" wide Stall door sings out	Yes No No Yes Yes Yes Yes No No Yes Yes Yes No Yes No No No Yes Yes No	Comments 17.Sin Comments
At least 18" clear floor space on pull side of door Threshold maximum 18" high, beveled on both sides Hardware postable with a close off it, no conventional door knobs or thumb latch devices) Hardware minimum 36", maximum 48" above the floor Clear, level floor space extends out 5 ft from both sides of the door Door adjacent to revolving door is accessible and unlocked Doors opening into hazardous area have hardware that is knurled or roughened Notes: Restrooms Description 5 ft turning space measured 12" from the floor At least one Sink Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucets operable with closed fist (lever or spring activated handle) At least one Siall—Single use restrooms Description Stall door is 36" wide Stall door sis 56" wide Stall door is 56" dooing Stall door is 56" high Tolet	YES No No Yes Yes Yes Yes Yes No No Yes Yes Yes Yes No No No No No	Comments 17.Sin Comments 34.Sin
At least 18" clear floor space on pull side of door Threshold maximum 18" high, beveled on both sides Hardware perable with a close off its (no conventional door knobs or thumb latch devices) Hardware minimum 36", maximum 48" above the floor Clear, level floor space extends out 5 ft from both sides of the door Door adjacent to revolving door is accessible and unlocked Doors opening into hazardous area have hardware that is knurled or roughened Notes: Restrooms Description Sit turning space measured 12" from the floor At least one Sink Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucets operable with closed fist (lever or spring activated handle) At least one Sails—Single use restrooms Description Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door is 36" wide Stall door is 96" side Stall door is operable with a closed fist, and 32" above the floor Cost hook is 54" high Toilet Description	YES No No Yes Yes Yes Yes Yes Yes No	Comments 17.Sin Comments
At least 18" clear floor space on pull side of door Threshold maximum 15" high, beveled on both sides Hardware openable with a clease filt (no conventional door knobs or thumb latch devices) Hardware minimum 36", maximum 48" above the floor Clear, level floor space extends out 5 ft from both sides of the door Door adjacent to revolving door is accessible and unlocked Doors opening into hazardous area have hardware that is knurled or roughened Notes: **Restrooms** Description 5 ft turning space measured 12" from the floor At least one Sink Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucets operable with closed fist (lever or spring activated handle) At least one Sill—Single use restrooms Description Stall door is 36" wide Stall door is 36" wide Stall door sings out Stall door is 56" wide Stall door sings out Stall door sings out Stall door is 56" high Toilet To	YES NO NO YES YES YES YES YES YES YES YES	Comments 17.Sin Comments 34.Sin
At least 18" clear floor space on pull side of door Threshold maximum 18" high, beveled on both sides Hardware peralbe with a clear off it (no conventional door knobs or thumb latch devices) Hardware minimum 36", maximum 48" above the floor Clear, level floor space extends out 5 ft from both sides of the door Door adjacent to revolving door is accessible and unicked Doors opening into hazardous area have hardware that is knurled or roughened Notes: Restrooms Description Sh turning space measured 12" from the floor At least one Sink Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucts operable with closed fist, (lever or spring activated handle) At least one Stall — Single use restrooms Description Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door is 56" wide Stall door is self closing Stall door is one center to nearest side wall	YES No No Yes Yes Yes Yes Yes Yes No	Comments 17.Sin Comments 34.Sin
At least 18" clear floor space on pull side of door Threshold maximum 15" high, beveled on both sides Hardware openable with a clease filt (no conventional door knobs or thumb latch devices) Hardware minimum 36", maximum 48" above the floor Clear, level floor space extends out 5 ft from both sides of the door Door adjacent to revolving door is accessible and unlocked Doors opening into hazardous area have hardware that is knurled or roughened Notes: **Restrooms** **Restrooms** Description 5 ft turning space measured 12" from the floor At least one Sink Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucets operable with closed fist (lever or spring activated handle) At least one Stall —Single use restrooms Description Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" vide Stall door is 36" wide Stall door is self closing Stall door is 54" high Toilet **Description** 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture	Yes No Yes Yes	Comments 17.Sin Comments 34.Sin
At least 18" clear floor space on pull side of door Threshold maximum 15" high, beveled on both sides Hardware openable with a clease filt (no conventional door knobs or thumb latch devices) Hardware minimum 36", maximum 48" above the floor Clear, level floor space extends out 5 ft from both sides of the door Door adjacent to revolving door is accessible and unlocked Doors opening into hazardous area have hardware that is knurled or roughened Notes: Restrooms Description Sh turning space measured 12" from the floor At least one Sink Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover expose oppe pipes with insulation Faucets openable with closed fist (lever or spring activated handle) At least one Sink Stall door is 36" wide Stall door is 36" wide Stall door is self-closing Stall door or openable with a closed fist, and 32" above the floor Cost hook is 54" high Toilet Description Description Description Description Description Description	Yes No No Yes Yes	Comments 17.Sin Comments 34.Sin
At least 18" clear floor space on pull side of door Threshold maximum 18" high, beveled on both sides Hardware penalbe with a close off it (no conventional door knobs or thumb latch devices) Hardware minimum 36", maximum 48" above the floor Clear, level floor space extends out 5 ft from both sides of the door Door adjacent to revolving door is accessible and unlocked Doors opening into hazardous area have hardware that is knurled or roughened Notes: Restroms Description Sit turning space measured 12" from the floor At least one Sink Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucets openable with closed fist (lever or spring activated handle) At least one salls—Single use restrooms Description Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 6" wide Stall door is openable with closed fist, and 32" above the floor Coat hook is 54" high Toilet Description 18" from center to nearest side wall 42" minimum clars appace from center to farthest wall or fisture Top of seat 17"-13" above the floor Gorab Bass Description On back and side wall closest to toilet	YES No No Yes Yes Yes Yes Yes No No No Yes Yes Yes Yes No	Comments 17.5in Comments 2. Comments Comments Comments Comments
At least 18" clear floor space on pull side of door Threshold maximum %" high, beveled on both sides Hardware protable with a close fits (no conventional door knobs or thumb latch devices) Hardware minimum 36", maximum 48" above the floor Clear, level floor space extends out 5 f from both sides of the door Door sligicarent to revolving door is accessible and unlocked Doors opening into hazardous area have hardware that is knurled or roughened Notes: Restrooms Description 5 ft turning space measured 12" from the floor At least me Sink Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legt, height 34" to top of rim Extends at least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucets openable with closed fits (lever or spring activated handle) At least one Silal Description At least one Silal—Single use restrooms Description Sal door is 36" wide Sal door is 36" wide Sal door is self closing Sal door sa a pull latch Lock on stall door is openable with a closed fist, and 32" above the floor Coat hook is 54" high Tolleg Description 18" from center to nearest side wall 42" minimum dear space from center to farthest wall or floature Top of seat 17"-19" above the floor Gest based shad wall closest to toilet 13" diameter	YES NO YES YES YES YES YES YES YES YES	Comments Comments 17.5in Comments Comments Comments Comments
At least 18" clear floor space on pull side of door Threshold maximum yi "pilp, beveled on both sides Hardware possible with a closed fits (no conventional door knobs or thumb latch devices) Hardware minimum 36", maximum 48" above the floor Clear, level floor space extends out 5 ft from both sides of the door Door adjacent to revolving door is accessible and unlocked Doors opening into hazardous area have hardware that is knurled or roughened Notes: Restrooms Description S ft turning space measured 12" from the floor At least ane Sink Opening the space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Estands at least 22" from the will Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed jobes with insulation Faucets openable with closed fist (lever or spring activated handle) At least one Sizell—Single use restrooms Description Accessible to person using wheelchair at 60" wideby 72" deep Stall door is sof dicting Stall door is one sa pull latch Lock on stall door is openable with a closed fist, and 32" above the floor Cost hook is 54" high Totlet Description On back and side wall closest to tollet 13" "disearance to wall Description On back and side wall closest to tollet 13" "disearance to wall	YES NO YES YES YES YES YES YES YES YES	Comments 17.5in Comments 2. Comments Comments Comments Comments
At least 18" clear floor space on pull side of door Threshold maximum yi 'pilp, beveled on both sides Hardware minimum 36", maximum 48" above the floor Clear, level floor space estends out 5 ff from both sides of the door Door adjacent to revolving door is accessible and uncked Doors opening into hazardous area have hardware that is knurled or roughened Notes: Restrooms Description S ft turning space measured 12" from the floor At least no Sink Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, helpit 34" to top of rim Extends at least 22" from the vall Open knee space a minimum 19" deep, 30" width, and 22" high Cover exposed pipse with insulation Faucets openable with closed fist (lever or spring activated handle) At least nos Stall Description At least as Sink Obscription Faucets openable with closed fist (lever or spring activated handle) At least nos Stall—Single use restrooms Description Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door is self closing Stall door is self closing Stall door is self closing Stall door is apull latch Lock on stall door is openable with a closed fist, and 32" above the floor Cost hook is 54" high Tothet Description On back and side wall closest to tollet 13" diameter 13" from center to nearest side wall on back and side wall closest to tollet 13" diameter	YES No No Yes Yes Yes Yes Yes No No No Yes	Comments Comments 17.5in Comments Comments Comments Comments
At least 18" clear floor space on pull side of door Threshold maximum %" high, beveled on both sides Hardware penalhe with a closed fits (no conventional door knobs or thumb latch devices) Hardware minimum 36", maximum 48" above the floor Clear, level floor space extends out 5 ft from both sides of the door Door adjacten to revolving door a scessible and unlocked Doors opening into hazardous area have hardware that is knurled or roughened Notes: **Restrooms** Description Sit turning space measured 12" from the floor At least one Shalt Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Estends at least 22" from the will be started as least 22" from the started as least between the started as least 22" from the started 22" from the star	YES NO YES YES YES YES YES YES YES YES	Comments Comments 17.5in Comments Comments Comments Comments
At test 135" clear floor space on pull side of door Threshold maximum N° high, beveled on both sides Hardware minimum 16", maximum 48" above the floor Clear, level floor space extends out 5 if from both sides of the door Door adjacent to revolving door is accessible and unlocked Doors opening into hazardous area have hardware that is knurled or roughened Notes: **Restrooms** **Description** **Description** **Si fruming space measured 12" from the floor Attestant existing **Description** **Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall **Open representative through the space of the space	YES NO NO YES YES YES YES YES YES YES YES	Comments 17.5in Comments 2. Comments Comments Comments Comments
An itest 18" clear floor space on pull ide of abov. Threshold maximum X" high, beveled on both sides Introduced organism with a clear file (no conventional door knobs or thumb latch devices) Introduced problem with a clear file (no conventional door knobs or thumb latch devices) Introduced problem with a clear file file conventional door knobs or thumb latch devices) Introduced problem with clear file file file file file file file file	YES NO NO YES YES YES YES YES YES YES YES	Comments 17.5in Comments 2. Comments Comments Comments Comments
At least 18" clear floor space on pull ide of door Threshold maximum Ni* Nigh, beveled on both sides Hardwave perinimum 36", maximum 46" above the floor Clear, level floor space extends on St from cohers idea of the door Door adjacent to revolving door is accessible and unlocked Doors opening into hazardous area have hardware that is knufred or roughened Notes: **Restrooms** **Description** **Si turning space measured 12" from the floor **Alceast measured 12" from the support floor floo	YES NO NO YES YES YES YES YES YES YES YES	Comments Comments 17.5in Comments Comments Comments Comments Comments Comments
An itest 18" clear floor space on pull ide of abov. Threshold maximum X" high, beveled on both sides Introduced organism with a clear file (no conventional door knobs or thumb latch devices) Introduced problem with a clear file (no conventional door knobs or thumb latch devices) Introduced problem with a clear file file conventional door knobs or thumb latch devices) Introduced problem with clear file file file file file file file file	YES NO NO YES YES YES YES YES YES YES YES	Comments Comments 17.5in Comments Comments Comments Comments Comments Comments

Floors, Drinking Fountains, Telephones	N/A		
Signs, Signals, and Switches	YES		
Switches, Controls and Signs			
Description		Comments	
Switches and controls for light, heat, ventilation, windows, fire alarms, thermostats, etc, must be a minimum of 36" and a maximum of 48" above the floor for a forward reach, a maximum of 54" for a side reach	yes		
Electrical outlets centered no lower than 18" above the floor	yes		
Warning signals must be visual as well as audible	Yes		
Notes:			
Swimming Pool/ Lake beach	N/A		
Shower Rooms	N/A		
Picknicking	N/A		
	N/A		

Facility Name: Cabot Park Size (Ac): 11.6 acres Address: 101 Eastside Parkway, Newtonville Ward: 2 General Facility Notes: Sidewalk along Eastside Pkwy provides accessibility to tennis courts and off-leash dog area.; no accessible pathways in the park; no accessible route connecting amenities; 2019 school construction included accessible play structures, basketball court, and other schoolyard pavement games; accessible path connections to new sidewalk and curb cut ramps at Eastside Pkwy. YES Site Furnishings Comments Description Yes Tables & Benches YES Number of Tables YES 2 Picnic tables Located adjacent to accessible paths No There are no benches along an accessible path Back and Arm Rests Yes 12 out of 16 benches have backrests Located adjacent to accessible paths Yes Notes: Trails & Paths YES Comments Surface (A=Asphalt, C=Concrete, SD= stone dust, NS= naturally surfaced, B=Boardwalk, BR=Bridge) YES Asphalt Dimensions (width) YES 5-ft minimum Rails NO Signage for visually impaired NO Notes: YES Play Areas Comments Facility Type (3-5 Yrs,5-12 Yrs) YES 3-5 yrs; 5-12 yrs Same experience provided to all YES Located adjacent to accessible paths No Enough space between equipment for wheelchair Yes Notes: Game Areas YES Comments Facility Type (RF=Rectangular Fields, BF= Ballfields, BK=Basketball, TN=Tennis, BC=Bocce) 3 BF, 2 BK, 2 TN, 4 BC Access Routes Located adjacent to accessible paths Yes Ballfields are adjacent to accessible route Berm cuts onto courts NA Equipment Yes Not on accessible route Spectator Seating Notes: N/A N/A Boat Docks Fishing Facilities N/A N/A N/A YES **Community Gardens** Ramps Site Access, Path of Travel, Entrances Path of Travel Description Comments Path does not require the use of stairs Yes Path does not require the use of wheelchair ramp Yes Path is stable, firm and slip resistant Yes Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50). Yes Continuous common surface, no changes in level greater than ½ inch Yes ntrances Comments Description No signage Primary public entrances accessible to person using wheelchair, must be signed, gotten to independently, and not be the service entrance Yes Level space extending 5 ft. from the door, interior and exterior of entrance doors Yes Minimum 32" clear width opening (i.e. 36" door with standard hinge) Yes At least 18" clear floor area on latch, pull side of door Yes Door handle no higher than 48" and operable with a closed fist Yes Vestibule is 4 ft plus the width of the door swinging into the space N/A Entrance(s) on a level that makes elevators accessible N/A Door mats less than 1/1" thick are securely fastened Yes Door mats more than ¾" thick are recessed Yes N/A Signs at non-accessible entrance(s) indicate direction to accessible entrance No Emergency egress – alarms with flashing lights and audible signals, sufficiently lighted Yes YES Stairs and Doors Description Comments Minimum 32" clear opening Yes At least 18" clear floor space on pull side of door Yes Threshold maximum $\ensuremath{\mathbb{M}}''$ high, beveled on both sides No Hardware operable with a closed fist (no conventional door knobs or thumb latch devices) Yes Hardware minimum 36", maximum 48" above the floor Clear, level floor space extends out 5 ft from both sides of the door

Door adjacent to revolving door is accessible and unlocked	N/A	
Doors opening into hazardous area have hardware that is knurled or roughened	N/A	
Notes:		
Restrooms	YES	
Description		Comments
5 ft turning space measured 12" from the floor	Yes	
At least one Sink	1	Comments
Description Clear floor space of 30" by 48" to allow a forward approach	Yes	Comments
Mounted without pedestal or legs, height 34" to top of rim	Yes	
Extends at least 22" from the wall	yes	
Open knee space a minimum 19" deep, 30" width, and 27" high	Yes	
Cover exposed pipes with insulation	Yes	
Faucets operable with closed fist (lever or spring activated handle)	Yes	
At least one Stall		
Description		Comments
Accessible to person using wheelchair at 60" wideby 72" deep	No	Single use bathrooms
Stall door is 36" wide	Yes	
Stall door swings out	Yes	
Stall door is self closing Stall door has a pull latch	No	
Lock on stall door is operable with a closed fist, and 32" above the floor	No Yes	
Coat hook is 54" high	No	62in
Toilet	1	I.
Description		Comments
18" from center to nearest side wall	No	
42" minimum clear space from center to farthest wall or fixture	Yes	
Top of seat 17"-19" above the floor	Yes	
Grab Bars		
Description		Comments
On back and side wall closest to toilet	No	
1½" diameter 1½" clearance to wall	Yes	
Located 30" above and parallel to the floor	No Yes	
Acid-etched or roughened surface	Yes	
42" long	No	30in
Fixtures .		
Description		Comments
1¼" diameter	Yes	
1½" clearance to wall	Yes	
Located 30" above and parallel to the floor	No	33.5in
Notes:		
	WEG	
Floors, Drinking Fountains, Telephones	YES	
Floors Paragination	1	Ica
Description Non-slip surface	No	Comments
Carpeting is high-density, low pile, non-absorbent, stretched taut, securely anchored	N/A	
Corridor width minimum is 3 ft	Yes	
Objects (signs, ceiling lights, fixtures) can only protrude 4" into the path of travel from a height of 27" to 80" above the floor	Yes	
Notes:		
Signs, Signals, and Switches	YES	
Switches, Controls and Signs		
Description		Comments
Switches and controls for light, heat, ventilation, windows, fire alarms, thermostats, etc, must be a minimum of 36" and a maximum of 48" above the floor for a forward reach, a maximum of 54" for a side reach	Yes	
Electrical outlets centered no lower than 18" above the floor	Yes	
Warning signals must be visual as well as audible	Yes	
Notes:		
Swimming Pool/ Lake beach	N/A	
Shower Rooms	N/A	
Picknicking	N/A	
Off Leash Dog Areas (OLA)	YES	
Description		Comments
Access Routes		I
Located adjacent to accessible paths	yes	
Area accesible	no	
Notes:		

Facility Name: Captain Ryan Park 'Police Park'			
Size (Ac): .4 acre			
Address: Washington Street and Cherry Street, West Newton			
Ward: 3			
General Facility Notes: Small passive pocket park; accessible pathways with benches.			
Site Furnishings YES			
Description	Yes	Comments	
Tables & Benches			
Number of Benches		4	
Number of Tables	YES	0	
Located adjacent to accessible paths Back and Arm Rests	yes		
Grills	yes		
Located adjacent to accessible paths	no		
Trash Cans			
Located adjacent to accessible paths	no		
Picnic Shelters			
Located adjacent to accessible paths	no		
Notes:			
Trails & Paths	YES		
Description	1.5	Comments	
Surface (A=Asphalt, C=Concrete, SD= stone dust, NS= naturally surfaced, B=Boardwalk, BR=Bridge)	yes	Asphalt	
Dimensions (width)	No		
Rails	No		
Signage for visually impaired	No		
Benches Notes:	yes		
Play Areas	N/A		
Game Areas	N/A		
Boat Docks	N/A		
Fishing Facilities	N/A		
Community Gardens	N/A		
Parking	N/A		
Ramps	N/A		
Site Access, Path of Travel, Entrances	YES		
Path of Travel			
Description		Comments	
Path does not require the use of stairs	No No		
Path does not require the use of wheelchair ramp Path is stable, firm and slip resistant	No YES		
Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50).	1.3	unknown, pathways are generally gradually slopped.	
Continuous common surface, no changes in level greater than ½ inch	YES	, , , , , , , , , , , , , , , , , , ,	
Any objects protruding onto the pathway must be detected by a person with a visual disability using a cane	No	not applicable	
Objects protruding more than 4" from the wall must be within 27" of the ground, or higher than 80"	No	not applicable	
Curb on the pathway must have curb cuts at drives, parking and drop-offs	No	not applicable	
Notes:			
Stairs and Doors	N/A		
Restrooms	N/A		
Floors, Drinking Fountains, Telephones	N/A		
Signs, Signals, and Switches	N/A		
Swimming Pool/ Lake beach	N/A		
Shower Rooms	N/A		
Picknicking	N/A		
Off Leash Dog Areas (OLA)	N/A		
	·		

Facility Name: Carleton Park			
Size (Ac): .1 acre			
Address: Carleton Street, Newton Corner			
Ward: 1			
General Facility Notes: The city's smallest park; level lawn area; no on-street parking; accessible sto	ne dust se	ating area with henches and nignic table: amenities are	
accessible from sidewalk.	iic aast se	and a second of the plant case, and mentioned are	
	IVEC.		
Site Furnishings	YES		
Description		Comments	
Tables & Benches			
Number of Benches	Yes	2	
Number of Tables	Yes	1	
Located adjacent to accessible paths	Yes	one bench and one picknick table adjacent to stone dust area	
Back and Arm Rests	Yes	both benches have backs but no arm rests	
<u>Grills</u>			
Located adjacent to accessible paths	N/A	N/A	
<u>Trash Cans</u>			
Located adjacent to accessible paths	no		
<u>Picnic Shelters</u>			
Located adjacent to accessible paths	no		
Notes:			
Trails & Paths	N/A		
Play Areas	N/A		
Game Areas	N/A		
Boat Docks	N/A		
Fishing Facilities	N/A		
Community Gardens	N/A		
Parking	N/A		
Ramps	N/A		
Site Access, Path of Travel, Entrances	YES		
Site Access			
Description		Comments	
Accessible path of travel from passenger disembarking area and parking area to accessible entrance	No	No parking area	
Surface evenly paved or hard-packed	yes		
Ponding of water?	no		
Path of Travel			
Description		Comments	
Path does not require the use of stairs	yes		
Path does not require the use of wheelchair ramp	yes		
Path is stable, firm and slip resistant	yes		
Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50).	yes		
Continuous common surface, no changes in level greater than ½ inch	yes		
	yes		
Notes:			
Stairs and Doors	N/A		
Restrooms	N/A		
Floors, Drinking Fountains, Telephones	N/A		
	N/A		
Signs, Signals, and Switches			
Swimming Pool/ Lake beach	N/A		
Shower Rooms N/A			
cknicking N/A			
Off Leash Dog Areas (OLA)	N/A		

Facility Name: Chaffin Park Size (Ac): 1.74 acre Address: Corner of Vernon Street and Centre Street, Newton Corner General Facility Notes: Paved accessible asphalt path from Centre st. and Vernon st. corner; accessible parking space in adjacent pkg lot on Vernon St.; Contiguous to Farlow Park; 2-5 yr play structure. YES Site Furnishings Comments Yes Tables & Benches Yes 7 (4 Double 3 Single) Number of Tables YES 1 Game Table Located adjacent to accessible paths YES YES Back and Arm Rests Located adjacent to accessible paths yes rash Cans Located adjacent to accessible paths yes 1 Big Belly Picnic Shelters Located adjacent to accessible paths NA Notes: YES Trails & Paths Comments Surface (A=Asphalt, C=Concrete, SD= stone dust, NS= naturally surfaced, B=Boardwalk, BR=Bridge) YES A With cranite curbing Dimensions (width) YES 6 ft Rails Signage for visually impaired No Notes: Play Areas Comments Facility Type (3-5 Yrs,5-12 Yrs) Yes 2 5-yrs Same experience provided to all no ccess Routes Yes Enough space between equipment for wh Yes Notes:Playground built in 2007 N/A N/A N/A **Boat Docks** Fishing Facilities Community Gardens Parking Description Comments Parking Amenities (L=lot, ST=street) Yes Accessible space located closest to accessible entrance Yes Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft Yes Minimum width of 13 ft includes 8 ft space plus 5 ft access aisle Yes Minimum of 1 van space for every accessible space, 8' wide + 8' aisle. N/A Sign with international symbol of accessibility at each space Yes Sign 5'-8' to top of sign Yes Surface evenly paved or hard-packed (no cracks) Yes Curbcut to pathway from parking lot at each space if sidewalk (curb) is present . Yes Curbcut is a minimum width of 3 ft, excluding sloped sides, has sloped sides, all slopes not to exceed 1:12, and textured or painted yellow Yes Notes: N/A YES Site Access, Path of Travel, Entrances Comments Accessible path of travel from passenger disembarking area and parking area to accessible entrance Yes Surface evenly paved or hard-packed Yes Ponding of water? No Path of Travel Description Comments Path does not require the use of stairs Yes Path does not require the use of wheelchair ramp Yes YES Path is stable, firm and slip resistant Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50). YES Continuous common surface, no changes in level greater than $\mbox{\%}$ inch YES Any objects protruding onto the pathway must be detected by a person with a visual disability using a cane no Objects protruding more than 4" from the wall must be within 27" of the ground, or higher than 80" YES Curb on the pathway must have curb cuts at drives,parking and drop-offs N/A Description Comments Primary public entrances accessible to person using wheelchair, must be signed, gotten to independently, and not be the service entrance YES Level space extending 5 ft. from the door, interior and exterior of entrance doors YES Minimum 32" clear width opening (i.e. 36" door with standard hinge) 30" At least 18" clear floor area on latch, pull side of door YES Door handle no higher than 48" and operable with a closed fist YES Vestibule is 4 ft plus the width of the door swinging into the space YES YES Door mats less than 1/2" thick are securely fastened YES

Door mats more than 1/1" thick are recessed	YES	
Grates in path of travel have openings of ½" maximum	No	
Signs at non-accessible entrance(s) indicate direction to accessible entrance	YES	
Emergency egress – alarms with flashing lights and audible signals, sufficiently lighted	YES	
Notes:		
Stairs and Doors	YES	
Stairs		
Description		Comments
Open risers	No	
Nosings not projecting Treads no less than 11" wide	YES YES	
Handrails on both sides	No	
Handrails 34"-38" above tread	No	
Handrail extends a minimum of 1' beyond top and bottom riser (if no safety hazard and space permits)	No	
Handgrip oval or round	No	
Handgrip has a smooth surface	YES	
Handgrip diam. 1½" - 1½"	No	
1½" clearance between wall and handrail	No	
Doors		
Description		Comments
Minimum 32" clear opening	YES	
Threshold maximum %" high, beveled on both sides Hardware operable with a closed fist (no conventional door knobs or thumb latch devices)	YES	
Hardware minimum 36", maximum 48" above the floor	YES	
Clear, level floor space extends out 5 ft from both sides of the door	YES	
Door adjacent to revolving door is accessible and unlocked	N/A	
Doors opening into hazardous area have hardware that is knurled or roughened	N/A	
Notes:	•	
Restrooms	YES	
Description		Comments
5 ft turning space measured 12" from the floor	YES	
At least one Sink		-
Description Collin to Coll	NEC.	Comments
Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim	YES YES	
Extends at least 22" from the wall	YES	
Open knee space a minimum 19" deep, 30" width, and 27" high	YES	
Cover exposed pipes with insulation	YES	
Faucets operable with closed fist (lever or spring activated handle)	YES	
At least one Stall		
Description		Comments
Accessible to person using wheelchair at 60" wideby 72" deep	YES	
Stall door is 36" wide	YES	
Stall door swings out	YES	
Stall door is self closing	No	
Stall door has a pull latch	No	
Lock on stall door is operable with a closed fist, and 32" above the floor	No	
Coat hook is 54" high	No	
Cost hook is 54" high Tollet		Comments
Coat hook is 54" high Tollet Description	No	Comments
Cost hook is 54" high Tollet		Comments
Coat hook is 54° high Toilet Description 18° from center to nearest side wall	No YES	Comments
Coat hook is 54" high Toilet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture	No YES YES	Comments
Cost hook is \$4* high Toilet Description 18* from center to nearest side wall 42* minimum clear space from center to farthest wall or fixture Top of seat 17*-19* above the floor Grab Bars Description	YES YES YES	Comments Comments
Coat hook is 54* high Toilet Description 18* from center to nearest side wall 42* minimum clear space from center to farthest wall or fixture Top of seat 17*-19* above the floor Grab Bars On back and side wall closest to toilet	YES YES YES	
Coat hook is 54° high Tollet Description 18° from center to nearest side wall 42° minimum clear space from center to farthest wall or fixture Top of seat 17"-30° above the floor Grab Bars Description On back and side wall closest to toilet 11s° diameter	YES YES YES YES YES YES	
Coat hook is 54" high Tollet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor Grab Bars Description On back and side wall closest to tollet 1½" clearance to wall	YES YES YES YES YES YES YES YES	
Coat hook is 54" high Tollet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor Grab Bars Description On back and side wall closest to toilet 11%" diameter 11%" clearance to wall Located 30" above and parallel to the floor	YES	
Coat hook is 54° high Tablet Description 18° from center to nearest side wall 42° minimum clear space from center to farthest wall or fixture Top of seat 17°-19° above the floor Grab Barx Description On back and side wall closest to toilet 1%° clearance to wall Located 30° above and parallel to the floor Acid-etched or roughened surface	YES	
Coat hook is 54" high Tollet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor Grab Bars Description On back and side wall closest to toilet 11%" diameter 11%" clearance to wall Located 30" above and parallel to the floor	YES	
Coat hook is 54° high Tollet Description 18° from center to nearest side wall 42° minimum clear space from center to farthest wall or fixture Top of seast 17°-19° above the floor Grab Bars Description On back and side wall closest to toilet 1¾° clearance to wall Located 30° above and parallel to the floor Acid-etched or roughened surface 42° long 42° long	YES	
Coat hook is 54" high Tollet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seast 17"-19" above the floor Grab Bars Description On back and side wall closest to toilet 11%" clearance to wall Located 30" above and parallel to the floor Adde-strede or roughened surface 42" long Fixtures Fixtures Description 11%" diameter	YES	Comments
Cost hook is 54° high Toilet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17".19" above the floor Grab Bars Description On back and side wall closest to toilet 11%" clearance to wall Located 30" above and parallel to the floor Acid etched or roughened surface 42" long Fixtures Description Description 11%" diameter	YES	Comments
Coat hook is 54" high Tablet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17": 9" above the floor Grab Bars Description On back and side wall closest to toilet 1%" clearance to wall Located 30" above and parallel to the floor Acid-etched or roughened surface 42" long Fixtures Description 1%" diameter 1%" diameter	YES	Comments
Cost hook is 54° high Toilet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17".19" above the floor Grab Bars Description On back and side wall closest to toilet 11%" clearance to wall Located 30" above and parallel to the floor Acid etched or roughened surface 42" long Fixtures Description Description 11%" diameter	YES	Comments
Coat hook is 54° high Tollet Description 18° from center to nearest side wall 42° minimum clear space from center to farthest wall or fixture Top of seat 17"-30° above the floor Grab Bars Description On back and side wall closest to tollet 1%" clearance to wall Located 30° above and parallel to the floor Acid-etched or roughened surface 42° long Fixtures Description Description Lift 'diameter 15° clearance to wall Located 30° above and parallel to the floor Located 30° above and parallel to the floor	YES	Comments
Cost hook is 54° high Toilet Description 18° from center to nearest side wall 42° minimum clear space from center to farthest wall or fixture Top of seat 17°-19° above the floor Grab Bars Description On back and side wall closest to toilet 11%' clearance to wall Located 30° above and parallel to the floor Acid-etched or roughened surface 42° long Fatures Description Description Statures Description 11%' clearance to wall Located 30° above and parallel to the floor Notes:	YES YES YES YES YES YES YES YES	Comments
Coat hook is 54" high Tolest Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor Grab Bars Description On back and side wall closest to toilet 1%" clearance to wall Located 30" above and parallel to the floor Acid-etched or roughened surface 42" long Fatures Description 1%" clearance to wall Located 30" above and parallel to the floor Notes: Floors, Drinking Fountains, Telephones	YES	Comments
Coat hook is 54° high Tollet Description 18° from center to nearest side wall 42° minimum clear space from center to farthest wall or fixture Top of seat 17°-19° above the floor Grab Bars Description On back and side wall closest to toilet 116° clearance to wall Located 30° above and parallel to the floor Acid-etched or roughened surface 42° long Flatures 116° clearance to wall Located 30° above and parallel to the floor Acid-etched or roughened surface 42° long Flatures 116° clearance to wall Located 30° above and parallel to the floor Notes: Floors, Drinking Fountains, Telephones	YES YES YES YES YES YES YES YES	Comments
Cost hook is 54° high Tollet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17".19" above the floor Grab Bars Description On back and side wall closest to tollet 11%" clearance to wall Located 30" above and parallel to the floor Acid etched or roughened surface 42" long Fixtures Description 11%" diameter 11%" clearance to wall Located 30" above and parallel to the floor Notes: Floors, Drinking Fountains, Telephones Floors, Drinking Fountains, Telephones Floors Description	YES	Comments
Coat hook is \$4" high Tablet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17" 19" above the floor Grab Bars Description On back and side wall closest to toilet 1%" clearance to wall Located 30" above and parallel to the floor Acid-etched or roughened surface 42" long Entures Description 1%" diameter 1%" clearance to wall Located 30" above and parallel to the floor Notes: Floors, Drinking Fountains, Telephones Floors Plocscription Non-silp surface	YES YES YES YES YES YES YES YES	Comments
Coat hook is 54" high Tollet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor Grab Bars Description On back and side wall closest to tollet 1½" clearance to wall Located 30" above and parallel to the floor Acid-etched or roughened surface 42" long Faktures Description 1½" clearance to wall Located 30" above and parallel to the floor Not 1½" clearance to wall Located 30" above and parallel to the floor Notes: Floors, Drinking Fountains, Telephones Boors Description	YES	Comments
Coat hook is 54" high Tollet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seast 17"-19" above the floor Grab Bars Description On back and side wall closest to toilet 11" clearance to wall Located 30" above and parallel to the floor Acid-etched or roughened surface 42" long Fixtures Description 11s" clearance to wall Located 30" above and parallel to the floor Acid-etched aroughened surface 42" long Fixtures Fixtures 15" clearance to wall Located 30" above and parallel to the floor Notes: Floors, Drinking Fountains, Telephones Ploors Non-slip surface Carpeting is high-density, low pile, non-absorbent, stretched taut, securely anchored	YES	Comments
Coat hook is 54" high Tollet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor Grab Bars Description On back and side wall closest to toilet 11%" clearance to wall Located 30" above and parallel to the floor Acid-etched or roughened surface 42" long Faktures Description 11%" clearance to wall Located 30" above and parallel to the floor Notes: Floors, Drinking Fountains, Telephones Floors Description Notes: Floors, Drinking Fountains, Telephones Floors Carpeting is ligh-density, low pile, non-absorbent, stretched taut, securely anchored Corridor width minimum is 3 ft	YES	Comments
Coat hook is \$4" high Tallet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17" 19" above the floor Grab Bars Description On back and side wall closest to toilet 1%" clearance to wall Located 30" above and parallel to the floor Acid-etched or roughened surface 42" long Fatures Description 1%" clearance to wall Located 30" above and parallel to the floor Notes: Floors Drinking Fountains, Telephones Floors Notes: Floors, Drinking Fountains, Telephones Carpeting is high-density, low pile, non-absorbent, stretched taut, securely anchored Corridor width minimum is 3 ft Objects (iganc, celling lights, fixtures) can only protrude 4" into the path of travel from a height of 27" to 80" above the floor	YES	Comments
Cost hook is \$4" high Tallet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17" 19" above the floor Grab Barx Description On back and side wall closest to toilet 1%" clearance to wall Located 30" above and parallel to the floor Acid-etched or roughened surface 42" long Flatures Description 11%" diameter 11%" clearance to wall Located 30" above and parallel to the floor Notes: Floors, Drinking Fountains, Telephones Floors Roors, Drinking Fountains, Telephones Carpeting is high-density, low pile, non-absorbent, stretched taut, securely anchored Corridor with minimum is 3 th Objects (signs, ceiling lights, fixtures) can only protrude 4" into the path of travel from a height of 27" to 80" above the floor Porhibing Fountains Description Spouts no higher than 36" from floor to outlet	YES	Comments Comments Comments
Coat hook is 54" high Tollet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor Grab Bars Description On back and side wall closest to toilet 1%" clearance to wall Located 30" above and parallel to the floor Acid-etched or roughened surface 42" long Flatures Description 1%" diameter 1%" clearance to wall Located 30" above and parallel to the floor Acid-etched or roughened surface 42" long Flatures Description 1%" clearance to wall Located 30" above and parallel to the floor Notes: Floors, Drinking Fountains, Telephones Floors Non-slip surface Carpeting is high-density, low pile, non-absorbent, stretched taut, securely anchored Corridor width minimum is 3 ft Objects (signs, calling lights, fixtures) can only protrude 4" into the path of travel from a height of 27" to 80" above the floor Drinking Fountains Description Description Description Souts no higher than 36" from floor to outlet Hand operated push button or level controls	YES	Comments Comments Comments
Coat hook is 54" high Tollet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seast 17"-19" above the floor Grab Bars Description On back and side wall closest to toilet 11" clearance to wall Located 30" above and parallel to the floor Adde-strebed or roughened surface 42" long Fixtures Description 11" clearance to wall Located 30" above and parallel to the floor Adde-strebed or roughened surface 42" long Fixtures Fixtures Description 11" clearance to wall Located 30" above and parallel to the floor Notes: Floors, Drinking Fountains, Telephones Bloors Description Non-silp surface Carpeting is high-density, low pile, non-absorbent, stretched taut, securely anchored Corridor width minimum is 3 ft Oridor width minimum is 3 ft Oridors (signs, ceiling lights, fixtures) can only protrude 4" into the path of travel from a height of 27" to 80" above the floor Prinking Fountains Description Spouts no higher than 36" from floor to outlet Hand operated push button or level controls Spouts no higher than 36" from floor to outlet Hand operated push button or level controls Spouts located near front with stream of water as parallel to front as possible	YES	Comments Comments Comments
Cost hook is \$4" high Tables Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17": 9" above the floor Grab Bars Description On back and side wall closest to toilet 1%" clearance to wall Located 30" above and parallel to the floor Acid-etched or roughened surface 42" long Flatures Description 1%" diameter 1%" clearance to wall Located 30" above and parallel to the floor Acid-etched or roughened surface 42" long Flatures Description 1%" diameter 1%" clearance to wall Located 30" above and parallel to the floor Notes: Floors, Drinking Fountains, Telephones Ebeors Carpeting is high-density, low pile, non-absorbent, stretched taut, securely anchored Corridor width minimum is 3 ft Objects (signs, celling lights, fixtures) can only protrude 4" into the path of travel from a height of 27" to 80" above the floor Pinking Fountains Description Spouts no higher than 36" from floor to outlet Hand operated push button or level controls Spouts to neigher than 36" from floor to outlet Hand operated push button or level controls Spouts to neigher than 36" from floor to outlet Hand operated push button or level controls Spouts to calcal arm of minimum 30" width, and no deeper than depth of fountain	YES	Comments Comments Comments
Coat hook is 54" high Tollet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor Grab Bars Description On back and side wall closest to toilet 1%" clearance to wall Located 30" above and parallel to the floor Acid-etched or roughened surface 42" long Fixtures Description 1%" clearance to wall Located 30" above and parallel to the floor Acid-etched or roughened surface 42" long Fixtures Description 1%" clearance to wall Located 30" above and parallel to the floor Notes: Floors, Drinking Fountains, Telephones Floors Notes: Carpeting is high-density, low pile, non-absorbent, stretched taut, securely anchored Corridor width minimum is 3 ft Objects (signs, ceiling lights, fixtures) can only protrude 4" into the path of travel from a height of 27" to 80" above the floor Drinking Fountains Description Description Description Souts no higher than 36" from floor to outlet Hand operated push button or level controls Spouts no higher than 36" from floor to outlet Hand operated push button or level controls Spouts no higher than 36" from floor to outlet Hand operated push button or level controls Spouts no higher than 36" from floor to outlet Hand operated push button or level controls Spouts no higher than 36" from floor to outlet Hand operated push button or level controls Spouts no higher than 36" from floor to outlet Hand operated push button or level controls Spouts no higher than 36" from floor to outlet and on deeper than depth of fountain If no clear knee space undementh, clear floor space 30" x 48" to allow parallel approach	YES	Comments Comments Comments
Coat hook is 54" high Tollet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor Grab Bars Description On back and side wall closest to toilet 11" clearance to wall Located 30" above and parallel to the floor Adde-strede or roughened surface 42" long Fixtures Description 11s" clearance to wall Located 30" above and parallel to the floor Adde-strede or roughened surface 42" long Fixtures Description 11s" clearance to wall Located 30" above and parallel to the floor Notes: Floors, Drinking Fountains, Telephones Floors Description On-street or wall by strace Carpeting is high-density, low pile, non-absorbent, stretched taut, securely anchored Corridor width minimum is 3 ft Ordicor street is high-density, low pile, non-absorbent, stretched taut, securely anchored Corridor width minimum is 3 ft Ordicor strains Description Spouts no higher than 36" from floor to outlet Hand operated push button or level controls Spouts no higher than 36" from floor to outlet Hand operated push button or level controls Spouts located near front with stream of water as parallel to front as possible If recessed, recess a minimum 30" width, and no deeper than depth of fountain If no clear knee space underneath, clear floor space 30" x 48" to allow parallel approach	YES	Comments Comments Comments Comments Comments
Coat hook is 54" high Tablet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17" 3" above the floor Grab Bars Description On back and side wall closest to toilet 1%" clearance to wall Located 30" above and parallel to the floor Acid-etched or roughened surface 42" long Fatures Description 1%" diameter 1%" clearance to wall Located 30" above and parallel to the floor Notes: Floors, Drinking Fountains, Telephones Floors Floors, Drinking Fountains, Telephones Floors Corridor with minimum is 3 ft Objects (signs, ceiling lights, fixtures) can only protrude 4" into the path of travel from a height of 27" to 80" above the floor Spouts no higher than 36" from floor to outlet Hand operated push button or level controls Spouts no higher than 36" from floor to outlet Hand operated push button or level controls Spouts to higher than 36" from floor to outlet Hand operated push button or level controls Spouts to higher than 36" from floor to outlet Hand operated push button or level controls Spouts located and from twill stream of waters aparallel to front as possible If recessed, recess a minimum 30" width, and no deeper than depth of fountain If no clear knee space underneath, clear floor space 30" x 48" to allow parallel approach Telephones Description	YES	Comments Comments Comments
Coat book is 54" high Tablet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor Brake 18" (19" above 19"	YES	Comments Comments Comments Comments Comments
Coat hook is 54" high Tablet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17" 3" above the floor Grab Bars Description On back and side wall closest to toilet 1%" clearance to wall Located 30" above and parallel to the floor Acid-etched or roughened surface 42" long Fatures Description 1%" diameter 1%" clearance to wall Located 30" above and parallel to the floor Notes: Floors, Drinking Fountains, Telephones Floors Floors, Drinking Fountains, Telephones Floors Corridor with minimum is 3 ft Objects (signs, ceiling lights, fixtures) can only protrude 4" into the path of travel from a height of 27" to 80" above the floor Spouts no higher than 36" from floor to outlet Hand operated push button or level controls Spouts no higher than 36" from floor to outlet Hand operated push button or level controls Spouts to higher than 36" from floor to outlet Hand operated push button or level controls Spouts to higher than 36" from floor to outlet Hand operated push button or level controls Spouts located and from twill stream of waters aparallel to front as possible If recessed, recess a minimum 30" width, and no deeper than depth of fountain If no clear knee space underneath, clear floor space 30" x 48" to allow parallel approach Telephones Description	YES	Comments Comments Comments Comments Comments
Coat hook is 54" high Tablet Description 18" from center to nearest side wall 42" minimum dear space from center to farthest wall or fixture Top of seat 17"-39" above the floor Grab Bars Description On back and side wall closest to tollet 1%" clearance to wall Located 30" above and parallel to the floor Acid-etched or roughened surface 42" long Fatures Description 1%" diameter 1%" clearance to wall Located 30" above and parallel to the floor Notes: Floors, Drinking Fountains, Telephones Floors, Drinking Fountains, Telephones Floors, Drinking Fountains, Telephones Floors, Original of the floor Notes: Description Non-silp surface Carpeting is high-density, low pile, non-absorbent, stretched taut, securely anchored Corridor would minimum is 3 ft Objects (signs, celling lights, fixtures) can only protrude 4" into the path of travel from a height of 27" to 80" above the floor Description Spouts no higher than 36" from floor to outlet Hand operated push button or level controls Spouts located near front with stream of water as parallel to front as possible If recessed, recess a minimum 30" width, and no deeper than depth of fountain If no clear ince space underneath, clear floor space 30" x 48" to allow parallel approach Telesahones Description Access within 12" of phone, 30" high by 30" wide	YES	Comments Comments Comments Comments Comments
Cost book is 54" high Tollet Tollet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or future Top of seat 17"-19" above the floor Grab Bass Description On back and side wall closest to toilet 11" diameter 11" diameter 11" diameter 21" clearance to wall Located 30" above and parallel to the floor Acid-et-ched or roughened surface 42" long Flatures Description 11" diameter 10" diameter 10" diameter 10" diameter 10" door and parallel to the floor Notes: Floors, Drinking Fountains, Telephones Boors Description Non-slip surface Carpeting is high-density, low pile, non-aborohent, stretched taut, securely anchored Corndor wordth minimum is 3 ft Objects (specia, cline lights, fistures) can only protrude 4" into the path of travel from a height of 27" to 80" above the floor Diribing Fountains Description Spouts on higher than 36" from floor to outlet Hand operated push button or level controls Spouts on higher than 36" from floor to outlet Hand operated push button or level controls Spouts on higher than 36" from floor to outlet Hand operated push button or level controls Spouts on higher than 36" from floor to outlet Hand operated push button or level controls Spouts on higher than 36" from floor to outlet Hand operated push button or level controls Spouts on higher than 36" from floor to evide Hand operated push button or level controls Spouts on higher than 36" from floor to evide Hand operated push button or level controls Spouts on higher than 36" from floor to evide Hand operated push button or level controls Spouts on higher than 36" from floor to evide Adjustable volume control on headest so identified Adjustable volume control on headest so identified	YES	Comments Comments Comments Comments Comments
Cost hook is 54" high Tollett Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor Grab Bars Description On back and side wall closest to toilet 1%" clearance to wall Located 30" above and parallel to the floor Acid-etched or roughened surface 42" long Fatures Description 1%" clearance to wall Located 30" above and parallel to the floor Notes: Floors, Drinking Fountains, Telephones Floors, Drinking Fountains, Telephones Places and parallel to the floor Notes: Carpeting is high-density, low pile, non-absorbent, stretched taut, securely anchored Corridor width minimum is 3 ft Objects (Signs, celline lights, fixtures) can only protrude 4" into the path of travel from a height of 27" to 80" above the floor Orbinking Fountains Description Spouts no higher than 36" from floor to outlet Hand operated push button or level controls Spouts no higher than 36" from floor to outlet Hand operated push button or level controls Spouts no higher than 36" from floor to outlet Hand operated push button or level controls Spouts no higher than 36" from floor to outlet Hand operated push button or level controls Spouts no higher than 36" from floor to outlet Hand operated push button or level controls Spouts no higher than 36" from floor to autlet Hand operated push button or level controls Spouts no higher than 36" from floor to autlet Hand operated push button or level controls Spouts no higher than 36" from floor to autlet Hand operated push button or level controls Spouts no higher than 36" from floor to autlet Hand operated push button or level controls Spouts no higher than 36" from floor to autlet Hand operated push button or level controls Adjustable volume control on headest to identified Adjustable volume control on headest to identified	YES	Comments Comments Comments Comments Comments

Signs, Signals, and Switches	YES			
Switches, Controls and Signs				
Description		Comments		
Switches and controls for light, heat, ventilation, windows, fire alarms, thermostats, etc, must be a minimum of 36" and a maximum of 48" above the floor for a forward reach, a maximum of 54" for a side reach	No			
Electrical outlets centered no lower than 18" above the floor	YES			
Warning signals must be visual as well as audible	N/A			
Signs				
Description		Comments		
Mounting height must be 60" to centerline of the sign	N/A			
Within 18" of door jamb or recessed	N/A			
Letters and numbers a t least 1%" high	N/A			
Letters and numbers raised .03"	N/A			
Letters and numbers contrast with the background color	n/a			
Notes:				
Swimming Pool/ Lake beach	N/A			
Shower Rooms	N/A			
Picknicking	N/A			
Off Leash Dog Areas (OLA)	N/A			

Facility Names Charleshank Dark Manantum Diago Diago	d¹	
Facility Name: Charlesbank Park 'Nonantum Place Playgro Size (Ac): .5 acres	ouna	
Address: Nonantum Place, Newton Corner		
Ward: 1		
General Facility Notes: Small pocket park; accessible route with ramp and hand rai	ls to honshos and nichic tal	hle: now accessible play equipment area
<u>General racinty Notes.</u> Sinai pocket park, accessible route with rainp and naid rain	is to believes and picine tai	оге, нем ассеззыве ріаў ечиртені агеа.
Site Furnishings Description	YES Yes	Comments
Tables & Benches		
Number of Benches Number of Tables	Yes	4 - 3 accessible
Located adjacent to accessible paths	Yes	-
Back and Arm Rests Grills	Yes	3 w/backs only
Located adjacent to accessible paths	N/A	
<u>Trash Cans</u>	,	
Located adjacent to accessible paths Picnic Shelters	Yes	
Located adjacent to accessible paths	N/A	
Notes:		
Trails & Paths	YES	
Description Surface (A=Asphalt, C=Concrete, SD= stone dust, NS= naturally surfaced, B=Boardwalk, BR=Bridge)	Yes	Comments C
Juniace (wespinals, c-concrete, 30= stolle dust, ris= hatdininy surfaces, b=boardwark, bri-bridge) Dimensions (width)	Yes	5' minimum
Rails Signage for visually impaired	Yes No	
sgrage or visually imparied Notes:	NO	
Play Areas	YES	
Description	0	Comments
Facility Type (3-5 Yrs,5-12 Yrs) Same experience provided to all	Yes Yes	3-5, 5-12
Access Routes	10	
Located adjacent to accessible paths	Yes	
Enough space between equipment for wheelchair Notes:	Yes	
Game Areas	N/A	
Boat Docks	N/A	
Fishing Facilities Community Gardens	N/A N/A	
Parking	N/A	
Ramps	YES	I
Description Slope Maximum 1:12	Yes	Comments
Minimum width 4 ft between handrails	Yes	
Handrails on both sides if ramp is longer than 6 ft Handrails at 34" and 19" from ramp surface	Yes Yes	
Handrails extend 12" beyond top and bottom	Yes	
Handgrip oval or round Handgrip smooth surface	Round Yes	
Handgrip diameter between 1%" and 2"	Yes	
Clearance of 1½" between wall and wall rail	N/A	
Non-slip surface Level platforms (4ft x 4 ft) at every 30 ft, at top, at bottom, at change of direction	Yes Yes	
Notes:	,	
Site Access, Path of Travel, Entrances	YES	
<u>Site Access</u>		Comments
Description Accessible path of travel from passenger disembarking area and parking area to accessible entrance	N/A	Comments no parking area and no street parking
Surface evenly paved or hard-packed	Yes	
Ponding of water? Disembarking area at accessible entrance	No N/A	
Path of Travel	1	
Description Path does not require the use of stairs	yes	Comments
Path does not require the use of stairs Path does not require the use of wheelchair ramp	yes no	
Path is stable, firm and slip resistant	yes	
Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50). Continuous common surface, no changes in level greater than ½ inch	yes	
Notes:		
Stairs and Doors	N/A	
Restrooms	N/A	
Floors, Drinking Fountains, Telephones Signs, Signals, and Switches	N/A N/A	
Swimming Pool/ Lake beach	N/A	
Shower Rooms Picknicking	N/A N/A	
Off Leash Dog Areas (OLA)	N/A	

Facility Name: Charles Brown and Oak Hill Middle Schools Playfic	elds		
Size (Ac): 11.3 acres			
Address: Wheeler Road, Newton Centre			
Ward: 8			
General Facility Notes: Ballfields and soccer fields; no accessible pathways to or within field a	reas. The footnri	nt for site specs includes the Oak Hill school and 2 par	king
ots.	саз. те тоотр	in the state speed modules the duti in soliton and 2 part	6
Site Furnishings	YES		
Description Number of benches	No	Comments	
Number of Tables Grills	No		
Located adjacent to accessible paths	NA		
Trash Cans Located adjacent to accessible paths	yes	2 bigbelly trash compactors; 2 bigbelly recycling units	
Vicinic Shelters Located adjacent to accessible paths	NA NA	T	
Notes:	'		
Tuella O Dasha	YES		
Trails & Paths Description	163	Comments	
Surface (A=Asphalt, C=Concrete, SD= stone dust, NS= naturally surfaced, B=Boardwalk, BR=Bridge) Dimensions (width)	Noi NA		
Rails Signage for visually impaired	NA NA		
Notes:	, ns		
	121/2		
Play Areas Game Areas	N/A YES		
Description Facility Type (RF=Rectangular Fields, BF= Ballfields, BK=Basketball, TN=Tennis, BC=Bocce)		Comments 3 RF, 2 BF	
Facility Type (Kr=Mectangular Fields, BF= Ballifields, BK=Basketball, TN= Tennis, BC=Bocce) Access Routes	yes	3 KF, 2 BF	
Located adjacent to accessible paths Berm cuts onto courts	yes No		
quipment			
Height Dimensions			
Spectator Seating			
Notes: There is 1 climbing structure, 2 little leagues fields, 1 softball field, 1 baseball field, 4 soccer fields and 1 track/f rrigated with well water.	field area. All ballfield	s ahev a backstop, players benches and proetive screens. The athleti	c field is
Boat Docks	N/A		
Fishing Facilities	N/A		
Community Gardens Parking	N/A YES		
<u>Fotal Spaces</u>	Accessible Sp	<u>naces</u>	
15 Spaces Description	3 Space	Comments	
Parking Amenities (L=lot, ST=street)	Yes	31	
Accessible space located closest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft	Yes na		
Minimum width of 13 ft includes 8 ft space plus 5 ft access aisle	no		
Minimum of 1 van space for every accessible space, 8' wide + 8' aisle. Sign with international symbol of accessibility at each space	Yes Yes	2	
Sign 5'-8' to top of sign	Yes	2	
Surface evenly paved or hard-packed (no cracks) Surface slope less than 1:20, 5%	yes		
Curbcut to pathway from parking lot at each space if sidewalk (curb) is present .	yes		
Curbcut is a minimum width of 3 ft, excluding sloped sides, has sloped sides, all slopes not to exceed 1:12, and textured or painted yellow Notes:	yes		
Ramps Site Access, Path of Travel, Entrances	N/A YES		
Site Access, Faul Of Fraver, Efficiences	ILS		
Description Accessible path of travel from passenger disembarking area and parking area to accessible entrance	No	Comments	
Accessible plant of travel from passetiger disentiarising area and parking area to accessible entrance. Surface evenly paved or hard-packed.	NA NA		
Ponding of water? Disembarking area at accessible entrance	Yes		
Distributing area at accessible entitative Path of Travel	No		
Description		Comments	
Path does not require the use of stairs Path does not require the use of wheelchair ramp	yes yes		
Path is stable, firm and slip resistant Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50).	yes Yes		
Slope maximum 1:20 (3%) and maximum cross pitch is 2% (1:50). Continuous common surface, no changes in level greater than ½ inch	No Yes	Path has cracks and some pot holes	
Notes:			
	15175		
Stairs and Doors Restrooms	N/A N/A		
Floors, Drinking Fountains, Telephones	N/A		
Signs, Signals, and Switches Swimming Pool/ Lake beach	N/A N/A		
Shower Rooms	N/A		

Picknicking	N/A
Off Leash Dog Areas (OLA)	N/A

acility Name: City Hall & War Memorial Grounds		
Size (Ac): 10 acres		
ddress: 1000 Commonwealth Avenue, Newton Centre		
Vard: 6		
General Facility Notes: Stone dust pathways loop around the ponds and lead to parkin	g: stone dust nath and	historic nand bridges in need of accessibility improvement
ncluding curb cuts; City Hall grounds include Millennium Park on Homer St. which is a		
	iccessible and leads to	the banding 3 accessible entrance, accessible concrete
idewalk around the building and grounds.		
ite Furnishings	YES	
escription	Yes	Comments
ables & Benches		
Number of Benches Number of Tables	YES	9 3 Picnic
Located adjacent to accessible paths	yes yes	3 PICNIC 2
Back and Arm Rests	yes	9
ash Cans	,,,,	
Located adjacent to accessible paths	yes	1
<u>cnic Shelters</u>	<u> </u>	·
Located adjacent to accessible paths	NA NA	
otes:		
	VEC	
Trails & Paths	YES	Community
Surface (A=Asphalt, C=Concrete, SD= stone dust, NS= naturally surfaced, B=Boardwalk, BR=Bridge)	yes	Comments A,C, SD
Dimensions (width)	yes	min 6 ft
Rails	No	THING IS
Signage for visually impaired	No	
otes:		
Play Areas	N/A	
Game Areas	N/A	
Boat Docks	N/A	
ishing Facilities	N/A	
Community Gardens	N/A	
Parking	N/A	
Ramps Site Access, Path of Travel, Entrances	N/A YES	
te Access	ILO	
escription		Comments
Accessible path of travel from passenger disembarking area and parking area to accessible entrance	NA NA	
Surface evenly paved or hard-packed	Yes	
Ponding of water?	No	
Disembarking area at accessible entrance	NA NA	
ath of Travel		
escription		Comments
Path does not require the use of stairs	Yes	
Path does not require the use of wheelchair ramp	Yes	
Path is stable, firm and slip resistant Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50).	Yes Yes	
Continuous common surface, no changes in level greater than ½ inch	No No	Elevation change between stone dust path and historic bridge
lotes:		
Stairs and Doors	N/A	
Restrooms	N/A	
loors, Drinking Fountains, Telephones	N/A	
Signs, Signals, and Switches	N/A	
Swimming Pool/ Lake beach	N/A	
Shower Rooms	N/A N/A	
Picknicking Dff Leash Dog Areas (OLA)	N/A	
/II LEGSII DOG AIEGS (ULA)	111/7	

Ī

Facility Name: Claflin Park			
Size (Ac): .75 acre			
Address: Lowell Street, Newton Centre			
Ward: 1			
General Facility Notes: Sloped Grassy area primarily used as dog park. Crumbling	g stairs and pathways do not	meet MAAB or ADA requirements	
Site Furnishings	N/A		
Trails & Paths	YES		
Description	1.25	Comments	
Surface (A=Asphalt, C=Concrete, SD= stone dust, NS= naturally surfaced, B=Boardwalk, BR=Bridge)	Yes	Asphalt	
Dimensions (width)	1.0	4-ft min.	
Rails	No		
Signage for visually impaired	No		
Notes:	NO		
notes.			
Play Areas	N/A		
Game Areas	N/A		
Boat Docks	N/A		
Fishing Facilities	N/A		
Community Gardens	N/A		
Parking	N/A N/A		
Ramps	N/A		
Site Access, Path of Travel, Entrances	YES		
Site Access Site Access	1123		
Description		Comments	
Accessible path of travel from passenger disembarking area and parking area to accessible entrance	NA NA	Comments	
Surface evenly paved or hard-packed	No		
Ponding of water?	No No		
	NA NA		
Disembarking area at accessible entrance	NA NA		
Path of Travel Description		Comments	
Description Path does not require the use of stairs	Yes	Comments	
Path does not require the use of stairs Path does not require the use of wheelchair ramp	Yes		
Path does not require the use of wheelchair ramp Path is stable, firm and slip resistant	Yes No		
Path is stable, firm and slip resistant Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50).	No No		
Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50). Continuous common surface, no changes in level greater than ½ inch	No No		
Continuous common surface, no changes in level greater than ½ inch Notes:	No		
Stairs and Doors	N/A		
Restrooms	N/A		
Floors, Drinking Fountains, Telephones	N/A		
Signs, Signals, and Switches	N/A		
Swimming Pool/ Lake beach	N/A		
Shower Rooms	N/A		· · · · · · · · · · · · · · · · · · ·
Picknicking	N/A	<u> </u>	
Off Leash Dog Areas (OLA)			

Facility Name: Cold Spring Park 'New Cold Spring Park' + 'Old Cold Sp	oring Pa	nrk'
Size (Ac): 65 acres		
Address: Beacon Street; Duncklee Street; Plymouth Road, Newton Highlands (main entrances)		
Nard: 6		
General Facility Notes: Accessible parking and path around tennis courts and to seasonal Farmers in accessible; outdoor exercise equipment is not accessible; steep paved maintenance road with pedeash area and ballfield not accessible; Acreage includes Old Cold Spring Park and New Cold Spring the Cochituate aqueduct.	estrian acc	ess into the park from Duncklee street not accessible; off-
Site Furnishings	YES	
Description	Yes	Comments
Aumber of Benches	yes	14 benches total
Number of Tables	Yes	2
Located adjacent to accessible paths Back and Arm Rests	No No	4 Benches along accessible route Only backrest, no armrest
irills	NO	Unity backress, no armiest
Located adjacent to accessible paths	NA	
rash Cans	I v	
Located adjacent to accessible paths icnic Shelters	Yes	1
Located adjacent to accessible paths	NA	
Notes:		
Trails & Paths	YES	
Description		Comments
Surface (A=Asphalt, C=Concrete, SD= stone dust, NS= naturally surfaced, B=Boardwalk, BR=Bridge) Dimensions (width)	Yes	A, SD 6-ft min
Rails	No No	6-1(1781)
Signage for visually impaired	No	
Notes:		
	INI/A	
Plav Areas Game Areas	N/A YES	
Description Control of the Control o	1.20	Comments
Facility Type (RF=Rectangular Fields, BF= Ballfields, BK=Basketball, TN=Tennis, BC=Bocce)	Yes	1 RF, 2 BF, 4 TN, 2 BK
Located adjacent to accessible paths	Yes	Only Tennis courts are adjacent to accessible route
Berm cuts onto courts	NA NA	Only Telling court die diglective deceasable fouce
quipment		
Spectator Seating	Yes	
lotes:		
Boat Docks	N/A	
Fishing Facilities	N/A	
Community Gardens	N/A	
Parking Total Spaces	YES Accessible S	naces
	62 5 Space	paces
Description		Comments
Parking Amenities (L=lot, ST=street)	Yes	Lot
Accessible space located closest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft	Yes	
Minimum width of 13 ft includes 8 ft space plus 5 ft access aisle	Yes	
Minimum of 1 van space for every accessible space, 8' wide + 8' aisle.	No	
Sign with international symbol of accessibility at each space Surface evenly paved or hard-packed (no cracks)	Yes	
Surface slope less than 1:20,5%	Yes	
Curbcut to pathway from parking lot at each space if sidewalk (curb) is present .	NA	
Curbcut is a minimum width of 3 ft, excluding sloped sides, has sloped sides, all slopes not to exceed 1:12, and textured or painted yellow Notes: Parking lot requires restriping. Accessible aisle striping doesn't seem to meet MAAB requirements.	NA	
Ramps	N/A	
Site Access, Path of Travel, Entrances	YES	
Description		Comments
Accessible path of travel from passenger disembarking area and parking area to accessible entrance	Yes	
Surface evenly paved or hard-packed Ponding of water?	Yes No	
Disembarking area at accessible entrance	Yes	
ath of Travel		
Pescription Path does not require the use of stairs	Yes	Comments
Path does not require the use of wheelchair ramp	No	Some portions of the trail do not meet ADA or MAAB slope requirements
Path is stable, firm and slip resistant	Yes	
Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50).	No Vor	
Continuous common surface, no changes in level greater than ½ inch Curb on the pathway must have curb cuts at drives, parking and drop-offs	Yes NA	
lotes:		
Stairs and Doors	N/A	
Restrooms Floors, Drinking Fountains, Telephones	N/A N/A	

Signs, Signals, and Switches	N/A		
Swimming Pool/ Lake beach	N/A		
Shower Rooms	N/A		
Picknicking	N/A		
Off Leash Dog Areas (OLA)	YES		
Description		omments	
Access Routes			
Located adjacent to accessible paths	No		
Area accesible	No	Lawn and dirt	
Notes:			

Facility Name: Coletti-Magni Park		
Size (Ac): .46 acres		
Address: Corner of Watertown Street and Bridge Street., Nonantum		
Ward: 1		
General Facility Notes: Accessible pathways w/benches and bus stop; Watertown St. cr	osswalk with curb cut	ramp at Bridge St. corner.
Site Furnishings	YES	
Description	1.20	Comments
Tables & Benches		
Number of Benches	yes	8 DuMor gray slat benches with backs, no arm rests
Number of Tables Located adjacent to accessible paths	yes	1 Chess table with four concrete slab pedestal seats, no backs, no arm rests
Back and Arm Rests	no	NO Arm rests, all benched are backed
<u>Grills</u>		
Located adjacent to accessible paths	NA NA	
Trash Cans	1	
Located adjacent to accessible paths Picnic Shelters	yes	2 bigbelly trash compactors; 2 bigbelly recycling units
Located adjacent to accessible paths	NA NA	
Notes: Covered bust stop with bench, no back, no arm rest, WWII memorial with 2 flagpoles	'	
Trails 2. Daths	YES	
Trails & Paths Description	IES	Comments
Surface (A=Asphalt, C=Concrete, SD= stone dust, NS= naturally surfaced, B=Boardwalk, BR=Bridge)	yes	С
Dimensions (width)	yes	Five foot wide concrete paths
Rails	no	
Signage for visually impaired Benches	no	8 DuMor gray slat benches with backs, no arm rests
Notes:	yes	d vumor gray stat detaches with rocks, no arminests
Dlan Assas	IN/A	
Play Areas Game Areas	N/A N/A	
Boat Docks	N/A	
Fishing Facilities	N/A	
Community Gardens	N/A	
Parking	N/A	Te
Description		Comments 5 Metered on street narkine snares on accessible narkine snares
	N/A No no	Comments 5 Metered on street parking spaces, no accessible parking spaces
Description Parking Amenities (L=lot, ST=street) Accessible space located closest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft	No	
Description Parking Amenities (L=lot, ST=street) Accessible space located closest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft Minimum width of 13 ft includes 8 ft space plus 5 ft access asisle	No no NA No	
Description Parking Amenities (L=lot, ST=street) Accessible space located closest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft Minimum width of 13 ft includes 8 ft space plus 5 ft access aisle Minimum of 1 van space for every accessible space, 8' wide + 8' aisle.	No no NA No no	
Description Parking Amenities (L=lot, ST=street) Accessible space located closest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft Minimum width of 13 ft includes 8 ft space plus 5 ft access asisle	No no NA No	
Description Parking Amenities (L=lot, ST=street) Accessible space located closest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft Minimum with of 13 ft includes 8 ft space plus 5 ft access asisle Minimum of 1 van space for every accessible space, 8' wide + 8' asisle. Sign with international symbol of accessibility at each space	No no NA No no NA	
Description Parking Amenities (Leilot, ST'estreet) Accessible space located closest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft Minimum width of 13 ft includes 8 ft space plus 5 ft access asisle Minimum of 1 van space for every accessible space, 8' wide + 8' asisle. Sign with international symbol of accessibility at each space Sign 5'-8' to top of sign Surface evenly paved or hard-packed (no cracks) Surface slope less than 1:20,5%	NO NO NA NA NA NA	
Description Parking Amenities (Leiot, ST-street) Accessible space located closest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft Minimum width of 13 ft includes 8 ft space plus 5 ft access aisle Minimum of 1 van space for every accessible space, 8' wide + 8' aisle. Sign with international symbol of accessibility at each space Sign 5-8' ft to top of sign Surface evenly paved or hard-packed (no cracks)	No no NA No no NA NA NA NA	
Description Parking Amenities (Leilot, ST'estreet) Accessible space located closest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft Minimum width of 13 ft includes 8 ft space plus 5 ft access asisle Minimum of 1 van space for every accessible space, 8' wide + 8' asisle. Sign with international symbol of accessibility at each space Sign 5'-8' to top of sign Surface evenly paved or hard-packed (no cracks) Surface slope less than 1:20,5%	No no NA No no NA NA NA NA	
Description Parking Amenities (L=lot, ST=street) Accessible space located closest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft Minimum width of 13 ft includes 8 ft space plus 5 ft access asise Minimum of 1 van space for every accessible space, 8' wide + 8' aisle. Sign with international symbol of accessibility at each space Sign S'-8' to top of sign Surface evenly paved or hard-packed (no cracks) Surface slope less than 1:20, 5% Notes: Ramps Site Access, Path of Travel, Entrances	NO NO NA NA NA NA NA	
Description Parking Amenities (Leiot, ST-street) Accessible space located closest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft Minimum width of 13 ft includes 8t space plus 5 ft access asisle Minimum of 1 van space for every accessible space, 8' wide + 8' aisle. Sign with international symbol of accessibility at each space Sign 5'-8' to top of sign Surface evenly paved or hard-packed (no cracks) Surface slope less than 1:20, 5% Notes: Ramps Site Access, Path of Travel, Entrances	NO NO NA NO NA NA NA NA NA	S Metered on street parking spaces, no accessible parking spaces
Description Parking Amenities (Leiot, ST-street) Accessible space located closest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft Minimum width of 13 ft includes 8 ft space plus 5 ft access alsie Minimum of 1 van space for every accessibile space, 8' wide + 8' alsie. Sign with international symbol of accessibility at each space Sign 5'-8' to top of sign Surface evenly paved or hard-packed (no cracks) Surface slope less than 1:20, 5% Notes: Ramps Site Access, Path of Travel, Entrances Site Access, Path of Travel, Entrances	NO NO NO NO NO NO NO NA NA NA NA NA NA NA	
Description Parking Amenities (Leiot, ST-street) Accessible space located closest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft Minimum width of 13 ft includes 8t space plus 5 ft access asisle Minimum of 1 van space for every accessible space, 8' wide + 8' aisle. Sign with international symbol of accessibility at each space Sign 5'-8' to top of sign Surface evenly paved or hard-packed (no cracks) Surface slope less than 1:20, 5% Notes: Ramps Site Access, Path of Travel, Entrances	NO NO NA NO NA NA NA NA NA	S Metered on street parking spaces, no accessible parking spaces
Description Parking Amenities (L=lot, ST=street) Accessible space located closest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft Minimum width of 13 ft includes 8 ft space plus 5 ft access asise Minimum of 1 van space for every accessible space, 8' wide + 8' aisle. Sign with international symbol of accessibility at each space Sign 5'-8' to top of sign Surface evenly paved or hard-packed (no cracks) Surface slope less than 1:20, 5% Notes: Ramps Site Access, Path of Travel, Entrances Site Access, Path of Travel, Entrances Description Accessible path of travel from passenger disembanking area and parking area to accessible entrance	NO NO NA NO NO NA NA NA NA NA NA NA VES	S Metered on street parking spaces, no accessible parking spaces
Description Parking Amenities (L=lot, ST=street) Accessible space located closest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft Minimum width of 13 ft includes 8 ft space plus 5 ft access asise Minimum of 1 van space for every accessible space, 8' wide + 8' asise. Sign with international symbol of accessibility at each space Sign 5'-8' to top of sign Surface evenly paved or hard-packed (no cracks) Surface slope less than 1:20, 5% Notes: Ramps Site Access, Path of Travel, Entrances Site Access, Path of Travel, Entrances Ste Access Description Accessible path of travel from passenger disembanking area and parking area to accessible entrance Surface evenly paved or hard-packed Ponding of water? Disembanking area at accessible entrance	NO NO NA NO NO NA NA NA NA NA NA NA VES	S Metered on street parking spaces, no accessible parking spaces
Description Parking Amenities (L=lot, ST=street) Accessible space located closest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft Minimum width of 13 ft includes 8 ft space plus 5 ft access asise Minimum of 1 van space for every accessible space, 8' wide + 8' aisle. Sign with international symbol of accessibility at each space Sign S'-8' to top of sign Surface evenly paved or hard-packed (no cracks) Surface slope less than 1:20, 5% Notes: Ramps Site Access, Path of Travel, Entrances Site Access Description Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed Ponding of water? Disembarking area at accessible entrance	NO NO NA NO NO NA NA NA NA NA NA NA VES	S Metered on street parking spaces, no accessible parking spaces Comments
Description Parking Amenities (Leliot, ST-street) Accessible space located closest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft Minimum width of 13 ft includes 8 ft space plus 5 ft access asise Minimum of 1 van space for every accessible space, 8' wide + 8' asile. Sign with international symbol of accessibility at each space Sign 5'-8' to top of sign Surface evenly paved or hard-packed (no cracks) Surface slope less than 1:20,5% Notes: Ramps Site Access, Path of Travel, Entrances Site Access, Path of Travel, Entrances Site Access Description Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed Ponding of water? Disembarking area at accessible entrance Path of Travel Description	NO NO NA NO NO NO NA NA NA NA VES	S Metered on street parking spaces, no accessible parking spaces
Description Parking Amenities (L=lot, ST=street) Accessible space located closest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft Minimum width of 13 ft includes 8 ft space plus 5 ft access asise Minimum of 1 van space for every accessible space, 8' wide + 8' aisle. Sign with international symbol of accessibility at each space Sign S'-8' to top of sign Surface evenly paved or hard-packed (no cracks) Surface slope less than 1:20, 5% Notes: Ramps Site Access, Path of Travel, Entrances Site Access Description Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed Ponding of water? Disembarking area at accessible entrance	NO NO NA NO NO NA NA NA NA NA NA NA VES	S Metered on street parking spaces, no accessible parking spaces Comments
Description Parking Amenities (I=lot, ST-street) Accessible space located closest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft Minimum width of 13 ft includes 8 ft space plus 5 ft access asise Minimum of 1 van space for every accessible space, 8' wide + 8' asie. Sign with international symbol of accessibility at each space Sign S-8' to top of sign Surface evenly paved or hard-packed (no cracks) Surface slope less than 1:20, 5% Notes: Ramps Site Access, Path of Travel, Entrances Site Access, Path of Travel, Entrances Site Access Description Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed Ponding of water? Disembarking area at accessible entrance Path of Travel Description Path does not require the use of stairs	No N	S Metered on street parking spaces, no accessible parking spaces Comments
Description Parking Amenities (Leiot, STestreet) Accessible space located closest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft Minimum width of 13 ft includes 8 ft space plus 5 ft access asise Minimum of 1 van space for every accessible space, 8 wide + 8° aisle. Sign with international symbol of accessibility at each space Sign 5'-8' to top of sign Surface evenly paved or hard-packed (no cracks) Surface slope less than 1:20, 5% Notes: Ramps Site Access, Path of Travel, Entrances Site Access, Path of Travel, Entrances Site Access Description Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed Ponding of water? Disembarking area at accessible entrance Path of Travel Description Path does not require the use of stairs Path does not require the use of stairs Path does not require the use of wheelchair ramp Path sit stailer, firm and slip resistant Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1.50).	NO NO NA NA NO NO NA NA NA NA NA VES yes yes yes	S Metered on street parking spaces, no accessible parking spaces Comments
Description Parking Amenities (Leilot, ST-street) Accessible space located closest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft Minimum width of 13 ft includes 8 ft space plus 5 ft access asisle Minimum of 1 van space for every accessible space, 8° wide + 8° asile. Sign with international symbol of accessibility at each space Sign 5'-8' to top of sign Surface evenly paved or hard-packed (no cracks) Surface slope less than 1:20, 5% Notes: Ramps Site Access, Path of Travel, Entrances Site Access Description Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed Ponding of water? Disembarking area at accessible entrance Path of Travel Description Path does not require the use of stairs Path does not require the use of wheelchair ramp Path is stable, firm and slip resistant	NO NO NO NO NA NO NO NA NA NA NA NA VES	S Metered on street parking spaces, no accessible parking spaces Comments
Description Parking Amenities (L=lot, ST=street) Accessible space located closest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft Minimum width of 13 ft includes 8 ft space plus 5 ft access asise Minimum of 1 van space for every accessible space, 8' wide + 8' asise. Sign with international symbol of accessibility at each space Sign S'-8' to top of sign Surface evenly paved or hard-packed (no cracks) Surface slope less than 1:20, 5% Notes: Ramps Site Access, Path of Travel, Entrances Site Access Description Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed Ponding of wate? Disembarking area at accessible entrance Path of Travel Description Path does not require the use of wheelchair ramp Path is stable, firm and slip resistant Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50). Continuous common surface, no changes in level greater than ¼ inch Notes:	No No No No No No No No	S Metered on street parking spaces, no accessible parking spaces Comments
Description Parking Amenities (L=lot, ST=street) Accessible space located closest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft Minimum width of 13 ft includes 8 ft space plus 5 ft access asise Minimum of 1 van space for every accessible space, 8' wide + 8' aisle. Sign with international symbol of accessibility at each space Sign 5'-8' to top of sign Surface evenly paved or hard-packed (no cracks) Surface slope less than 1:20, 5% Notes: Ramps Site Access, Path of Travel, Entrances Site Access Description Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed Ponding of water? Disembarking area at accessible entrance Path of Travel Description Path does not require the use of stairs Path does not require the use of stairs Path does not require the use of wheelchair ramp Path is stable, firm and slip resistant Siope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50). Continuous common surface, no changes in level greater than ½ inch Notes: Stairs and Doors	No no no NA NA No no no NA NA NA NA NA NA VES yes yes yes yes yes yes	S Metered on street parking spaces, no accessible parking spaces Comments
Description Parking Amenities (L-lot, ST-street) Accessible space located closest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft Minimum width of 13 ft includes 8 ft space plus 5 ft access asise Minimum of 1 van space for every accessible space, 8' wide + 8' asile. Sign with international symbol of accessibility at each space Sign 5'8' to top of sign Surface evenly paved or hard-packed (no cracks) Surface slope less than 1:20, 5% Notes: Ramps Site Access, Path of Travel, Entrances Site Access Description Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed Ponding of water? Disembarking area at accessible entrance Path of Travel Description Path does not require the use of stairs Path does not require the use of stairs Path does not require the use of wheelchair ramp Path is stable, firm and slip resistant Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50). Continuous common surface, no changes in level greater than ½ inch Notes: Stairs and Doors Restrooms	No No No No No No No No	S Metered on street parking spaces, no accessible parking spaces Comments
Description Parking Amenities (L=lot, ST=street) Accessible space located closest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft Minimum width of 13 ft includes 8 ft space plus 5 ft access asise Minimum of 1 van space for every accessible space, 8' wide + 8' aisle. Sign with international symbol of accessibility at each space Sign 5'-8' to top of sign Surface evenly paved or hard-packed (no cracks) Surface slope less than 1:20, 5% Notes: Ramps Site Access, Path of Travel, Entrances Site Access Description Accessible path of travel from passenger disembanking area and parking area to accessible entrance Surface evenly paved or hard-packed Ponding of water? Disembanking area at accessible entrance Path of travel Description Path does not require the use of stairs Path does not require the use of wheelchair ramp Path is stable, firm and slip resistant Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50). Continuous common surface, no changes in level greater than ½ inch Notes: Stairs and Doors Restrooms Floors, Drinking Fountains, Telephones Signs, Signals, and Switches	No No No No No No No No	S Metered on street parking spaces, no accessible parking spaces Comments
Description Parking Amenities (L=lot, ST=street) Accessible space located closest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft Minimum width of 13 ft includes 8 ft space plus 5 ft access asise Minimum of 1 van space for every accessible space, 8' wide + 8' asile. Sign with international symbol of accessibility at each space Sign 5'-8' to top of sign Surface evenly paved or hard-packed (no cracks) Surface slope less shan 1:20, 5% Notes: Ramps Site Access, Path of Travel, Entrances Site Access Description Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed Ponding of water? Disembarking area at accessible entrance Path of Travel Description Path does not require the use of stairs Path does not require the use of stairs Path does not require the use of wheelchair ramp Path is stable, firm and slip resistant Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50). Continuous common surface, no changes in level greater than ½ inch Notes: Stairs and Doors Restrooms Floors, Drinking Fountains, Telephones Signs, Signals, and Swyitches Swimming Pool/ Lake beach	NO NO NO NA NO NO NA	S Metered on street parking spaces, no accessible parking spaces Comments
Description Parking Amenities (I=lot, ST-street) Accessible space located closest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft Minimum width of 13 ft includes 8 ft space plus 5 ft access asise Minimum of 1 van space for every accessible space, 8 wide + 8° aisle. Sign with international symbol of accessibility at each space Sign 5°.8° to top of sign Surface evenly paved or hard-packed (no cracks) Surface slope less than 1:20, 5% Notes: Ramps Site Access, Path of Travel, Entrances Site Access Description Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed Ponding of water? Disembarking area at accessible entrance Path of Travel Description Path does not require the use of stairs Path does not require the use of stairs Path does not require the use of wheelchair ramp Path is stable, firm and slip resistant Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50). Continuous common surface, no changes in level greater than ½ inch Notes: Stairs and Doors Restrooms Floors, Drinking Fountains, Telephones Signs, Signals, and Switches Swimming Pool/ Lake beach Shower Rooms	No No No No No No No No	S Metered on street parking spaces, no accessible parking spaces Comments
Description Parking Amenities (L=lot, ST=street) Accessible space located closest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft Minimum width of 13 ft includes 8 ft space plus 5 ft access asise Minimum of 1 van space for every accessible space, 8' wide + 8' asile. Sign with international symbol of accessibility at each space Sign 5'-8' to top of sign Surface evenly paved or hard-packed (no cracks) Surface slope less shan 1:20, 5% Notes: Ramps Site Access, Path of Travel, Entrances Site Access Description Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed Ponding of water? Disembarking area at accessible entrance Path of Travel Description Path does not require the use of stairs Path does not require the use of stairs Path does not require the use of wheelchair ramp Path is stable, firm and slip resistant Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50). Continuous common surface, no changes in level greater than ½ inch Notes: Stairs and Doors Restrooms Floors, Drinking Fountains, Telephones Signs, Signals, and Swyitches Swimming Pool/ Lake beach	NO NO NO NO NA NO NO NO NA	S Metered on street parking spaces, no accessible parking spaces Comments

Facility Name: Cronin's Cove		
Size (Ac): .5		
Address: Lake Avenue, Newton Highlands		
Ward: 6		
General Facility Notes: Steps down from street to a sloped, inaccessible path w/b	enches: no accesible entran	ce: access to Crystal Lake shoreline and canoe launch.
Santa Sany 1000	enones, no accessore enaction	
Site Furnishings	YES	
Description		Comments
Tables & Benches	YES	Laure
Number of Benches Number of Tables	NO AFP	6 benches
Located adjacent to accessible paths	No	ramp leading to natural dirt path level
Back and Arm Rests	YES	
Grills		
Located adjacent to accessible paths Took Care	NA NA	
Trash Cans Located adjacent to accessible paths	No	1
Picnic Shelters		
Located adjacent to accessible paths	NA	
Notes:		
	11/20	
Trails & Paths	YES	Termination of the second of t
Description Surface (A=Asphalt, C=Concrete, SD= stone dust, NS= naturally surfaced, B=Boardwalk, BR=Bridge)	YES	Comments NS
Dimensions (width)		Varies
Rails	No	
Signage for visually impaired	No	
Notes:		
Diam Arras	N/A	
Play Areas	N/A N/A	
Game Areas Boat Docks	Yes	
Description	144	Comments
Facility Type (R=River, P= Pond)	Yes	Pond
Access Routes		
Located adjacent to accessible paths Handrails	No No	
Notes:	1.0	
Fishing Facilities	N/A	
Community Gardens	N/A	
Parking Ramps	N/A N/A	
Site Access, Path of Travel, Entrances	YES	
Site Access		
Description		Comments
Accessible path of travel from passenger disembarking area and parking area to accessible entrance	No	
Surface evenly paved or hard-packed	YES	+
Ponding of water? Disembarking area at accessible entrance	No No	
Path of Travel		+
Description		Comments
Path does not require the use of stairs	YES	
Path does not require the use of wheelchair ramp	YES	
Path is stable, firm and slip resistant Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50).		
Continuous common surface, no changes in level greater than ½ inch		
Any objects protruding onto the pathway must be detected by a person with a visual disability using a cane	NO	
Objects protruding more than 4" from the wall must be within 27" of the ground, or higher than 80"		
Curb on the pathway must have curb cuts at drives,parking and drop-offs	NO	
Notes:		
Stairs and Doors	N/A	
Restrooms	N/A	
Floors, Drinking Fountains, Telephones	N/A	
Signs, Signals, and Switches Swimming Pool/ Lake beach	N/A N/A	
Shower Rooms	N/A	
Picknicking	N/A	
Off Leash Dog Areas (OLA)	N/A	

Facility Name: Crystal Lake Park Size (Ac): 2.0 acres; Crystal Lake: 24 acres Address: 30 Rogers Street, Newton Highlands Ward: 6 General Facility Notes: Parking lot currently not accessible; portions of the bathhouse are accessible; steep slope down to the lake beach area; a ramp from the bathouse to beach area is not accessible; accessible dead-end stone dust pathway runs behind 230 Lake Ave. to Levingston Cove; asphalt sidewalk along Rogers St. constructed in 2016; acrerage breakdown: bathhouse and parking lot: .7 acres; newly acquired 20 Rogers: 1.0 acre; portion of 230 Lake Avenue plus easement behind house: .2 acres. YES Site Furnishings Comments Tables & Benches 4 at sshoreline Number of Benches Yes Number of Tables Yes 10 Located adjacent to accessible paths No Backed benches only, no armrests Back and Arm Rests Yes Grills NA Located adjacent to accessible paths NA Located adjacent to accessible paths Picnic Shelters Located adjacent to accessible paths NA YES Trails & Paths Comments Surface (A=Asphalt, C=Concrete, SD= stone dust, NS= naturally surfaced, B=Boardwalk, BR=Bridge) Yes NS Varies; dirt path Dimensions (width) Rails No Signage for visually impaired No Notes: YES Aquatics Comments Description Facility Type (P=Pool, L=Lake Beach, SP=Splash Pad) Yes Accessible Entrance Nο No accessible path to the park's shoreline. Shoreline is elevated and retained by a wall, public Location from accessible parking NA Safety features i.e. warning for visually impaired NA NA Location from accessible path into water NA Handrails Shade provided (ST=Shade Trees, SS=Shade Shelter) Yes Trees Notes: Play Areas N/A Game Areas N/A N/A **Boat Docks** Fishing Facilities **Community Gardens** N/A YES **Parking** Accessible Spaces Total Spaces 25 2 Spaces Description Comments Parking Amenities (L=lot, ST=street) striped accessible parking spaces do not meet MAAB requirements No Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft NA Minimum width of 13 ft includes 8 ft space plus 5 ft access aisle Yes Minimum of 1 van space for every accessible space, 8' wide + 8' aisle. Yes Sign with international symbol of accessibility at each space Yes Surface evenly paved or hard-packed (no cracks) Yes No Surface slope less than 1:20, 5% NA Curbcut to pathway from parking lot at each space if sidewalk (curb) is present Curbcut is a minimum width of 3 ft, excluding sloped sides, has sloped sides, all slopes not to exceed 1:12, and textured or painted yellow NA Notes: Parking spaces on a slope exceeding MAAB requirements YES Ramps Comments Description

Yes

Yes

Yes

Yes

No

Round

Slope Maximum 1:12

Handgrip oval or round

Handgrip smooth surface

Minimum width 4 ft between handrails

Handrails on both sides if ramp is longer than 6 ft

Handrails at 34" and 19" from ramp surface

Handrails extend 12" beyond top and bottom

Handgrip diameter between 1½" and 2"	V	I
Clearance of 1½" between wall and wall rail	Yes	
	NA	
Non-slip surface	Yes	
Level platforms (4ft x 4 ft) at every 30 ft, at top, at bottom, at change of direction	Yes	
Notes:		
City Assess Dath of Travel Fathers	VEC	
	YES	
Site Access		I
Description Associate and the second distribution and additional distribution and addi		Comments
Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed		
Ponding of water?		
Disembarking area at accessible entrance		
Path of Travel		
Description		Comments
Path does not require the use of stairs	No	All paths are primarily exceeding max slopes
Path does not require the use of wheelchair ramp	Yes	,
Path is stable, firm and slip resistant	Yes	Beach is sand, but paths leading to sand area is slip resistant
Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50).	Yes	Only at ramp and a few other sections. Generally paths are not accessible
Continuous common surface, no changes in level greater than ¼ inch	NO	
Entrances		
Description		Comments
Primary public entrances accessible to person using wheelchair, must be signed, gotten to independently, and not be the service entrance		
Level space extending 5 ft. from the door, interior and exterior of entrance doors		
Minimum 32" clear width opening (i.e. 36" door with standard hinge)		
At least 18" clear floor area on latch, pull side of door		
Door handle no higher than 48" and operable with a closed fist		
Vestibule is 4 ft plus the width of the door swinging into the space		
Entrance(s) on a level that makes elevators accessible		
Door mats less than ½" thick are securely fastened		
Door mats more than '%" thick are recessed		
Grates in path of travel have openings of %" maximum		
Signs at non-accessible entrance(s) indicate direction to accessible entrance		
Emergency egress – alarms with flashing lights and audible signals, sufficiently lighted		
Notes: Bathhouse in moldy due to COVID 19 Closure - Inspection not possible		
	1/50	
	YES	
Notes: Bathhouse in moldy due to COVID 19 Closure - Inspection not possible		
Partner was	VEC	
	YES	
Notes: Bathhouse in moldy due to COVID 19 Closure - Inspection not possible		
Floors Drinking Fountains Tolombons	YES	
Floors, Drinking Fountains, Telephones Notes: Bathhouse in moldy due to COVID 19 Closure - Inspection not possible	TES	
notes. Batimouse in moley due to covid 13 closure - inspection not possible		
Signs Signals and Switches	YES	
Signs, Signals, and Switches Notes: Bathhouse in moldy due to COVID 19 Closure - Inspection not possible	113	
Lake beach	YES	
Description	_	Comments
Ramp at least 34" wide with a non-slip surface extending into the shallow end, slope not exceeding 1:6 with handrails on both sides	Yes	
Lifting device	No	
Transfer area 18" above the path of travel and a minimum of 18" wide	NA	
Unobstructed path of travel not less than 48" wide around pool	NA	
Non-slip surface	No	
Notes:		
	VEC	
	YES	
Notes: Bathhouse in moldy due to COVID 19 Closure - Inspection not possible		
Dicknicking	N/Δ	
	N/A N/A	

Facility Name: Davis 'Tom Torchia' Playground			
Size (Ac): 2.0 acres			_
Address: Eden Street, West Newton			_
Ward: 3			
General Facility Notes: Softball field with no accessible route, basketball court	and playground with accessible	a routa from the 'Family access narking lot: accessible	
pathway from Eden Ave. sidewalk; no curb ramp at entrance; accessible playgr			
Site Furnishings	YES		_
Description Tables & Benches	Yes	Comments	
Number of Benches	Yes	3 - 1 accessible	
Number of Tables Located adjacent to accessible paths	N/A Yes		
Back and Arm Rests	Yes		
Grills Located adjacent to accessible paths	N/A		
Trash Cans	NA		
Located adjacent to accessible paths Picnic Shelters	Yes		
Located adjacent to accessible paths	N/A		
Notes:			
Trails & Paths	YES		_
Description		Comments	
Surface (A=Asphalt, C=Concrete, SD= stone dust, NS= naturally surfaced, B=Boardwalk, BR=Bridge) Dimensions (width)	Yes Yes	A 5'	
Rails	N/A		
Signage for visually impaired Benches	No	see above	
Notes:	·		
Aquatics	YES		_
Description Facility Type (P=Pool, L=Lake Beach, SP=Splash Pad)	Yes	Comments	_
Accessible Entrance	Yes		
Location from accessible parking Safety features i.e. warning for visually impaired	No		
Location from accessible path into water	Yes		
Handrails Shade provided (ST=Shade Trees, SS=Shade Shelter)	N/A Yes	57	
Notes:	,	-	_
Play Areas	YES	le .	
Description Facility Type (3-5 Yrs,5-12 Yrs)	Yes	Comments 18 m - Syrs and 5 - 12 yrs	
Same experience provided to all	no	Yes in 18m - 5 yrs No in 5 - 12 yrs.	
Access Routes Located adjacent to accessible paths	Yes		-
Enough space between equipment for wheelchair	Yes		
Play Areas built in 2017			
Game Areas	YES		
Description		Comments	
Facility Type (RF=Rectangular Fields, BF= Ballfields, BK=Basketball, TN=Tennis, BC=Bocce) Access Routes	Yes	BF and BK	
Located adjacent to accessible paths	Yes		
Berm cuts onto courts Equipment	No		
Spectator Seating			
Notes:			
Post Deale	N/A		_
Boat Docks Fishing Facilities	N/A N/A		_
Community Gardens	N/A		_
Parking Ramps	N/A N/A		_
Site Access, Path of Travel, Entrances	YÉS		
Site Access Description		Comments	
Accessible path of travel from passenger disembarking area and parking area to accessible entrance	N/A	no designated parking space	
Surface evenly paved or hard-packed Ponding of water?	Yes No		
Disembarking area at accessible entrance	No		
Path of Travel Description		Comments	
Path does not require the use of stairs	Yes		
Path does not require the use of wheelchair ramp Path is stable, firm and slip resistant	Yes Yes		
Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50).	Yes		
Continuous common surface, no changes in level greater than ½ inch Any objects protruding onto the pathway must be detected by a person with a visual disability using a cane	Yes Yes		
Any objects protruding onto the partiway must be detected by a person with a visual disability using a cane Objects protruding more than 4" from the wall must be within 27" of the ground, or higher than 80"	Yes N/A		
Curb on the pathway must have curb cuts at drives, parking and drop-offs	N/A		

Entrances			
	Comments		
N/A	no public building		
N/A			
N/A	_		
	N/A		

Facility Name: Edmands Park 'Cabot Woods'		
Size (Ac): 32.6 acres		
Address: Blake Street, Newtonville		
Ward: 2		
General Facility Notes: large, natural, wooded area with meadow and uneven dir	t trail throughout; unofficia	off-leash dog area; park is inaccessible.
Site Furnishings	YES	
Description		Comments
Tables & Benches		
Number of Benches	yes	2 Benches both with backs, one with arm rests
Number of Tables	no	
Located adjacent to accessible paths	no	
Back and Arm Rests	yes	
<u>Grills</u>		
Located adjacent to accessible paths		
Trash Cans		
Located adjacent to accessible paths	yes	Two trash bins located at parking areas; 2 pet waste stations
Picnic Shelters	•	•
Located adjacent to accessible paths	NA NA	
Notes: There is an informational kiosk on site.		
Trails 9. Daths	YES	
Trails & Paths	1123	Comments
Description Control of the Control o		Comments NS
Surface (A=Asphalt, C=Concrete, SD= stone dust, NS= naturally surfaced, B=Boardwalk, BR=Bridge)	yes	
Dimensions (width)		varies
Rails	No	
Signage for visually impaired	No	
Benches Notes:	yes	2 Benches both with backs, one with arm rests
Play Areas	N/A	
	N/A N/A	
Game Areas		
Game Areas Boat Docks	N/A	
Game Areas Boat Docks Fishing Facilities	N/A N/A	
Game Areas Boat Docks Fishing Facilities Community Gardens	N/A N/A N/A	
Game Areas Boat Docks Fishing Facilities Community Gardens Parking	N/A N/A N/A N/A N/A	
Game Areas Boat Docks Fishing Facilities Community Gardens Parking Ramps	N/A N/A N/A N/A	
Game Areas Boat Docks Fishing Facilities Community Gardens Parking Ramps Site Access, Path of Travel, Entrances	N/A N/A N/A N/A N/A N/A	
Game Areas Boat Docks Fishing Facilities Community Gardens Parking Ramps Site Access, Path of Travel, Entrances	N/A N/A N/A N/A N/A N/A	Comments
Game Areas Boat Docks Fishing Facilities Community Gardens Parking Ramps Site Access, Path of Travel, Entrances	N/A N/A N/A N/A N/A N/A	Comments
Game Areas Boat Docks Fishing Facilities Community Gardens Parking Ramps Site Access, Path of Travel, Entrances Bite Access Description	N/A N/A N/A N/A N/A N/A VES	Comments
Game Areas Boat Docks Fishing Facilities Community Gardens Parking Ramps Site Access, Path of Travel, Entrances Site Access Description Accessible path of travel from passenger disembarking area and parking area to accessible entrance	N/A N/A N/A N/A N/A N/A YES	Comments
Game Areas Boat Docks Fishing Facilities Community Gardens Parking Ramps Site Access, Path of Travel, Entrances Site Access Description Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed	N/A N/A N/A N/A N/A N/A YES	Comments
Game Areas Boat Docks Fishing Facilities Community Gardens Parking Ramps Site Access, Path of Travel, Entrances Site Access, Path of Travel, Entrances Site Access Description Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed Ponding of water? Disembarking area at accessible entrance	N/A N/A N/A N/A N/A N/A N/A N/A O N/A VES	Comments
Game Areas Boat Docks Fishing Facilities Community Gardens Parking Ramps Site Access, Path of Travel, Entrances Site Access Description Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed Pending of water? Disembarking area at accessible entrance Path of Travel	N/A N/A N/A N/A N/A N/A N/A N/A O N/A VES	
Game Areas Boat Docks Fishing Facilities Community Gardens Parking Ramps Site Access, Path of Travel, Entrances Site Access Description Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed Pending of water? Disembarking area at accessible entrance Path of Travel	N/A N/A N/A N/A N/A N/A N/A N/A O N/A VES	Comments
Game Areas Boat Docks Fishing Facilities Community Gardens Parking Ramps Site Access, Path of Travel, Entrances Site Access, Path of Travel, Entrances Site Access Description Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed Ponding of water? Disembarking area at accessible entrance Path of Tavel Description	N/A N/A N/A N/A N/A V/ES	
Game Areas Boat Docks Fishing Facilities Community Gardens Parking Ramps Site Access, Path of Travel, Entrances Site Access, Path of Travel, Entrances Site Access Description Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed Ponding of water? Disembarking area at accessible entrance Path of Travel Description Path does not require the use of stairs	N/A N/A N/A N/A N/A N/A N/A N/A YES	
Game Areas Boat Docks Fishing Facilities Community Gardens Parking Ramps Site Access, Path of Travel, Entrances Site Access Description Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed Ponding of water? Disembarking area at accessible entrance Path of Travel Description Path does not require the use of stairs Path does not require the use of wheelchair ramp	N/A	
Game Areas Boat Docks Fishing Facilities Community Gardens Parking Ramps Site Access, Path of Travel, Entrances Site Access, Path of Travel, Entrances Site Access Description Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed Ponding of water? Disembarking area at accessible entrance Path of Travel Description Path does not require the use of stairs Path does not require the use of wheelchair ramp Path is stable, firm and slip resistant Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50).	N/A N/A N/A N/A N/A N/A YES	
Game Areas Boat Docks Fishing Facilities Community Gardens Parking Ramps Site Access, Path of Travel, Entrances Site Access, Path of Travel, Entrances Site Access Description Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed Ponding of water? Disembarking area at accessible entrance Path of Travel Description Path does not require the use of wheelchair ramp Path is stable, firm and slip resistant Slope maximum 220 (5%) and maximum cross pitch is 2% (1:50). Continuous common surface, no changes in level greater than 1% inch	N/A N/A N/A N/A N/A N/A YES	
Game Areas Boat Docks Fishing Facilities Community Gardens Parking Ramps Site Access, Path of Travel, Entrances Site Access, Path of Travel, Entrances Site Access Description Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed Ponding of water? Disembarking area at accessible entrance Path of Travel Description Path does not require the use of wheelchair ramp Path is stable, firm and slip resistant Slope maximum 210 (5%) and maximum cross pitch is 2% (1:50). Continuous common surface, no changes in level greater than ½ inch Notes:	N/A N/A N/A N/A N/A N/A N/A N/A YES	
Game Areas Boat Docks Fishing Facilities Community Gardens Parking Ramps Site Access, Path of Travel, Entrances Site Access Description Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed Pending of water? Disembarking area at accessible entrance Path of Travel Description Path does not require the use of wheelchair ramp Path is stable, firm and silp resistant Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50). Continuous common surface, no changes in level greater than ¼ inch Notes: Stairs and Doors	N/A	
Game Areas Boat Docks Fishing Facilities Community Gardens Parking Ramps Site Access, Path of Travel, Entrances Site Access, Path of Travel, Entrances Site Access Description Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed Ponding of water? Disembarking area at accessible entrance Path of Travel Description Path does not require the use of stairs Path does not require the use of wheelchair ramp Path is stable, firm and slip resistant Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50). Continuous common surface, no changes in level greater than ½ inch Notes: Stairs and Doors Restrooms	N/A N/A	
Surface evenly paved or hard-packed Ponding of water? Disembanking area at accessible entrance Path of Travel Description Path does not require the use of stairs Path does not require the use of wheelchair ramp Path is stable, firm and slip resistant Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50).	N/A N/A	
Game Areas Boat Docks Fishing Facilities Community Gardens Parking Ramps Site Access, Path of Travel, Entrances Site Access, Path of Travel, Entrances Site Access Description Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed Ponding of water? Disembarking area at accessible entrance Path of Travel Description Path does not require the use of stairs Path does not require the use of wheelchair ramp Path is stable, firm and silp resistant Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50). Continuous common surface, no changes in level greater than ½ inch Notes: Stairs and Doors Restrooms Floors, Drinking Fountains, Telephones	N/A	
Game Areas Boat Docks Fishing Facilities Community Gardens Parking Ramps Site Access, Path of Travel, Entrances Site Access, Path of Travel, Entrances Site Access Description Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed Ponding of water? Disembarking area at accessible entrance Path of Travel Description Path does not require the use of stairs Path does not require the use of wheelchair ramp Path is stable, firm and slip resistant Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50). Continuous common surface, no changes in level greater than ½ inch Notes: Stairs and Doors Restrooms	N/A	
Game Areas Boat Docks Fishing Facilities Community Gardens Parking Ramps Site Access, Path of Travel, Entrances Site Access, Path of Travel, Entrances Site Access Description Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed Ponding of water? Disembarking area at accessible entrance Path of Travel Description Path oes not require the use of stairs Path does not require the use of wheelchair ramp Path is stable, firm and slip resistant Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50). Continuous common surface, no changes in level greater than % inch Notes: Stairs and Doors Restrooms Floors, Drinking Fountains, Telephones Signs, Signals, and Switches Swimming Pool/ Lake beach Shower Rooms	N/A	
Game Areas Boat Docks Fishing Facilities Community Gardens Parking Ramps Site Access, Path of Travel, Entrances Site Access Description Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed Pending of water? Disembarking area at accessible entrance Path of Travel Description Path does not require the use of wheelchair ramp Path is stable, firm and silp resistant Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50). Continuous common surface, no changes in level greater than % inch Notes: Stairs and Doors Restrooms Floors, Drinking Fountains, Telephones Signs, Signals, and Switches	N/A	

Facility Name: Eliot Memorial Park		
Size (Ac): .2 acres		
Address: Eliot Memorial Road, Newton Centre		
Ward: 7		
General Facility Notes: historic memorial overlook area; not accessible; no	paths; no site furnishings and amenities	
City Francisking	N/A	
Site Furnishings	N/A	
Trails & Paths	N/A N/A	
Play Areas	N/A	
Game Areas	N/A N/A	
Boat Docks	N/A N/A	
Fishing Facilities	N/A	
Community Gardens Parking	N/A	
Ramps	N/A	
Site Access, Path of Travel, Entrances	N/A	
Stairs and Doors	N/A	
Restrooms	N/A	
Floors, Drinking Fountains, Telephones	N/A	
Signs, Signals, and Switches	N/A	
Swimming Pool/ Lake beach	N/A	
Shower Rooms	N/A	
Picknicking	N/A	
Off Leash Dog Areas (OLA)	N/A	

Facility Name: Elmwood Park	
Size (Ac): 1.5 acres	
Address: LowellAvenue and Elmwood Avenue, Newtonville	
Ward: 2	
General Facility Notes: large, rectangular-shaped traffic island; tree	es, shrubs and lawn only; no pathways; two new benches in lawn area; not accessible.
Site Furnishings	YES
Description	Yes Comments
Tables & Benches	
Number of Benches	Yes 2
Number of Tables	No No
Located adjacent to accessible paths	No No
Back and Arm Rests	Yes benches have backs but no arm rests
Grills	
Located adjacent to accessible paths	NA NA
Trash Cans	·
Located adjacent to accessible paths	NA NA
Picnic Shelters	
Located adjacent to accessible paths	NA NA
Notes:	
Trails & Paths	N/A
Plav Areas	N/A
Game Areas	N/A
Boat Docks	N/A
Fishing Facilities	N/A
Community Gardens	N/A
Parking	N/A
Ramps	N/A
Site Access, Path of Travel, Entrances	N/A
Stairs and Doors	N/A
Restrooms	N/A
Floors, Drinking Fountains, Telephones	N/A
Signs, Signals, and Switches	N/A
Swimming Pool/ Lake beach	N/A
Shower Rooms	N/A
Picknicking	N/A
Off Leash Dog Areas (OLA)	N/A

Facility Name: Emerson Playground		
Size (Ac): 1.0 acres		
Address: Pettee Street, Newton Upper Falls (adjacent to Emerson Community Center)		
Ward: 5		
General Facility Notes: no internal pathways on the playfield; accessible playground area with poure	d in place s	safety surfacing; accessible pathways and benches;
accessible picnic table; accessible basketball court; accessible parking in adjacent building lot; adjace	ent to Eme	rson Community Center.
Site Furnishings	YES	
Description Tables & Benches	Yes	Comments
Number of Benches	Yes	7 benches
Number of Tables	Yes	2 picnic tables
Located adjacent to accessible paths	Yes	
Back and Arm Rests Grills	Yes	3 out of 7 benches are backed, no arm rests
Located adjacent to accessible paths	NA	
Trash Cans		
Located adjacent to accessible paths Picnic Shelters	Yes	
Located adjacent to accessible paths	Yes	
Notes:		
Trails 9 Daths	YES	
Trails & Paths Description	TES	Comments
Surface (A=Asphalt, C=Concrete, SD= stone dust, NS= naturally surfaced, B=Boardwalk, BR=Bridge)	Yes	Asphalt
Dimensions (width)	Yes	4-ft min
Rails Signage for visually impaired	NO NO	
Signage or visually imparied	NO	
Play Areas Description	YES	Comments
Facility Type (3-5 Yrs,5-12 Yrs)	Yes	3-5,5-12
Same experience provided to all	Yes	
Access Routes		
Located adjacent to accessible paths Enough space between equipment for wheelchair	Yes Yes	
Notes:	163	
	VEC	
Game Areas Description	YES	Comments
Facility Type (RF=Rectangular Fields, BF= Ballfields, BK=Basketball, TN=Tennis, BC=Bocce)	Yes	RF, BK, BF
Access Routes		
Located adjacent to accessible paths	Yes	Only basket ball court is along accessible route
Berm cuts onto courts Equipment	NA	
Spectator Seating	Yes	
Notes:		
	N/A	
	N/A	
	N/A N/A	
	N/A	
	YÉS	
Site Access		
Description Accessible path of travel from passenger disembarking area and parking area to accessible entrance	NA NA	Comments
Surface evenly paved or hard-packed	NA NA	
Ponding of water?	NA	
Disembarking area at accessible entrance	NA	
Path of Travel Description		Comments
Path does not require the use of stairs	Yes	Comments
Path does not require the use of wheelchair ramp	Yes	
Path is stable, firm and slip resistant	Yes	
Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50). Continuous common surface, no changes in level greater than % inch	Yes Yes	
	N/A	
	N/A	
Floors, Drinking Fountains, Telephones	N/A	
Signs, Signals, and Switches	N/A	
	N/A N/A	
	N/A	
	N/A	

Facility Name: Hamilton Playground 'Lower Falls'		
Size (Ac): 4.3 acres		
Address: 545 Grove St., Lower Falls		
Ward: 4		
General Facility Notes: Accessible play aparatus area constructed in 2013; level sidewalk circumvent	ts playfield	; no internal pathways; Lower Falls Community Center
building accessible with lift and accessible parking; formerly Hamilton School.		
Site Furnishings	YES	
Description Tables & Benches		Comments
Number of Benches	yes	15 benches - 5 dumor gray slat benches with backs no arm rests, 2 backless bences, 8 benches with
Number of Tables	yes	backs and arm rests 1 picnic table
Located adjacent to accessible paths	no	
Back and Arm Rests	yes	15 benches - 5 dumor gray slat benches with backs no arm rests, 2 backless bences, 8 benches with backs and arm rests
Grilis Located adjacent to accessible paths	no	
Trash Cans Located adjacent to accessible paths	yes	2 big belly trash bin and 2 big belly recycling unit, located in parking lot
Picnic Shelters	yes	
Located adjacent to accessible paths Notes: Two bike racks, one pest waste station, one backless players bench.	no	1 picnic table
Trails & Paths	YES	
Description Surface (A=Asphalt, C=Concrete, SD= stone dust, NS= naturally surfaced, B=Boardwalk, BR=Bridge)	no	Comments
Dimensions (width)		
Rails Signage for visually impaired		
Benches	yes	15 benches - 5 dumor gray slat benches with backs no arm rests, 2 backless bences, 8 benches with backs and arm rests
Notes:		
Play Areas Description	YES	Comments
Facility Type (3-5 Yrs, 5-12 Yrs)	yes	Fibar safety surfacing.
Same experience provided to all Access Routes	yes	
Located adjacent to accessible paths	no	
Enough space between equipment for wheelchair	no	
Notes:		
Game Areas	YES	
Description		Comments
Facility Type (RF-Rectangular Fields, BF= Ballfields, BK=Basketball, TN=Tennis, BC=Bocce) Access Routes	yes	2 TN, 2 BF, 3 RF
Located adjacent to accessible paths	no	
Berm cuts onto courts Equipment	no	
Spectator Seating		
There are 16 parking spaces (15 + 1 handicap parking space). Athletic field is irrigated with well water.		
Post Posts	N/A	
Boat Docks Fishing Facilities	N/A	
Community Gardens	YES	
Description Access Routes		Comments
Located adjacent to accessible paths	yes	
Notes:		
	11.50	
Parking Total Spaces	YES Accessible Spo	ares
16	1 Space	
Description Parking Amenities (L=lot, ST=street)		Comments
Accessible space located closest to accessible entrance	yes	L
Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft	na	
Minimum width of 13 ft includes 8 ft space plus 5 ft access aisle Minimum of 1 van space for every accessible space, 8' wide + 8' aisle.	yes yes	
Sign with international symbol of accessibility at each space	yes	
Sign 5'-8' to top of sign Surface evenly paved or hard-packed (no cracks)	yes no	
Surface slope less than 1:20,5%	yes	
Curbcut to pathway from parking lot at each space if sidewalk (curb) is present .	NA	accessible parking space abutts the building.
Curbcut is a minimum width of 3 ft, excluding sloped sides, has sloped sides, all slopes not to exceed 1:12, and textured or painted yellow Notes:	no	
Ramps	N/A	
Site Access, Path of Travel, Entrances	YES	
Site Access Description		Comments

Accessible path of travel from passenger disembarking area and parking area to accessible entrance	yes	
Surface evenly paved or hard-packed	yes	
Ponding of water?		
Disembarking area at accessible entrance	yes	
Path of Travel		
Description Call the control and the control a		Comments
Path does not require the use of stairs Path does not require the use of wheelchair ramp	yes	
Path is stable, firm and slip resistant		
Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50).	yes	
Stope maximum 1.20 (5%) and maximum cross pricin 5.2% (1.30). Continuous common surface, no changes in level greater than ½ inch	yes	
Any objects protruding onto the pathway must be detected by a person with a visual disability using a cane		
Objects protruding more than 4" from the wall must be within 27" of the ground, or higher than 80"		
Curb on the pathway must have curb cuts at drives, parking and drop-offs		
Entrances		
Description		Comments
Primary public entrances accessible to person using wheelchair, must be signed, gotten to independently, and not be the service entrance	yes	Commence
Level space extending 5 ft. from the door, interior and exterior of entrance doors	yes	
Minimum 32" clear width opening (i.e. 36" door with standard hinge)	yes	
At least 18" clear floor area on latch, pull side of door	Yes	
Door handle no higher than 48" and operable with a closed fist	Yes	
Vestibule is 4 ft plus the width of the door swinging into the space		N/A
Entrance(s) on a level that makes elevators accessible	Yes	
Door mats less than ½" thick are securely fastened	No	
Door mats more than ½" thick are recessed	No	
Grates in path of travel have openings of ½" maximum		N/A
Signs at non-accessible entrance(s) indicate direction to accessible entrance	Yes	
Emergency egress – alarms with flashing lights and audible signals, sufficiently lighted	Yes	
Notes:		
Stairs and Doors	YES	
Stairs		
Description		Comments
Open risers	No	
Nosings not projecting	No	
Treads no less than 11" wide	Yes	
Handrails on both sides	Yes	
Handrails 34"-38" above tread	Yes	
Handrail extends a minimum of 1' beyond top and bottom riser (if no safety hazard and space permits)	Yes	
Handgrip oval or round	Yes	
Handgrip has a smooth surface	Yes	
Handgrip diam. 1½" - 1½"	Yes	
1½" clearance between wall and handrail	Yes	
<u>Doors</u>		
Description		Comments
Minimum 32" clear opening	yes	
At least 18" clear floor space on pull side of door	yes	
Threshold maximum %" high, beveled on both sides	Yes	
Hardware operable with a closed fist (no conventional door knobs or thumb latch devices)	Yes	
Hardware operable with a closed fist (no conventional door knobs or thumb latch devices) Hardware minimum 36", maximum 48" above the floor	Yes Yes	
Hardware minimum 36", maximum 48" above the floor	Yes	N/A
Hardware minimum 36", maximum 48" above the floor Clear, level floor space extends out 5 ft from both sides of the door	Yes	N/A N/A
Hardware minimum 36", maximum 48" above the floor Clear, level floor space extends out 5 ft from both sides of the door Door adjacent to revolving door is accessible and unlocked	Yes	
Hardware minimum 36", maximum 48" above the floor Clear, level floor space extends out 5 ft from both sides of the door Door adjacent to revolving door is accessible and unicoked Doors opening into hazardous area have hardware that is knufled or roughened	Yes	
Hardware minimum 36", maximum 48" above the floor Clear, level floor space extends out 5 ft from both sides of the door Door adjacent to revolving door is accessible and unicoked Doors opening into hazardous area have hardware that is knufled or roughened	Yes Yes	
Hardware minimum 36", maximum 48" above the floor Clear, level floor space extends out 5 ft from both sides of the door Door adjacent to revolving door is accessible and unlocked Doors opening into hazardous area have hardware that is knurled or roughened	Yes	N/A
Hardware minimum 36", maximum 48" above the filoor Clear, level floor space extends out 5 ft from both sides of the door Door adjacent to revolving door is accessible and unlocked Doors opening into hazardous area have hardware that is knurled or roughened Notes: Restrooms Description	Yes Yes	
Hardware minimum 36", maximum 48" above the floor Clear, level floor space extends out 5 ft from both sides of the door Door adjacent to revolving door is accessible and unlocked Doors opening into hazardous area have hardware that is knurled or roughened Notes: Restrooms Description 5 ft turning space measured 12" from the floor	Yes Yes	N/A
Hardware minimum 36", maximum 48" above the filoor Clear, level floor space extends out 5 ft from both sides of the door Door adjacent to revolving door is accessible and unlocked Doors opening into hazardous area have hardware that is knurled or roughened Notes: Restrooms Description	Yes Yes	N/A Comments
Hardware minimum 36", maximum 48" above the filoor Clear, level floor space extends out 5 ft from both sides of the door Door adjacent to revolving door is accessible and unlocked Doors opening into hazardous area have hardware that is knurled or roughened Notes: Restrooms Description 5 ft turning space measured 12" from the floor At least one Sink Description	Yes Yes YES Yes	N/A
Hardware minimum 36", maximum 48" above the filoor Clear, level floor space extends out 5 ft from both sides of the door Door adjacent to revolving door is accessible and unlocked Doors opening into hazardous area have hardware that is knurled or roughened Notes: Restrooms Description 5 ft turning space measured 12" from the floor At least one Sink Description Clear floor space of 30" by 48" to allow a forward approach	Yes Yes Yes Yes	N/A Comments
Hardware minimum 36", maximum 48" above the floor Clear, level floor space extends out 5 ft from both sides of the door Door adjacent to revolving door is accessible and unlocked Doors opening into hazardous area have hardware that is knurled or roughened Notes: Restrooms Description 5 ft turning space measured 12" from the floor At least one Sink Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim	YES YES Yes Yes Yes	N/A Comments
Hardware minimum 36", maximum 48" above the floor Clear, level floor space extends out 5 ft from both sides of the door Door adjacent to revolving door is accessible and unlocked Doors opening into hazardous area have hardware that is knurled or roughened Notes: Restrooms Description 5 ft turning space measured 12" from the floor At least one Sink Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall	YES YES Yes Yes Yes Yes Yes	N/A Comments
Hardware minimum 36", maximum 48" above the filoor Clear, level floor space extends out 5 ft from both sides of the door Door adjacent to revolving door is accessible and unlocked Doors opening into hazardous area have hardware that is knurled or roughened Notes: Restrooms Description S ft turning space measured 12" from the floor At least one Silon Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high	YES YES YES YES YES YES YES YES	N/A Comments
Hardware minimum 36", maximum 48" above the floor Clear, level floor space extends out 5 ft from both sides of the door Door adjacent to revolving door is accessible and unlocked Doors opening into hazardous area have hardware that is knurled or roughened Notes: Restrooms Description 5 ft turning space measured 12" from the floor At least one Sink Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation	YES Ye	N/A Comments
Hardware minimum 36", maximum 48" above the floor Clear, level floor space extends out 5 ft from both sides of the door Door adjacent to revolving door is accessible and unlocked Doors opening into hazardous area have hardware that is knurled or roughened Notes: Restrooms Description 5 ft turning space measured 12" from the floor At least one Sisk Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Fauceto operable with closed fist (lever or spring activated handle)	YES YES YES YES YES YES YES YES	N/A Comments
Hardware minimum 36", maximum 48" above the floor Clear, level floor space extends out 5 ft from both sides of the door Door adjacent to revolving door is accessible and unlocked Doors opening into hazardous area have hardware that is knurled or roughened Notes: Restrooms Description S ft turning space measured 12" from the floor At least one Sink Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucts Openable with Closed fist (lever or spring activated handle) At least one Stall	YES Ye	Comments Comments
Hardware minimum 36", maximum 48" above the floor Clear, level floor space extends out 5 ft from both sides of the door Door adjacent to revolving door is accessible and unlocked Doors opening into hazardous area have hardware that is knurled or roughened Notes: Restrooms Description 5 ft turning space measured 12" from the floor At least one Sink Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucets openable with closed fist (lever or spring activated handle) At least one Sink Description	YES	N/A Comments
Hardware minimum 36", maximum 48" above the floor Clear, level floor space extends out 5 ft from both sides of the door Door adjacent to revolving door is accessible and unlocked Doss opening into hazardous area have hardware that is knurled or roughened Notes: Restrooms Description 5 ft turning space measured 12" from the floor At least one Sink Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucets operable with closed fist (lever or spring activated handle) At least one Stall Description Coccerification Accessible to person using wheelchair at 50" wideby 72" deep	Yes Yes Yes Yes Yes Yes Yes Yes Y	Comments Comments
Hardware minimum 36", maximum 48" above the floor Clear, level floor space extends out 5 ft from both sides of the door Door adjacent to revolving door is accessible and unlocked Doors opening into hazardous area have hardware that is knurled or roughened Notes: Restrooms Description 5 ft turning space measured 12" from the floor At least one Sink Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, helight 34" to top of rim Extends at least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucets operable with closed fist (lever or spring activated handle) At least one Stall Description Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide	Yes	Comments Comments
Hardware minimum 36", maximum 48" above the floor Clear, level floor space extends out 5 ft from both sides of the door Door adjacent to revolving door is accessible and unlocked Doors opening into hazardous area have hardware that is knurled or roughened Notes: Restrooms Description 5 ft turning space measured 12" from the floor At least one Sink Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucets openable with closed fist (lever or spring activated handle) At least noe Sink Description Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door is 36" wide	YES	Comments Comments
Hardware minimum 36", maximum 48" above the floor Clear, level floor space extends out 5 ft from both sides of the door Door adjacent to revolving door is accessible and unicoked Doors opening into hazardous area have hardware that is knurled or roughened Notes: Restrooms Description 5 ft turning space measured 12" from the floor At least one Sink Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucts openable with closed fist (lever or spring activated handle) At least one Stall Description Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door is 36" wide Stall door is self closing	Yes Yes Yes Yes Yes Yes Yes Yes Y	Comments Comments
Hardware minimum 36", maximum 48" above the floor Clear, level floor space extends out 5 ft from both sides of the door Door adjacent to revolving door is accessible and unlocked Doors opening into hazardous area have hardware that is knurled or roughened Notes: Restrooms Description 5 ft turning space measured 12" from the floor At least one Sink Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucets operable with closed fist (lever or spring activated handle) At least one Stall Description Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door is 36" wide Stall door is a6" door is self closing Stall door is a9" using some the stall stall door is self closing Stall door is an application.	Yes	Comments Comments Comments
Hardware minimum 36", maximum 48" above the floor Clear, level floor space extends out 5 ft from both sides of the door Door adjacent to revolving door is accessible and unlocked Doors opening into hazardous area have hardware that is knurled or roughened Notes: Restrooms Description 5 ft turning space measured 12" from the floor At least one Sink Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall Open knees pace a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucets openable with closed fist (lever or spring activated handle) At least one Sink Description Sald door is 36" wide Stall door sins of "Wide Sald or sing she wide y 72" deep Stall door is 56" wide Stall door sins 56" wide Stall door sins pull latch Lock on stall door is openable with a closed fist, and 32" above the floor	Yes Yes Yes Yes Yes Yes Yes Yes Y	Comments Comments
Hardware minimum 36", maximum 48" above the floor Clear, level floor space extends out 5 ft from both sides of the door Door adjacent to revolving door is accessible and unlocked Doors opening into hazardous area have hardware that is knurled or roughened Notes: Restrooms Description S ft turning space measured 12" from the floor At least one Sink Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucets openable with closed fist (lever or spring activated handle) At least one Stall Description Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door is 56" wide Stall door is self closing Stall door is self closing Stall door is self closing Stall door is 54" high	Yes	Comments Comments Comments
Hardware minimum 36", maximum 48" above the floor Clear, level floor space extends out 5 ft from both sides of the door Door adjacent to revolving door is accessible and unlocked Doors opening into hazardous area have hardware that is knurled or roughened Notes: Restrooms Description 5 ft turning space measured 12" from the floor At least one Sink Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucets operable with closed fist (lever or spring activated handle) At least one Stall Description Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door is 36" wide Stall door is self closing Stall door is 154" high Tollets	Yes	Comments Comments Comments 42in
Hardware minimum 36", maximum 48" above the floor Clear, level floor space extends out 5 ft from both sides of the door Door adjacent to revolving door is accessible and inclosed Doors opening into hazardous area have hardware that is knurled or roughened Notes: Restrooms Description Sit turning space measured 12" from the floor At least one Sink Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wail Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucets openable with closed fist (lever or spring activated handle) At least one Sisk Description Stall door is self closing Stall door is self closing Stall door is operable with a closed fist, and 32" above the floor Cost hook is 54" high Tollet Description	YES	Comments Comments Comments
Hardware minimum 36", maximum 48" above the floor Clear, level floor space extends out 5 ft from both sides of the door Door adjaction to revolving door is accessible and inclosed Doors opening into hazardous area have hardware that is knurled or roughened Notes: Restrooms Description 5 ft turning space measured 12" from the floor At least one Sink Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucets openable with closed fist (lever or spring activated handle) At least one Siall At least one Siall Open knee space a minimum 19" deep, 30" width, and 27" deep Stall door is 36" wide Stall door is 36" wide Stall door is 36" wide Stall door swings out Stall door is self closing Stall door swings out Stall door is self closing Stall door swings out Stall door is self closing Stall door swings out Stall door is self closing Stall door swings out Stall door is openable with a closed fist, and 32" above the floor Coat hook is 54" high Tollet Description 18" from center to nearest side wall	Yes	Comments Comments Comments 42in
Hardware minimum 36", maximum 48" above the floor Clear, level floor space extends out 5 ft from both sides of the door Door adjacent to revolving door is accessible and unlocked Doos opening into hazardous area have hardware that is knurled or roughened Notes: Restrooms Description Sh turning space measured 12" from the floor At least one Sink Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucets operable with closed fist (lever or spring activated handle) At least one Sill Description Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door is 36" wide Stall door is 16" dosing Stall door is operable with a closed fist, and 32" above the floor Coat hook is 54" high Tollet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fisture	Yes Yes Yes Yes Yes Yes Yes Yes Y	Comments Comments Comments 42in
Hardware minimum 36", maximum 48" above the floor Clear, level floor space extends out 5 ft from both sides of the door Door adjacent to revolving door is accessible and minoloced Doors opening into hazardous area have hardware that is knurled or roughened Notes: Restrooms Description 5 ft turning space measured 12" from the floor At least one Sink Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall Doen knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucets operable with closed fist (lever or spring activated handle) At least one Silk Description Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door is 16" wide Stall door is operable with a closed fist, and 32" above the floor Cost hook is 54" high Tollet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fisture Top of seat 17"-19" above the floor	Yes	Comments Comments Comments 42in
Hardware minimum 36", maximum 48" above the floor Clear, level floor space extends out 5 ft from both sides of the door Door adjactent to revolving door is accessible and inclosed Doors opening into hazardous area have hardware that is knurled or roughened Notes: Restrooms Description 5 ft turning space measured 12" from the floor At least one Sink Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucets operable with closed fist (lever or spring activated handle) At least one Stall Description Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door swings out Stall door swings cout in the surface of the start of the surface of t	Yes Yes Yes Yes Yes Yes Yes Yes Y	Comments Comments Comments Comments Comments Comments
Hardware minimum 36", maximum 48" above the floor Clear, level floor space extends out 5 ft from both sides of the door Door adjacent to revolving door is accessible and unlocked Doos opening into hazardous area have hardware that is knurled or roughened Notes: Restrooms Description S ft turning space measured 12" from the floor At least one Sink Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucets operable with closed fist (lever or spring activated handle) At least one Sinl Description Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door is 36" wide Stall door is self closing Stall door is self closing Stall door is self or sing a special with a closed fist, and 32" above the floor Cost hooks is 54" high Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor Grab Bars Description	Yes Yes Yes Yes Yes Yes Yes Yes Y	Comments Comments Comments 42in
Hardware minimum 36", maximum 48" above the floor Clear, level floor space extends out 5 ft from both sides of the door Door adjacent to revolving door is accessible and incloded Doors opening into hazardous area have hardware that is knurled or roughened Notes: Restrooms Description Sit turning space measured 12" from the floor At least one Sink Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucets openable with closed fist (lever or spring activated handle) At least one Silk Description Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door is self closing Stall door is self closing Stall door is openable with a closed fist, and 32" above the floor Cost took is 54" high Tolles Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fisture Top of seat 17"-19" above the floor Grab Bass Description On back and side wall closest to toilet	YES	Comments Comments Comments Comments Comments Comments
Hardware minimum 36", maximum 48" above the floor Clear, level floor space extends out 5 ft from both sides of the door Door adjacent to revolving door is accessible an unlocked Doors opening into hazardous area have hardware that is knurled or roughened Notes: Restrooms Description 5 ft turning space measured 12" from the floor At least one Sink Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 32" from the wall Open knees space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucets operable with closed fist (lever or spring activated handle) At least one Siall Description Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door is 36" wide Stall door is operable with a closed fist, and 32" above the floor Coart hook is 54" high Tollet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fisture Top of seal 17" 3" above the floor Grab Bars Description Oh back and side wall closest to toilet 1%" diameter	Yes	Comments Comments Comments Comments Comments Comments
Hardware minimum 36", maximum 48" above the floor Clear, level floor space extends out 5 ft from both sides of the door Door adjacent to revolving door is accessible and unlocked Doors opening into hazardous area have hardware that is knurled or roughened Notes: Restrooms Description 5 ft turning space measured 12" from the floor At least one Sink Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucets operable with closed fist (lever or spring activated handle) At least one Stall Description Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door is 36" wide Stall door is self closing Stall door is self closing Stall door is operable with a closed fist, and 32" above the floor Cost hook is 54" high Tollet Description All "form enter to nearest side wall 42" minimum clear space from center to farthest wall or fisture Top of seal 17"-15" above the floor Grab Bars Description On back and side wall closest to toillet 11%" clearance to wall	YES	Comments Comments Comments Comments Comments Comments
Hardware minimum 36", maximum 48" above the floor Clear, level floor space extends out 5 ft from both sides of the door Door adjacter to revolving door is accassible an unlocked Doors opening into hazardous area have hardware that is knuffed or roughened Notes: Restrooms Description 5 ft turning space measured 12" from the floor At least one Sink Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucets operable with closed fist (lever or spring activated handle) Atleast one Sill Description Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 56" wide Stall door is self closing Stall door is operable with a closed fist, and 32" above the floor Coat hook is 54" high Tellet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fisture Top of seat 17"-19" above the floor Grab Bars Description On back and side wall closest to toilet 11%" clearance to wall Locked 30" above and parallel to the floor	Yes	Comments Comments Comments Comments Comments Comments
Hardware minimum 36", maximum 48" above the floor Clear, level floor space extends out 5 ft from both sides of the door Door adjacent to revolving door is accessible and unlocked Doors opening into hazardous area have hardware that is knurled or roughened Notes: Restrooms Description 5 ft turning space measured 12" from the floor At least one Siak Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 3" to top of rim Extends at least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucets openable with closel fist (lever or spring activated handle) At least one Stall Description Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door is 36" wide Stall door is self closing Stall door is openable with closed fist, and 32" above the floor Coat hook is 54" high Telles Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor Grab Bars Description 13" clear center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor Grab Bars Description 13" clear and side wall closest to toilet 13" clearance to wall 14" clearance to wall	Yes	Comments Comments Comments Comments Comments Comments
Hardware minimum 36", maximum 48" above the floor Clear, level floor space extends out 5 ft from both sides of the door Door adjacent to revolving door is accessible and unlocked Doors opening into hazardous area have hardware that is knurled or roughened Notes: Restrooms Description Sot turning space measured 12" from the floor At least are Sink Oescription Oescription Sot turning space measured 12" from the floor At least are Sink Oescription Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucets operable with closed fist (lever or spring activated handle) At least and exist Description Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door is 96" wide Stall door is 97" wide Tallet Description Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 96" wide Tallet Description Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 96" wide Stall door of 97" wide Stall door is 96" wide Stall door of 97" wide Stall door of 97" wide Stall door of 97" wide Sta	Yes	Comments Comments Comments Comments Comments Comments
Hardware minimum 36", maximum 48" above the floor Clear, level floor space extends out 5 ft from both sides of the door Door adjacent to revolving door is accessible and unicoked Doors opening into hazardous area have hardware that is knurled or roughened Notes: Restrooms Description 5 ft turning space measured 12" from the floor At least one Sink Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall Open knee space a minimum 39" deep, 30" width, and 27" high Cover exposed plays with insulation Faucets operable with closed fist (lever or spring activated handle) At least one Stall Description Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door is 36" wide Stall door is wings out Stall door is self closing Stall door is self closing Stall door is self closing Stall door is not person wings out Stall door is not consume to the floor Cost hook is 54" high Tollest Description 18" from center to nearest side wall Lock on stall good or so goverable with a closed fist, and 32" above the floor Cost hook is 54" high Tollest Description 18" from center to nearest side wall Lock on stall god and side wall closest to tollet 13" diameter 13" diameter 13" diameter 13" clearance to wall Locket 30" above and garaillel to the floor Addet-ched or roughened surface 42" long Pattures	Yes	Comments Comments Comments Comments Comments Comments A2in Comments
Hardware minimum 36", maximum 48" above the floor Clear, Iveel floor space extends out 5 ft from both sides of the door Door adjacent to revolving door is accessible and unlocked Doos pening into hazardous area have hardware that is knufed or roughened Notes: Restrooms Description S it turning space measured 12" from the floor Atlest one Sink Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to 10p of rim Extends at least 22" from the wall Opens knee space a minimum 19" deep, 30" width, and 27" high Cover expode pipes with insulation Faucet operable with closed fist (lever or spring activated handle) At least one Siall Description Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door is 36" wide Stall door is self closing Stall door is ap aul latch Lock on stall door is operable with a closed fist, and 32" above the floor Cast hook is 54" high Tollet Description On back and side wall closest to toilet 1%" clearance to wall Lock cort organised solve and parallel to the floor Accessible to person using wheelchair at 60" wideby 72" deep Stall door is self closing Stall door is self closing Stall door is self closing Stall door is cort organised swith a closed fist, and 32" above the floor Cast hook is 54" high Tollet Description On back and side wall closest to toilet 1%" clearance to wall Located 30" above and parallel to the floor Accessible to generate the recomment of arthest wall or fixture Top of seat 17"-19" above the floor Accessible to generate the floor organised surface 42" long Baltures Description	YES	Comments Comments Comments Comments Comments Comments
Hardware minimum 36", maximum 48" above the floor Cless, fivell floor space extends out 5 ft from both sides of the door Door adjacent for revelving floor is accessible and unlocked Doors opening into hazandous area have hardware that is knurled or roughened Notes: Restrooms Description 5 ft turning space measured 12" from the floor At least one Sink Description Cless floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover expoded pipes with insulation Faucets openable with closed fist (lever or spring activated handle) Attleast one Stall Description Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door is 36" wide Stall door is self closing Stall door has a pul llatch Lock on stall door is openable with a closed fist, and 32" above the floor Coat hook is 54" high Description 18" from center to nearest side wall 42" minimum dies space from center to farthest wall or fisture Top of seat 17"-19" above the floor Grab Bars Description On back and side wall closest to toilet 13" "diameter This diameter 13" "diameter Description 13" diameter	Yes	Comments Comments Comments Comments Comments Comments A2in Comments
Hardware minimum 36", maximum 48" above the floor Clear, fivel floor space extends out 5 ft from both iddes of the door Door adjacent to revolving door is accessible and unlocked Doors pening into hazardous area have hardware that is knurled or roughened Notes: Restrooms Description S it turning space measured 12" from the floor Atlest ane Shi Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Estends at least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover expode plep swith insulation Faucets operable with closed fist (lever or spring activated handle) At least one Stall Description Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door is 36" wide Description 18" from center to nearest side wall 42" minimum dear space from center to farthest wall or fixture Top of seat 7"-19" above the floor Goat back and side wall closest to toilet 11" distance Description Description On back and side wall closest to toilet 11" clearance to roughened surface 42" long Haluss Description	YES	Comments Comments Comments Comments Comments Comments A2in Comments

Notes:		
	WEG	
Floors, Drinking Fountains, Telephones	YES	
Floors		
Description		Comments
Non-slip surface	No	
Carpeting is high-density, low pile, non-absorbent, stretched taut, securely anchored	Yes	
Corridor width minimum is 3 ft	Yes	
Objects (signs, ceiling lights, fixtures) can only protrude 4" into the path of travel from a height of 27" to 80" above the floor	Yes	
<u>Drinking Fountains</u>		
Description		Comments
Spouts no higher than 36" from floor to outlet	Yes	
Hand operated push button or level controls	Yes	
Spouts located near front with stream of water as parallel to front as possible	Yes	
If recessed, recess a minimum 30" width, and no deeper than depth of fountain	Yes	
If no clear knee space underneath, clear floor space 30" x 48" to allow parallel approach	Yes	
Notes:		
Signs, Signals, and Switches	YES	
Switches, Controls and Signs		
Description		Comments
Switches and controls for light, heat, ventilation, windows, fire alarms, thermostats, etc, must be a minimum of 36" and a maximum of 48" above the floor for a forward	Yes	
reach, a maximum of 54" for a side reach		
Electrical outlets centered no lower than 18" above the floor	Yes	
Warning signals must be visual as well as audible	Yes	
<u> </u>		
Swimming Pool/ Lake beach	N/A	
Shower Rooms	N/A	
Picknicking	N/A	
Off Leash Dog Areas (OLA)	N/A	

Facility Name: Harry Gath Memorial Pool and Bathhouse			
Size (Ac): .6 Acres inclusive of the Bathouse building			
Address: 250 Albemarle Road, Newtonville			
Ward: 2			
General Facility Notes: Interior renovation in 2013 included: updated accessible bathrooms, accessib	le pool de	ck, and pool accessible with lift access; accessible bubbler;	
kiddie pool not accessible; adjacent fieldhouse is accessible; on-street parking on Albemarle Rd.			
	N/A		
Trails & Paths	N/A VEC		
Aquatics Description	YES	Comments	
Facility Type (P=Pool, L=Lake Beach, SP=Splash Pad)	Pool		
Accessible Entrance	Yes		
Location from accessible parking Safety features i.e. warning for visually impaired	Yes		
Location from accessible path into water	Yes		
Handrails	Yes		
Shade provided (ST=Shade Trees, SS=Shade Shelter)	SS		
Notes:			
Play Areas	N/A		
	N/A YES		
Parking Notes: See Albemarle Park Parking Count	TES		
ů			
Ramps	YES		
Description		Comments	
Slope Maximum 1:12	Yes		
Minimum width 4 ft between handrails	Yes		
Handrails on both sides if ramp is longer than 6 ft Handrails at 34" and 19" from ramp surface	Yes		
Handrails extend 12" beyond top and bottom	Yes		
Handgrip oval or round	Round		
Handgrip smooth surface	Yes		
Handgrip diameter between 1½" and 2" Clearance of 1½" between wall and wall rail	Yes		
Non-slip surface	Yes		
Level platforms (4ft x 4 ft) at every 30 ft, at top, at bottom, at change of direction	Yes		
Notes:			
	YES		
Path of Travel Description		Comments	
Path does not require the use of stairs	no		
Path does not require the use of wheelchair ramp	no		
Path is stable, firm and slip resistant	yes		
Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50). Continuous common surface, no changes in level greater than ¼ inch	no yes		
Entrances	,		
Description		Comments	
Primary public entrances accessible to person using wheelchair, must be signed, gotten to independently, and not be the service entrance Notes:	No		
Stairs and Doors	YES		
Description Open description	No	Comments	
Open risers Nosings not projecting	Yes		
Treads no less than 11" wide	Yes		
Handrails on both sides	Yes		
Handrails 34"-38" above tread Handrail extends a minimum of 1' beyond top and bottom riser (if no safety hazard and space permits)	Yes		
Handgrip oval or round	No		
Handgrip has a smooth surface	Yes		
Handgrip diam. 1½" - 1½" 1½" clearance between wall and handrail	No Yes		
Doors	165		
Description		Comments	
Minimum 32" clear opening	Yes	N/A	
At least 18" clear floor space on pull side of door Closing speed minimum 3 seconds to within 3" of the latch		N/A N/A	
Maximum pressure 5 pounds interior doors		N/A	
Threshold maximum ½" high, beveled on both sides	Yes		
Hardware operable with a closed fist (no conventional door knobs or thumb latch devices) Hardware minimum 36", maximum 48" above the floor	Yes		
Clear, level floor space extends out 5 ft from both sides of the door	Yes		
Door adjacent to revolving door is accessible and unlocked		N/A	
Doors opening into hazardous area have hardware that is knurled or roughened Notes:		N/A	

Restrooms Description	VEC	
	YES	Comments
5 ft turning space measured 12" from the floor	Yes	Comments
At least one Sink		
Description		Comments
Clear floor space of 30" by 48" to allow a forward approach	Yes	
Mounted without pedestal or legs, height 34" to top of rim	Yes	
Extends at least 22" from the wall	Yes	
Open knee space a minimum 19" deep, 30" width, and 27" high	Yes	
Cover exposed pipes with insulation	No	
Faucets operable with closed fist (lever or spring activated handle) At least one Stall	Yes	
	1	C
Description Accessible to person using wheelchair at 60" wideby 72" deep	Yes	Comments
Stall door is 36" wide	Yes	
Stall door swings out	Yes	
Stall door is self closing	No	
Stall door has a pull latch	Yes	
Lock on stall door is operable with a closed fist, and 32" above the floor	Yes	
Coat hook is 54" high	No	
Toilet		-
Description		Comments
18" from center to nearest side wall	Yes	40%
42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor	No Yes	40in
Top or seat 17 - 19 above the noon	res	
Description		Comments
On back and side wall closest to toilet	Yes	
1½" diameter	Yes	
1½" clearance to wall	Yes	
Located 30" above and parallel to the floor	Yes	
Acid-etched or roughened surface	Yes	
42" long	Yes	
Fixtures		
Description		Comments
1%" diameter	Yes	
1%" clearance to wall	Yes	
Located 30" above and parallel to the floor	Yes	
Notes:		
Floor Dainting Fountains Tolonhouse	YES	
Floors, Drinking Fountains, Telephones	TES	
Floors		[c
Description Non-slip surface	Yes	Comments
Carpeting is high-density, low pile, non-absorbent, stretched taut, securely anchored	ies	N/A
Corridor width minimum is 3 ft	Yes	'
Objects (signs, ceiling lights, fixtures) can only protrude 4" into the path of travel from a height of 27" to 80" above the floor	Yes	
<u>Drinking Fountains</u>		
Description		Comments
Spouts no higher than 36" from floor to outlet		
· · · · · · · · · · · · · · · · · · ·	NA	Drinking fountains inoperatble due to lead
Hand operated push button or level controls	NA	Drinking fountains inoperatble due to lead
Hand operated push button or level controls Spouts located near front with stream of water as parallel to front as possible	NA NA	Drinking fountains inoperatble due to lead Drinking fountains inoperatble due to lead
Hand operated push button or level controls Spouts located near front with stream of water as parallel to front as possible If recessed, recess a minimum 30° width, and no deeper than depth of fountain	NA NA NA	Drinking fountains inoperatble due to lead Drinking fountains inoperatble due to lead Drinking fountains inoperatble due to lead
Hand operated push button or level controls Spouts located near front with stream of water as parallel to front as possible If necessed, necess a minimum 30" width, and no deeper than depth of fountain If no clear knee space underneath, clear floor space 30" x 48" to allow parallel approach	NA NA	Drinking fountains inoperatble due to lead Drinking fountains inoperatble due to lead
Hand operated push button or level controls Spouts located near front with stream of water as parallel to front as possible If recessed, recess a minimum 30° width, and no deeper than depth of fountain	NA NA NA	Drinking fountains inoperatble due to lead Drinking fountains inoperatble due to lead Drinking fountains inoperatble due to lead
Hand operated push button or level controls Spouts located near front with stream of water as parallel to front as possible If necessed, necess a minimum 30" width, and no deeper than depth of fountain If no clear knee space underneath, clear floor space 30" x 48" to allow parallel approach	NA NA NA	Drinking fountains inoperatble due to lead Drinking fountains inoperatble due to lead Drinking fountains inoperatble due to lead
Hand operated push button or level controls Spouts located near front with stream of water as parallel to front as possible If necessed, necess a minimum 307 width, and no desper than depth of fountain If no clear knee space underneath, clear floor space 30" x 48" to allow parallel approach Notes:	NA NA NA NA	Drinking fountains inoperatble due to lead Drinking fountains inoperatble due to lead Drinking fountains inoperatble due to lead
Hand operated push button or level controls Spouts located near front with stream of water as parallel to front as possible If recessed, recess a minimum 30" width, and no deeper than depth of fountain If no clear knee space underneath, clear floor space 30" x 48" to allow parallel approach Notes: Signs, Signals, and Switches	NA NA NA	Drinking fountains inoperatble due to lead Drinking fountains inoperatble due to lead Drinking fountains inoperatble due to lead
Hand operated push button or level controls Spouts located near front with stream of water as parallel to front as possible If recessed, recess a minimum 30" width, and no deeper than depth of fountain If no clear knee space underneath, clear floor space 30" x 48" to allow parallel approach Notes: Signs, Signals, and Switches Switches, Controls and Signs	NA NA NA NA	Drinking fountains inoperatible due to lead
Hand operated push button or level controls Spouts located near front with stream of water as parallel to front as possible If recessed, recess a minimum 30" width, and no deeper than depth of fountain If no clear knee space underneath, clear floor space 30" x 48" to allow parallel approach Notes: Signs, Signals, and Switches Switches, Centrols and Signs Description Switches and controls for light, heat, ventilation, windows, fire alarms, thermostats, etc, must be a minimum of 36" and a maximum of 48" above the floor for a forward	NA NA NA NA NA	Drinking fountains inoperatble due to lead Drinking fountains inoperatble due to lead Drinking fountains inoperatble due to lead
Hand operated push button or level controls Spouts located near front with stream of water as parallel to front as possible if recessed, recess a minimum 30" width, and no deeper than depth of fountain if no clear knee space underneath, clear floor space 30" x 48" to allow parallel approach Notes: Signs, Signals, and Switches Switches, Controls and Signs Description Switches and controls for light, heat, ventilation, windows, fire alarms, thermostats, etc., must be a minimum of 36" and a maximum of 48" above the floor for a forward reach, a maximum of 54" for a side reach.	NA NA NA NA NA YES	Drinking fountains inoperatible due to lead
Hand operated push button or level controls Spouts located near front with stream of water as parallel to front as possible If recessed, recess a minimum 307 width, and no deeper than depth of fountain if no clear knee space underneath, clear floor space 30" x 48" to allow parallel approach Notes: Signs, Signals, and Switches Switches, Controls and Signs Description Switches and controls for light, heat, ventilation, windows, fire alarms, thermostats, etc. must be a minimum of 36" and a maximum of 48" above the floor for a forward reach, a maximum of 54" for a side reach Electrical outlets centered no lower than 18" above the floor	NA NA NA NA NA VES YES Yes	Drinking fountains inoperatible due to lead
Hand operated push button or level controls Spouts located near front with stream of water as parallel to front as possible If recessed, reces a minimum 30" width, and no deeper than depth of fountain If no clear knee space underneath, clear floor space 30" x 48" to allow parallel approach Notes: Signs, Signals, and Switches Switches, Controls and Signs Description Switches and controls for light, heat, ventilation, windows, fire alarms, thermostats, etc., must be a minimum of 36" and a maximum of 48" above the floor for a forward reach, a maximum of 54" for a side reach Electrical outlet centered no lover than 18" above the floor Warning signals must be visual as well as audible	NA NA NA NA NA YES	Drinking fountains inoperatible due to lead
Hand operated push button or level controls Spouts located near front with stream of water as parallel to front as possible If recessed, recess a minimum 307 width, and no deeper than depth of fountain if no clear knee space underneath, clear floor space 30" x 48" to allow parallel approach Notes: Signs, Signals, and Switches Switches, Controls and Signs Description Switches and controls for light, heat, ventilation, windows, fire alarms, thermostats, etc. must be a minimum of 36" and a maximum of 48" above the floor for a forward reach, a maximum of 54" for a side reach Electrical outlets centered no lower than 18" above the floor	NA NA NA NA NA NA VES Yes Yes	Drinking fountains inoperatible due to lead
Hand operated push button or level controls Spouts located near front with stream of water as parallel to front as possible If recessed, reces a minimum 30" width, and no deeper than depth of fountain If no clear knee space underneath, clear floor space 30" x 48" to allow parallel approach Notes: Signs, Signals, and Switches Switches, Controls and Signs Description Switches and controls for light, heat, ventilation, windows, fire alarms, thermostats, etc., must be a minimum of 36" and a maximum of 48" above the floor for a forward reach, a maximum of 54" for a side reach Electrical outlet centered no lover than 18" above the floor Warning signals must be visual as well as audible	NA NA NA NA NA NA VES Yes Yes	Drinking fountains inoperatible due to lead
Hand operated push button or level controls Spous Isocated near front with stream of water as parallel to front as possible If necessed, necess a minimum 30" width, and no deeper than depth of fountain If no clear knee space underneath, clear floor space 30" x 48" to allow parallel approach Notes: Signs, Signals, and Switches Switches, Controls and Signs Description Switches and controls for light, heat, ventilation, windows, fire alarms, thermostats, etc., must be a minimum of 36" and a maximum of 48" above the floor for a forward reach, a maximum of 54" for a side reach Electrical outlet centered no lover than 18" above the floor Warning signals must be visual as well as audible Notes:	NA NA NA NA NA NA VES Yes Yes	Drinking fountains inoperatible due to lead
Hand operated push button or level controls Spouts located near front with stream of water as parallel to front as possible If recessed, reces a minimum 30" width, and no deeper than depth of fountain If no clear knee space underneath, clear floor space 30" x 48" to allow parallel approach Notes: Signs, Signals, and Switches Switches, Controls and Signs Description Switches and controls for light, heat, ventilation, windows, fire alarms, thermostats, etc., must be a minimum of 36" and a maximum of 48" above the floor for a forward reach, a maximum of 54" for a side reach Electrical outlet centered no lover than 18" above the floor Warning signals must be visual as well as audible	NA N	Drinking fountains inoperatible due to lead
Hand operated push button or level controls Spouts located near front with stream of water as parallel to front as possible If recessed, recess a minimum 30" width, and no deeper than depth of fountain If no clear knee space underneath, clear floor space 30" x 48" to allow parallel approach Notes: Signs, Signals, and Switches Switches, Controls and Signs Description Switches and controls for light, heat, ventilation, windows, fire alarms, thermostats, etc., must be a minimum of 36" and a maximum of 48" above the floor for a forward reach, a maximum of 54" for a side reach Electrical outlet centered no lover than 18" above the floor Warning signals must be visual as well as audible Notes: Swimming Pool/ Lake beach	NA Ves Ves Ves No	Drinking fountains inoperatble due to lead Drinking fountains inoperatble due to lead
Hand operated push button or level controls Spouts located near front with stream of water as parallel to front as possible If recessed, recess a minimum 30" width, and no deeper than depth of fountain If no clear knee space underneath, clear floor space 30" x 48" to allow parallel approach Notes: Signs, Signals, and Switches Switches, Controls and Signs Description Switches and controls for light, heat, ventilation, windows, fire alarms, thermostats, etc., must be a minimum of 36" and a maximum of 48" above the floor for a forward reach, a maximum of 54" for a side reach Electrical outlets centered no lover than 18" above the floor Warning signals must be visual as well as audible Notes: Switches and controls for light, heat, ventilation, windows, fire alarms, thermostats, etc., must be a minimum of 36" and a maximum of 48" above the floor for a forward reach, a maximum of 54" for a side reach Notes: Switches and controls for light, heat, ventilation, windows, fire alarms, thermostats, etc., must be a minimum of 36" and a maximum of 48" above the floor for a forward reach, a maximum of 54" for a side reach Notes: Switches and controls for light, heat, ventilation, windows, fire alarms, thermostats, etc., must be a minimum of 36" and a maximum of 48" above the floor for a forward reach, a maximum of 54" for a side reach Switches and controls for light, heat, ventilation, windows, fire alarms, thermostats, etc., must be a minimum of 36" and a maximum of 48" above the floor for a forward reach, a maximum of 48" above the floor for a forward reach, a maximum of 48" above the floor for a forward reach, a maximum of 54" for a side reach Switches and controls for light, heat, ventilation, windows, fire alarms, thermostats, etc., must be a minimum of 36" and a maximum of 48" above the floor for a forward reach, a maximum of 36" and a maximum of 48" above the floor for a forward reach, a maximum of 36" and a maximum of 48" above the floor for a forward reach, a maximum of 36" and a maximum of 48" abov	NA N	Drinking fountains inoperatble due to lead Drinking fountains inoperatble due to lead
Hand operated push button or level controls Spous located near front with stream of water as parallel to front as possible If recessed, recess a minimum 30° width, and no deeper than depth of fountain if no clear knee space underneath, clear floor space 30° x 48" to allow parallel approach Notes: Signs, Signals, and Switches Switches Controls and Signs Description Switches and controls for light, heat, ventilation, windows, fire alarms, thermostats, etc, must be a minimum of 36" and a maximum of 48" above the floor for a forward reach, a maximum of 54" for a side reach Electrical outlets centered no lower than 18" above the floor Warming signals must be visual as well as audible Notes: Swimming Pool/ Lake beach Description Ramp at least 34" wide with a non-slip surface extending into the shallow end, slope not exceeding 1:6 with handralls on both sides Litting device Transfer area 18" above the path of travel and a minimum of 18" wide	NA N	Drinking fountains inoperatble due to lead Drinking fountains inoperatble due to lead
Hand operated push button or level controls Spouts located near front with stream of water as parallel to front as possible If necessed, necess a minimum 30" width, and no desper than depth of Gountain If no clear knee space underneath, clear floor space 30" x 48" to allow parallel approach Notes: Signs, Signals, and Switches Switches, Controls and Signs Switches, Controls and Signs Switches and controls for light, heat, ventilation, windows, fire alarms, thermostats, etc., must be a minimum of 36" and a maximum of 48" above the floor for a forward reach, a maximum of 54" for a side reach Electrical outlets centered no lower than 18" above the floor Warning signals must be visual as well as audible Notes: Swimming Pool/ Lake beach Description Ramp at least 34" wide with a non-slip surface extending into the shallow end, slope not exceeding 1.6 with handrails on both sides Uring device Uring device Unobstructed path of travel not less than 48" wide around pool	VES YES Yes Yes No No No YES	Drinking fountains inoperatble due to lead Drinking fountains inoperatble due to lead
Hand operated push button or level controls Spouts located near front with stream of water as parallel to front as possible If necessed, necess a minimum 30" width, and no deeper than depth of fountain If no clear knee space underneath, clear floor space 30" x 48" to allow parallel approach Notes: Signs, Signals, and Switches Switches, Centrols and Signs Description Switches and controls for light, heat, ventilation, windows, fire alarms, thermostats, etc., must be a minimum of 36" and a maximum of 48" above the floor for a forward reach, a maximum of 34" for a side reach Electrical outlets centered no lower than 18" above the floor Warning signals must be visual as well as audible Notes: Swimming Pool/ Lake beach Description Ramp at least 34" wide with a non-slip surface extending into the shallow end, slope not exceeding 1:6 with handralls on both sides Lifting device Transfer area 18" above the path of travel and a minimum of 18" wide Unobstructed path of travel not less than 48" wide around pool Non-slip surface	NA N	Drinking fountains inoperatble due to lead Drinking fountains inoperatble due to lead
Hand operated push button or level controls Spouts located near front with stream of water as parallel to front as possible If recessed, recess a minimum 30° width, and no deeper than depth of fountain if no clear knee space underneath, clear floor space 30° x 48" to allow parallel approach Notes: Signs, Signals, and Switches Switches, Controls and Signs Switches, Controls on Signs Switches and controls for light, heat, ventilation, windows, fire alarms, thermostats, etc., must be a minimum of 36" and a maximum of 48" above the floor for a forward reach, a maximum of 54" for a side reach Electrical outlets centered no lower than 18" above the floor Warning signals must be visual as well as audible Notes: Swimming Pool/ Lake beach Description Ramp at least 34" wide with a non-slip surface extending into the shallow end, slope not exceeding 1.6 with handrails on both sides Urtining device Urtining device Unobstructed path of travel not less than 48" wide around pool	VES YES Yes Yes No No No YES	Drinking fountains inoperatble due to lead Drinking fountains inoperatble due to lead
Hand operated push button or level controls Spouts located near front with stream of water as parallel to front as possible If necessed, necess a minimum 30" width, and no deeper than depth of fountain If no clear knee space underneath, clear floor space 30" x 48" to allow parallel approach Notes: Signs, Signals, and Switches Switches, Controls and Signs Description Switches and controls for light, heat, ventilation, windows, fire alarms, thermostats, etc., must be a minimum of 36" and a maximum of 48" above the floor for a forward reach, a maximum of 54" for a side reach Bettrical outlets centered no lower than 18" above the floor Warning signals must be visual as well as audible Notes: Swimming Pool/ Lake beach Description Ramp at least 34" wide with a non-slip surface extending into the shallow end, slope not exceeding 1:6 with handralls on both sides Lifting device Transfer area 18" above the path of travel and a minimum of 18" wide Unobstructed path of travel not less than 48" wide around pool Non-slip surface	VES YES Yes Yes No No No YES	Drinking fountains inoperatble due to lead Drinking fountains inoperatble due to lead
Hand operated push button or level controls Spouts located near front with stream of water as parallel to front as possible If necessed, recess a minimum 307 width, and no deeper than depth of fountain If no clear knee space underneath, clear floor space 30" x 48" to allow parallel approach Notes: Signs, Signals, and Switches Switches, Controls and Signs Description Switches and controls for light, heat, ventilation, windows, fire alarms, thermostats, etc. must be a minimum of 36" and a maximum of 48" above the floor for a forward reach, a maximum of 54" for a side reach Electrical outlets centered no lover than 18" above the floor Warning signals must be visual as well as audible Notes: Switches and controls for light, heat, ventilation, windows, fire alarms, thermostats, etc. must be a minimum of 36" and a maximum of 48" above the floor for a forward reach, a maximum of 54" for a side reach Notes: Switches and controls for light, heat, ventilation, windows, fire alarms, thermostats, etc. must be a minimum of 36" and a maximum of 48" above the floor for a forward reach, a maximum of 36" for a side reach Switches and controls for light, heat, ventilation, windows, fire alarms, thermostats, etc. must be a minimum of 36" and a maximum of 48" above the floor for a forward reach, a maximum of 36" and a maximum of 48" above the floor for a forward reach, a maximum of 36" and a maximum of 48" above the floor for a forward reach, a maximum of 36" and a maximum of 48" above the floor for a forward reach, a maximum of 36" and a maximum of 36" and a minimum of 36" and a min	NA N	Drinking fountains inoperatble due to lead Drinking fountains inoperatble due to lead
Hand operated push button or level controls Spouts located near front with stream of water as parallel to front as possible If necessed, recess a minimum 30" width, and no deeper than depth of fountain If no clear knee space underneath, clear floor space 30" x 48" to allow parallel approach Notes: Signs, Signals, and Switches Switches, Centrols and Signs Description Switches and controls for light, heat, ventilation, windows, fire alarms, thermostats, etc., must be a minimum of 36" and a maximum of 48" above the floor for a forward reach, a maximum of 54" for a side reach Bettrical outlets centered no lower than 18" above the floor Warning signals must be visual as well as audible Notes: Swimming Pool/ Lake beach Description Ramp at least 34" wide with a non-slip surface extending into the shallow end, slope not exceeding 1:6 with handralls on both sides Lifting device Transfer area 18" above the path of travel and a minimum of 18" wide Unobstructed path of travel not less than 48" wide around pool Non-slip surface Notes:	VES YES Yes Yes No No No YES	Drinking fountains inoperatible due to lead Drinking fountains inoperated due to lead Comments Comments
Hand operated push button or level controls Spouts located near front with stream of water as parallel to front as possible If recessed, recess a minimum 30 width, and no deeper than depth of fountain If no clear knee space underneath, clear floor space 30" x 48" to allow parallel approach Notes: Signs, Signals, and Switches Switches. Controls and Signs Description Switches and controls for light, heat, ventilation, windows, fire alarms, thermostats, etc., must be a minimum of 36" and a maximum of 48" above the floor for a forward reach, a maximum of 54" for a side reach Electrical outlets centered no lower than 18" above the floor Warning signals must be visual as well as audible Notes: Swimming Pool/ Lake beach Description Ramp at least 34" wide with a non-slip surface extending into the shallow end, slope not exceeding 1:6 with handrails on both sides Lithing device Transfer area 18" above the path of travel and a minimum of 18" wide Unobstructed path of travel not less than 48" wide around pool Non-slip surface Notes: Shower Rooms Description	NA N	Drinking fountains inoperatible due to lead Drinking fountains inoperate due to lead Comments Comments Comments
Hand operated push button or level controls Spouts located near front with stream of water as parallel to front as possible If recessed, recess a minimum 30 width, and no deeper than depth of fountain If no clear knee space underneath, clear floor space 30" x 48" to allow parallel approach Notes: Signs, Signals, and Switches Switches, Controls for light, heat, ventilation, windows, fire alarms, thermostats, etc., must be a minimum of 36" and a maximum of 48" above the floor for a forward reach, a maximum of 54" for a side reach Electrical outlets centered no lower than 18" above the floor Warning signals must be visual as well as audible Notes: Swimming Pool/ Lake beach Description Ramp at least 34" wide with a non-slip surface extending into the shallow end, slope not exceeding 1.6 with handrails on both sides Uthing device Transfer area 18" above the path of travel and a minimum of 18" wide Unobstructed path of travel not less than 48" wide around pool Non-slip surface Notes: Shower Rooms Description Salls 36" by 60" minimum, with a 36" door opening	VES YES YES Ves Ves Ves Ves Ves Ves Ves Ve	Drinking fountains inoperatible due to lead Drinking fountains inoperated due to lead Comments Comments
Hand operated push button or level controls Spouts located near front with stream of water as parallel to front as possible If recessed, recess a minimum 30 width, and no deeper than depth of fountain If no clear knee space underneath, clear floor space 30" x 48" to allow parallel approach Notes: Signs, Signals, and Switches Switches. Controls and Signs Description Switches and controls for light, heat, ventilation, windows, fire alarms, thermostats, etc., must be a minimum of 36" and a maximum of 48" above the floor for a forward reach, a maximum of 54" for a side reach Electrical outlets centered no lower than 18" above the floor Warning signals must be visual as well as audible Notes: Swimming Pool/ Lake beach Description Ramp at least 34" wide with a non-slip surface extending into the shallow end, slope not exceeding 1:6 with handrails on both sides Lithing device Transfer area 18" above the path of travel and a minimum of 18" wide Unobstructed path of travel not less than 48" wide around pool Non-slip surface Notes: Shower Rooms Description	NA N	Drinking fountains inoperatible due to lead Drinking fountains inoperate due to lead Comments Comments Comments
Hand operated push button or level controls Spouts located near front with stream of water as parallel to front as possible If nocessed, roces a minimum 30 width, and no deeper than depth of fountain If no clear knee space underneath, clear floor space 30" x 48" to allow parallel approach Notes: Signs, Signals, and Switches Switches, Controls and Signs Description Switches and controls for light, heat, ventilation, windows, fire alarms, thermostats, etc., must be a minimum of 36" and a maximum of 48" above the floor for a forward reach, a maximum of 54" for a side reach Bettrical outlets centered no lover than 18" above the floor Warning signals must be visual as well as audible Notes: Swimming Pool/ Lake beach Description Ramp at least 34" wide with a non-slip surface extending into the shallow end, slope not exceeding 1:6 with handrails on both sides Lifting device Transfer area 18" above the path of travel and a minimum of 18" wide Unobstructed path of travel not less than 48" wide around pool Non-slip surface Notes: Shower Rooms Description Satal 36" by 90" minimum, with a 36" door opening Floors are pitched to drain the stall at the corner farthest from entrance	NA N	Drinking fountains inoperatible due to lead Drinking fountains inoperate due to lead Comments Comments Comments
Hand operated push button or level controls Spouts located near front with stream of water as parallel to front as possible If recessed, recess a minimum yor width, and no deeper than depth of fountain If no clear knee space underneath, clear floor space 30" x 48" to allow parallel approach Notes: Signs, Signals, and Switches Switches, Controls and Signs Description Switches and controls for light, heat, ventilation, windows, fire alarms, thermostats, etc., must be a minimum of 36" and a maximum of 48" above the floor for a forward reach, a maximum of 56" for a side reach Bectrical outlets centered no lower than 18" above the floor Warming signals must be visual as well as audible Notes: Swimming Pool/ Lake beach Description Ramp at least 34" wide with a non-slip surface extending into the shallow end, slope not exceeding 1:6 with handraits on both sides Lufting device Transfer area 18" above the path of travel and a minimum of 18" wide Unostructed path of travel not less than 48" wide around pool Non-slip surface Notes: Shower Rooms Description Salla 36" by 60" minimum, with a 36" door opening Floors are non-slip surface Floors are non-slip surface Floors are non-slip surface	YES YES YES YES YES YES NO YES YES YES YES YES YES YES	Drinking fountains inoperatible due to lead Drinking fountains inoperate due to lead Comments Comments Comments
Hand operated push button or level controls Spouts located near front with stream of water as parallel to front as possible If recessed, recess a minimum 30" width, and no deeper than depth of fountain If no clear knee space underneath, clear floor space 30" x 48" to allow parallel approach Notes: Signs, Signals, and Switches Switches, Controls and Signs Switches, Controls for light, heat, ventilation, windows, fire alarms, thermostats, etc, must be a minimum of 36" and a maximum of 48" above the floor for a forward reach, a maximum of 54" for a side reach Electrical outlets centered no lower than 18" above the floor Warning signals must be visual as well as audible Notes: Swimming Pool/ Lake beach Description Ramp at least 34" wide with a non-slip surface extending into the shallow end, slope not exceeding 1.6 with handrails on both sides Litting device Unobstructed path of travel not less than 48" wide around pool Non-slip surface Notes: Shower Rooms Description Stalls 36" by 60" minimum, with a 36" door opening Floors are non-lisp urface Controls operate by a single lever with a pressure balance mixing valve	VES Ves Ves No No Ves Ves Ves Ves Ves Ves Ves Ve	Drinking fountains inoperatible due to lead Drinking fountains inoperate due to lead Comments Comments Comments
Hand operated push button or level controls Spouts located near front with stream of water as parallel to front as possible If recessed, recess a minimum 30 width, and no deeper than depth of fountain If no clear knee space underneath, clear floor space 30" x 48" to allow parallel approach Notes: Signs, Signals, and Switches Switches, Controls and Signs Description Switches and controls for light, heat, ventilation, windows, fire alarms, thermostats, etc, must be a minimum of 36" and a maximum of 48" above the floor for a forward reach, a maximum of 54" for a side reach Beactrical outsite centered no lover than 18" above the floor Warning signals must be visual as well as audible Notes: Swimming Pool/ Lake beach Description Ramp at least 34" wide with a non-slip surface extending into the shallow end, slope not exceeding 1:6 with handrails on both sides Litting device Transfer area 18" above the path of travel and a minimum of 18" wide Unobstructed path of travel not less than 48" wide around pool Non-slip surface Notes: Shower Rooms Description Salls 36" by 60" minimum, with a 36" door opening Floors are pitched to drain the stall at the corner farthest from entrance Floors are non-slip surface Controls are located on the center wall adjacent to the hinged seat	NA N	Drinking fountains inoperatible due to lead Drinking fountains inoperate due to lead Comments Comments Comments
Hand operated push button or level controls Spouts located near front with stream of water as parallel to front as possible If recessed, recess a minimum 30 width, and no desper than depth of fountain If no clear knee space underneath, clear floor space 30" x 48" to allow parallel approach Notes: Signs, Signals, and Switches Switches, Controls and signs Description Switches and controls for light, heat, ventilation, windows, fire alarms, thermostats, etc, must be a minimum of 36" and a maximum of 48" above the floor for a forward reach, a maximum of 54" for a side reach Bettratical outsite centered no lower than 18" above the floor Warning signals must be visual as well as audible Notes: Swimming Pool/ Lake beach Description Ramp at least 34" wide with a non-alip surface extending into the shallow end, slope not exceeding 1.6 with handrails on both sides Litting device Unobstructed path of travel not less than 48" wide around pool Non-slip surface Notes: Shower Rooms Description Salls 36" by 60" minimum, with a 36" door opening Floors are pon-slip surface Floors are pon-slip surface Controls operate by a single lever with a pressure balance mixing valve Controls operate by a single lever with a pressure balance mixing valve Controls are located on the center wall adjacent to the hinged seat Shower heads attached to a flexible metal hose Shower heads attached to a flexible from 42" to 72" above the floor Seat is hinged and padded and at least 16" deep, folds upward, securely attached to side wall, height is 18" to the top of the seat, and at least 24" long	YES	Drinking fountains inoperatible due to lead Drinking fountains inoperate due to lead Comments Comments Comments
Hand operated push button or level controls Spouts located near front with stream of water as parallel to front as possible If recessed, recess a minimum 30" width, and no deeper than depth of fountain If no clear knee space underneath, clear floor space 30" x 48" to allow parallel approach Notes: Signs, Signals, and Switches Switches Controls and Signs Description Switches and controls for light, heat, ventilation, windows, fire alarms, thermostats, etc., must be a minimum of 36" and a maximum of 48" above the floor for a forward reach, a maximum of 56" for a side reach Electrical outlets centered no lower than 18" above the floor Warning signals must be visual as well as audible Notes: Swimming Pool/ Lake beach Description Ramp at least 34" wide with a non-slip surface extending into the shallow end, slope not exceeding 1:6 with handrails on both sides Lithing device Transfer area 18" above the path of travel and a minimum of 18" wide Unobstructed path of travel not less than 48" wide around pool Non-slip surface Notes: Shower Rooms Description Salal \$6" by 60" minimum, with a 36" door opening Floors are non-slip surface Controls are path and the stall at the corner farthest from entrance Floors are non-slip surface Controls operate by a single lever with a pressure balance mixing valve Controls are located on the center wall adjacent to the hinged seat Shower heads attached to a flexible metal hose Shower heads attached to to all mounting adjustable from 42" to 72" above the floor Seat is hinged and padded and least 15" deep, flods upward, securely attached to side wall, height is 18" to the top of the seat, and at least 24" long Soap trays without handhold features unless they can support 250 pounds	NA N	Drinking fountains inoperatible due to lead Drinking fountains inoperate due to lead Comments Comments Comments
Hand operated push button or level controls Spous located near from with stream of water as parallel to front as possible If recessed, recess a minimum 20 width, and no desper than depth of fountain If no clear knee space underneath, clear floor space 30" x 48" to allow parallel approach Notes: Signs, Signals, and Switches Switches, Controls and Signs Description Switches and controls for light, heat, ventilation, windows, fire alarms, thermostats, etc, must be a minimum of 36" and a maximum of 48" above the floor for a forward reach, a maximum of 54" for a side reach Electrical outlets centered no lower than 18" above the floor Warning signals must be visual as well as a utilible Notes: Swimming Pool/ Lake beach Description Ramp at least 34" wide with a non-slip surface extending into the shallow end, slope not exceeding 1:6 with handrails on both sides Ulting device Transfer area 18" above the path of travel and a minimum of 18" wide Unobstructed path of travel not less than 48" wide around pool Non-slip surface Notes: Shower Rooms Description Satal 36" by 60" minimum, with a 36" door opening Floors are pitched to drain the stall at the corner farthest from entrance Floors are pitched to drain the stall at the corner farthest from entrance Floors are pitched to drain the stall at the corner farthest from entrance Floors are pitched to drain the stall at the corner farthest from entrance Floors are pitched to drain the stall at the corner farthest from entrance Floors are pitched to drain the stall at the corner farthest from entrance Floors are pitched to drain the stall at the corner farthest from entrance Floors are pitched to drain the stall at the corner farthest from entrance Floors are pitched to drain the stall at the corner farthest from entrance Floors are pitched to drain the stall at the corner farthest from entrance Floors are provided, one 30" and one 48" long, or one continuous thaped but 2 grab bars are provided, one 30" and one 48" long, or one continuous thap	YES	Drinking fountains inoperatible due to lead Drinking fountains inoperate due to lead Comments Comments Comments
Hand operated push button or level controls Spous located near from with stream of water as parallel to front as possible If recessed, reces an inimum 30" width, and no desper than depth of fountain If no clear knee space underneath, clear floor space 30" x 48" to allow parallel approach Notes: Signs, Signals, and Switches Switches, Controls and Signs Description Switches and controls for light, heat, ventilation, windows, fire alarms, thermostats, etc, must be a minimum of 36" and a maximum of 48" above the floor for a forward reach, a maximum of 54" for a sider reach Electrical outlets centered no lower than 18" above the floor Warning signals must be visual as well as a sudible Notes: Swimming Pool/ Lake beach Description Ramp at least 34" wide with a non-silp surface extending into the shallow end, slope not exceeding 1:6 with handrails on both sides Ulfing device Transfer area 18" above the path of travel and a minimum of 18" wide Unobstructed path of fravel not less than 48" wide around pool Non-silp surface Notes: Shower Rooms Description Scalp 15" by 60" minimum, with a 36" door opening Floors are pitched to drain the stall at the corner farthest from entrance Floors are non-silp surface Controls opened by a single lever with a pressure balance mixing valve Controls are located on the center wall adjacent to the hinged seat Shower heads attached to vall mounting adjustable from 42" to 72" above the floor Seat is hinged and padded and at least 15" deep, folds upward, securely attached to side wall, height is 18" to the top of the seat, and at least 24" long Soap trays without handhold features unless they can support 250 pounds Grab bass are placed horizontally at 36" above the floor line	NA N	Drinking fountains inoperatible due to lead Drinking fountains inoperate due to lead Comments Comments Comments
Hand operated push button or level controls Spous located near front with stream of water as parallel to front as possible If recessed, recess a minimum 20 width, and no desper than depth of fountain If no dear knee space underneath, clear floor space 30" x 48" to allow parallel approach Notes: Signs, Signals, and Switches Switches, Controls and Signs Description Switches and controls for light, heat, ventilation, windows, fire alarms, thermostats, etc, must be a minimum of 36" and a maximum of 48" above the floor for a forward reads, a maximum of 54" for a side reach. Electrical outlets centered no lower than 18" above the floor Warning signals must be visual as well as audible Notes: Swimming Pool/ Lake beach Description Samp at least 34" wide with a non-slip surface extending into the shallow end, slope not exceeding 1:6 with handrails on both sides Lifting device Transfer area 18" above the path of travel and a minimum of 18" wide Unobstructed path of travel not less than 48" wide around pool Non-slip surface Notes: Shower Rooms Description Salls 36" by 60" minimum, with a 36" door opening Floors are pitched to drain the stall at the corner farthest from entrance Floors are pitched to drain the stall at the corner farthest from entrance Controls are located on the center wall adjacent to the hinged seat Shower heads attached to a flexible metal hose Show the heads attached to a flexible metal hose Sop trays without handhold features unless they can support 250 pounds 2 grab bars are provided, one 30" and one 48" (ng. or one continuous thaped bar 2 grab bars are provided, one 30" and one 48" (ng. or one continuous thaped bar	YES	Drinking fountains inoperatible due to lead Drinking fountains inoperate due to lead Comments Comments Comments
Hand operated push button or level controls Spous located near from with stream of water as parallel to front as possible If recessed, reces an inimum 30" width, and no desper than depth of fountain If no clear knee space underneath, clear floor space 30" x 48" to allow parallel approach Notes: Signs, Signals, and Switches Switches, Controls and Signs Description Switches and controls for light, heat, ventilation, windows, fire alarms, thermostats, etc, must be a minimum of 36" and a maximum of 48" above the floor for a forward reach, a maximum of 54" for a sider reach Electrical outlets centered no lower than 18" above the floor Warning signals must be visual as well as a sudible Notes: Swimming Pool/ Lake beach Description Ramp at least 34" wide with a non-silp surface extending into the shallow end, slope not exceeding 1:6 with handrails on both sides Ulfing device Transfer area 18" above the path of travel and a minimum of 18" wide Unobstructed path of fravel not less than 48" wide around pool Non-silp surface Notes: Shower Rooms Description Scalp 15" by 60" minimum, with a 36" door opening Floors are pitched to drain the stall at the corner farthest from entrance Floors are non-silp surface Controls opened by a single lever with a pressure balance mixing valve Controls are located on the center wall adjacent to the hinged seat Shower heads attached to vall mounting adjustable from 42" to 72" above the floor Seat is hinged and padded and at least 15" deep, folds upward, securely attached to side wall, height is 18" to the top of the seat, and at least 24" long Soap trays without handhold features unless they can support 250 pounds Grab bass are placed horizontally at 36" above the floor line	YES	Drinking fountains inoperatible due to lead Drinking fountains inoperate due to lead Comments Comments Comments
Hand operated push button or level controls Spous located near front with stream of water as parallel to front as possible If recessed, recess a minimum 30" withs, and no deeper than deight of fountain If no clear knee space undermeath, clear floor space 30" x 48" to allow parallel approach Notes: Signs, Signals, and Switches Switches, Controls and Signs Description Switches and controls for light, heat, ventilation, windows, fire alarms, thermostats, etc, must be a minimum of 36" and a maximum of 48" above the floor for a forward neach, a maximum of 54" for a side reach Electrical outlets centered no lower than 18" above the floor Warning signals must be visual as well as audible Notes: Swimming Pool/ Lake beach Description Ramp at least 34" wide with a non-slip surface extending into the shallow end, slope not exceeding 1.6 with handralls on both sides Ulfing device Transfer area 18" above the path of travel and a minimum of 18" wide Unobstructed path of travel not less than 48" wide around pool Non-silp surface Notes: Shower Rooms Description Satial 36" by 60" minimum, with a 36" door opening Floors are piched to drain the stall at the corner farthest from entrance Floors are piched to drain the stall at the corner farthest from entrance Floors are piched to drain the stall at the corner farthest from entrance Floors are non-slip surface Controls are located on the center wall adjucent to the hinged seat Shower heads attached to a flexible metal hose Shower head	YES	Drinking fountains inoperatible due to lead Drinking fountains inoperate due to lead Comments Comments Comments
Hand operated push button or level controls Spous located near from with stream of water as parallel to front as possible If recessed, reces an inimum 30" width, and no desper than depth of fountain If no clear knee space underneath, clear floor space 30" x 48" to allow parallel approach Notes: Signs, Signals, and Switches Switches, Controls and Signs Description Switches and controls for light, heat, ventilation, windows, fire alarms, thermostats, etc, must be a minimum of 36" and a maximum of 48" above the floor for a forward reach, a maximum of 54" for a sider reach Electrical outlets centered no lower than 18" above the floor Warning signals must be visual as well as a sudible Notes: Swimming Pool/ Lake beach Description Ramp at least 34" wide with a non-silp surface extending into the shallow end, slope not exceeding 1:6 with handrails on both sides Ulfing device Transfer area 18" above the path of travel and a minimum of 18" wide Unobstructed path of fravel not less than 48" wide around pool Non-silp surface Notes: Shower Rooms Description Scalp 15" by 60" minimum, with a 36" door opening Floors are pitched to drain the stall at the corner farthest from entrance Floors are non-silp surface Controls opened by a single lever with a pressure balance mixing valve Controls are located on the center wall adjacent to the hinged seat Shower heads attached to vall mounting adjustable from 42" to 72" above the floor Seat is hinged and padded and at least 15" deep, folds upward, securely attached to side wall, height is 18" to the top of the seat, and at least 24" long Soap trays without handhold features unless they can support 250 pounds Grab bass are placed horizontally at 36" above the floor line	YES	Drinking fountains inoperatible due to lead Drinking fountains inoperate due to lead Comments Comments Comments

Facility Name: Heartbreak Hill Park @ Waban Hill Reservoir Size (Ac): 5.1 acres Address: Manet Road, Chestnut Hill Ward: 7 General Facility Notes: Full renovation of the park constructed in 2019 to 2020; 1/4 mile perimeter stabilized stone dust path is accessible; new stair and handrail meet MAAB requirements; accessible parking space at one of the two park entrances; two benches with accessible companion pad; timber curbing along the outside perimeter of path installed as guide to the visually impaired; new plaza surface is accessible; path to plaza and stairs require a curb cut from Ward street; existing gate house building not open to the public and is not accessible. Site Furnishings Comments Yes Description Number of Benches YES 2 Benches with back and armrest; 1 reclaimed granite seatwall at plaza Number of Tables No YES Located adjacent to accessible paths 2 benches are along the path; granite seatwall located at plaza Back and Arm Rests YES rash Cans Located adjacent to accessible paths YES Trash and Recycling; Dog waste bin not on path Notes: Trails & Paths YES Description Comments Surface (A=Asphalt, C=Concrete, SD= stone dust, NS= naturally surfaced, B=Boardwalk, BR=Bridge) YES SD; C; A 6 FEET WIDE Rails YES Kickrail along outside perimeter of stone dust path Signage for visually impaired NO Notes: N/A N/A N/A Play Areas Game Areas Boat Docks **Fishing Facilities** N/A YES **Community Gardens** Parking Total Spaces Accessible Spaces Up to 25 Description Parking Amenities (L=lot, ST=street) YES Single pull-in accessible parking space Parking space directly adjavent to path of travel Accessible space located closest to accessible entrance Minimum width of 13 ft includes 8 ft space plus 5 ft access aisle YES 6 foot access aisle Sign with international symbol of accessibility at each space YES Surface evenly paved or hard-packed (no cracks) YES paved in 2020 Surface slope less than 1:20, 5% YES Curbcut to pathway from parking lot at each space if sidewalk (curb) is present . YES Curbcut is a minimum width of 3 ft, excluding sloped sides, has sloped sides, all slopes not to exceed 1:12, and textured or painted yellow curb cut is the same length as the parking space Notes: N/A Ramps Site Access, Path of Travel, Entrances Comments Description Accessible path of travel from passenger disembarking area and parking area to accessible entrance YES Surface evenly paved or hard-packed Ponding of water? NO Disembarking area at accessible entrance YES ath of Travel Comments Yes Description Path does not require the use of stairs YES Path does not require the use of wheelchair ramp YES Path is stable, firm and slip resistant YES Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50). YES Continuous common surface, no changes in level greater than ½ inch YES Any objects protruding onto the pathway that may not be detected by a person with a visual disability using a cane NO Objects protruding more than 4" from the wall must be within 27" of the ground, or higher than 80" NO Curb on the pathway must have curb cuts at drives,parking and drop-offs YES YES Stairs and Doors Description NO concrete stairs Nosings not projecting YES stainless steel round tube YES Handrails 34"-38" above tread YES Handrail extends a minimum of 1' beyond top and bottom riser (if no safety hazard and space permits) YES Handgrip has a smooth surface YES Notes: Floors, Drinking Fountains, Telephones Signs, Signals, and Switches Swimming Pool/ Lake beach

Shower Rooms	N/A
Picknicking	N/A
Off Leash Dog Areas (OLA)	N/A

Facility Name: Horace Mann School Playground (formerly Carr School Playground) Size (Ac): 7.8 acres Address: Nevada Street, Newtonville General Facility Notes: building made fully accessible in 2012; there are no internal pathways to ball fields; play area accessible through parking lot; play area not accessible. YES Site Furnishings Comments Tables & Benches No Number of Tables No Located adjacent to accessible paths No Back and Arm Rests Backs only Located adjacent to accessible paths N/A Trash Cans Located adjacent to accessible paths Yes icnic Shelters N/A Notes: Trails & Paths YES Comments Surface (A=Asphalt, C=Concrete, SD= stone dust, NS= naturally surfaced, B=Boardwalk, BR=Bridge) Yes Α Dimensions (width) Yes minimum 6' Rails N/A Signage for visually impaired No See above Notes: Play Areas YES Comments Facility Type (3-5 Yrs,5-12 Yrs) Yes 5 - 12 yrs Same experience provided to all No Access Routes Located adjacent to accessible paths Yes Enough space between equipment for wheelchair Yes Playground relocated in 2013 YES Game Areas Comments Facility Type (RF=Rectangular Fields, BF= Ballfields, BK=Basketball, TN=Tennis, BC=Bocce) RF,BF Access Routes Located adjacent to accessible paths No Berm cuts onto courts NA quipment Yes NO aloong accessible route Spectator Seating Notes: N/A **Boat Docks** N/A N/A YES **Fishing Facilities** Community Gardens Accessible Spaces Total Spaces Description Comments Parking Amenities (L=lot, ST=street) Yes L Accessible space located closest to accessible entrance No Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft $\,$ No Minimum width of 13 ft includes 8 ft space plus 5 ft access aisle Yes Minimum of 1 van space for every accessible space, 8^\prime wide + 8^\prime aisle. N/A Sign with international symbol of accessibility at each space Yes Sign 5'-8' to top of sign Surface evenly paved or hard-packed (no cracks) Yes Surface slope less than 1:20, 5% Yes Curbcut to pathway from parking lot at each space if sidewalk (curb) is present . Yes Curbcut is a minimum width of 3 ft, excluding sloped sides, has sloped sides, all slopes not to exceed 1:12, and textured or painted yellow Yes Parking is designed for school purposes. Use of parking lot for public nights and weekends. Ramps Site Access, Path of Travel, Entrances Site Access Comments Accessible path of travel from passenger disembarking area and parking area to accessible entrance N/A Building is not for public use. Surface evenly paved or hard-packed N/A Ponding of water? N/A Disembarking area at accessible entrance N/A Path of Travel Comments Description Path does not require the use of stairs Yes Yes Path does not require the use of wheelchair ramp Path is stable, firm and slip resistant

Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50).	Yes	
Continuous common surface, no changes in level greater than ½ inch	Yes	
Any objects protruding onto the pathway must be detected by a person with a visual disability using a cane	N/A	
Objects protruding more than 4" from the wall must be within 27" of the ground, or higher than 80"	N/A	
Curb on the pathway must have curb cuts at drives, parking and drop-offs	N/A	
<u>Entrances</u>		
Description		Comments
Primary public entrances accessible to person using wheelchair, must be signed, gotten to independently, and not be the service entrance	N/A	
Level space extending 5 ft. from the door, interior and exterior of entrance doors	N/A	
Minimum 32" clear width opening (i.e. 36" door with standard hinge)	N/A	
At least 18" clear floor area on latch, pull side of door	N/A	
Door handle no higher than 48" and operable with a closed fist	N/A	
Vestibule is 4 ft plus the width of the door swinging into the space	N/A	
Entrance(s) on a level that makes elevators accessible	N/A	
Door mats less than ¼" thick are securely fastened	N/A	
Door mats more than 1/3" thick are recessed	N/A	
Grates in path of travel have openings of ½" maximum	N/A	
Signs at non-accessible entrance(s) indicate direction to accessible entrance	N/A	
Emergency egress – alarms with flashing lights and audible signals, sufficiently lighted	N/A	
Notes:	12.72	
Stairs and Doors	N/A	
Restrooms	N/A	
Floors, Drinking Fountains, Telephones	N/A	
Signs, Signals, and Switches	N/A	
Swimming Pool/ Lake beach	N/A	
Shower Rooms	N/A	
Picknicking	N/A	
Off Leash Dog Areas (OLA)	N/A	

Facility Name: Hunnewell Playground		
Size (Ac): 4.6 acres		
Address: Grasmere Street, off Hunnewell Avenue, Newton Corner		
Ward: 1		
General Facility Notes: Park is inaccessible; no accessible route to tot lot; no accessi Grassmere Street entrance.	ble route to ballfield or fe	nced off-leash area; no accessible parking; steep stairs at the
Site Furnishings	YES	
Description	Yes	Comments
Tables & Benches		
Number of Benches Number of Tables	yes	2 Benches with backs 1 picnic table
Located adjacent to accessible paths	no	1 pictic table
Back and Arm Rests	Yes	Benches have backrest, no armrests
Grills Located adjacent to accessible paths	NA NA	
Trash Cans	NA NA	
Located adjacent to accessible paths	no	
Picnic Shelters Located adjacent to accessible paths	NA NA	
Notes: Three pest waste stations. Enclosed off leash dog park.	NA NA	
	10.70	
Trails & Paths Play Areas	N/A YES	
Description	11.3	Comments
Facility Type (3-5 Yrs,5-12 Yrs)	yes	Fibar safety surfacing.
Same experience provided to all	no	
Access Routes Located adjacent to accessible paths	no	
Enough space between equipment for wheelchair	no	
Notes:		
Game Areas	YES	
Description Control of the Control o		Comments
Facility Type (RF=Rectangular Fields, BF= Ballfields, BK=Basketball, TN=Tennis, BC=Bocce) Access Routes	yes	1 BF with backstop, players benches and protective screens.
Located adjacent to accessible paths	no	
Berm cuts onto courts	no	
Spectator Seating	No	1
Notes:	1	
Boat Docks	N/A	
Fishing Facilities	N/A	
Community Gardens Parking	N/A N/A	
Ramps	N/A	
Site Access, Path of Travel, Entrances	N/A	
Stairs and Doors Stairs	YES	
Description		Comments
Open risers	yes	
Nosings not projecting Treads no less than 11" wide	yes	
Handrails on both sides	yes	
Handrails 34"-38" above tread	yes	
Handrail extends a minimum of 1' beyond top and bottom riser (if no safety hazard and space permits) Handgrip oval or round	yes yes	
Handgrip has a smooth surface	yes	
Handgrip diam. 1¼" - 1¼"	yes	
1%" clearance between wall and handrail Notes:		
Restrooms	N/A	
Floors, Drinking Fountains, Telephones	N/A	
Signs, Signals, and Switches Swimming Pool/ Lake beach	N/A N/A	
Shower Rooms	N/A	
Picknicking	N/A	
Off Leash Dog Areas (OLA) Description	YES	Comments
Access Routes		Commence
Located adjacent to accessible paths	no	
Area accesible Notes:	no	
The state of the s		

Facility Name: Hyde Playground Size (Ac): 1.0 acres Address: Lincoln Street, Newton Highlands (adjacent to Hyde Community Center) General Facility Notes: Accessible garden area w/benches on Lincoln St.; accessible pathway from Lincoln to Erie; accessible concrete walkway to playstructure and accessible playground area constructed in 2019. YES Site Furnishings Comments Description Tables & Benches Yes 17 total 8are accessible Number of Tables Yes both accessible Located adjacent to accessible paths Yes 3 of the 8 are backless the rest back only Back and Arm Rests Located adjacent to accessible paths N/A Trash Cans Yes Located adjacent to accessible paths icnic Shelters N/A Notes: YES Trails & Paths Comments Surface (A=Asphalt, C=Concrete, SD= stone dust, NS= naturally surfaced, B=Boardwalk, BR=Bridge) Yes С Dimensions (width) Yes minimum 5' Rails Signage for visually impaired No see above Notes: Play Areas YES Comments Facility Type (3-5 Yrs,5-12 Yrs) 2 - 5 yrs and 5 - 12 yrs Yes Same experience provided to all Access Routes Located adjacent to accessible paths Yes Enough space between equipment for wheelchair Yes Play Areas: Playground built in 2019 YES Game Areas Comments Facility Type (RF=Rectangular Fields, BF= Ballfields, BK=Basketball, TN=Tennis, BC=Bocce) RF ccess Routes Located adjacent to accessible paths Yes Berm cuts onto courts N/A uipment N/A Height Dimensions N/A Spectator Seating N/A Notes: N/A **Boat Docks** Fishing Facilities N/A N/A N/A Community Gardens Parking N/A YES Ramps Site Access, Path of Travel, Entrances Comments Description Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed Yes Ponding of water? No Disembarking area at accessible entrance Yes Path of Travel Description Comments Path does not require the use of stairs Yes Path does not require the use of wheelchair ramp Yes Path is stable, firm and slip resistant Yes Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50). Yes Continuous common surface, no changes in level greater than $\mbox{\%}$ inch Yes Any objects protruding onto the pathway must be detected by a person with a visual disability using a cane Yes Objects protruding more than 4" from the wall must be within 27" of the ground, or higher than 80" Yes Curb on the pathway must have curb cuts at drives,parking and drop-offs Yes Notes: The building adjacent to the playground is a private community Center Stairs and Doors N/A N/A N/A N/A N/A N/A Restrooms Restrooms Floors, Drinking Fountains, Telephones Signs, Signals, and Switches Swimming Pool/ Lake beach Shower Rooms N/A

Off Leash Dog Areas (OLA)	N/A	
•		

Facility Name: Islington Oval		
Size (Ac): 1.5 acres		
Address: Islington Road, Auburndale		
Ward: 4		
General Facility Notes: Inaccessible oval island; no pathways; site furn	iture not accessible.	
	lvrc	
Site Furnishings	YES	
Description	Yes Comments	
Tables & Benches	T T	
Number of Benches		y slat benches with backs.
Number of Tables	No	
Located adjacent to accessible paths	No No	
Back and Arm Rests	Backs, no arm res	sts
Grills	T T	
Located adjacent to accessible paths	No	
Trash Cans	T T	
Located adjacent to accessible paths Picnic Shelters	No	
Located adjacent to accessible paths	No	
Located adjacent to accessible paths Notes:	NO NO	
notes.		
Trails & Paths	N/A	
Play Areas	N/A	
Game Areas	N/A	
Boat Docks	N/A	
Fishing Facilities	N/A	
Community Gardens	N/A	
Parking	N/A	
Ramps	N/A	
Site Access, Path of Travel, Entrances	N/A	
Stairs and Doors	N/A	
Restrooms	N/A	
Floors, Drinking Fountains, Telephones	N/A	
Signs, Signals, and Switches	N/A	
Swimming Pool/ Lake beach	N/A	
Shower Rooms	N/A	
Picknicking	N/A	

Facility Name: Joanne C. Pellegrini Memorial Playground 'Hawt	horn'	
Size (Ac): 4.2 acres		
Address: Hawthorn Street, Nonantum		
Ward: 1		
General Facility Notes: Community center with accessible parking lot; park entry from Haw	thorn Street and ra	amn to building entrance: accessible playground and
basketball half-court, shade structure with picnic tables constructed in 2013.	thom street and ra	imp to building entrance, accessible playground and
Site Furnishings	YES	
Description Tables & Benches	Yes	Comments
Number of Benches	yes	11
Number of Tables	yes	2
Located adjacent to accessible paths Back and Arm Rests	Yes	Mixed
Grills	<u> </u>	
Located adjacent to accessible paths Trash Cans	N/A	
Located adjacent to accessible paths	Yes	
Picnic Shelters		
Located adjacent to accessible paths Notes:	Yes	
Trails & Paths	YES	
Description	1.20	Comments
Surface (A=Asphalt, C=Concrete, SD= stone dust, NS= naturally surfaced, B=Boardwalk, BR=Bridge)	Yes	Asphalt Minimum 6'
Dimensions (width) Rails	No	Minimum 6:
Signage for visually impaired	No	
Notes:		
Play Areas Description	YES	Comments
Facility Type (3-5 Yrs,5-12 Yrs)	Yes	Playground & Tot Lot
Same experience provided to all	Yes	yes in the 5 - 12yrs - No in tot lot
Access Routes Located adjacent to accessible paths	Yes	
Enough space between equipment for wheelchair	Yes	
Notes:		
Game Areas	YES	
Description Facility Type (RF=Rectangular Fields, BF= Ballfields, BK=Basketball, TN=Tennis, BC=Bocce)	RF, BK, TN	Comments lighted multipurpose field
Access Routes	<u> </u>	
Located adjacent to accessible paths Berm cuts onto courts	Yes N/A	
Notes:	,	
Parking	YES	
Total Spaces	Accessible S	<u>paces</u>
19 Description	1 Space	Comments
Parking Amenities (L=lot, ST=street)	Lot	
Accessible space located closest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft	Yes N/A	
Minimum width of 13 ft includes 8 ft space plus 5 ft access aisle	Yes	
Minimum of 1 van space for every accessible space, 8' wide +8' aisle. Sign with international symbol of accessibility at each space	N/A	
Sign 5'-8' to top of sign	Yes	
Surface evenly paved or hard-packed (no cracks)	Yes	
Surface slope less than 1:20,5% Curbcut to pathway from parking lot at each space if sidewalk (curb) is present.	Yes	
Curbcut is a minimum width of 3 ft, excluding sloped sides, has sloped sides, all slopes not to exceed 1:12, and textured or painted yellow		
Notes:		
D	YES	
Ramps Description	1123	Comments
Slope Maximum 1:12		
Minimum width 4 ft between handrails Handrails on both sides if ramp is longer than 6 ft	Yes	
Handrails at 34" and 19" from ramp surface	Yes	
Handrails extend 12" beyond top and bottom	V	
Handgrip oval or round Handgrip smooth surface	Yes Yes	
Handgrip diameter between 1½" and 2"	Yes	
Clearance of 1%" between wall and wall rail Non-slip surface	Yes	
Level platforms (4ft x 4 ft) at every 30 ft, at top, at bottom, at change of direction	No	
Notes:		
Site Access, Path of Travel, Entrances	YES	
Site Access Constitution		Commonto

Accessible path of travel from passenger disembarking area and parking area to accessible entrance	Yes	
Surface evenly paved or hard-packed	Yes	
Ponding of water?	No	
Disembarking area at accessible entrance	Yes	
Path of Travel		
Description		Comments
Path does not require the use of stairs	Yes	
Path does not require the use of wheelchair ramp	Yes	
Path is stable, firm and slip resistant	Yes	
Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50).	ies	
Continuous common surface, no changes in level greater than ½ inch		
Any objects protruding onto the pathway must be detected by a person with a visual disability using a cane	Yes	
Objects protruding more than 4" from the wall must be within 27" of the ground, or higher than 80"	Yes	
Curb on the pathway must have curb cuts at drives, parking and drop-offs	Yes	
<u>Entrances</u>		
Description		Comments
Primary public entrances accessible to person using wheelchair, must be signed, gotten to independently, and not be the service entrance	Yes	Needs signage
Level space extending 5 ft. from the door, interior and exterior of entrance doors	Yes	
Minimum 32" clear width opening (i.e. 36" door with standard hinge)	Yes	
At least 18" clear floor area on latch, pull side of door	Yes	
Door handle no higher than 48" and operable with a closed fist	Yes	
Vestibule is 4 ft plus the width of the door swinging into the space	Yes	
Entrance(s) on a level that makes elevators accessible		
	N/A	
Door mats less than ¼" thick are securely fastened	No	
Door mats more than ½" thick are recessed	No	
Grates in path of travel have openings of ½" maximum	N/A	
Signs at non-accessible entrance(s) indicate direction to accessible entrance	No	
Emergency egress – alarms with flashing lights and audible signals, sufficiently lighted	Yes	
Notes:		
Stairs and Doors	YES	
Doors Doors		
Description		Comments
Minimum 32" clear opening	Yes	
At least 18" clear floor space on pull side of door	Yes	
Threshold maximum X" high, beveled on both sides	Yes	
Hardware operable with a closed fist (no conventional door knobs or thumb latch devices)		
	Yes	
Hardware minimum 36", maximum 48" above the floor	Yes	
Clear, level floor space extends out 5 ft from both sides of the door	Yes	
Door adjacent to revolving door is accessible and unlocked	N/A	
Doors opening into hazardous area have hardware that is knurled or roughened	N/A	
Notes:		
Restrooms	YES	
Description		Comments
occupation .		comments
Description 5 ft turning space measured 12" from the floor	Yes	commencs
	Yes	Commens
5 ft turning space measured 12" from the floor	Yes	Comments
5 ft turning space measured 12° from the floor At least one Sink	Yes	
5 ft turning space measured 12" from the floor At least one Sink Description Clear floor space of 30" by 48" to allow a forward approach		
5 ft turning space measured 12" from the floor At least one Sink Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim	Yes No	
5 ft turning space measured 12" from the floor At least one Sink Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall	Yes No Yes	
5 ft turring space measured 12" from the floor At least one Sink Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends as least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high	Yes No Yes Yes	
5 ft turning space measured 12" from the floor At least one Sink Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall Open knee space a minimum 3" deep, 30" width, and 27" high Cover exposed pipes with insulation	Yes No Yes Yes	
5 ft turning space measured 12" from the floor At least one Sink Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucets operable with closed fist (lever or spring activated handle)	Yes No Yes Yes	
5 ft turning space measured 12" from the floor At least one Sink Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 4" to top of rim Extends as least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucts openable with closed fist (lever or spring activated handle) At least one Stall	Yes No Yes Yes	Comments
5 ft turning space measured 12" from the floor At least one Sink Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucets openable with closed fist (lever or spring activated handle) At least one Siall Description	Yes No Yes Yes No Yes	
5 ft turning space measured 12" from the floor At least one Sink Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucts operable with closed fist (lever or spring activated handle) At least one Stall Description Accessible to person using wheelchair at 60" wideby 72" deep	Yes No Yes Yes No Yes	Comments
5 ft turning space measured 12" from the floor At least one Sink Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 4" to top of rim Extends at least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucts obgenable with closed fist (lever or spring activated handle) At least one Stall Description Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide	Yes No Yes Yes No Yes Yes Yes	Comments
5 ft turning space measured 12" from the floor At least one Sink Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucets operable with closed fist (lever or spring activated handle) At least one Stall Description Accessible to person using wheelchair at 60" wideby 72" deep Stall door swings out	Yes No Yes Yes No Yes Yes Yes Yes Yes	Comments
5 ft turning space measured 12" from the floor At least one Sink Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucets openable with closed fist (lever or spring activated handle) At least one Stall Description Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door is 36" wide Stall door is self closing	Yes No Yes No Yes No Yes No Yes Yes No	Comments
5 ft turning space measured 12" from the floor At least one Sink Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 4" to top of rim Extends at least 22" from the well Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucts openable with closed fist (lever or spring activated handle) At least one Stall Description Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door is 96" doos is self closing Stall door is 40 closing Stall door is 40 closing Stall door is 40 closing	Yes No Yes Yes No Yes Yes No Yes Yes Yes Yes Yes No No	Comments
5 ft turning space measured 12" from the floor At text one Shit Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends as least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucets operable with closed fist (lever or spring activated handle) At least one Stall Description Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door swings out Stall door is self closing Stall door is self closing Stall door is operable with a closed fist, and 32" above the floor	Yes No Yes Yes No Yes Yes Ves Yes Yes Yes Yes Yes Y	Comments
5 ft turning space measured 12" from the floor Att least one Sink Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucets operable with closed fist (lever or spring activated handle) At least one Stall Description Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door is 36" wide Stall door swings out Stall door swings out Stall door swings out Cook on stall door is operable with a closed fist, and 32" above the floor Coot hook is 54" high	Yes No Yes Yes No Yes Yes No Yes Yes Yes Yes Yes No No	Comments
5 ft turning space measured 12" from the floor At least one Sink Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the well Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucets operable with closed fist (lever or spring activated handle) At least one Stall Description Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door is 36" wide Stall door as est closing Stall door has a pull latch Lock on stall door is est floxing Stall door has a pull latch Lock on stall door is persole with a closed fist, and 32" above the floor Coat hook is 54" high	Yes No Yes Yes No Yes Yes Ves Yes Yes Yes Yes Yes Y	Comments Comments But at 41 inches high
5 ft turning space measured 12" from the floor At least one Sink Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends as least 22" from the wast 23" from the wast 24" f	Yes No Yes	Comments
5 ft turning space measured 12" from the floor Att least one Sink Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucets operable with closed fist (lever or spring activated handle) At least one Stall Description Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door is 36" wide Stall door is self closing Stall door say sall door is operable with a closed fist, and 32" above the floor Cout hook is 54" high Tollest Tollest Tollest Tollest Tollest Tomorement roll nearest side wall	Yes No Yes No Yes Yes No Yes No Yes	Comments Comments But at 41 inches high
5 ft turning space measured 12" from the floor At least one Sink Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the well Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucets operable with closed fist (lever or spring activated handle) At least one Stall Description Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door is 36" wide Stall door as elf closing Stall door has a pull latch Lock on stall door is elf closing Stall door host operable with a closed fist, and 32" above the floor Coat hook is 54" high Tollet Description 18" from center to nearest side wall	Ves No Yes Ves No Ves Ves Ves Yes Yes Yes Yes Yes Yes Yes No No Yes	Comments Comments But at 41 inches high
5 ft turning space measured 12" from the floor At text one Shit Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends as least 22" from the was 12" Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucets operable with closed fist (lever or spring activated handle) At least one Stall Description Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door is 16" wide Stall door is self closing Stall door is a pull latch Lock on stall door is operable with a closed fist, and 32" above the floor Coar to hook is 54" high Toilet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor	Yes No Yes No Yes Yes No Yes No Yes	Comments Comments But at 41 inches high
5 ft turning space measured 12" from the floor Att least one Sink Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucets operable with closed fist (liever or spring activated handle) Att least one Stall Description Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door sis 96" wide Stall door sis elf closing Stall door is self closing Stall door so is perable with a closed fist, and 32" above the floor Cost hook is 54" high Toilet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fisture Top of seat 17"-19" above the floor Grab Bars	Ves No Yes Ves No Ves Ves Ves Yes Yes Yes Yes Yes Yes Yes No No Yes	Comments Comments But at 41 inches high
5 ft turning space measured 12" from the floor At text one Shit Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends as least 22" from the was 12" Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucets operable with closed fist (lever or spring activated handle) At least one Stall Description Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door is 16" wide Stall door is self closing Stall door is a pull latch Lock on stall door is operable with a closed fist, and 32" above the floor Coar to hook is 54" high Toilet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor	Ves No Yes Ves No Ves Ves Ves Yes Yes Yes Yes Yes Yes Yes No No Yes	Comments Comments But at 41 inches high
5 ft turning space measured 12" from the floor Att least one Sink Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucets operable with closed fist (liever or spring activated handle) Att least one Stall Description Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door sis 96" wide Stall door sis elf closing Stall door is self closing Stall door so is perable with a closed fist, and 32" above the floor Cost hook is 54" high Toilet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fisture Top of seat 17"-19" above the floor Grab Bars	Ves No Yes Ves No Ves Ves Ves Yes Yes Yes Yes Yes Yes Yes No No Yes	Comments Comments But at 41 inches high Comments
S fit turning space measured 12" from the floor At least one Sink Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestatior legs, height 44" to top of rim Extends at least 22" from the well Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucets operable with closed fist (lever or spring activated handle) At least one Stall Description Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door is 36" wide Stall door as est closing Stall door has a pull latch Lock on stall door is est closing Stall door hook is 54" high Tollet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor Got Bass. Description	Yes No Yes Yes Yes No No Yes	Comments Comments But at 41 inches high Comments
5 ft turning space measured 12" from the floor At least one Sink Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends as least 22" from the well Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucets operable with closed fist (lever or spring activated handle) At least one Stall Description Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door is 36" wide Stall door is self closing Stall door is operable with closed fist, and 32" above the floor Cost hook is 54" high Toilet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fisture Top of seat 17"-19" above the floor Grab Bass On back and side wall closest to toilet	Yes No Yes No Yes Yes No Yes	Comments Comments But at 41 inches high Comments
5 ft turning space measured 12" from the floor Att least one Shit Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucets operable with closed fist (lever or spring activated handle) At least one Stall Description Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door sis elf closing Stall door say for special door is operable with a closed fist, and 32" above the floor Cox to not is 54" high Tollet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor Grab Bars Description On back and side wall closest to toilet 11%" diameter	Yes No Yes No Yes No Yes No Yes	Comments Comments But at 41 inches high Comments
5 ft turning space measured 12" from the floor Att least ane Sink Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucets operable with closed fist (lever or spring activated handle) Att least one Stall Description Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door is 36" wide Stall door is 36" wide Stall door is 36" look Stall door sha pull latch Lock on stall door is person using wheelchair at 60" wideby 72" deep Stall door is self closing Stall door sha pull latch Lock on stall door is person by the floor Coat hook is 54" high Toilet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture To of seat 17".19" above the floor Grab Bars Description On back and side wall closest to toilet 1½" clearance to wall	Yes No Yes No Yes Yes Ves Yes Yes Yes Yes Yes No No Yes	Comments Comments But at 41 inches high Comments Comments
5 ft turning space measured 12" from the floor At text one Shit Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends as leat 22" from the was 12" Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucets operable with closed fist (lever or spring activated handle) At least one Stall Description Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door sie 91" door 40" Stall door is 96" wide Stall door is 91" door 40" Stall door is 91" door 40" Cover exposed pipes with closed fist, and 32" above the floor Cox to not all door is operable with a closed fist, and 32" above the floor Cox to hook is 54" high Tollet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor Grab Bars Description On back and side wall closest to toilet 11%" diameter 11%" clearance to wall Located 30" above and parallel to the floor Acld-etched or roughened surface	Yes No Yes No Yes No Yes No Yes	Comments Comments But at 41 inches high Comments Comments
5 ft turning space measured 12" from the floor Att least one Sink Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucets openable with closed fist (lever or spring activated handle) Att least one Stall Bescription Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Cover exposed place with a closed fist, and 32" above the floor Cout hook is 54" high Tailet Tailet Toget ("minimum clear space from center to farthest wall or fisture Top of sext 17"-19" above the floor Grab Bars Description On back and side wall closest to toilet 11%" clearance to wall Located 30" above and parallel to the floor Acid -etched or orughened surface 42" long 42" long 42" ong	Yes No Yes No Yes	Comments Comments But at 41 inches high Comments Comments
S fit turning space measured 12" from the floor At least one Sink Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucets openable with closed fist (lever or spring activated handle) At least one Stall Description Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door is 36" wide Stall door is self closing Stall door is self closing Stall door is openable with a closed fist, and 32" above the floor Coat hook is 54" high Tallet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fisture Top of seat 17"-19" above the floor Grab Bars Description On back and side wall closest to toilet 11%" clearance to wall Located 30" above and parallel to the floor Acid-etched or roughened surface 42" long Flatures	Yes No Yes No Yes No Yes No Yes	Comments Comments But at 41 inches high Comments Comments 33inches
5 ft turning space measured 12" from the floor At test one Sink Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extend sal least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucets operable with closed fist (lever or spring activated handle) At least one Sill Description Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door sill one is 36" wide Stall door is 96" wide Stall door is 96" door a pull latch Lock on stall door is operable with a closed fist, and 32" above the floor Cost took is 54" high Toilet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor Grab Bars Description On back and side wall closest to toilet 11%" clearnace to wall Located 30" above and parallel to the floor Acid etched or roughened surface 42" long Fixtures Description	Yes No Yes No Yes No Yes No Yes	Comments Comments But at 41 inches high Comments Comments
5 ft turning space measured 12" from the floor Att least one Shink Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucets operable with closed fist (lever or spring activated handle) At least one Stall Description Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door sis sif closing Stall door is sif closing Stall door is self closing Stall door so is operable with a closed fist, and 32" above the floor Cost hook is 54" high Tollet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor Grab Bars Description On back and side wall closest to toilet 1½" clearance to wall Located 30" above and parallel to the floor Acid-etched or oughened surface 42" long Fixtures Description 1½" diameter 1½" clearance to wall Located 30" above and parallel to the floor Acid-etched or oughened surface 42" long Fixtures Description 1½" diameter	Yes No Yes	Comments But at 41 inches high Comments Comments 33inches
5 ft turning space measured 12" from the floor At least one Sink Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends as least 22" from the way and	Yes No Yes No Yes Yes Yes Yes Yes No No Yes Yes Yes No No Yes	Comments But at 41 inches high Comments Comments 33inches
S ft turning space measured 12" from the floor At test one Sink Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends as least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucets operable with closed fist (lever or spring activated handle) At least one Sall Description Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door is 36" wide Stall door is 96" wide Stall door is 96" wide Stall door is 96" high Tollet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor Grab Bass Description On back and side wall closest to toilet 11%" clearance to wall Located 30" above and parallel to the floor Acid-etched or roughened surface 42" long Fatures Description 11%" diameter 11%" clearance to wall Located 30" above and parallel to the floor Acid-etched or roughened surface 42" long Fatures Description 11%" diameter 11%" clearance to wall Located 30" above and parallel to the floor	Yes No Yes	Comments Comments But at 41 inches high Comments Comments 33inches
S ft turning space measured 12" from the floor At teast one Shit Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucets openable with closed fist (lever or spring activated handle) At teast one Stall Description Accessible to person using wheelchair at 60" wideby 72" deep Stall door is self closing Stall door is self closing Stall door is self closing Stall door is openable with a closed fist, and 32" above the floor Coat hook is 54" high Tollet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor Grab Bats On back and side wall closest to toilet 11%" clearance to wall Located 30" above and paraillel to the floor Acid-exched or roughened surface 42" long Flatures Description Ith Giameter 11%" clearance to wall	Yes No Yes No Yes Yes Yes Yes Yes No No Yes Yes Yes No No Yes	Comments Comments But at 41 inches high Comments Comments 33inches
S ft turning space measured 12" from the floor At test one Sink Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends as least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucets operable with closed fist (lever or spring activated handle) At least one Sall Description Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door is 36" wide Stall door is 96" wide Stall door is 96" wide Stall door is 96" high Tollet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor Grab Bass Description On back and side wall closest to toilet 11%" clearance to wall Located 30" above and parallel to the floor Acid-etched or roughened surface 42" long Fatures Description 11%" diameter 11%" clearance to wall Located 30" above and parallel to the floor Acid-etched or roughened surface 42" long Fatures Description 11%" diameter 11%" clearance to wall Located 30" above and parallel to the floor	Yes No Yes No Yes Yes Yes Yes Yes No No Yes Yes Yes No No Yes	Comments But at 41 inches high Comments Comments 33inches
S it turning space measured 12" from the floor At least one Sink Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucets openable with closed fist (lever or spring activated handle) At least one Stall Description Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door is 36" wide Stall door say a pull latch Lock on stall door is self closing Stall door is self closing Stall door is perable with a closed fist, and 32" above the floor Coat book is 54" high Tollet Description Accessible to person using wheelchair at 60" wideby 71" deep Stall door say a pull latch Lock on stall door is self cosing Stall door ray a pull latch Lock on stall door is perable with a closed fist, and 32" above the floor Coat book is 54" high Tollet Description On book and side wall closest to toilet 1s" clearance to wall Located 30" above and parallel to the floor Acid etched or roughened surface 42" long Fixtures Description 1s" diameter 1s" clearance to wall Located 30" above and parallel to the floor Notes:	Yes No Yes No Yes	Comments But at 41 inches high Comments Comments 33inches
S it turning space measured 12" from the floor At least one Sink Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucets openable with closed fist (lever or spring activated handle) At least one Stall Description Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door is 36" wide Stall door sat off doing Stall door sat off doing Stall door so stall door wings out Cost hook is 34" high Tollet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor On back and side wall closest to toillet 13" disarreer 13" clearance to wall Located 30" above and parallel to the floor Acid-et-thed or orughened surface 42" long Flatures Floors, Drinking Fountains, Telephones	Yes No Yes No Yes Yes Yes Yes Yes No No Yes Yes Yes No No Yes	Comments But at 41 inches high Comments Comments 33inches
S ft turning space measured 12" from the floor At least one Sink Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucets operable with closed fist (lever or spring activated handle) At least one Stall Description Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 56" wide Stall door is self closing Stall door sa spull latch Lock on stall door is perable with a closed fist, and 32" above the floor Cost hook is 54" high Toilet Description Active the content to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 17"-19" above the floor Grab Bars Description On back and side wall closest to toilet 11%" clearance to wall Located 30" above and parallel to the floor Acid-et-thed or roughend surface 42" long Fixtures Description 11%" diameter 11%" clearance to wall Located 30" above and parallel to the floor Notes:	Yes No Yes No Yes	Comments But at 41 inches high Comments Comments 33inches
S ft turning space measured 12" from the floor At least one Sink Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucets openable with closed fist (lever or spring activated handle) At least one Stall Description Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door sat off closing Stall door so sat off closing Stall door so sat off closing Stall door so sat off closing Stall door sat 3" righ Tollet Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fisture Top of seal 17"-19" above the floor Grab Bars Description On back and side wall closest to tollet 13" clearance to wall Located 30" above and parallel to the floor Adde-tetched or orughened surface 42" long Flowers Floors, Drinking Fountains, Telephones	Yes No Yes No Yes	Comments But at 41 inches high Comments Comments 33inches
S it turning space measured 12" from the floor At least one Sink Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucets operable with closed fits (flever or spring activated handle) At least one Stall Description Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door is 36" wide Stall door is 36" wide Stall door is self closing Stall door is self closing Stall door is openable with a closed fist, and 32" above the floor Coat hook is 54" high Tallet Tallet Description 18" from center to nearest side wall 42" milimum deer space from center to farthest wall or fixture Trop of seal 17"-30" above the floor Description On back and side wall closest to toilet 13" diameter 14" clearance to wall Located 30" above and parallel to the floor Notes:	Yes No Yes No Yes	Comments But at 41 inches high Comments Comments Comments Comments Comments
S it turning space measured 12" from the floor At least one Sink Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pies with insulation Faucets openable with closed fist (lever or spring activated handle) At least one Stall Description Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door is 36" wide Stall door is 36" shee Stall door sheep and litatch Lock on stall door is openable with a closed fist, and 32" above the floor Cost took is 54" high Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fisture Tool seal 17"-19" above the floor Grab Bars Description On back and side wall closest to tollet 13%" clearance to wall Located 30" above and parallel to the floor Ackid-et-thed or roughened surface 42" long Fibrures Description 13" clearance to wall Located 30" above and parallel to the floor Notes: FLOORS, Drinking Fountains, Telephones Description Description Description	Yes No Yes Yes No Yes Yes No Yes Yes	Comments But at 41 inches high Comments Comments Comments Comments Comments
S ft turning space measured 12" from the floor At least one Sink Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucets operable with closed first (lever or spring activated handle) At least one Stall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucets operable with closed first (lever or spring activated handle) At least one Stall Open stall door is 36" wide Stall door is 36" kneep to stall door is spensable with a closed first, and 32" above the floor Cost hook is 54" high Tolket Description 18" from center to nearest side wall 42" minimum clear space from center to farthest wall or fixture Top of seat 37"-19" above the floor On back and side wall closest to toilet 11" diameter 11" clearance to wall Located 30" above and parallel to the floor Notes: Floors, Drinking Fountains, Telephones Booss Description Nor-slips surface	Yes No Yes No Yes No Yes No Yes	Comments But at 41 inches high Comments Comments Comments Comments Comments
S it turning space measured 12" from the floor At hast one Sink Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wail Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with incubation Faucets operable with closed fist (lever or spring activated handle) At least one Stall Description Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide Stall door is 36" wide Stall door is 36" wide Stall door is self closing Stall door is self	Yes No Yes	Comments But at 41 inches high Comments Comments Comments Comments Comments
S it turning space measured 12" from the floor At least one Sink Description Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall Open knee space a minimum 13" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucets operable with closed fist (lever or spring activated handle) At least one Stall Description Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 30" wide Stall door is 30" wide Stall door is 30" wide Stall door is 54" high Tailest Description 18" from center to nearest side wall 42" minimum clear space from center to furthest wall or fixture Top of seat 17"-19" above the floor Grab Beas Description On back and side wall closest to toilet 13" diameter 13" clearance to wall Located 30" above and parallel to the floor Acid stetched or roughened surface 42" long Floors, Drinking Fountains, Telephones Floors, Drinking Fountains, Telephones Floors, Drinking Fountains, Telephones Execription Notes:	Yes No Yes Ves No Yes Ves No Yes Yes	Comments Comments But at 41 inches high Comments Comments Comments Comments Comments
S ft turning space measured 12" from the floor Altest one Sink Description Clear filtor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to stop of rim Estends at least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucts openable with closed fist (lever or spring activated handle) Altestan os Sall Description Accessible to person using wheelchair at 60" wideby 72" deep Stall doors wings out Stall doors sall door is 36" wide Stall doors wings out Stall door is salf closing Stall door is salf door is openable with a closed fist, and 32" above the floor Cost book is 54" high Tollet Description 18" from center to nearest side wall 42" innifirum clear space from center to farthest wall or fixture Top of sast 37" above the floor Grab Bars Description On back and side wall closest to tollet 11" damneter 11" damneter 42" long Faluers Floors, Drinking Fountains, Telephones Ploors, Drinking Fountains, Telephones Description Notes: Floors, Drinking Fountains, Telephones Control width minimum is 3 it. Objects (pignor) with minimum is 3 it.	Yes No Yes Ves No Yes Ves No Yes Yes	Comments But at 41 inches high Comments Comments Comments Comments Comments

Spouts no higher than 36" from floor to outlet	Yes	
Hand operated push button or level controls	Yes	
Spouts located near front with stream of water as parallel to front as possible	Yes	
If recessed, recess a minimum 30" width, and no deeper than depth of fountain	Yes	
If no clear knee space underneath, clear floor space 30" x 48" to allow parallel approach	Yes	
Signs, Signals, and Switches	YES	
Switches, Controls and Signs		
Description		Comments
Switches and controls for light, heat, ventilation, windows, fire alarms, thermostats, etc, must be a minimum of 36" and a maximum of 48" above the floor for a forward reach, a maximum of 54" for a side reach	Yes	
Electrical outlets centered no lower than 18" above the floor	Yes	
Warning signals must be visual as well as audible	Yes	
Signs		
Description		Comments
Mounting height must be 60" to centerline of the sign		
Within 18" of door jamb or recessed		
Letters and numbers a t least 11/1" high		
Letters and numbers raised .03"		
Letters and numbers contrast with the background color	Yes	
Notes:		
	N/A	
Shower Rooms	N/A	
Picknicking	N/A	
Off Leash Dog Areas (OLA)	N/A	<u> </u>

Facility Name: Kennard Park Size (Ac): 14.0 acres Address: Dudley Road, Newton Centre Ward: 8 General Facility Notes: Lawn and natural wooded area; inaccessible dirt footpaths throughout the wooded areas; accessible parking; building is Parks, Recreation & Culture HQ and has accessible ramped entrance; continguous to Kennard Conservation Area and the Town of Brookline. Site Furnishings Comments Description Yes Tables & Benches Number of Tables No Located adjacent to accessible paths No Back and Arm Rests No Located adjacent to accessible paths No Trash Cans Located adjacent to accessible paths No icnic Shelters No Notes: YES Trails & Paths Comments Surface (A=Asphalt, C=Concrete, SD= stone dust, NS= naturally surfaced, B=Boardwalk, BR=Bridge) NS variable wifth 3' to 5' Dimensions (width) Rails no Signage for visually impaired No Notes: Play Areas N/A N/A N/A Game Areas Boat Docks Fishing Facilities **Community Gardens** N/A YES Accessible Spaces Description Comments Parking Amenities (L=lot, ST=street) Accessible space located closest to accessible entrance No No accessible spots Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft No Minimum width of 13 ft includes 8 ft space plus 5 ft access aisle No Minimum of 1 van space for every accessible space, 8' wide + 8' aisle. No Sign with international symbol of accessibility at each space $\label{eq:constraint} % \[\frac{1}{2} \left(\frac{1}{2}$ No Sign 5'-8' to top of sign No Surface evenly paved or hard-packed (no cracks) No No Surface slope less than 1:20, 5% Curbcut to pathway from parking lot at each space if sidewalk (curb) is present . No Curbcut is a minimum width of 3 ft, excluding sloped sides, has sloped sides, all slopes not to exceed 1:12, and textured or painted yellow No Notes: YES Comments Slope Maximum 1:12 to building Minimum width 4 ft between handrails YES Handrails on both sides if ramp is longer than 6 ft YES Handrails at 34" and 19" from ramp surface YES Handrails extend 12" beyond top and bottom YES Handgrip oval or round round Handgrip smooth surface YES Handgrip diameter between 1¼" and 2" YES Clearance of 11/2" between wall and wall rail YES YES Level platforms (4ft x 4 ft) at every 30 ft, at top, at bottom, at change of direction YES Notes: This is ramp into building. Front door is not accessible once you reach top of ramp. YES Site Access, Path of Travel, Entrances Description Comments Accessible path of travel from passenger disembarking area and parking area to accessible entrance No Surface evenly paved or hard-packed No No Ponding of water? Disembarking area at accessible entrance No ath of Travel Comments Description YES Path does not require the use of stairs Path does not require the use of wheelchair ramp YES Path is stable, firm and slip resistant No non acessible naturlized paths Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50). No Continuous common surface, no changes in level greater than ½ inch No Any objects protruding onto the pathway must be detected by a person with a visual disability using a cane No Objects protruding more than $4^{\prime\prime}$ from the wall must be within 27" of the ground, or higher than $80^{\prime\prime}$ No

Curb on the pathway must have curb cuts at drives,parking and drop-offs	No	
Entrances	1	1
Description		Comments
Primary public entrances accessible to person using wheelchair, must be signed, gotten to independently, and not be the service entrance	No	Comments
Level space extending 5 ft. from the door, interior and exterior of entrance doors	No	
Minimum 32" clear width opening (i.e. 36" door with standard hinge)	No	
At least 18" clear floor area on latch, pull side of door	No	
	No	
Door handle no higher than 48" and operable with a closed fist Vestibule is 4 ft plus the width of the door swinging into the space		
	No	
Entrance(s) on a level that makes elevators accessible Door mats less than %" thick are securely fastened	No No	
Door mats more than ¼" thick are recessed	No	
Grates in path of travel have openings of %" maximum	No	
Signs at non-accessible entrance(s) indicate direction to accessible entrance	No	
Emergency egress – alarms with flashing lights and audible signals, sufficiently lighted	No	
Notes:		
	IVEC.	
Stairs and Doors	YES	
<u>Stairs</u>		
Description		Comments
Open risers	No	
Nosings not projecting	No	
Treads no less than 11" wide	No	
Handrails on both sides	No	
Handrails 34"-38" above tread	No	
Handrail extends a minimum of 1' beyond top and bottom riser (if no safety hazard and space permits)	No	
Handgrip oval or round	No	
Handgrip has a smooth surface	No	
Handgrip diam. 1½" - 1½"	No	
1½" clearance between wall and handrail	No	
<u>Doors</u>		T
Description		Comments
Minimum 32" clear opening	No	
At least 18" clear floor space on pull side of door	No	
Closing speed minimum 3 seconds to within 3" of the latch	No	
Maximum pressure 5 pounds interior doors	No	
Threshold maximum ¼" high, beveled on both sides	No	
Hardware operable with a closed fist (no conventional door knobs or thumb latch devices)	No	
Hardware minimum 36", maximum 48" above the floor	No	
Clear, level floor space extends out 5 ft from both sides of the door	No	
Door adjacent to revolving door is accessible and unlocked	No No	
Doors opening into hazardous area have hardware that is knurled or roughened	NO	
Notes: Building and entrance are not accessible.		
Restrooms	N/A	·
Floors, Drinking Fountains, Telephones	N/A	
Signs, Signals, and Switches	N/A	
Swimming Pool/ Lake beach	N/A	
Shower Rooms	N/A	
JIIOWEI NOUIII3		
Dicknicking	N/A	
Picknicking Off Leash Dog Areas (OLA)	N/A N/A	

Facility Name: Louise Levingston Cove		
Size (Ac): .5 acres		
Address: Lake Avenue, Newton Highlands		
Ward: 6		
General Facility Notes: Accessible stone dust portion of pathway eroded and inaccessible; wheelchai Rd. entrances; renovation of the park set to begin in FY 22; Park Renovation will provide accessibility		
Site Furnishings	YES	
Description	Yes	Comments
Tables & Benches Number of Benches	7	
Number of Tables	No	
Located adjacent to accessible paths	3	3 benches are located next to cement paths that are level.
Back and Arm Rests Grills	6	all benches have backs and arm rests
Located adjacent to accessible paths	No	
<u>Trash Cans</u>		
Located adjacent to accessible paths Picnic Shelters	YES	
Located adjacent to accessible paths	No	
Notes:		
Trails & Paths	YES	
Description		Comments
Surface (A=Asphalt, C=Concrete, SD= stone dust, NS= naturally surfaced, B=Boardwalk, BR=Bridge)	C & SD	some areas are cement other are stone dust that has washed out in spots
Dimensions (width) Rails	4' YES	
Signage for visually impaired	No	
Benches	7	
Notes:		
Play Areas	N/A	
Game Areas	N/A	
	N/A N/A	
	N/A	
	N/A	
	YES	Communication
Description Slope Maximum 1:12	Yes	Comments
Minimum width 4 ft between handrails	Yes	
Handrails on both sides if ramp is longer than 6 ft	Yes	
Handrails at 34" and 19" from ramp surface Handrails extend 12" beyond top and bottom	Yes	
Handgrip oval or round	Yes	Round
Handgrip smooth surface Handgrip diameter between 1X" and 2"	Yes	
Clearance of 1½" between wall and wall rail	NA NA	
Non-slip surface	Yes	
Level platforms (4ft x 4 ft) at every 30 ft, at top, at bottom, at change of direction Notes: Ramp handrails are not continuous	Yes	
Site Access, Path of Travel, Entrances	YES	
Site Access		
Description Associated the second distribution and soldier and sol	N-	Comments
Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed	No No	
Ponding of water?	YES	
Disembarking area at accessible entrance	No	
Path of Travel Description		Comments
Path does not require the use of stairs	YES	
Path does not require the use of wheelchair ramp	no	ramp use required
Path is stable, firm and slip resistant Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50).	no no	portions are stable other parts no.
Continuous common surface, no changes in level greater than ½ inch	no	
Any objects protruding onto the pathway must be detected by a person with a visual disability using a cane	no	
Objects protruding more than 4" from the wall must be within 27" of the ground, or higher than 80" Curb on the pathway must have curb cuts at drives, parking and drop-offs	no no	
Control the patrickey made have controlled at diversioning and disposits Notes:	110	
	21/2	
	N/A N/A	
	N/A	
Signs, Signals, and Switches	N/A	<u> </u>
	N/A N/A	
Picknicking	N/A	
	N/A	

Facility Name: Lowell Park		
Size (Ac): .6 acres		
Address: Watertown Street and Walnut Street and Lowell Avenue, Newtonville		
Ward: 2		
General Facility Notes: Large, triangular traffic island; accessible pathways with ber	nches from sidewalk const	ructed in 2012.
Site Furnishings	YES	
Description Table 8 Parks	Yes	Comments
Tables & Benches Number of Benches	3	
Number of Tables	No	
Located adjacent to accessible paths	3	
Back and Arm Rests	3	
<u>Grills</u>		
Located adjacent to accessible paths Trash Cans	No	
Located adjacent to accessible paths	1	
<u>Picnic Shelters</u>		
Located adjacent to accessible paths	No	
Notes:		
Trails & Paths	YES	
Description		Comments
Surface (A=Asphalt, C=Concrete, SD= stone dust, NS= naturally surfaced, B=Boardwalk, BR=Bridge)	A	
Dimensions (width) Rails	5' No	
Signage for visually impaired	No No	
Benches	2	
Notes:		
Play Areas	N/A	
Game Areas	N/A	
Boat Docks Fishing Facilities	N/A N/A	
Community Gardens	N/A	
Parking	N/A	
Ramps	N/A	
Site Access, Path of Travel, Entrances	YES	
Site Access Description		Comments
Description Accessible path of travel from passenger disembarking area and parking area to accessible entrance	No	Comments
Surface evenly paved or hard-packed	YES	
Ponding of water?	No	
Disembarking area at accessible entrance	No	
Path of Travel Description		Comments
Path does not require the use of stairs	YES	
Path does not require the use of wheelchair ramp	YES	
Path is stable, firm and slip resistant	YES	
Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50).	YES	
Continuous common surface, no changes in level greater than ½ inch Any objects protruding onto the pathway must be detected by a person with a visual disability using a cane	YES No	
Any objects protruding onto the pathway must be detected by a person with a visual disability using a cane Objects protruding more than 4" from the wall must be within 27" of the ground, or higher than 80"	No No	
Curb on the pathway must have curb cuts at drives, parking and drop-offs	No	
Stairs and Doors	N/A	
Restrooms	N/A	
Floors, Drinking Fountains, Telephones	N/A	
Signs, Signals, and Switches Swimming Pool/ Lake beach	N/A N/A	
Shower Rooms	N/A	
Picknicking	N/A	
Off Leash Dog Areas (OLA)	N/A	

Facility Name: Lyons Park		
Size (Ac): 5.3 acres		
Address: Commonwealth Ave., at Islington Road, Auburndale		
Ward: 4		
General Facility Notes: Little League field/bleachers not accessible; Marty Sender Pathway (DCR) lead inaccessible; Bathrooms/concession are accessible but no accessible path to the building. Accessible 2021 construction; contiguous to Auburndale Park; accessible stone dust trail from Lyons to Auburndale.	path to co	oncession stand from Commonwealth Ave. planned for 2020-
Site Furnishings Description	ILS	Comments
Tables & Benches		Commence
Number of Benches	YES	7
Number of Tables	No	
Located adjacent to accessible paths	No	
Back and Arm Rests	Yes	3 out of 7 benches have backrests
<u>Grills</u>		
Located adjacent to accessible paths	NA	
<u>Trash Cans</u>		
Located adjacent to accessible paths	No	
Picnic Shelters Located adjacent to accessible paths	NA	T
Notes:	NA	
NOTES.		
Trails & Paths	YES	
Description		Comments
Surface (A=Asphalt, C=Concrete, SD= stone dust, NS= naturally surfaced, B=Boardwalk, BR=Bridge)	Yes	NS, sD
Dimensions (width)		4 ft min.
Rails	no	
Signage for visually impaired	no	
Notes:		
DI. A	AL / A	
	N/A	
	YES	I c
Description Facility Type (RF=Rectangular Fields, BF= Ballfields, BK=Basketball, TN=Tennis, BC=Bocce)	Yes	Comments RF
	res	Dr.
Access Routes Located adjacent to accessible paths	No	
Berm cuts onto courts	NA NA	
Equipment		
Spectator Seating	Yes	
Notes:		
Boat Docks	N/A	
	N/A	
Community Gardens	N/A	
	N/A	
Off Leash Dog Areas (OLA)	N/A	

Facility, Names Lieuward Dayle		
Facility Name: Linwood Park Size (Ac): 1.25 acres		
Address: Linwood Ave. and Walnut St., Newtonville		
Ward: 2		
General Facility Notes: Large traffic island with perimeter sidewalks; accessible ro	ute through the park; site f	ırniture accessible.
Site Furnishings	YES	
Description	Yes	Comments
Tables & Benches Number of Benches	yes	1
Number of Belicies Number of Tables	yes No	1
Located adjacent to accessible paths	No	Bench is not along a path
Back and Arm Rests	yes	Bench with back only, no armrest
<u>Grills</u>		•
Located adjacent to accessible paths	NA	
<u>Trash Cans</u>		
Located adjacent to accessible paths	NA	
<u>Picnic Shelters</u>		
Located adjacent to accessible paths	NA	
Notes:		
Trails & Paths	YES	
Description Description	1123	Comments
Surface (A=Asphalt, C=Concrete, SD= stone dust, NS= naturally surfaced, B=Boardwalk, BR=Bridge)	Yes	Concrete
Dimensions (width)	Yes	6-ft min
Rails	No	
Signage for visually impaired	No	
notes:	•	
Play Areas	N/A N/A	
Play Areas Game Areas	N/A	
Play Areas Game Areas Boat Docks	N/A N/A	
Play Areas Game Areas Boat Docks Fishing Facilities	N/A	
Play Areas Game Areas Boat Docks Fishing Facilities Community Gardens	N/A N/A N/A	
Play Areas Game Areas Boat Docks Fishing Facilities Community Gardens Parking	N/A N/A N/A N/A	
Play Areas Game Areas Boat Docks Fishing Facilities Community Gardens Parking	N/A N/A N/A N/A N/A	
Play Areas Game Areas Boat Docks Fishing Facilities Community Gardens Parking Ramps Site Access, Path of Travel, Entrances	N/A N/A N/A N/A N/A N/A	
Play Areas Game Areas Boat Docks Fishing Facilities Community Gardens Parking Ramps Site Access, Path of Travel, Entrances Brack Access Description	N/A N/A N/A N/A N/A N/A YES	Comments
Play Areas Game Areas Boat Docks Fishing Facilities Community Gardens Parking Ramps Site Access, Path of Travel, Entrances Site Access, Path of Travel and parking area and parking area to accessible entrance	N/A N/A N/A N/A N/A N/A YES	Comments no parking
Play Areas Game Areas Boat Docks Fishing Facilities Community Gardens Parking Ramps Site Access, Path of Travel, Entrances Site Access, Path of Travel area and parking area to accessible entrance Surface evenly paved or hard-packed	N/A N/A N/A N/A N/A N/A YES	
Play Areas Game Areas Boat Docks Fishing Facilities Community Gardens Parking Ramps Site Access, Path of Travel, Entrances Site Access Description Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed Ponding of water?	N/A N/A N/A N/A N/A N/A YES	
Play Areas Game Areas Boat Docks Fishing Facilities Community Gardens Parking Ramps Site Access, Path of Travel, Entrances Site Access Description Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed Ponding of water? Disembarking area at accessible entrance	N/A N/A N/A N/A N/A N/A YES	
Play Areas Game Areas Boat Docks Fishing Facilities Community Gardens Parking Ramps Site Access, Path of Travel, Entrances Site Access Description Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed Ponding of water?	N/A N/A N/A N/A N/A N/A YES	
Play Areas Game Areas Boat Docks Fishing Facilities Community Gardens Parking Ramps Site Access, Path of Travel, Entrances Site Access, Pescription Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed Ponding of water? Disembarking area at accessible entrance Path of Travel	N/A N/A N/A N/A N/A N/A YES	no parking
Play Areas Game Areas Boat Docks Fishing Facilities Community Gardens Parking Ramps Site Access, Path of Travel, Entrances Site Access, Path of Travel, Entrances Site Access Description Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed Ponding of water? Disembarking area at accessible entrance Path of Tavel Description	N/A N/A N/A N/A N/A N/A N/A N/A N/A VES NO NA	no parking
Play Areas Game Areas Boat Docks Fishing Facilities Community Gardens Parking Ramps Site Access, Path of Travel, Entrances Site Access, Path of Travel, Entrances Observation Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed Ponding of water? Disembarking area at accessible entrance Path of Travel Description Path does not require the use of stairs Path does not require the use of wheelchair ramp Path os table, firm and slip resistant	N/A N/A N/A N/A N/A N/A YES	no parking
Play Areas Game Areas Boat Docks Fishing Facilities Community Gardens Parking Ramps Site Access, Path of Travel, Entrances Site Access, Path of Travel, Entrances Site Access Description Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed Ponding of water? Disembarking area at accessible entrance Path of Travel Description Path does not require the use of stairs Path does not require the use of wheelchair ramp Path is stable, firm and slip resistant Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50).	N/A	no parking
Play Areas Game Areas Boat Docks Fishing Facilities Community Gardens Parking Ramps Site Access, Path of Travel, Entrances Site Access Description Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed Ponding of water? Disembarking area at accessible entrance Path of Travel Description Path does not require the use of wheelchair ramp Path does not require the use of wheelchair ramp Path is stable, firm and slip resistant Slope maximum 120 (5%) and maximum cross pitch is 2% (1:50). Continuous common surface, no changes in level greater than % inch	N/A N/A N/A N/A N/A N/A N/A N/A N/A YES NO NA Yes Yes Yes	no parking
Play Areas Game Areas Boat Docks Fishing Facilities Community Gardens Parking Ramps Site Access, Path of Travel, Entrances Site Access Description Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed Ponding of water? Disembarking area at accessible entrance Path of Travel Description Path does not require the use of wheelchair ramp Path does not require the use of wheelchair ramp Path is stable, firm and slip resistant Slope maximum 120 (5%) and maximum cross pitch is 2% (1:50). Continuous common surface, no changes in level greater than % inch	N/A	no parking
Play Areas Game Areas Boat Docks Fishing Facilities Community Gardens Parking Ramps Site Access, Path of Travel, Entrances Site Access Description Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed Ponding of water? Disembarking area at accessible entrance Path of Travel Description Path does not require the use of wheelchair ramp Path is stable, firm and slip resistant Path does not require the use of wheelchair ramp Path is stable, firm and slip resistant Siope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50). Continuous common surface, no changes in level greater than % inch Notes:	N/A	no parking
Play Areas Game Areas Boat Docks Fishing Facilities Community Gardens Parking Ramps Site Access, Path of Travel, Entrances Site Access, Path of Travel, Entrances Site Access, Path of Travel, Entrances Site Access Description Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed Ponding of water? Disembarking area at accessible entrance Path of Travel Description Path does not require the use of stairs Path does not require the use of wheelchair ramp Path is stable, firm and slip resistant Siope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50). Continuous common surface, no changes in level greater than ½ inch Notes: Stairs and Doors	N/A	no parking
Play Areas Game Areas Boat Docks Fishing Facilities Community Gardens Parking Ramps Site Access, Path of Travel, Entrances Site Access, Path of Travel, Entrances Site Access Description Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed Ponding of water? Disembarking area at accessible entrance Path of Tavel Description Path of Tavel Description Path does not require the use of stairs Path does not require the use of wheelchair ramp Path is stable, firm and slip resistant Slope maximum 1.20 (5%) and maximum cross pitch is 2% (1.50). Continuous common surface, no changes in level greater than ½ inch Notes: Stairs and Doors Restrooms	N/A	no parking
Play Areas Game Areas Boat Docks Fishing Facilities Community Gardens Parking Ramps Site Access, Path of Travel, Entrances Site Access Description Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed Ponding of water? Disembarking area at accessible entrance Path of Travel Description Path does not require the use of stairs Path does not require the use of stairs Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50). Continuous common surface, no changes in level greater than ½ inch Notes: Stairs and Doors Restrooms Floors, Drinking Fountains, Telephones	N/A	no parking
Boat Docks Fishing Facilities Community Gardens Parking Ramps Site Access, Path of Travel, Entrances Site Access Description Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed Ponding of water? Disembarking area at accessible entrance Path of Travel Description Path des not require the use of stairs Path does not require the use of wheelchair ramp Path is stable, firm and slip resistant Slope maximum 120 (5%) and maximum cross pitch is 2% (1:50). Continuous common surface, no changes in level greater than 1% inch Notes: Stairs and Doors Restrooms Floors, Drinking Fountains, Telephones Signs, Signals, and Switches	N/A	no parking
Play Areas Game Areas Boat Docks Fishing Facilities Community Gardens Parking Ramps Site Access, Path of Travel, Entrances Site Access, Path of Travel, Entrances Site Access, Path of Travel, Entrances Site Access Description Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed Ponding of water? Disembarking area at accessible entrance Path of Travel Description Path does not require the use of stairs Path does not require the use of wheelchair ramp Path is stable, firm and slip resistant Slope maximum 1.20 (5%) and maximum cross pitch is 2% (1:50). Continuous common surface, no changes in level greater than ½ inch Notes: Stairs and Doors Restrooms Floors, Drinking Fountains, Telephones Signs, Signals, and Switches Swimming Pool/ Lake beach	N/A	no parking
Play Areas Game Areas Boat Docks Fishing Facilities Community Gardens Parking Ramps Site Access, Path of Travel, Entrances Site Access, Path of Travel, Entrances Site Access, Path of Travel, Entrances Site Access Description Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed Ponding of water? Disembarking area at accessible entrance Path of Travel Description Path does not require the use of stairs Path does not require the use of wheelchair ramp Path is stable, firm and silip resistant Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50). Continuous common surface, no changes in level greater than ½ inch Notes: Stairs and Doors Restrooms Floors, Drinking Fountains, Telephones Signs, Signals, and Switches Swimming Pool/ Lake beach Shower Rooms	N/A	no parking
Play Areas Game Areas Boat Docks Fishing Facilities Community Gardens Parking Ramps Site Access, Path of Travel, Entrances Site Access, Path of Travel, Entrances Site Access Description Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed Ponding of water? Disembarking area at accessible entrance Path of Travel Description Path does not require the use of stairs Path does not require the use of wheelchair ramp Path is stable, firm and slip resistant Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50). Continuous common surface, no changes in level greater than ½ inch Notes: Stairs and Doors Restrooms Floors, Drinking Fountains, Telephones Signs, Signals, and Switches Swimming Pool/ Lake beach	N/A	no parking

Facility Name: Warren E. Lincoln Playground Size (Ac): 5.42 acres ddress: Montclair Rd, Waban Vard: 5 Seneral Facility Notes: multi-use playing Fields 3-5 yr Play structure; 5-12 yr play structure; no paths to amenities. Site Furnishings YES Seneral Facility Notes: multi-use playing Fields 3-5 yr Play structure; 5-12 yr play structure; no paths to amenities. Site Furnishings YES Secretoria Yes Comments Secretoria Note of Tables Secretoria Sec
Address: Montclair Rd, Waban Vard: 5 Intereral Facility Notes; multi-use playing Fields 3-5 yr Play structure; 5-12 yr play structure; no paths to amenities. Intereral Facility Notes; multi-use playing Fields 3-5 yr Play structure; 5-12 yr play structure; no paths to amenities. Interest of facility Notes; multi-use playing Fields 3-5 yr Play structure; 5-12 yr play structure; no paths to amenities. Interest of facility Notes; multi-use playing Fields 3-5 yr Play structure; no paths to amenities. Interest of facility Notes; multi-use playing Fields 3-5 yr Play structure; no paths to amenities. Interest of facility Notes; multi-use playing Fields 3-5 yr Play structure; no paths to amenities. Interest of facility Notes; multi-use playing Fields 3-5 yr Play structure; no paths to amenities. Interest of facility Notes; multi-use playing Fields 3-5 yr Play structure; no paths to amenities. Interest of facility Notes; multi-use playing Fields 3-5 yr Play structure; no paths to amenities. Interest of facility Notes; multi-use playing Fields 3-5 yr Play structure; no paths to amenities. Interest of facility Notes; multi-use playing Fields 3-5 yr Play structure; no paths to amenities. Interest of facility Notes; multi-use playing fields 3-5 yr Play structure; no paths to amenities. Interest of facility Notes; multi-use playing fields 3-5 yr Play structure; no paths to amenities. Interest of facility Notes; multi-use playing fields 3-5 yr Play structure; no paths to amenities. Interest of facility Notes; multi-use playing fields 3-5 yr Play structure; no paths to amenities. Interest of facility Notes; multi-use playing fields 3-5 yr Play structure; no paths to amenities. Interest of facility Notes; multi-use playing fields 3-5 yr Play structure; no paths to amenities. Interest of facility Notes; multi-use playing fields 3-5 yr Pla
Avaid: 5 Semeral Facility Notes; multi-use playing Fields 3-5 yr Play structure; 5-12 yr play structure; no paths to amenities. Site Furnishings SECRETION YES Comments Notes of Arabia Located adjustors according paths Bock and Amberts Notes of Arabia Located adjustors to according paths Bock and Amberts No Located adjustors according paths No Located adjustors according paths Society (Arabia) Located adjustors according paths Domerous (Arabia) Located adjustors according paths No Located adjustors according paths No No Domerous (Arabia) No No No No No No No No No N
Site Furnishings YES SCORDING YES COMMENTS Number of Reaches Num
Site Furnishings Secription Yes Comments Secription Yes Comments Secription Yes Comments Secription Yes Source Secription Yes Source Secription Yes Source Source
Ves
Ves
Number of Benches yes 3 benches Number of Tables Na A Na Cacacida alignent to accessible paths No
Number of Tables
tocated adjacent to accessible paths Back and Arm Riests Back and Back
Sack and Arm Rests Its Located adjacent to accessible paths Trails & Paths Serription Surface (Anasphalt, C.Concrete, SD- stone dust, NS- naturally surfaced, B-Boardwalk, BR-Bridge) No No Rails Rails No Signage for visually impaired Otes: Play Areas Serription Pacility Type (3-5 Yrs. 5-12 Yrs) Serription Facility Type (3-5 Yrs. 5-12 Yrs) Serription Rocated adjacent to accessible paths Froulty Type (3-5 Yrs. 5-12 Yrs) Serription No Located adjacent to accessible paths Froulty Type (3-5 Yrs. 5-12 Yrs) No Serription No Located adjacent to accessible paths Frough space between equipment for wheelchair No Yes Frough space between equipment for wheelchair
Ilse cared adjacent to accessible paths Located adjacent to accessible paths Otes: VES
Located adjacent to accessible paths shi Case Located adjacent to accessible paths no
Located adjacent to accessible paths Located adj
Located adjacent to accessible paths Located adjacent to accessible paths Located adjacent to accessible paths No No No No No No No No No N
Located adjacent to accessible paths Located adjacent to accessible paths Otes: Trails & Paths Serciption Surface (A-Asphalt, C-Concrete, SD+ stone dust, NS+ naturally surfaced, B-Boardwalk, BR-Bridge) Dimensions (width) Rails No Signage for visually impaired Otes: Play Areas Serciption Facility Type (3-5 Yrs, 5-12 Yrs) Same experience provided to all Located adjacent to accessible paths No Enough space between equipment for wheelchair No Enough space between equipment for wheelchair No Enough space between equipment for wheelchair No No Enough space between equipment for wheelchair No No No No No No Enough space between equipment for wheelchair No Enough space between equipment for wheelchair
Trails & Paths Secription Surface (Ar-Asphalt, C*Concrete, SD* stone dust, NS* naturally surfaced, B*Boardwalk, BR*Bridge) No No pathways within this park Dimensions (width) Rails No No Signage for visually impaired No VES Secription Facility Type (3-5 Yrs, 5-12 Yrs) Same experience provided to all Comments YES Same experience provided to all Costed adjacent to accessible paths Food to secretary of the secretary
Frails & Paths Surface (A-Asphalt, C-Concrete, SD= stone dust, NS= naturally surfaced, B=Boardwalk, BR=Bridge) Dimensions (width) Dimensions (width) No Signage for visually impaired No Signage for visually impaired No Otes: Play Areas Secription Facility Type (3-5 Yrs, 5-12 Yrs) Same experience provided to all Vess (A-Asphalt, C-Concrete, SD= stone dust, NS= naturally surfaced, B=Boardwalk, BR=Bridge) No Otes: Play Areas Secription Facility Type (3-5 Yrs, 5-12 Yrs) Same experience provided to all No Executed Signage for accessible paths No Enough space between equipment for wheelchair Yes Surfaced (A-Asphalt, C-Concrete, SD= stone dust, NS= naturally surfaced, B=Boardwalk, BR=Bridge) No No Enough space between equipment for wheelchair Yes
escription Comments Surface (Ar-Asphalt, C=Concrete, SD= stone dust, NS= naturally surfaced, B=Boardwalk, BR=Bridge) No No No pathways within this park No No No Individual No No No Individual N
escription Comments Surface (Ar-Asphalt, C=Concrete, SD= stone dust, NS= naturally surfaced, B=Boardwalk, BR=Bridge) No No No pathways within this park No No No Individual No No No Individual N
Surface (A-Asphalt, C-Concrete, SD+ stone dust, NS+ naturally surfaced, B+Boardwalk, BR-Bridge) Dimensions (width) Rails Signage for visually impaired Otes: VES
Dimensions (width)
Signage for visually impaired No Otes: YES Play Areas YES Secription Comments Facility Type (3-5 Yrs, 5-12 Yrs) Yes 3-5 yrs, 5-12 yrs Same experience provided to all No Incompany of the provided of the p
VES
VES
escription Comments Facility Type (3-5 Yrs, 5-12 Yrs) Yes 3-5 yrs, 5-12 yrs Same experience provided to all No Casted adjacent to accessible paths Enough space between equipment for wheelchair Comments A yes 3-5 yrs, 5-12 yrs A yes 3-5 yrs
escription Comments Facility Type (3-5 Yrs, 5-12 Yrs) Yes 3-5 yrs, 5-12 yrs Same experience provided to all No Casted adjacent to accessible paths Enough space between equipment for wheelchair Comments A yes 3-5 yrs, 5-12 yrs A yes 3-5 yrs
Facility Type (3-5 Yrs, 5-12 Yrs)
Located adjacent to accessible paths Located adjacent to accessible paths Enough space between equipment for wheelchair Yes
Located adjacent to accessible paths No Enough space between equipment for wheelchair Yes
Enough space between equipment for wheelchair Yes
Same Areas YES
Definition in the secretary in the secre
Facility Type (RF-Rectangular Fields, BF-Ballfields, BK-Basketball, TN=Tennis, BC-Bocce) Yes 1BF, 1RF
rees Routes
Located adjacent to accessible paths No
Berm cuts onto courts NA
uioment
Spectator Seating Yes Ottes:
uics.
Soat Docks N/A
ishing Facilities N/A
Community Gardens N/A
Parking N/A Ramps N/A
ATHUS IN/A
ite Acress Path of Travel Entrances
ite Access. Path of Travel. Entrances N/A
ite Access, Path of Travel, Entrances N/A tairs and Doors N/A N/A
ite Access, Path of Travel, Entrances tairs and Doors N/A lestrooms N/A loors, Drinking Fountains, Telephones N/A
itie Access, Path of Travel, Entrances Itairs and Doors In/A Sestrooms In/A Sestrooms In/A Signs, Signals, and Switches In/A Identify Sountains, Telephones In/A Identify Sountains, Telephones In/A Identify Sountains, Telephones In/A
ite Access. Path of Travel. Entrances Itairs and Doors Itairs and Switches Itairs and Swit
ite Access, Path of Travel, Entrances N/A tairs and Doors N/A lestrooms N/A cloors, Drinking Fountains, Telephones N/A igns, Signals, and Switches N/A wimming Pool/ Lake beach N/A shower Rooms N/A
ite Access. Path of Travel. Entrances Itairs and Doors Itairs and Switches Itairs and Swit

Facility Name: Nahanton Park		
Size (Ac): 57.0 acres		
Address: Nahanton Street and Winchester Street entrances, Newton Highlands		
Ward: 8		
General Facility Notes: Accessible parking in lot; no accessible route to Nature Center building; acces	sible stone	edust riverpath (Florries Path): bridge at Florries path not
accessible; accessible stone dust path from lower Winchester St. parking lot to Nahanton St. side; co		
Park.		
Site Furnishings Description	YES Yes	Comments
Tables & Benches	ies	Comments
Number of Senches	No	
Number of Tables Located adjacent to accessible paths	6 Yes	
Back and Arm Rests	Yes	Mixed
Grills		
Located adjacent to accessible paths Trash Cans	No	
Located adjacent to accessible paths	Yes	
Picnic Shelters Located adjacent to accessible paths	No	
Notes:	NO	
Trails & Paths	YES	
Description		Comments
Surface (A=Asphalt, C=Concrete, SD= stone dust, NS= naturally surfaced, B=Boardwalk, BR=Bridge)	SD & NS	
Dimensions (width) Rails	Approx 6ft No	
Signage for visually impaired	No	
Benches Natural Control of the Contr	No	
Notes:		
Boat Docks	YES	
Description Description	ILJ	Comments
Facility Type (R=River, P= Pond)	River	Boat dock is semi accessable
Access Routes Located adjacent to accessible paths	Yes	
Handrails	No	
Notes:		
Fishing Facilities	N/A	
Community Gardens	YES	
Accord Pourton		Portions are along stone dust trail. Other gradens are not along accessible routes
Access Routes Located adjacent to accessible paths	Yes	
	Yes	Total of the transport of the control of the state of the
Located adjacent to accessible paths	Yes	or doub are along stone day, outer graders are not along accessive routes
Located adjacent to accessible paths Notes:	YES	To the first of the design and the design of
Located adjacent to accessible paths	YES Accessible Spo	
Located adjacent to accessible paths Notes: Parking Total Spaces	YES Accessible Spo	ices
Located adjacent to accessible paths Notes: Parking Total Spaces	YES Accessible Spo	
Located adjacent to accessible paths Notes: Parking Total Spaces 25 Description Parking Amenities (L-iot, ST-street) Accessible space located closest to accessible entrance	YES Accessible Space 1 Space Lot Yes	ices
Located adjacent to accessible paths Notes: Parking Total Spaces 25 Description Parking amenities (L-lot, ST-street) Accessible space located closest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft	YES Accessible Spc 1 Space Lot Yes N/A	ices
Located adjacent to accessible paths Notes: Parking Total Spaces 25 Description Parking Amenities (L-lot, ST-street) Accessible space located closest to accessible entrance Where spaces aconate be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft Minimum width of 13 ft includes 8 ft space plus 5 ft access aisle	YES Accessible Spc 1 Space Lot Yes N/A Yes	ices
Located adjacent to accessible paths Notes: Parking Total Spaces 25 Description Parking amenities (L-lot, ST-street) Accessible space located closest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft	YES Accessible Spc 1 Space Lot Yes N/A	ices
Located adjacent to accessible paths Notes: Parking Total Spaces 25 Description Parking Amenities (Linio, ST-street) Accessible space located closest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft Minimum width of 13 ft includes 8 ft space plus 5 ft access aside Minimum of 1 van space for every accessible space, 8' wide + 8' aside. Sign with international symbol of accessibility at each space Sign 5'-8' to top of sign	YES Accessible Spc 1 Space Lot Yes N/A Yes Yes Yes	ices
Located adjacent to accessible paths Notes: Parking Total Spaces 25 Description Parking Amenities (L-lot, ST-street) Accessible space located closest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance Minimum width of 13 ft includes 8 ft space plus 5 ft access aisle Minimum of 1 van space for every accessible space, 8' wide + 8' aisle. Sign with international symbol of accessibility at each space	YES Accessible Spc 1 Space Lot Yes N/A Yes N/A Yes	ices
Located adjacent to accessible paths Notes: Parking Total Spaces 25 Description Parking Amenities (L-lot, ST-street) Accessible space located closest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft Minimum with of 13 ft includes 8 ft space plus 5 ft access aisle Minimum of 1 van space for every accessible space, 8' wide + 8' aisle. Sign with international symbol of accessibility at each space Sign 5'-8' to pof sign Surface evenly paved or hard-packed (no cracks)	YES Accessible Spc 1 Space Lot Yes N/A Yes N/A Yes N/A Yes N/A Yes	ices
Located adjacent to accessible paths Notes: Parking Total Spaces 25 Description Parking Amenities (L-lot, ST-street) Accessible space located closest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft Minimum width of 13 ft includes 8 ft space plus 5 ft access aisle Minimum of 1 van space for every accessible space, 8' wide + 8' aisle. Sign with international symbol of accessibility at each space Sign 5' 8' to top of sign Surface evenly paved or hard-packed (no cracks) Surface slope less than 1:20,5% Curbcut to pathway from parking lot at each space if sidewalk (curb) is present. Curbcut to a minimum width of 3 ft, excluding sloped sides, has sloped sides, all slopes not to exceed 1:12, and textured or painted yellow	YES Accessible Spa 1 Space Lot Yes N/A Yes N/A Yes NO Yes	ices
Located adjacent to accessible paths Notes: Parking Total Spaces 25 Description Parking amenities (Liolo, ST-street) Accessible space located closest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft Minimum width of 13 ft includes 8 ft space plus 5 ft access aisle Minimum of 1 van space for every accessible space, 8' wide + 8' aisle. Sign with international symbol of accessibility at each space Sign 5'-8' to top of sign Surface evenly paved or hard-packed (no cracks) Surface slope less than 1:20, 5% Curbcut to pathway from parking lot at each space if sidewalk (curb) is present.	YES Accessible Spc 1 Space Lot Yes N/A Yes Yes No Yes N/A Yes No N/A Yes N/A	ices
Located adjacent to accessible paths Notes: Parking Total Spaces 25 Description Parking Amenities (Linio, ST extreet) Accessible space located closest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance. Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft Minimum width of 13 ft includes 8 ft space plus 5 ft access aisle Minimum of 1 van space for every accessible space, 8' wide + 8' aisle. Sign with international symbol of accessibility at each space Sign 5'-8' to top of sign Surface evenly paved or hard-packed (no cracks) Surface slope less than 1:20, 5's Curbcut to pathway from parking lot at each space if sidewalk (curb) is present. Curbcut is a minimum width of 3 ft, excluding sloped sides, has sloped sides, all slopes not to exceed 1:12, and textured or painted yellow Notes:	YES Accessible Space Lot Yes NA Yes N/A Yes No Yes No Yes N/A N/A	ices
Located adjacent to accessible paths Notes: Parking Total Spaces 25 Description Parking Amenities (L-lot, ST-street) Accessible space located closest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft Minimum width of 13 ft includes 8 ft space plus 5 ft access aisle Minimum of 1 van space for every accessible space, 8' wide + 8' aisle. Sign with international symbol of accessibility at each space Sign 5'-8' to top of sign Surface evenly paved or hard-packed (no cracks) Surface slope less than 1:20, 5% Curbcut to pathway from parking lot at each space if sidewalk (curb) is present. Curbcut to aminimum width of 3 ft, excluding sloped sides, has sloped sides, all slopes not to exceed 1:12, and textured or painted yellow Notes: Ramps	YES Accessible Space 1 Space Lot Yes N/A Yes N/A Yes NO Yes N/A N/A	ices
Located adjacent to accessible paths Notes: Parking Total Spaces 25 Description Parking Amenities (L-lot, ST-street) Accessible space located closest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft Minimum width of 13 ft includes 8 ft space plus 5 ft access aisle Minimum of 1 van space for every accessible space, 8' wide + 8' aisle. Sign with international symbol of accessibility at each space Sign 5'-8' to pof sign Surface evenly paved or hard-packed (no cracks) Surface slope less than 1:20,5% Curbcut to pathway from parking lot at each space if sidewalk (curb) is present. Curbcut is a minimum width of 3 ft, excluding sloped sides, has sloped sides, all slopes not to exceed 1:12, and textured or painted yellow Notes: Ramps Site Access, Path of Travel, Entrances	YES Accessible Space Lot Yes NA Yes N/A Yes No Yes No Yes N/A N/A	ices
Located adjacent to accessible paths Notes: Parking Total Spaces 25 Description Parking Amenities (L-lot, ST-street) Accessible space located closest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft Minimum width of 13 ft includes 8 ft space plus 5 ft access aisle Minimum of 1 van space for every accessible space, 8' wide + 8' aisle. Sign with international symbol of accessibility at each space Sign 5'-8' to top of sign Surface evenly paved or hard-packed (no cracks) Surface slope less than 1:20, 5% Curbcut to pathway from parking lot at each space if sidewalk (curb) is present. Curbcut to aminimum width of 3 ft, excluding sloped sides, has sloped sides, all slopes not to exceed 1:12, and textured or painted yellow Notes: Ramps	YES Accessible Space 1 Space Lot Yes N/A Yes N/A Yes NO Yes N/A N/A	ices
Located adjacent to accessible paths Notes: Parking Total Spaces 25 Description Parking Amenities (L-lot, ST-street) Accessible space located closent to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft Minimum width of 13 ft includes 8 ft space plus 5 ft access aisle Minimum of 1 van space for every accessible space, 8' wide + 8' aisle. Sign with international symbol of accessibility at each space Sign 5'-8' to top of sign Surface evenly paved or hard-packed (no cracks) Surface slope less than 1:20, 5% Curbcut to pathway from parking lot at each space if sidewalk (curb) is present. Curbcut is a minimum width of 3 ft, excluding sloped sides, has sloped sides, all slopes not to exceed 1:12, and textured or painted yellow Notes: Ramps Site Access Description Accessible path of travel from passenger disembarking area and parking area to accessible entrance	YES	Comments
Located adjacent to accessible paths Notes: Parking Total Spaces 25 Description Parking Amenities (L-lot, ST-street) Accessible space located closest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft Minimum width of 13 ft includes 8 ft space plus 5 ft access aisle Minimum of 1 van space for every accessible space, 8' wide + 8' aisle. Sign with international symbol of accessibility at each space Sign 5'.5' to top of sign Surface evenly paved or hard-packed (no cracks) Surface slope less than 1:20,5% Curbcut to pathary from parking lot at each space if sidewalk (curb) is present. Curbcut is a minimum width of 3 ft, excluding sloped sides, has sloped sides, all slopes not to exceed 1:12, and textured or painted yellow Notes: Ramps Site Access, Path of Travel, Entrances Sike Access.	YES Accessible Space Lot Yes N/A Yes N/A Yes NO Yes NO Yes N/A N/A N/A N/A YES	Comments
Notes: Parking Total Spaces 25 Description Parking Amenities (Liniot, ST-street) Accessible space located closest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft Minimum width of 3 ft includes 8 ft space plus 5 ft access asiale Minimum of 1 van space for every accessible space, 8' wide + 8' asiale. Sign with international symbol of accessiblity at each space Sign street evenly paved or hard-packed (no cracks) Surface spole ests then 1:20, 5% Curbcut to pathway from parking lot at each space if sidewalk (curb) is present. Curbcut is a minimum width of 3 ft, excluding sloped sides, has sloped sides, all slopes not to exceed 1:12, and textured or painted yellow Notes: Ramps Site Access, Path of Travel, Entrances Site Access. Description Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed	YES	Comments
Located adjacent to accessible paths Notes: Parking Total Spaces 25 Description Parking Amenities (Linlot, 5T-street) Accessible pace located closest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft Minimum width of 13 ft includes 8 ft space plus 5 ft access asise Minimum of 1 van space for every accessible space, 8" wide + 8" asise. Sign with international symbol of accessibility at each space Sign 3-8" to top of sign Surface evenly paved or hard-packed (no cracks) Surface slope less than 1:20, 5% Curbcut to pathway from parking lot at each space if sidewalk (curb) is present. Curbcut is a minimum width of 3 ft, excluding sloped sides, has sloped sides, all slopes not to exceed 1:12, and textured or painted yellow Notes: Ramps Site Access Description Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed Ponding of water? Disembarking area at accessible entrance Path of Travel Path of Travel	YES Accessible Spc 1 Space Lot Yes No Yes N/A Yes No Yes N/A Yes N/A Yes N/A Yes N/A	Comments
Located adjacent to accessible paths Notes: Parking Total Spaces 25 Description Parking Amenities (Liolo, 5T-street) Accessible space located closest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft Minimum width of 13 ft includes 8 ft space plus 5 ft access aisle Minimum of 1 van space for every accessible space, 8' wide + 8' aisle. Sign with international symbol of accessibility at each space Sign 5'8' to top of sign Surface evenly paved or hard-packed (no cracks) Surface evenly paved or hard-packed (no cracks) Curbcut to pathway from parking lot at each space if sidewalk (curb) is present. Curbcut is a minimum width of 3 ft, excluding sloped sides, has sloped sides, all slopes not to exceed 1:12, and textured or painted yellow Notes: Ramps Site Access, Path of Travel, Entrances Site Access, Path of Travel, Entrances Servace evenly paved or hard-packed Ponding Accessible entrance Ponding area at accessible entrance Potestription	YES	Comments
Located adjacent to accessible paths Notes: Parking Total Spaces 25 Description Parking Amenities (Linlot, 5T-street) Accessible pace located closest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft Minimum width of 13 ft includes 8 ft space plus 5 ft access asise Minimum of 1 van space for every accessible space, 8" wide + 8" asise. Sign with international symbol of accessibility at each space Sign 3-8" to top of sign Surface evenly paved or hard-packed (no cracks) Surface slope less than 1:20, 5% Curbcut to pathway from parking lot at each space if sidewalk (curb) is present. Curbcut is a minimum width of 3 ft, excluding sloped sides, has sloped sides, all slopes not to exceed 1:12, and textured or painted yellow Notes: Ramps Site Access Description Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed Ponding of water? Disembarking area at accessible entrance Path of Travel Path of Travel	YES Accessible Spc 1 Space Lot Yes No Yes N/A Yes No Yes N/A Yes N/A Yes N/A Yes N/A	Comments
Notes: Parking Total Spaces 25 Description Parking amenities (Linlot, 5T-street) Accessible paths (Linlot, 5T-street) Accessible paths (Linlot, 5T-street) Accessible spaces cannot be located within 200 ft of accessible entrance. Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft Minimum width of 13 ft includes 8 ft space plus 5 ft access aisle Minimum of 1 van space for every accessible space, 8' wide + 8' aisle. Sign with international symbol of accessibility at each space Sign 5'-8' to top of sign Surface evenly paved or hard-packed (no cracks) Surface spole pists than 1:20, 5' Curbout to pathway from parking lot at each space if sidewalk (curb) is present. Curbout is a minimum width of 3 ft, excluding sloped sides, has sloped sides, all slopes not to exceed 1:12, and textured or painted yellow Notes: Ramps Site Access, Path of Travel, Entrances Site Access, Path of Travel, Entrances Site Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed Ponding of water? Disembarking area at accessible entrance Path does not require the use of stairs Path does not require the use of wheelchair ramp Path does not require the use of wheelchair ramp Path does not require the use of wheelchair ramp Path does not require the use of wheelchair ramp	YES	Comments
Notes: Parking Total Spaces 25 Description Parking Amenities (Linio, ST-street) Accessible space located closest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft Minimum width of 13 ft includes 8 ft space plus 5 ft access aside Minimum of 1 van space for every accessible space, 8' wide +8' aside. Sign with international symbol of accessibility at each space Sign 5'-8' to top of sign Surface evenly paved or hard-packed (no cracks) Surface slope less than 1:20, 5' Curbcut to pathway from parking lot at each space if sidewalk (curb) is present. Curbcut is a minimum width of 3 ft, excluding sloped sides, has sloped sides, all slopes not to exceed 1:12, and textured or painted yellow Notes: Ramps Site Access. Path of Travel, Entrances Site Access. Path of Travel, Entrances Site Access where the passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed Ponding of water? Disembarking area at accessible entrance Path of Travel Path of Travel Path of Travel Path does not require the use of stairs Path does not require the use of stairs Path does not require the use of trairs Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50).	YES	Comments
Notes: Parking Total Spaces 25 Description Parking amenities (Linlot, 5T-street) Accessible paths (Linlot, 5T-street) Accessible paths (Linlot, 5T-street) Accessible spaces cannot be located within 200 ft of accessible entrance. Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft Minimum width of 13 ft includes 8 ft space plus 5 ft access aisle Minimum of 1 van space for every accessible space, 8' wide + 8' aisle. Sign with international symbol of accessibility at each space Sign 5'-8' to top of sign Surface evenly paved or hard-packed (no cracks) Surface spole pists than 1:20, 5' Curbout to pathway from parking lot at each space if sidewalk (curb) is present. Curbout is a minimum width of 3 ft, excluding sloped sides, has sloped sides, all slopes not to exceed 1:12, and textured or painted yellow Notes: Ramps Site Access, Path of Travel, Entrances Site Access, Path of Travel, Entrances Site Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed Ponding of water? Disembarking area at accessible entrance Path does not require the use of stairs Path does not require the use of wheelchair ramp Path does not require the use of wheelchair ramp Path does not require the use of wheelchair ramp Path does not require the use of wheelchair ramp	YES	Comments
Notes: Parking Total Spaces 25 Description Accessible game located discest to accessible entrance Where spaces cannot be located within 200 for accessible entrance, drop-off area is provided within 100 ft Minimum width of 13 ft includes 8 ft space plus 5 ft accessible entrance, drop-off area is provided within 100 ft Minimum width of 13 ft includes 8 ft space plus 5 ft accessible entrance, drop-off area is provided within 100 ft Minimum of 1 van space for every accessible space, es wide + 8° asile. Sign with international symbol of accessibility at each space Sign 5° 8° to top of sign Surface evenly paved or hard-packed (no cracks) Surface solope less than 1:20, 5% Curbcut to pathway from parking lot at each space if sidewalk (curb) is present. Curbcut is a minimum width of 3 ft, excluding sloped sides, has sloped sides, all slopes not to exceed 1:12, and textured or painted yellow Notes: Ramps Site Access, Path of Travel, Entrances Beackess Description Accessible gath of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed Poonting of water? Disembarking area at accessible entrance Path of Travel Description Path does not require the use of stairs Spath sates, firm and slip resistant Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50). Continuous common surface, no changes in level greater than 5 inch Objects protuding more than 4" from the wall must be within 27" of the ground, or higher than 80"	YES Accessible Spc Lot Yes Ves N/A Yes N/A Yes N/A Yes N/A N/A Yes N/A N/A Yes N/A	Comments
Located adjacent to accessible paths Notes: Parking Total Spaces 25 Description Parking Amenities (Lalot, ST-street) Accessible packed closest to accessible entrance Where spaces cannot be located visitin 200 ft of accessible entrance, drop-off area is provided within 100 ft Minimum with of 13 ft includes 8 ft space plus 5 ft access alise Minimum of 1 van space for every accessible space, 8' wide + 8' alise. Sign with international symbol of accessibility at each space Sign 5's to top of sign Surface evenly paved or hard-packed (no cracks) Surface spece stath no 120, 5's Curbcut to pathway from parking tot at each space if sidewalk (curb) is present. Curbcut is a minimum width of 3 ft, excluding sloped sides, has sloped sides, all slopes not to exceed 1:12, and textured or painted yellow Notes: Ramps Site Access, Path of Travel, Entrances Site Access, Path of Travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed Ponding of water? Disembarking area at accessible entrance Path does not require the use of statirs Path does not require the use of wheelchair ramp Path is stable, firm and slip resistant Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50). Continuous common surface, no hard-packing in level greater than 5 inch Any objects protruding onto the pathway must be detected by a person with a visual disability using a cane	YES	Comments

Primary public entrances accessible to person using wheelchair, must be signed, gotten to independently, and not be the service entrance	No	
Level space extending 5 ft. from the door, interior and exterior of entrance doors	No	
Minimum 32" clear width opening (i.e. 36" door with standard hinge)	Yes	
At least 18" clear floor area on latch, pull side of door	Yes	
Door handle no higher than 48" and operable with a closed fist	Yes	Hieght is acceptable but cannot be operated with close fist
Vestibule is 4 ft plus the width of the door swinging into the space	Yes	
Entrance(s) on a level that makes elevators accessible	N/A	
Door mats less than ¾* thick are securely fastened	No	
Door mats more than ¼" thick are recessed	No	
Grates in path of travel have openings of %" maximum	N/A	
Signs at non-accessible entrance(s) indicate direction to accessible entrance	No	
Emergency egress – alarms with flashing lights and audible signals, sufficiently lighted	Yes	
Notes:		
A	IVEC.	
Stairs and Doors	YES	
<u>Doors</u>	1	Ic
Description	W	Comments
Minimum 32" clear opening	Yes	
At least 18" clear floor space on pull side of door	Yes	
Threshold maximum %" high, beveled on both sides Hardware operable with a closed fist (no conventional door knobs or thumb latch devices)	Yes No	
Hardware minimum 36", maximum 48" above the floor	Yes	
Clear, level floor space extends out 5 ft from both sides of the door Door adjacent to revolving door is accessible and unlocked	No N/A	
Doors opening into hazardous area have hardware that is knurled or roughened	N/A	
Doors opening into nazardous area nave naroware that is knuned or roughened Notes:	37/4	
Hotes.		
Restrooms	YES	
Description	11.5	Comments
Description 5 ft turning space measured 12" from the floor	Yes	Commence
At least one Sink		
Description		Comments
Clear floor space of 30" by 48" to allow a forward approach	Yes	Comments
Mounted without pedestal or legs, height 34" to top of rim	No	33nches
Extends at least 22" from the wall	Yes	January
Open knee space a minimum 19" deep, 30" width, and 27" high	Yes	
Cover exposed pipes with insulation	Yes	
Faucets operable with closed fist (lever or spring activated handle)	Yes	
At least one Stall	1	
Description		Comments
Accessible to person using wheelchair at 60" wideby 72" deep	Yes	Comments
Stall door is 36" wide	No	35in wide
Stall door swings out	Yes	33iii wide
Stall door is self closing	No	
Stall door has a pull latch	No	
Lock on stall door is operable with a closed fist, and 32" above the floor	No	
Coat hook is 54" high	N/A	
Toilet	1.4	
Description		Comments
18" from center to nearest side wall	Yes	
42" minimum clear space from center to farthest wall or fixture	Yes	
Top of seat 17"-19" above the floor	No	33 in high
Grab Bars	1	
Description		Comments
On back and side wall closest to toilet	Yes	
1½" diameter	Yes	
1½" clearance to wall	Yes	
Located 30° above and parallel to the floor	Yes	
Acid-etched or roughened surface	Yes	
42" long	Yes	
<u>Fixtures</u>		
Description		Comments
1%" diameter	Yes	
1½" clearance to wall	Yes	
Located 30" above and parallel to the floor	Yes	
Notes:		
Floors, Drinking Fountains, Telephones	YES	
Floors		
Description		Comments
Non-slip surface	No	
Carpeting is high-density, low pile, non-absorbent, stretched taut, securely anchored	N/A	
Corridor width minimum is 3 ft	Yes	
Objects (signs, ceiling lights, fixtures) can only protrude 4" into the path of travel from a height of 27" to 80" above the floor	N/A	
<u>Drinking Fountains</u>		
Description		Comments
Spouts no higher than 36" from floor to outlet	Yes	
Hand operated push button or level controls	Yes	
Spouts located near front with stream of water as parallel to front as possible	Yes	
If recessed, recess a minimum 30" width, and no deeper than depth of fountain	Yes	
If no clear knee space underneath, clear floor space 30" x 48" to allow parallel approach	Yes	
Telephones		
Description		Comments
Highest operating part a maximum 54" above the floor	No	
Access within 12" of phone, 30" high by 30" wide	No	
Adjustable volume control on headset so identified	No	
Adjustable volume control on headset so identified Notes:	No	
	No	
Notes:		
Notes: Signs, Signals, and Switches	No YES	
Notes: Signs, Signals, and Switches Switches, Controls and Signs		
Notes: Signs, Signals, and Switches		Comments

Switches and controls for light, heat, ventilation, windows, fire alarms, thermostats, etc, must be a minimum of 36" and a maximum of 48" above the floor for a forward reach, a maximum of 54" for a side reach	No	50 inches high	
Electrical outlets centered no lower than 18" above the floor	N/A		
Warning signals must be visual as well as audible	Yes		
Signs			
Description		Comments	
Mounting height must be 60" to centerline of the sign	Yes		
Within 18" of door jamb or recessed	Yes		
Letters and numbers a t least 1%" high	Yes		
Letters and numbers raised .03"	Yes		
Letters and numbers contrast with the background color	Yes		
Notes:			
Swimming Pool/ Lake beach	N/A		
	N/A		
	N/A		
	N/A		

Facility Name: Newton Centre Common/Green		
Size (Ac): 2.0 acres		
Address: Centre Street, Newton Centre, (divided by Langley Road)		
Ward: 6		
General Facility Notes: Accessible pathways and sidewalk; new benches (Total of 7) with companio	n pads (To	al of 3) added along pathways in 2019.
Cito Eurnichings	YES	
Site Furnishings Description	Yes	Comments
Tables & Benches	1100	Commence
Number of Benches	yes	13 total - 12 benches with backs and arm rests, 1 dumor bench w/ gray slats and back, no arm rest
Number of Tables	yes	2 picnic tables
Located adjacent to accessible paths	yes	
Back and Arm Rests	yes	all have backs and arm rests
<u>Grills</u>		
Located adjacent to accessible paths	no	
<u>Trash Cans</u>		
Located adjacent to accessible paths	yes	2 big belly trash bins and 2 big belly recycling units
Picnic Shelters	1	2 picnic tables
Located adjacent to accessible paths	yes	
Notes: There is a wwl, wwll and korean war monumnet w/ flagpole and kiosk. There is an irrigated (city water) award winnin, There are 3 bike racks along with park lighting. There are 21 metered parking spaces abutting this location. There are no han		
There are 3 bike racks along with park righting. There are 21 metered parking spaces abutting this location. There are no main	ilcap accessit	ne parking spaces.
Trails & Paths	YES	
Description	1.20	Comments
Surface (A=Asphalt, C=Concrete, SD= stone dust, NS= naturally surfaced, B=Boardwalk, BR=Bridge)	yes	A, C
Dimensions (width)	yes	varies - minimum is 7 feet
Rails	No	
Signage for visually impaired	No	
Benches	yes	12 benches with backs and arm rests
Notes:		
	1	
Plav Areas	N/A	
Game Areas	N/A	
Boat Docks	N/A	
Fishing Facilities	N/A	
Community Gardens	N/A	
Parking	N/A	
Ramps Site Assess Bath of Travel Entrances	N/A YES	
Site Access, Path of Travel, Entrances	ILO	
Description	1	Comments
Accessible path of travel from passenger disembarking area and parking area to accessible entrance	yes	multiple access points
Surface evenly paved or hard-packed	yes	
Ponding of water?	no	
Disembarking area at accessible entrance	yes	
Path of Travel		-
Description		Comments
Path does not require the use of stairs	yes	
Path does not require the use of wheelchair ramp	yes	
Path is stable, firm and slip resistant	yes	
Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50).	yes	
Continuous common surface, no changes in level greater than ½ inch	yes	
Notes:		
	1	
Stairs and Doors	N/A	
Restrooms	N/A	
Floors, Drinking Fountains, Telephones	N/A	
Signs, Signals, and Switches	N/A	
Swimming Pool/ Lake beach	N/A	
Shower Rooms	N/A	
Picknicking	N/A	
Off Leash Dog Areas (OLA)	N/A	

Facility Name: Newton Centre Playground Size (Ac): 17.9 acres Address: 81 Tyler Terrace, Newton Centre (contiguous to Mason Rice School) General Facility Notes: Master plan for accessibility in 2006; Olmsted-designed historic park; steeply sloped bowl shaped park; accessible pathway network; large, universal play equipment area in center of park with accessible route; accessible parking on Bowen St. and in Mason-Rice parking lot; formerly Brewer Playground. YES Site Furnishings Comments Yes Tables & Benches Yes Number of Tables Yes Located adjacent to accessible paths Yes 9 benches and both tables 5 w/ back and arm and all others back only Back and Arm Rests Located adjacent to accessible paths N/A Trash Cans Yes Located adjacent to accessible paths icnic Shelters N/A Notes: YES Trails & Paths Comments Surface (A=Asphalt, C=Concrete, SD= stone dust, NS= naturally surfaced, B=Boardwalk, BR=Bridge) Yes Α Dimensions (width) Yes minimum 5' Rails N/A Signage for visually impaired No Yes 9 are accessible Notes: Play Areas YES Comments Facility Type (3-5 Yrs,5-12 Yrs) 2 - 5 yrs and 5 - 12 yrs Yes Same experience provided to all Access Routes Located adjacent to accessible paths Yes Enough space between equipment for wheelchair Yes Notes: Playground built in 2008 YES Game Areas Comments Facility Type (RF=Rectangular Fields, BF= Ballfields, BK=Basketball, TN=Tennis, BC=Bocce) BF, Bk and TN ccess Routes Located adjacent to accessible paths Yes Berm cuts onto courts Yes uipment Height Dimensions Spectator Seating Notes: **Boat Docks** Fishing Facilities N/A N/A Community Gardens Parking Yes Comments Parking Amenities (L=lot, ST=street) Yes ST no designated parking spot Accessible space located closest to accessible entrance No Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft $\,$ No Minimum width of 13 ft includes 8 ft space plus 5 ft access aisle No Minimum of 1 van space for every accessible space, 8^\prime wide + 8^\prime aisle. No Sign with international symbol of accessibility at each space No Sign 5'-8' to top of sign No Surface evenly paved or hard-packed (no cracks) No Surface slope less than 1:20, 5% No Curbcut to pathway from parking lot at each space if sidewalk (curb) is present . No Curbcut is a minimum width of 3 ft, excluding sloped sides, has sloped sides, all slopes not to exceed 1:12, and textured or painted yellow No Ramps Site Access, Path of Travel, Entrances Site Access Comments Accessible path of travel from passenger disembarking area and parking area to accessible entrance Yes Surface evenly paved or hard-packed Yes No Ponding of water? Disembarking area at accessible entrance Yes Path of Travel Comments Description Path does not require the use of stairs Yes Path does not require the use of wheelchair ramp Yes Path is stable, firm and slip resistant

Slope maximum 1:20 [5/8] and maximum cross pitch is 2% (1:50]. Yes Continuous common surface, no changes in level greater than ½ inch Any objects protruding onto the pathway must be detected by a person with a visual disability using a cane Yes Objects protruding more than 4" from the wall must be within 27" of the ground, or higher than 80" Yes Curb on the pathway must have curb cuts at drives,parking and drop-offs N/A Minimum 25 N/A		Comments
Any objects protruding onto the pathway must be detected by a person with a visual disability using a cane Ves Objects protruding more than 4" from the wall must be within 27" of the ground, or higher than 80" Ves Curb on the pathway must have curb cuts at drives, parking and drop-offs NA Intrances PESCription Primary public entrances accessible to person using wheelchair, must be signed, gotten to independently, and not be the service entrance No Level space extending 5 ft. from the door, interior and exterior of entrance doors No Minimum 32" clear width opening (i.e. 36" door with standard hinge) No At least 18" clear floor area on latch, pull side of door No Door handle no higher than 46" and operable with a closed fist No Vestibule is 4 if plus the width of the door swinging into the space Entrance(s) on a level that makes elevators accessible No Door mats less than ½" thick are securely fastened No Grates in path of travel have openings of ½" maximum No		Comments
Objects protruding more than 4" from the wall must be within 27" of the ground, or higher than 80" Ves Curb on the pathway must have curb cuts at drives,parking and drop-offs N/A N/A N/A N/A Primary public entrances accessible to person using wheelchair, must be signed, gotten to independently, and not be the service entrance No Level space extending 5 ft. from the door, interior and exterior of entrance doors No Minimum 32" clear width opening (i.e. 36" door with standard hinge) No At least 18" clear floor area on latch, pull side of door No Door handle no higher than 48" and openable with a closed fist No Entrance(s) on a level that makes elevators accessible No Door mats less than ½" thick are securely fastened No Door mats more than ½" thick are recessed No Grates in path of travel have opening in ½" maximum No		Comments
Curb on the pathway must have curb cuts at drives,parking and drop-offs **Potential Contraction** **Potential Contraction** **Point Primary public entrances accessible to person using wheelchair, must be signed, gotten to independently, and not be the service entrance **No Level space extending 5 ft. from the door, interior and exterior of entrance doors **No **Minimum 32" clear width opening (i.e. 36" door with standard hinge) **At least 18" clear floor area on latch, pull side of door **No **Door handle on higher than 48" and operable with a closed fist **No **Vestibule is 4 ft plus the width of the door swinging into the space **No **Door mats less than 3" thick are securely fastened **No **Door mats less than 3" thick are recessed **No **Grates in path of travel have openings of %" maximum **No **No **Grates in path of travel have openings of %" maximum **No		Comments
Intrances Pescription Primary public entrances accessible to person using wheelchair, must be signed, gotten to independently, and not be the service entrance No Level space extending 5 ft. from the door, interior and exterior of entrance doors No Minimum 32" clear width opening (i.e. 36" door with standard hinge) No At least 18" clear floor area on latch, pull side of door No Door handle no higher than 48" and operable with a closed fist No Vestibule is 4 ft plus the width of the door swinging into the space No Entrance(s) on a level that makes elevators accessible No Door mats less than ½" thick are securely fastened No Graftes in path of travel have openings of ½" maximum No		Comments
Intrances Pescription Primary public entrances accessible to person using wheelchair, must be signed, gotten to independently, and not be the service entrance No Level space extending 5 ft. from the door, interior and exterior of entrance doors No Minimum 32" clear width opening (i.e. 36" door with standard hinge) No At least 18" clear floor area on latch, pull side of door No Door handle no higher than 48" and operable with a closed fist No Vestibule is 4 ft plus the width of the door swinging into the space No Entrance(s) on a level that makes elevators accessible No Door mats less than ½" thick are securely fastened No Graftes in path of travel have openings of ½" maximum No		Comments
Description Primary public entrances accessible to person using wheelchair, must be signed, gotten to independently, and not be the service entrance No No Minimum 3.2" clear width opening (i.e. 36" door with standard hinge) No At least 18" clear floor area on latch, pull side of door Door handle no higher than 48" and operable with a closed fist No Uestibule is 4 flup tust he width of the door swinging into the space Entrance(s) on a level that makes elevators accessible No Door mats less than ½" thick are securely fratened No Door mats mone than ½" thick are recessed No Grates in path of travel have openings of ½" maximum No		Comments
Primary public entrances accessible to person using wheekhair, must be signed, gotten to independently, and not be the service entrance No Level space extending 5 ft. from the door, interior and exterior of entrance doors No Minimum 32" clear width opening (i.e. 36" door with standard hinge) No At least 18" clear floor area on later, pull side of door No Door handle no higher than 48" and operable with a closed fist No Vestibule is 4 ft plus the width of the door swinging into the space Entrance(s) on a level that makes elevators accessible No Door mats less than 3" thick are securely fastened No Door mats nore than 3" thick are recessed No Grates in path of travel have openings of 3" maximum No		
Level space extending 5 ft. from the door, interior and exterior of entrance doors Minimum 32" clear width opening (i.e. 36" door with standard hinge) At least 18" clear floor area on latch, pull side of door No Ooor handle no higher than 48" and operable with a closed fist No Vestibule is 4 ft plus the width of the door swinging into the space No Entrance(s) on a level that makes elevators accessible No Door mats less than 3" thick are securely fastened No Graftes in path of travel have openings of %" maximum No		
Minimum 32" dear width opening (i.e. 36" door with standard hinge) At least 18" dear floor area on latch, pull side of door No Door handle no higher than 48" and operable with a closed fist No Vestibule is 4 if plus the width of the door swinging into the space Intrance(s) on a level that makes elevators accessible No Door mats less than ½" thick are securely fastened No Door mats for than ½" thick are recessed No Grates in path of travel have openings of ½" maximum No		
At least 18" clear floor area on latch, pull side of door Door handle no higher than 48" and operable with a closed fist No Vestibule is 4 ft plus the width of the door swinging into the space No Entrance(s) on a level that makes elevators accessible No Door mats more than %" thick are recessed No Grates in path of travel have openings of %" maximum No		
Door handle no higher than 48" and operable with a closed fist Vestibule is 4 ft plus the width of the door swinging into the space No Entrance(s) on a level that makes elevators accessible No Door mats less than %" thick are securely fastened No Grates in path of travel have openings of %" maximum No		
Vestibule is 4 ft plus the width of the door swinging into the space No Entrance(s) on a level that makes elevators accessible No Door mats less than %" thick are securely fastened No Door mats nore than %" thick are recessed No Grates in path of travel have openings of %" maximum No		
Entrance(s) on a level that makes elevators accessible No Door mats less than ½" thick are securely fastened No Door mats more than ½" thick are recessed No Grates in path of travel have openings of ½" maximum No		
Door mats less than %" thick are securely fastened No Door mats more than %" thick are recessed No Grates in path of travel have openings of %" maximum No		
Door mats more than %" thick are recessed No Grates in path of travel have openings of %" maximum No	-	
Grates in path of travel have openings of ½" maximum No		
	_	
Signs at non-accessible entrance(s) indicate direction to accessible entrance		
NO NO		
Emergency egress – alarms with flashing lights and audible signals, sufficiently lighted No		
Notes: building is notaccessible at all		
Stairs and Doors YES		
tairs		
Description	10	Comments
Open risers No		
Nosings not projecting Yes		
Treads no less than 11" wide Yes		
Handrails on both sides Yes		
Handrails on both sides Yes Handrails 34"-38" above tread Yes		
Handrails 34"-38" above tread Yes Handrail extends a minimum of 1' beyond top and bottom riser (if no safety hazard and space permits) No		
Handgrip oval or round Yes Handgrip has a smooth surface Yes		
Handgrip diam. 1/1" - 1/1" Yes	_	
1½" clearance between wall and handrail Yes		
<u>10075</u>		
Description		Comments
Minimum 32" clear opening Yes		
At least 18" clear floor space on pull side of door No		
Closing speed minimum 3 seconds to within 3" of the latch No		
Maximum pressure 5 pounds interior doors No		
Threshold maximum "" high, beveled on both sides Yes		
Hardware operable with a closed fist (no conventional door knobs or thumb latch devices) No		
Hardware minimum 36", maximum 48" above the floor Yes		
Clear, level floor space extends out 5 ft from both sides of the door No		
Door adjacent to revolving door is accessible and unlocked N/A		
Doors opening into hazardous area have hardware that is knurled or roughened N/A		
Notes:		
Restrooms YES		
Description	[6	Comments
Description		Comments
Description		Comments
Description St turning space measured 12" from the floor No		
Description St turning space measured 12" from the floor No taleast one Sink		Comments Comments
Description No \$ ft turning space measured 12" from the floor No tt least one Sink The state of Sink Description Clear floor space of 30" by 48" to allow a forward approach No		
Description No \$ ft turning space measured 12" from the floor No *** It least one Sink **** ***Description Clear floor space of 30" by 48" to allow a forward approach No Mounted without pedestal or legs, height 34" to top of rim No		
Description No 5 ft turning space measured 12" from the floor No tt tests one Sink No Clear floor space of 30" by 48" to allow a forward approach No Mounted without pedestal or legs, height 34" to top of rim No Extends at least 22" from the wall No		
Description No 5 ft turning space measured 12" from the floor No Value test one Sink Description Clear floor space of 30" by 48" to allow a forward approach No Mounted without pedestal or legs, height 34" to top of rim No Extends a least 22" from the wall No Open knees space a minimum 19" deep, 30" width, and 27" high No		
Description No 5 ft turning space measured 12" from the floor No 4 least one Sink Vescription Clear floor space of 30" by 48" to allow a forward approach No Mounted without pedestal or legs, height 34" to top of rim No Extends at least 22" from the wall No Open knee space a minimum 19" deep, 30" width, and 27" high No Cover exposed pipes with insulation Yes		
Description No 5 ft turning space measured 12" from the floor No k tests one Sink Description Clear floor space of 30" by 48" to allow a forward approach No Mounted without pedestal or legs, height 34" to top of rim No Extends at least 22" from the wall No Open knees pace an inimum 19" deep, 30" width, and 27" high No Cover exposed pipes with insulation Yes		
Description 5 ft turning space measured 12" from the floor No 1 turning space measured 12" from the floor No 1 turning space measured 12" from the floor 1 turning space of 30" by 48" to allow a forward approach No 1 turning space of 30" by 48" to allow a forward approach No 1 turning space of 30" by 48" to allow a forward approach No 2 turning space of 30" by 48" to allow a forward approach No 2 turning space of 30" by 48" to allow a forward approach No 2 turning space of 30" by 48" to allow a forward approach No 2 turning space of 30" by 48" to allow a forward approach No 3 turning space of 30" by 48" to allow a forward approach No 4 turning space of 30" by 48" to allow a forward approach No 5 turning space of 30" by 48" to allow a forward approach No 5 turning space of 30" by 48" to allow a forward approach No 5 turning space of 30" by 48" to allow a forward approach No 5 turning space of 30" by 48" to allow a forward approach No 5 turning space of 30" by 48" to allow a forward approach No 5 turning space of 30" by 48" to allow a forward approach No 5 turning space of 30" by 48" to allow a forward approach No 6 turning space of 30" by 48" to allow a forward approach No 6 turning space of 30" by 48" to allow a forward approach No 6 turning space of 30" by 48" to allow a forward approach No 6 turning space of 30" by 48" to allow a forward approach No 6 turning space of 30" by 48" to allow a forward approach No 6 turning space of 30" by 48" to allow a forward approach No 6 turning space of 30" by 48" to allow a forward approach No 6 turning space of 30" by 48" to allow a forward approach No 6 turning space of 30" by 48" to allow a forward approach No 6 turning space of 30" by 48" to allow a forward approach No 6 turning space of 30" by 48" to allow a forward approach No 6 turning space of 30" by 48" turning space of	C	Comments
Description S it turning space measured 12" from the floor No No No No Description Clear floor space of 30" by 48" to allow a forward approach No Mounted without pedestal or legs, height 34" to top of rim Extends a least 22" from the wall No Open knee space a minimum 19" deep, 30" width, and 27" high No Cover exposed pipes with insulation Faucets operable with closed fist (lever or spring activated handle) No tt east one \$1581	C	
No No No No No No No No	C	Comments
Description 5 ft turning space measured 12" from the floor 5 ft turning space measured 12" from the floor 1		Comments
Description S it turning space measured 12" from the floor No No Clear floor space of 30" by 48" to allow a forward approach No Mounted without pedestal or legs, height 34" to top of rim No Extends at least 22" from the wall No Open knee space a minimum 19" deep, 30" width, and 27" high No Cover exposed pipes with insulation Faucets operable with closed fist (lever or spring activated handle) No Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 35" wide No Stall door is 35" wide No Stall door swings out		Comments
Pescription No No No No No No No		Comments
Description 5 ft turning space measured 12" from the floor 5 ft turning space measured 12" from the floor 10 clear floor space of 30" by 48" to allow a forward approach 10 clear floor space of 30" by 48" to allow a forward approach 10 clear floor space of 30" by 48" to allow a forward approach 10 clear floor space of 30" by 48" to allow a forward approach 10 clear floor space of 30" by 48" to allow a forward approach 10 clear floor space of 30" by 48" to allow a forward approach 10 clear floor space of 30" by 48" to allow a forward approach 10 clear floor space a minimum 15" deep, 20" width, and 27" high 10 cover exposed pipes with insulation 10 cover exposed pipes with closed fist (lever or spring activated handle) 10 cover exposed pipes with closed fist (lever or spring activated handle) 11 clear tone Stall 12 clear floor space a minimum 15" deep, 20" wideby 72" deep 12 clear floor in 36" wide 13 clear floor in 36" wide 14 clear floor in 36" wide 15 clear floor in 36" wide 16 clear floor in 36" wide 17 clear floor in 36" wide 17 clear floor in 36" wide 18 clear floor in 36" wide 18 clear floor in 36" wide 19 clear floor in 36" wide 19 clear floor in 36" wide 10 clear floor in 36" wide		Comments
Description 5 it turning space measured 12" from the floor 5 it turning space measured 12" from the floor Clear floor space of 30" by 48" to allow a forward approach No Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucts operative with closed fist (lever or spring activated handle) Ves Statil door is 36" wide Accessible to person using wheelchair at 60" wideby 72" deep Statil door is 36" wide Stall door is 36" wide Stall door is 96" closing No Lock on stall door is operable with a closed fist, and 32" above the floor No Lock on stall door is operable with a closed fist, and 32" above the floor		Comments
Pescription No No No No No No No		Comments
Pescription No S ft turning space measured 12" from the floor No No S ft turning space measured 12" from the floor No Pescription Pescription No Pescription Pe		Comments
Description 5 ft turning space measured 12" from the floor 5 ft turning space measured 12" from the floor Clear floor space of 30" by 48" to allow a forward approach Clear floor space of 30" by 48" to allow a forward approach No Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall Open knee space a minimum 15" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucets operable with closed fist (lever or spring activated handle) No Att least one Stall Description Accessible to person using wheelchair at 60" wideby 72" deep Stall door is 36" wide No Stall door is 36" wide Stall door is self closing Stall door is self closing Stall door is self closing No Lock on stall door is operable with a closed fist, and 32" above the floor Coat hook is 54" high No No Coat hook is 54" high No No Coat hook is 54" high No No No No No No No No No N		Comments
No No No No No No No No		Comments
No No No No No No No No		Comments
Description No 5 ft turning space measured 12" from the floor No Let least one Sink Description Clear floor space of 30" by 48" to allow a forward approach No Mounted without pedestal or legs, height 34" to top of rim No Extends at least 22" from the wall No Open knee space a minimum 15" deep, 30" width, and 27" high No Cover exposed pipes with insulation Yes Faucets operable with closed fits (lever or spring activated handle) No No not stall No Accessible to person using wheelchair at 60" wideby 72" deep No Stall door is 36" wide No Stall door is 36" wide No Stall door is self closing No Stall door is self closing No Stall door is perable with a closed fist, and 32" above the floor No Cost hook is 54" high No Oct to hook is 54" high No Description No 1.8" from center to nearest side wall No 42" minimum deen space from center to farthest wall or fisture No Top of seat 17"-19" above the floor		Comments
No No No No No No No No		Comments Comments Comments
No No No No No No No No		Comments
Description No 5 ft turning space measured 12" from the floor No Let least one Sink Description Clear floor space of 30" by 48" to allow a forward approach No Mounted without pedestal or legs, height 34" to top of rim No Extends at least 22" from the wall No Open knee space a minimum 15" deep, 30" width, and 27" high No Cover exposed pipes with insulation Yes Faucets operable with closed fits (flever or spring activated handle) No No tast one Stall No Description No Stall door is 36" wide No Stall door is 36" wide No Stall door say fell closing No Stall door say fell closing No Stall door is all door is openable with a closed fist, and 32" above the floor No Ocat hook is 54" high No Description Inform center to nearest side wall No 42" minimum clear space from center to farthest wall or fixture No Top of seat 17"-19" above the floor Yes From enter to mearest side wall No A" minimu		Comments Comments Comments
No No No No No No No No		Comments Comments Comments
No No No No No No No No		Comments Comments Comments
No St turning space measured 12" from the floor No No St turning space measured 12" from the floor No No St turning space measured 12" from the floor No No St turning space of 30" by 48" to allow a forward approach No No No St teends at least 22" from the wall No No St teends at least 22" from the wall No No No No No No No		Comments Comments Comments
No No No No No No No No		Comments Comments Comments
No No No No No No No No		Comments Comments Comments
Description No 5 ft turning space measured 12" from the floor No Let least one SIME Postription Clear floor space of 30" by 48" to allow a forward approach No Mounted without pedestal or legs, height 34" to top of rim No Extends at least 22" from the wall No Open knee space a minimum 19" deep, 30" width, and 27" high No Cover exposed pipes with insulation Yes Faucets operable with closed fist (lever or spring activated handle) No Vescription No Cescription or No Stall door is 36" wide No Stall door sive get deep side with a closed fist, and 32" above the floor No Stall door is a pull latch No Lock on stall door is openable with a closed fist, and 32" above the floor No Stall door is a pull latch No Lock on stall door is proprible with a closed fist, and 32" above the floor No Coat hook is 54" high No Stall door is a pull latch No Or pot seat 17"-19" above the floor No Pescription No 18" from cente		Comments Comments Comments
No No No No No No No No		Comments Comments Comments
No No No No No No No No		Comments Comments Comments
No No No No No No No No		Comments Comments Comments
No No No No No No No No		Comments Comments Comments
Description No It teats are Sink No It teats are Sink No It teats are Sink No Clear floor space of 30" by 48" to allow a forward approach No Mounted without pedietat or legs, height 34" to op of rim No Extends at least 22" from the wall No Open knee space a minimum 19" deep, 30" width, and 27" high No Cover exposed pipss with insulation Yes Faucets operable with closed fist (lever or spring activated handle) No It teats are Siall No Excerption No Accessible to person using wheelchair at 60" wideby 72" deep No Accessible to person using wheelchair at 60" wideby 72" deep No Stall door is 36" wide No Stall door is 36" wide No Stall door is aprile with a closed fist, and 32" above the floor No Coat hook is 34" high No Octa hook is 34" high No Exerciption No Accessible wall No 42" minimum clear space from center to farthest wall or fixture No Poscrip		Comments Comments Comments
Pescription In time, space measured 12" from the floor In the set one Sink Vescription Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucts operable with closed fist (lever or spring activated handle) Vescription Accessible to person using wheelchair at 60" wideby 72" deep Accessible to person using wheelchair at 60" wideby 72" deep Astall door is 36" wide Stall door is 36" wide Stall door is 48 a pull latch Lock on stall door sha a pull latch Lock on stall door sha a pull latch Lock on stall door sha a pull latch Lock on stall door is operable with a closed fist, and 32" above the floor Coat thook is 54" high No Coat thook is 54" high 18" from center to nearest side wall 18" from center to nearest side wall of fisture Top of seat 17" 19" above the floor 10" diameter No Acid-ettched or roughened surface A2" long No Acid-ettched or roughened surface A2" long 10" diameter Lock cases 30" above and parallel to the floor No Acid-ettched or roughened surface A2" long 10" diameter Lock cases 30" above and parallel to the floor No Acid-ettched or roughened surface A2" long 10" diameter Lock cases 30" above and parallel to the floor No Lock deed 30" above and parallel to the floor No Lock deed 30" above and parallel to the floor No Lock deed 30" above and parallel to the floor No Lock deed 30" above and parallel to the floor No Lock deed 30" above and parallel to the floor		Comments Comments Comments
Pescription In time, space measured 12" from the floor In the set one Sink Vescription Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucts operable with closed fist (lever or spring activated handle) Vescription Accessible to person using wheelchair at 60" wideby 72" deep Accessible to person using wheelchair at 60" wideby 72" deep Astall door is 36" wide Stall door is 36" wide Stall door is 48 a pull latch Lock on stall door sha a pull latch Lock on stall door sha a pull latch Lock on stall door sha a pull latch Lock on stall door is operable with a closed fist, and 32" above the floor Coat thook is 54" high No Coat thook is 54" high 18" from center to nearest side wall 18" from center to nearest side wall of fisture Top of seat 17" 19" above the floor 10" diameter No Acid-ettched or roughened surface A2" long No Acid-ettched or roughened surface A2" long 10" diameter Lock cases 30" above and parallel to the floor No Acid-ettched or roughened surface A2" long 10" diameter Lock cases 30" above and parallel to the floor No Acid-ettched or roughened surface A2" long 10" diameter Lock cases 30" above and parallel to the floor No Lock deed 30" above and parallel to the floor No Lock deed 30" above and parallel to the floor No Lock deed 30" above and parallel to the floor No Lock deed 30" above and parallel to the floor No Lock deed 30" above and parallel to the floor		Comments Comments Comments
Pescription Sit turning space measured 12" from the floor Kt least one Sink Pescription Clear floor space of 90" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim No Statends at least 22" from the wall Open kines space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Yes Faucets operable with closed fist (lever or spring activated handle) **Pescription **Accessible to person using wheelchair at 60" wideby 72" deep **Accessible to person using wheelchair at 60" wideby 72" deep **Stall door is 30" side of using the space of usin		Comments Comments Comments
Pescription In time, space measured 12" from the floor In the set one Sink Vescription Clear floor space of 30" by 48" to allow a forward approach Mounted without pedestal or legs, height 34" to top of rim Extends at least 22" from the wall Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Open knee space a minimum 19" deep, 30" width, and 27" high Cover exposed pipes with insulation Faucts operable with closed fist (lever or spring activated handle) Vescription Accessible to person using wheelchair at 60" wideby 72" deep Accessible to person using wheelchair at 60" wideby 72" deep Astall door is 36" wide Stall door is 36" wide Stall door is 48 a pull latch Lock on stall door sha a pull latch Lock on stall door sha a pull latch Lock on stall door sha a pull latch Lock on stall door is operable with a closed fist, and 32" above the floor Coat thook is 54" high No Coat thook is 54" high 18" from center to nearest side wall 18" from center to nearest side wall of fisture Top of seat 17" 19" above the floor 10" diameter No Acid-ettched or roughened surface A2" long No Acid-ettched or roughened surface A2" long 10" diameter Lock cases 30" above and parallel to the floor No Acid-ettched or roughened surface A2" long 10" diameter Lock cases 30" above and parallel to the floor No Acid-ettched or roughened surface A2" long 10" diameter Lock cases 30" above and parallel to the floor No Lock deed 30" above and parallel to the floor No Lock deed 30" above and parallel to the floor No Lock deed 30" above and parallel to the floor No Lock deed 30" above and parallel to the floor No Lock deed 30" above and parallel to the floor		Comments Comments Comments
Peccipition No No No No No No No		Comments Comments Comments

Carpeting is high-density, low pile, non-absorbent, stretched taut, securely anchored	Yes		
Corridor width minimum is 3 ft	Yes		
Objects (signs, ceiling lights, fixtures) can only protrude 4" into the path of travel from a height of 27" to 80" above the floor	No		
<u>Drinking Fountains</u>			
Description		Comments	
Spouts no higher than 36" from floor to outlet	N/A		
Hand operated push button or level controls	N/A		
Spouts located near front with stream of water as parallel to front as possible	N/A		
If recessed, recess a minimum 30" width, and no deeper than depth of fountain	N/A		
If no clear knee space underneath, clear floor space 30" x 48" to allow parallel approach	N/A		
Telephones		•	
Description		Comments	
Highest operating part a maximum 54" above the floor	N/A		
Access within 12" of phone, 30" high by 30" wide	N/A		
Adjustable volume control on headset so identified	N/A		
Notes:	,		
Signs, Signals, and Switches	YES		
Switches, Controls and Signs	ILS		
	1	Ic	
Description Switches and controls for light, heat, ventilation, windows, fire alarms, thermostats, etc, must be a minimum of 36" and a maximum of 48" above the floor for a forward		Comments	
reach, a maximum of 54" for a side reach	No		
Electrical outlets centered no lower than 18" above the floor	Yes		
Warning signals must be visual as well as audible	No		
Signs		•	
Description		Comments	
Mounting height must be 60° to centerline of the sign	Yes		
Within 18" of door jamb or recessed	Yes		
Letters and numbers a t least 1%" high	Yes		
Letters and numbers raised .03"	Yes		
Letters and numbers contrast with the background color	Yes		
Notes:			
Swimming Pool/ Lake beach	N/A		
Shower Rooms	N/A		
	N/A		
Picknicking			
Off Leash Dog Areas (OLA)	YES	In .	
Description	l	Comments	
<u>Access Routes</u>			
Located adjacent to accessible paths	Yes		
Area accesible	No		
Notes:			

Facility Name: Newton Highlands Playground Size (Ac): 12.6 acres Address: Winchester St., Newton Highlands General Facility Notes: Large park renovated in 2018/2019; fully accessible; includes accessible trail and path network throughout and into the wooded section of the park; accessible parking lot. YES Site Furnishings Comments Yes Tables & Benches YES 19 Benches Number of Tables YES 3 Tables; one is ADA compliant Located adjacent to accessible paths YES All benches and tables are along an accessible path Back and Arm Rests All benches have back and arm rests Located adjacent to accessible paths YES Notes: YES Trails & Paths Comments Surface (A=Asphalt, C=Concrete, SD= stone dust, NS= naturally surfaced, B=Boardwalk, BR=Bridge) YES A; SD Dimensions (width) 6 feet minimum NO Rails Signage for visually impaired NO Notes: YES Play Areas Facility Type (3-5 Yrs,5-12 Yrs) YES 3-5 Yrs; 5-12 Yrs YES Same experience provided to all Located adjacent to accessible paths YES Enough space between equipment for wheelchair YES Notes: YES Game Areas Comments Facility Type (RF=Rectangular Fields, BF= Ballfields, BK=Basketball, TN=Tennis, BC=Bocce) YES 1 RF; 1 BF; 1 BK; 2 TN Access Routes Located adjacent to accessible paths YES Berm cuts onto courts YES Equipment YES accessible spectator seating at all amenities Spectator Seating Notes: N/A N/A Boat Docks Fishing Facilities N/A YES **Community Gardens** Required Accessible Spaces Total Spaces 2 Space Comments Parking Amenities (L=lot, ST=street) YES Accessible space located closest to accessible entrance YES Minimum width of 13 ft includes 8 ft space plus 5 ft access aisle YES Minimum of 1 van space for every accessible space, 8' wide + 8' aisle. YES Sign with international symbol of accessibility at each space YES Surface evenly paved or hard-packed (no cracks) YES Surface slope less than 1:20, 5% YES Curbcut to pathway from parking lot at each space if sidewalk (curb) is present . YES one curb cut for both parking spaces Curbcut is a minimum width of 3 ft, excluding sloped sides, has sloped sides, all slopes not to exceed 1:12, and textured or painted yellow YES Notes: N/A YES Ramps Site Access, Path of Travel, Entrances Comments Description YES Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed YES Ponding of water? NO Disembarking area at accessible entrance YES Path of Travel Comments Description Path does not require the use of stairs NO Winchester street entrance can be accessed by stairs or sloped path Path does not requires the use of wheelchair ramp YES YES Path is stable, firm and slip resistant Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50). YES Continuous common surface, no changes in level greater than $\mbox{\ensuremath{\upredset}{M}}$ inch YES Any objects protruding onto the pathway that may not be detected by a person with a visual disability using a cane NO Objects protruding more than 4" from the wall must be within 27" of the ground, or higher than 80" NO Notes:

Stairs and Doors	YES	YES	
Salis			
Description		Comments	
Open risers	NO	Concrete stairs	
Nosings not projecting	YES		
Treads no less than 11" wide	YES		
Handrails on both sides	YES		
Handrails 34"-38" above tread	YES		
Handrail extends a minimum of 1' beyond top and bottom riser (if no safety hazard and space permits)	YES		
Handgrip oval or round	YES	Round stainless steel tube	
Handgrip has a smooth surface	YES		
Notes:			
Restrooms	N/A		
Floors, Drinking Fountains, Telephones	N/A		
Signs, Signals, and Switches	N/A		
Swimming Pool/ Lake beach	N/A	_	
Shower Rooms	N/A		
Picknicking	N/A		

Facility Name: Newton South High School Winkler Stadium				
Size (Ac): 7.0 acres				
Address: 140 Brandeis Road, Newton Centre (contiguous to Oak Hill Middle School playfields)				
Ward: 8				
General Facility Notes: Accessible pathways to ballfields, football field, fieldhouse and track; Li	ift to bleachers;	facility opened fall 2009.		
Site Furnishings	YES			
Description	Yes	Comments		
Tables & Benches	YES	Spectator Stands		
Number of Benches Number of Tables	YES No	Spectator Stands		
Located adjacent to accessible paths	YES			
Back and Arm Rests	No			
<u>Grills</u>		1		
Located adjacent to accessible paths Trash Cans	No			
Located adjacent to accessible paths	YES			
<u>Picnic Shelters</u>				
Located adjacent to accessible paths	No			
Notes:				
Trails & Paths	YES			
Description		Comments		
Surface (A=Asphalt, C=Concrete, SD= stone dust, NS= naturally surfaced, B=Boardwalk, BR=Bridge)	YES	A		
Dimensions (width)	No.	8FT		
Rails Signage for visually impaired	No No			
Notes:				
Play Areas	N/A			
Game Areas	YES			
Description Facility Type (RF=Rectangular Fields, BF= Ballfields, BK=Basketball, TN=Tennis, BC=Bocce)		Comments BF RF ,Shot Put ,Track		
Access Routes		DI NI ,SIULPUL, ITOLA		
Located adjacent to accessible paths	No			
Berm cuts onto courts	NA			
<u>Equipment</u>	V	Chading and should be associated		
Spectator Seating Notes:	Yes	Stadium grand stand is accessible		
Boat Docks	N/A			
Fishing Facilities	N/A			
Community Gardens	N/A			
Parking	YES			
<u>Total Spaces</u> 151-200	Accessible S 6 Space	<u>ooces</u>		
Description Description	о зрасс	Comments		
Parking Amenities (L=lot, ST=street)	YES	L		
Accessible space located closest to accessible entrance	YES			
Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft Minimum width of 13 ft includes 8 ft space plus 5 ft access aisle	YES YES			
Minimum of 1 van space for every accessible space, 8' wide + 8' aisle.	YES			
Sign with international symbol of accessibility at each space	YES			
Sign 5'-8' to top of sign	YES			
Surface evenly paved or hard-packed (no cracks) Surface slope less than 1:20,5%	YES			
Curbcut to pathway from parking lot at each space if sidewalk (curb) is present .	YES			
Curbcut is a minimum width of 3 ft, excluding sloped sides, has sloped sides, all slopes not to exceed 1:12, and textured or painted yellow	YES			
Ramps Site Access, Path of Travel, Entrances	N/A YES			
Site Access, Patri Or Traver, Entrances	1123			
Description		Comments		
Accessible path of travel from passenger disembarking area and parking area to accessible entrance	YES			
Surface evenly paved or hard-packed Ponding of water?	YES No			
Disembarking area at accessible entrance	YES			
Path of Travel				
Description		Comments		
Path does not require the use of stairs Path does not require the use of stairs	YES			
Path does not require the use of wheelchair ramp Path is stable, firm and slip resistant	YES			
Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50).	YES			
Continuous common surface, no changes in level greater than ½ inch	YES			
Any objects protruding onto the pathway must be detected by a person with a visual disability using a cane Objects protruding more than 4" from the wall must be within 27" of the ground, or higher than 80"	No No			
Objects protruding more than 4" from the wall must be within 2.7" of the ground, or higher than 80" Curb on the pathway must have curb cuts at drives, parking and drop-offs	No YES			
Notes:		<u> </u>		
Stairs and Doors	N/A			

Floors, Drinking Fountains, Telephones	N/A
Signs, Signals, and Switches	N/A
Swimming Pool/ Lake beach	N/A
Shower Rooms	N/A
Picknicking	N/A
Off Leash Dog Areas (OLA)	N/A

Facility Name: Newton Veterans Memorial Park				
Size (Ac): 0.1 acres				
Address: Washington Street, opposite Newton History Museum, Newton Corner				
Ward: 1				
General Facility Notes: Small memorial park area alongside Washington St.; sidew	alk; benches and one short	pathway to memorial markers.		
Site Furnishings YES				
Description Tables & Benches	Yes	Comments		
Number of Benches	6			
Number of Tables	No			
Located adjacent to accessible paths	No			
Back and Arm Rests	2			
Grills	l No	T		
Located adjacent to accessible paths Trash Cans	No			
Located adjacent to accessible paths	No			
Picnic Shelters	<u> </u>			
Located adjacent to accessible paths	No			
Notes:				
Trails & Paths	YES			
Description	1	Comments		
Surface (A=Asphalt, C=Concrete, SD= stone dust, NS= naturally surfaced, B=Boardwalk, BR=Bridge)	A & C			
Dimensions (width)	4'			
Rails	No			
Signage for visually impaired Benches	No No			
Notes:	110			
Play Areas	N/A			
Game Areas	N/A			
Boat Docks Fishing Facilities	N/A N/A			
Community Gardens	N/A			
Parking	N/A			
Ramps	N/A			
Site Access, Path of Travel, Entrances	YES			
Site Access		Te		
Description Accessible path of travel from passenger disembarking area and parking area to accessible entrance	No	Comments		
Surface evenly paved or hard-packed	YES			
Ponding of water?	No			
Disembarking area at accessible entrance	No			
Path of Travel		I Community		
Description Path does not require the use of stairs	YES	Comments		
Path does not require the use of wheelchair ramp	YES			
Path is stable, firm and slip resistant	YES			
Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50).	YES			
Continuous common surface, no changes in level greater than ¼ inch	YES			
Any objects protruding onto the pathway must be detected by a person with a visual disability using a cane Objects protruding more than 4" from the wall must be within 27" of the ground, or higher than 80"	No No			
Curb on the pathway must have curb cuts at drives,parking and drop-offs	YES			
Notes:				
Stairs and Doors	N/A			
Restrooms	N/A			
Floors, Drinking Fountains, Telephones	N/A N/A			
Signs, Signals, and Switches Swimming Pool/ Lake beach	N/A N/A			
Shower Rooms	N/A			
Picknicking	N/A			
Off Leash Dog Areas (OLA)	N/A			

Facility Name: Richard J. Forte Memorial Park 'Allison Park'				
Size (Ac): 6.0 acres				
Address: 235 rear California Street				
Ward: 1				
General Facility Notes: Accessible route connecting exercise equipment stations, bocce courts, bb court & tot lot; accessible parking; accessible route abuts but does not connect to adjacent DCR Charles River Reservation multiuse path.				
Site Furnishings	YES			
Description Tables & Benches		Comments		
Number of Benches	Yes	8		
Number of Tables	No			
Located adjacent to accessible paths Back and Arm Rests	Yes Yes			
Grills				
Located adjacent to accessible paths Trash Cans	No			
Located adjacent to accessible paths	Yes			
Picnic Shelters				
Located adjacent to accessible paths Notes:	NA			
Trails & Paths	YES			
Description	123	Comments		
Surface (A=Asphalt, C=Concrete, SD= stone dust, NS= naturally surfaced, B=Boardwalk, BR=Bridge)	Yes	A, C, SD		
Dimensions (width) Rails	No			
Signage for visually impaired	No			
Benches Notes:	No			
Play Areas	YES			
Play AleaS Description	ILO	Comments		
Facility Type (3-5 Yrs,5-12 Yrs)	Yes	3-5 Yrs		
Same experience provided to all Access Routes	Yes			
Located adjacent to accessible paths	Yes			
Enough space between equipment for wheelchair Notes:	Yes			
NOC.				
Como Arons	YES			
Game Areas Description	TES	Comments		
Facility Type (RF=Rectangular Fields, BF= Ballfields, BK=Basketball, TN=Tennis, BC=Bocce)	Yes	RF, BF, BK, BC		
Access Routes Located adjacent to accessible paths	Yes			
Berm cuts onto courts	NA			
Spectator Seating	Yes			
Notes:				
Parking	YES			
<u>Total Spaces</u>	Accessible Space	aces		
42 Description	2 Space	Comments		
Parking Amenities (L=lot, ST=street)	Yes	Lot		
Accessible space located closest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft	Yes NA			
Minimum width of 13 ft includes 8 ft space plus 5 ft access aisle	Yes			
Minimum of 1 van space for every accessible space, 8' wide + 8' aisle. Sign with international symbol of accessibility at each space	No Yes			
Surface evenly paved or hard-packed (no cracks)	Yes			
Surface slope less than 1:20, 5%	Yes			
Curbout to pathway from parking lot at each space if sidewalk (curb) is present. Curbout is a minimum width of 3 ft, excluding sloped sides, has sloped sides, all slopes not to exceed 1:12, and textured or painted yellow	Yes Yes			
Notes:	•			
Ramps N/A				
Site Access, Path of Travel, Entrances Site Access	YES			
Description		Comments		
Accessible path of travel from passenger disembarking area and parking area to accessible entrance	Yes			
Surface evenly paved or hard-packed Ponding of water?	Yes No			
Disembarking area at accessible entrance	Yes			
Path of Travel Comments Description Comments				
Path does not require the use of stairs	Yes			
Path does not require the use of wheelchair ramp Path is stable, firm and slip resistant	Yes Yes			
Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50).	Yes			
Continuous common surface, no changes in level greater than ½ inch	Yes			
Notes:				

N/A	
YES	
123	Comments
Yes	
	Comments
Yes	Commence
	Comments
Yes	Comments
	34in
	5411
INO	
	Comments
Ves	Commence
1.00	
	Comments
Yes	Commence
Yes	
Yes	
	Comments
Yes	
Yes	
	33in
	,
INI/A	
IN/A	
	Yes Yes Yes No Yes Ves Yes No Yes Yes Yes Yes Yes No Yes

Facility Name: Richard J. McGrath Park Size (Ac): 10.1 acres Address: 1600 Washington Street, West Newton (behind Warren Apartments) General Facility Notes: No accessible route from parking lot to soccer fields, ballfields and one set of tennis courts (east side); tennis court and off-leash dog area (west side of the park) renovation completed in 2018 with accessible route from Washington St. and the parking lot; formerly Warren Jr. High Playground. YES Site Furnishings Comments Description Tables & Benches YES 3 wpa benches Number of Tables YES 1 picnic Located adjacent to accessible paths No Back and Arm Rests YES Located adjacent to accessible paths NA rash Cans Located adjacent to accessible paths No icnic Shelters No Notes: YES Trails & Paths Comments Surface (A=Asphalt, C=Concrete, SD= stone dust, NS= naturally surfaced, B=Boardwalk, BR=Bridge) A Leading to tennise courts on the west end of the park Dimensions (width) YES 5 ft Rails No Signage for visually impaired No No Notes: Play Areas YES **Game Areas** Description Comments Facility Type (RF=Rectangular Fields, BF= Ballfields, BK=Basketball, TN=Tennis, BC=Bocce) RF, 2 BF, 7 TN ccess Routes Located adjacent to accessible paths NO One of the two tennis court banks are along accessible path Berm cuts onto courts Yes Spectator Seating Yes Notes: N/A **Boat Docks** N/A N/A YES **Fishing Facilities Community Gardens** Parking Required Accessible Spaces **Total Spaces** 3 Space Description Comments Parking Amenities (L=lot, ST=street) YES L Accessible space located closest to accessible entrance YES Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft $\,$ NA Minimum width of 13 ft includes 8 ft space plus 5 ft access aisle Yes Minimum of 1 van space for every accessible space, 8' wide + 8' aisle. NO Sign with international symbol of accessibility at each space Yes Surface evenly paved or hard-packed (no cracks) Yes Surface slope less than 1:20, 5% Curbcut to pathway from parking lot at each space if sidewalk (curb) is present . NA Notes: N/A YES Ramps Site Access, Path of Travel, Entrances Comments Description Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed Yes Ponding of water? No Disembarking area at accessible entrance Yes Path of Travel Comments Path does not require the use of stairs Yes Path does not require the use of wheelchair ramp Yes Path is stable, firm and slip resistant Yes Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50). Yes Continuous common surface, no changes in level greater than $\mbox{\%}$ inch Yes Notes: Stairs and Doors N/A Restrooms Floors, Drinking Fountains, Telephones Signs, Signals, and Switches Swimming Pool/ Lake beach N/A N/A N/A Shower Rooms N/A

	N/A		
Off Leash Dog Areas (OLA)	YES	YES	
Description	Yes	Comments	
Access Routes			
Located adjacent to accessible paths	YES		
Area accesible	YES		
Notes:			

Facility Name: Richardson Playground		
Size (Ac): 5.4 acres		
Address: Allen Avenue, Waban		
Ward: 5		
General Facility Notes: Inaccessible little league field; no accessible paths; inaccessible tot lot near B	eethoven.	
Site Furnishings	YES	
Description		Comments
Tables & Benches		T
Number of Benches Number of Tables	yes	6 dumor benches 1 picnic table
Located adjacent to accessible paths	no	2 print total
Back and Arm Rests	yes	3 benches with backs and no arm rests, 3 benches with no backs and no arm rests
Grills		
Located adjacent to accessible paths Frash Cans	NA	
Located adjacent to accessible paths	no	1 big belly trash bin and 1 big belly recycling unit
Picnic Shelters		
Located adjacent to accessible paths	NA	
Notes: There is one bike rack, one spectator bleacher stand.		
Trails & Paths	YES	
Description	123	Comments
Surface (A=Asphalt, C=Concrete, SD= stone dust, NS= naturally surfaced, B=Boardwalk, BR=Bridge)	yes	A
Dimensions (width)	yes	Four foot wide non-continuous path.
Rails	No	
Signage for visually impaired	No	There are 3 dumor gray slat benches with backs, There are 3 dumor gray slat benches with NO
Benches	yes	backs
Notes:		
Dlay Areas	YES	
Play Areas Description	ILJ	Comments
Facility Type (3-5 Yrs,5-12 Yrs)	yes	Fibar safety surfacing.
Same experience provided to all	yes	
Access Routes		
Located adjacent to accessible paths	No	
Enough space between equipment for wheelchair Notes: Athletic areas are irrigated with city water.	yes	
notes. Admitted dieds die inflated with dity water.		
Game Areas	YES	
Description		Comments
Facility Type (RF=Rectangular Fields, BF= Ballfields, BK=Basketball, TN=Tennis, BC=Bocce)	yes	1 BF (irrigated enclosed little league field w/ scoreboard, practice area, backstop, benches, protective screens, and shed), 1 RF - irrigated
Access Routes		
Located adjacent to accessible paths	no	
Berm cuts onto courts	no	
Equipment		T
Spectator Seating Notes:	yes	
initia.		
Boat Docks	N/A	
Fishing Facilities	N/A	
Community Gardens Parking	N/A N/A	
Ramps	N/A	
Site Access. Path of Travel. Entrances	N/A	
Stairs and Doors	N/A	
Restrooms	N/A	
Floors, Drinking Fountains, Telephones	N/A	
Signs, Signals, and Switches Swimming Pool/ Lake beach	N/A N/A	
Shower Rooms	N/A	
Picknicking	N/A	
Off Leash Dog Areas (OLA)	N/A	

Facility Name: River Street Playground		
Size (Ac): .5 acres		
Address: River St., West Newton		
Ward: 3		
General Facility Notes: Inaccessible play equipment area with sand safety surface; accessible pathwa	y with ber	nch and companion pad from entrance.
	,	
	YES	Comments
Description Tables & Benches	Yes	Comments
Number of Benches	Yes	3
Number of Tables	No	
Located adjacent to accessible paths Back and Arm Rests	Yes Yes	1 bench back rest only
Back and Arm Kests	Yes	Dack rest only
Located adjacent to accessible paths	N/A	
rash Cans		
Located adjacent to accessible paths vicinc Shelters	Yes	
Located adjacent to accessible paths	N/A	
Notes:		
Trails & Paths	YES	
Description	ILJ	Comments
Surface (A=Asphalt, C=Concrete, SD= stone dust, NS= naturally surfaced, B=Boardwalk, BR=Bridge)	Yes	A
Dimensions (width)	Yes	Minimum 5 '
Rails Signage for visually impaired	N/A No	
Notes:	110	
Plav Areas	YES	
Description		Comments
Facility Type (3-5 Yrs,5-12 Yrs)	Yes	5 - 12 yrs
Same experience provided to all screes Routes	No	
Located adjacent to accessible paths	Yes	
Enough space between equipment for wheelchair	Yes	
Notes: Playground built in 1990		
	N/A	
	N/A	
	N/A N/A	
	N/A	
	N/A	
Site Access, Path of Travel, Entrances	YES	
Description		Comments
Accessible path of travel from passenger disembarking area and parking area to accessible entrance	Yes	
Surface evenly paved or hard-packed	Yes	
Ponding of water? Disembarking area at accessible entrance	No Yes	
rath of Travel		
Description		Comments
Path does not require the use of stairs Path does not require the use of wheelchair ramp	Yes Yes	
Path is stable, firm and slip resistant	Yes	
Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50).	Yes	
Continuous common surface, no changes in level greater than ¼ inch	Yes	
Any objects protruding onto the pathway must be detected by a person with a visual disability using a cane Objects protruding more than 4" from the wall must be within 27" of the ground, or higher than 80"	Yes N/A	
Curb on the pathway must have curb cuts at drives, parking and drop-offs	N/A	
Notes:		
	N/A	<u> </u>
	N/A N/A	
	N/A N/A	
Swimming Pool/ Lake beach	N/A	
Shower Rooms	N/A	
	N/A N/A	

Facility Name Calanta Calanta INA annuil II Diagram	d	
Facility Name: Solomon Schecter 'Memorial' Playgro Size (Ac): 3.9 acres	ouna	
Address: Stein Circle, Oak Hill		
Ward: 8		
General Facility Notes: No pathways to play equipment; formerly Memoria	l/Solomon Schecter School	
Site Furnishings	YES	
Description	Yes	Comments
Tables & Benches Number of Benches	YES	7 Benches
Number of Tables	yes	2 Tables
Located adjacent to accessible paths	YES	path from neighborhoods to benches
Back and Arm Rests		
<u>Grills</u>		
Located adjacent to accessible paths Trash Cans	No	
Located adjacent to accessible paths	No	
Picnic Shelters		1
Located adjacent to accessible paths	No	
Notes:		
Trails 9 Daths	YES	
Trails & Paths Description	1E3	Comments
Surface (A=Asphalt, C=Concrete, SD= stone dust, NS= naturally surfaced, B=Boardwalk, BR=Bridge)	YES	C
Dimensions (width)		5"
Rails	No	
Signage for visually impaired	No	
Benches Notes:	No	
Notes:		
Play Areas	YES	
Description		Comments
Facility Type (3-5 Yrs,5-12 Yrs)	YES	
Same experience provided to all	YES	
Access Routes Located adjacent to accessible paths	No	
Enough space between equipment for wheelchair	No	
Notes:		•
Como Aroas	YES	
Game Areas Description	1123	Comments
Facility Type (RF=Rectangular Fields, BF= Ballfields, BK=Basketball, TN=Tennis, BC=Bocce)		RF, BF. TN
<u>Access Routes</u>		
Located adjacent to accessible paths	No	
Berm cuts onto courts Equipment	No	
Spectator Seating	No	
Notes:		
Boat Docks	N/A	
Fishing Facilities	N/A N/A	
Community Gardens	N/A	
Parking	N/A	
Ramps	N/A	
Site Access, Path of Travel, Entrances Notes:	N/A	
Stairs and Doors	N/A	
Restrooms	N/A N/A	
Floors, Drinking Fountains, Telephones	N/A	
Signs, Signals, and Switches	N/A	
Swimming Pool/ Lake beach	N/A	
	N/A	
Shower Rooms Picknicking Off Leash Dog Areas (OLA)	N/A N/A N/A	

Г.,	
Facility Name: Spears Park	
Size (Ac): .25 acres	
Address: Corner of Washington Street and Walnut Park, Nonantum	
Ward: 1	
General Facility Notes: Open lawn on corner lot with no pathways; no amenities. Potent change.	ial location for pocket park or community garden. Level lawn with very little topographical
Site Furnishings	N/A
Trails & Paths	N/A
Play Areas	N/A
Game Areas	N/A
Boat Docks	N/A
Fishing Facilities	N/A
Community Gardens	N/A
Parking	N/A
Ramps	N/A
Site Access, Path of Travel, Entrances	N/A
Stairs and Doors	N/A
Restrooms	N/A
Floors, Drinking Fountains, Telephones	N/A
Signs, Signals, and Switches	N/A
Swimming Pool/ Lake beach	N/A
Shower Rooms	N/A
Picknicking	N/A
Off Leash Dog Areas (OLA)	N/A

Facility Name: Stearns Park Size (Ac): 3.4 acres Address: Jassett Street, Nonantum Ward: 1 General Facility Notes: 2006 master plan; phase 1: accessible tennis courts with ramp to adjacent housing project; accessible playground and half-court area on Jasset St constructed in 2011; accessible route from the street to play structure and courts; park is sloped and not all pathways are accessible. Site Furnishings Comments Description Yes Tables & Benches Yes 15 Number of Tables Yes Located adjacent to accessible paths Yes 8 benches and 2 tables Back and Arm Rests Located adjacent to accessible paths N/A Trash Cans Yes Located adjacent to accessible paths icnic Shelters N/A Notes: YES Trails & Paths Comments Surface (A=Asphalt, C=Concrete, SD= stone dust, NS= naturally surfaced, B=Boardwalk, BR=Bridge) Yes А Dimensions (width) Yes 5' Rails No Signage for visually impaired No Yes see above Notes: Play Areas YES Comments Facility Type (3-5 Yrs,5-12 Yrs) Yes 2 -5 yrs and 5 - 12 yrs Same experience provided to all Access Routes Located adjacent to accessible paths Yes Enough space between equipment for wheelchair Yes Notes: Playground built in 2011 YES Game Areas Comments Facility Type (RF=Rectangular Fields, BF= Ballfields, BK=Basketball, TN=Tennis, BC=Bocce) BF, BK and TN Access Routes Located adjacent to accessible paths Yes Berm cuts onto courts Yes quipment No Spectator Seating Notes: N/A **Boat Docks** N/A N/A YES **Fishing Facilities** Community Gardens Parking Comments Description Yes Parking Amenities (L=lot, ST=street) Accessible space located closest to accessible entrance N/A No designated accessible space Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft N/A Minimum width of 13 ft includes 8 ft space plus 5 ft access aisle N/A Minimum of 1 van space for every accessible space, 8' wide + 8' aisle. N/A Sign with international symbol of accessibility at each space N/A Sign 5'-8' to top of sign N/A Surface evenly paved or hard-packed (no cracks) Yes Surface slope less than 1:20, 5% Curbcut to pathway from parking lot at each space if sidewalk (curb) is present . N/A Curbcut is a minimum width of 3 ft, excluding sloped sides, has sloped sides, all slopes not to exceed 1:12, and textured or painted yellow N/A Notes: N/A YES Ramps Site Access, Path of Travel, Entrances Comments Description Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed Yes Ponding of water? No Disembarking area at accessible entrance No Path of Travel Comments Path does not require the use of stairs Yes Path does not require the use of wheelchair ramp No Path is stable, firm and slip resistant Yes Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50). In most areas Continuous common surface, no changes in level greater than $\mbox{\ensuremath{\upredskip}{\%}}$ inch Yes

Any objects protruding onto the pathway must be detected by a person with a visual disability using a cane	Yes	
Objects protruding more than 4" from the wall must be within 27" of the ground, or higher than 80"	N/A	
Curb on the pathway must have curb cuts at drives, parking and drop-offs	N/A	
Notes:		
Stairs and Doors	N/A	
Restrooms	N/A	
Floors, Drinking Fountains, Telephones	N/A	
Signs, Signals, and Switches	N/A	
Swimming Pool/ Lake beach	N/A	
Shower Rooms	N/A	
Picknicking	N/A	
Off Leash Dog Areas (OLA)	N/A	

Facility Name: The Reverend Louis E. Ford Playground 'Curve Street P	laygrou	ınd'		
Size (Ac): 2.0 acres				
Address: Behind Baptist Church on Curve Street, West Newton				
Ward: 4				
General Facility Notes: inaccessible playground area; park expansion and renovation with all accessib	ole amenit	ies planned.		
	VEC			
ore remaining	YES	Comments		
	Yes	Comments		
Tables & Benches				
Number of Benches Number of Tables	yes	2 benches with backs and no arm rests 1 picnic table		
	yes	1 picnic table		
Located adjacent to accessible paths Back and Arm Rests	no ves	2 benches with backs and no arm rests		
Grills	yes	2 benches with backs and no arm rests		
	NA.	T.		
Located adjacent to accessible paths Trash Cans	NA			
Located adjacent to accessible paths	yes	I		
Picnic Shelters	yes			
Located adjacent to accessible paths	NA			
Notes:	NA.			
nutes.				
Trails & Paths	NI/A			
	N/A YES			
	IES	Comments		
Description Facility Type (3-5 Yrs, 5-12 Yrs)	yes	Fibar safety surfacing.		
Same experience provided to all	yes	Trust safety surfacing.		
Access Routes	yes			
Located adjacent to accessible paths	no	There are no paths at this location.		
Enough space between equipment for wheelchair	yes	mere are no patris at dris location.		
Lindgrishete detween equipment for wineerings. Notes:	yes			
	N/A			
Parking	N/A			
	N/A			
Picknicking N/A				
Off Leash Dog Areas (OLA)	N/A			

Facility Name: Thompsonville-Bowen Playground - DOES N	IOT INCLUDE SCH	OOL
Size (Ac): 8.8 acres		
Address: Langley Path and Cypress Street, Thompsonville (adjacent to Bowen School	1)	
Ward: 6		
General Facility Notes: No accessible route to ballfields; steep pathway from Langley Path; new accessible playground in Bowen schoolyard.	Path down to adjoining	Bowen School; no designated accessible parking on Langley
Site Furnishings	YES	
Description	Yes	Comments
Tables & Benches Number of Benches	I w.	Ι,
Number of Benches Number of Tables	Yes	2
Located adjacent to accessible paths	no	
Back and Arm Rests	no	
Grills		
Located adjacent to accessible paths	NA NA	
Trash Cans		T
Located adjacent to accessible paths Picnic Shelters	yes	1 big belly trash bin and 1 big belly recycling unit, located off asphalt drive
Located adjacent to accessible paths	no	
Notes:		
Trails 9 Daths	YES	
Trails & Paths Description	1123	Comments
Surface (A=Asphalt, C=Concrete, SD= stone dust, NS= naturally surfaced, B=Boardwalk, BR=Bridge)	yes	A, non-accessible pathway from cul de sac to school
Dimensions (width)	yes	Ten feet wide
Rails	No	
Signage for visually impaired	No	
Notes:		
Play Areas	YES	
Description		Comments
Facility Type (3-5 Yrs,5-12 Yrs) Same experience provided to all	no No	
Access Routes	NO	
Located adjacent to accessible paths	no	
Enough space between equipment for wheelchair	no	
Notes:		
Game Areas	YES	
Description	123	Comments
Facility Type (RF=Rectangular Fields, BF= Ballfields, BK=Basketball, TN=Tennis, BC=Bocce)		1 RF, 2 BF with backstops, players benches, protective screens and one shed, 1 Basketball Standard
racinty type (nr=nectangular rietus, pr= bainteius, pn=basketuali, tn=1ellilis, pc=bucce)	yes	1 kr, 2 br with backstops, players beniches, protective screens and one sned, 1 basketban standard
Access Routes		
Located adjacent to accessible paths Berm cuts onto courts	no	
Equipment	IIO.	
Spectator Seating	No	
Notes: Athletic field is irrigated with well water.		
	181/4	
Boat Docks	N/A N/A	
Fishing Facilities Community Gardens	N/A	
Parking	N/A	
Ramps	N/A	
Site Access, Path of Travel, Entrances	N/A	
Stairs and Doors	N/A	
Restrooms	N/A	
Floors, Drinking Fountains, Telephones Signs, Signals, and Switches	N/A N/A	
Swimming Pool/ Lake beach	N/A	
Shower Rooms	N/A	
Picknicking	N/A	
Off Leash Dog Areas (OLA)	N/A	

Facility Name: Upper Falls Greenway Size (Mi): 1.0 mile Address: Easy St. to Oak St., Upper Falls General Facility Notes: 1 Miles accessible stone dust rail trail with accessible parkingon-street on Oak Street; accessible entrance from Oak Street. YES Site Furnishings Comments Tables & Benches Yes Number of Tables NO Located adjacent to accessible paths Yes Back rests only Back and Arm Rests Located adjacent to accessible paths NA Trash Cans Yes Located adjacent to accessible paths icnic Shelters NA Notes: Trails & Paths YES Comments Surface (A=Asphalt, C=Concrete, SD= stone dust, NS= naturally surfaced, B=Boardwalk, BR=Bridge) Yes C, SD Dimensions (width) 6 ft min. Rails No Signage for visually impaired No Notes: N/A Play Areas **Game Areas** Comments Facility Type (RF=Rectangular Fields, BF= Ballfields, BK=Basketball, TN=Tennis, BC=Bocce) Yes BC Access Routes Located adjacent to accessible paths Yes Berm cuts onto courts No Equipment No Spectator Seating Notes: N/A N/A Boat Docks Fishing Facilities Community Gardens Total Spaces Accessible Spaces 2 Spaces Description Comments Yes Parking Amenities (L=lot, ST=street) ST Accessible space located closest to accessible entrance Yes Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft $\,$ NA Minimum width of 13 ft includes 8 ft space plus 5 ft access aisle Yes Minimum of 1 van space for every accessible space, 8' wide + 8' aisle. No Sign with international symbol of accessibility at each space Yes Surface evenly paved or hard-packed (no cracks) Yes Surface slope less than 1:20, 5% Curbcut to pathway from parking lot at each space if sidewalk (curb) is present . No Shared curb cut Curbcut is a minimum width of 3 ft, excluding sloped sides, has sloped sides, all slopes not to exceed 1:12, and textured or painted yellow Yes Notes: N/A YES Ramps Site Access, Path of Travel, Entrances Comments Description Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed Yes Ponding of water? No Disembarking area at accessible entrance Yes Path of Travel Comments Path does not require the use of stairs Yes Path does not require the use of wheelchair ramp Yes Path is stable, firm and slip resistant Yes Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50). Yes Continuous common surface, no changes in level greater than % inch Yes Notes: Stairs and Doors Restrooms Floors, Drinking Fountains, Telephones Signs, Signals, and Switches Swimming Pool/ Lake beach N/A N/A N/A N/A Shower Rooms N/A

Picknicking	N/A
Off Leash Dog Areas (OLA)	N/A

Facility Name: Ward Park		
Size (Ac): 3.5 acres		
Address: Montrose Street, Newton Centre		
Ward: 7		
General Facility Notes: ballfield and soccer field not accessible; contiguous to Ward School Pla	waround	
<u>general racinty Notes.</u> Dannett and soccer neith not accessible, contiguous to ward school ria	iygi oulla.	
Site Furnishings	YES	
Description Tables & Benches		Comments
Number of Benches	No	
Number of Tables	No	
Located adjacent to accessible paths Back and Arm Rests	No No	
<u>n</u>	1.0	
Located adjacent to accessible paths	No	
Trash Cans Located adjacent to accessible paths	YES	T
Picnic Shelters		
Located adjacent to accessible paths	No	
Notes:		
Trails & Paths	YES	
Description		Comments
Surface (A=Asphalt, C=Concrete, SD= stone dust, NS= naturally surfaced, B=Boardwalk, BR=Bridge) Dimensions (width)	YES Yes	A- From Lorna RD To School 8ft
Dimensions (wioth) Rails	Yes No	811
Signage for visually impaired	No	
Notes:		
Play Areas	N/A	
Game Areas	YES	Comments
Description Facility Type (RF=Rectangular Fields, BF= Ballfields, BK=Basketball, TN=Tennis, BC=Bocce)	Yes	Comments BF BK RF, TN
Access Routes		
Located adjacent to accessible paths Berm cuts onto courts	YES No	Acess to RF Courts are not accessible
Equipment	No	Courts are not accessible
Spectator Seating	Yes	
Notes:		
Boat Docks	N/A	
Fishing Facilities	N/A	
Fishing Facilities Community Gardens Parking	N/A N/A YES	
Fishing Facilities Community Gardens Parking Total Spaces	N/A N/A	oaces.
Fishing Facilities Community Gardens Parking	N/A N/A YES Accessible S	ouces Comments
Fishing Facilities Community Gardens Parking Total Spaces 55 Description Parking Amenities (L-lot, ST-street)	N/A N/A YES Accessible Si	
Fishing Facilities Community Gardens Parking Total Spaces 55 Description Parking Amenities (Lalot, ST-street) Accessible space located closest to accessible entrance	N/A N/A YES Accessible Si 0 YES NA	Comments
Fishing Facilities Community Gardens Parking Total Spaces 55 Description Parking Amenities (L-lot, ST-street)	N/A N/A YES Accessible Si	Comments
Fishing Facilities Community Gardens Parking Total Spaces 55 Description Parking Amenities (Lislot, ST-street) Accessible space located closest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft Minimum withor 13 ft includes 8 ft space plus 5 ft access aisle Minimum of 1 van space for every accessible space, 8' wide + 8' aisle.	N/A N/A YES Accessible S ₁ 0 YES NA NA NA NA	Comments
Fishing Facilities Community Gardens Parking Total Spaces 55 Description Parking Amenities (Lalot, ST-street) Accessible space located closest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft Minimum width of 13 ft includes 8 ft space plus 5 ft access asise Minimum of 1 ava space for every accessible space, 8' wide + 8' asile. Sign with international symbol of accessibility at each space	N/A N/A YES Accessible Si O YES NA NA NA NA NA NA	Comments
Fishing Facilities Community Gardens Parking Total Spaces 55 Description Parking Amenities (Lislot, ST-street) Accessible space located closest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft Minimum withor 13 ft includes 8 ft space plus 5 ft access aisle Minimum of 1 van space for every accessible space, 8' wide + 8' aisle.	N/A N/A YES Accessible S ₁ 0 YES NA NA NA NA	Comments
Fishing Facilities Community Gardens Parking Total Spaces 55 Description Parking Amenities (Lalot, ST-street) Accessible space located closest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance Where spaces cannot be located within 200 ft of accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, Sign with international symbol of accessible space, 8' wide + 8' aidle. Sign with international symbol of accessibility at each space Surface evenly paved or hard-packed (no cracks) Surface slope less than 120, 9's Curbout to pathway from parking lot at each space if sidewalk (curb) is present.	N/A N/A YES Accessible Si O YES NA	Comments
Fishing Facilities Community Gardens Parking Total Spaces 55 Description Parking Amenities (Lviot, ST-street) Accessible space located diosest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft Minimum width of 13 ft includes 8 ft space plus 5 ft access asise Minimum of 1 van space for every accessible space, 8' wide + 8' asise. Sign with international symbol of accessibility at each space Surface evenly paved or hard-packed (no cracks) Surface slope less than 1:20,5%	N/A N/A N/A YES Accessible Si 0 YES NA NA NA NA NA NA YES YES	Comments
Fishing Facilities Community Gardens Parking Total Spaces 55 Description Parking Amenities (L-lot, ST-sstreet) Accessible space located closest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft Minimum width of 13 ft includes 8 ft space plus 5 ft access aisle Minimum of 1-2 van space for every accessible space, 8 wide + 8° aisle. Sign with international symbol of accessibility at each space Surface evenly paved or hard-packed (no cracks) Surface slope less than 1:20, 5% Curbcut to pathway from parking lot at each space if sidewalk (curb) is present. Curbcut is a minimum width of 3 ft, excluding sloped sides, has sloped sides, all slopes not to exceed 1:12, and textured or painted yellow	N/A N/A YES Accessible Si O YES NA	Comments
Fishing Facilities Community Gardens Parking Total Spaces 55 55 Description Parking Amenities (Lviot, STextreet) Accessible space located dosest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft Minimum width of 18 ft includes 8 ft space plus 5 ft access aisle Minimum of 1 van space for every accessible space, 8' wide + 8' aisle. Sign with international symbol of accessibility at each space Surface evenly paved or hard-packed (nor cracks) Surface slope less than 1:20, 5% Curbcut to pathway from parking lot at each space if sidewalk (curb) is present. Curbcut is a minimum width of 3 ft, excluding sloped sides, has sloped sides, all slopes not to exceed 1:12, and textured or painted yellow Notes:	N/A N/A YES Accessible S O YES NA	Comments
Fishing Facilities Community Gardens Parking Total Spaces 55 Description Parking Amenities (L-lot, ST-street) Accessible space located closest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft Minimum width of 13 ft includes 8 ft space plus 5 ft access aisle Minimum of 1 van space for every accessible space, 8' wide + 8' aisle. Sign with international symbol of accessibility at each space Surface evenly paved or hard-packed (no cracks) Surface slope less than 1:20,5% Curbcut to pathway from parking lot at each space if sidewalk (curb) is present. Curbcut is a minimum width of 3 ft, excluding sloped sides, has sloped sides, all slopes not to exceed 1:12, and textured or painted yellow Notes: Ramps Site Access, Path of Travel, Entrances	N/A N/A YES Accessible Si O YES NA	Comments
Fishing Facilities Community Gardens Parking Total Spaces 55 Description Parking Amenities (Lelot, ST-street) Accessible space located closest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, Minimum withor 13 ft includes 8 ft space plus ST access aisle Minimum of 1 van space for every accessible space, 8' wide + 8' aisle. Sign with international symbol of accessibility at each space Surface evenly paved or hard-packed (no cracks) Surface slope less than 1:20, 5% Curbcut to pathway from parking lot at each space if sidewalk (curb) is present. Curbcut is a minimum width of 3 ft, excluding sloped sides, has sloped sides, all slopes not to exceed 1:12, and textured or painted yellow Notes: Ramps Site Access, Path of Travel, Entrances	N/A N/A YES Accessible S O YES NA	Comments ST, L School lot
Fishing Facilities Community Gardens Parking Total Spaces 55 Description Parking Amenities (L-lot, ST-street) Accessible space located closest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft Minimum width of 13 ft includes 8 ft space plus 5 ft access aisle Minimum of 1 van space for every accessible space, 8' wide + 8' aisle. Sign with international symbol of accessibility at each space Surface evenly paved or hard-packed (no cracks) Surface slope less than 1:20,5% Curbcut to pathway from parking lot at each space if sidewalk (curb) is present. Curbcut is a minimum width of 3 ft, excluding sloped sides, has sloped sides, all slopes not to exceed 1:12, and textured or painted yellow Notes: Ramps Site Access, Path of Travel, Entrances	N/A N/A YES Accessible S O YES NA	Comments
Fishing Facilities Community Gardens Parking Total Spaces 55 55 55 56 Description Parking Amenities (Listot, STextreet) Accessible space located closest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft Minimum withor 13 ft includes it space plus 5 ft access aisle Minimum of 1 van space for every accessible space, 8' wide + 8' aisle. Sign with international symbol of accessibility at each space Surface evenly paved or hard-packed (no cracks) Surface slope less than 1:20,5% Curbcut to pathway from parking lot at each space if sidewalk (curb) is present. Curbcut is a minimum width of 3 ft, excluding sloped sides, has sloped sides, all slopes not to exceed 1:12, and textured or painted yellow Notes: Ramps Site Access, Path of Travel, Entrances Site Access, Path of Travel, Entrances Site Access Description Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed	N/A N/A N/A YES Accessible Si O YES NA NA NA NA NA NA NA NA Ves Yes NA NA NA Ves Yes	Comments ST, L School lot
Fishing Facilities Community Gardens Parking Total Spaces 55 Description Parking Amenities (L-lot, ST-street) Accessible space located closest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance Where spaces cannot be located within 200 ft of accessible entrance Minimum width of 13 ft includes 8 ft space plus 5 ft access sisle Minimum of 1 van space for every accessible space, 8' wide + 8' akile. Sign with international symbol of accessibility at each space Surface evenly paved or hard-packed (no cracks) Surface slope less than 1.20, 5% Curbcut to pathway from parking lot at each space if sidewalk (curb) is present. Curbcut is a minimum width of 3 ft, excluding sloped sides, has sloped sides, all slopes not to exceed 1:12, and textured or painted yellow Notes: Ramps Site Access, Path of Travel, Entrances Site Access, Path of Travel, Entrances Site Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed Ponding of water?	N/A N/A YES Accessible Si O YES NA NA NA NA NA NA NA NA Ves Yes NA NA Ves Yes Yes Yes Yes Yes Yes	Comments ST, L School lot
Fishing Facilities Community Gardens Parking Total Spaces 55 Description Parking Amenities (Li-lot, ST-street) Accessible space located closest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft Minimum withor of 31 ft includes 81 space plus 51 ft access asise Minimum of 1 van space for every accessible space, 8' wide + 8' asiale. Sign with international symbol of accessibility at each space Surface evenly paved or hard-packed (no cracks) Surface slope less than 12.0, 5% Curbcut to pathway from parking lot at each space if sidewalk (curb) is present. Curbcut is a minimum width of 3 ft, excluding sloped sides, has sloped sides, all slopes not to exceed 1:12, and textured or painted yellow Notes: Ramps Site Access, Path of Travel, Entrances Site Access Description Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed	N/A N/A N/A YES Accessible Si O YES NA NA NA NA NA NA NA NA Ves Yes NA NA NA Ves Yes	Comments ST, L School lot
Fishing Facilities Community Gardens Parking Total Spaces 55 Description Parking Amenities (Li-lot, ST-street) Accessible space located dosest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft Minimum width of 13 ft includes at Space plus ST access aisle Minimum of 1 van space for every accessible space, 8' wide + 8' aisle. Sign with international symbol of accessibility at each space Surface evenly paved or hard-packed (no cracks) Surface slope less than 1:20,5% Curbout to pathway from parking lot at each space if sidewalk (curb) is present. Curbout is a minimum width of 3 ft, excluding sloped sides, has sloped sides, all slopes not to exceed 1:12, and textured or painted yellow Notes: Ramps Site Access, Path of Travel, Entrances Site Access, Path of Travel, Entrances Site Access and Entrance and parking area and parking area to accessible entrance Surface evenly paved or hard-packed Ponding of water? Disembarking area at accessible entrance Path of Tavel Description Description Description Description	N/A N/A YES Accessible Si O YES NA NA NA NA NA NA NA NA NA Ves Yes Yes Ves Ves Yes Yes Yes Yes Yes	Comments ST, L School lot
Fishing Facilities Community Gardens Parking Total Spaces 55 Description Parking Amenties (L-lot, ST-street) Accessible space located closest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance Where spaces cannot be located within 200 ft of accessible entrance Minimum width of 13 ft includes 8 ft space plus 5 ft access aisle Minimum of 1 van space for every accessible space, 8' wide + 8' aisle. Sign with international symbol of accessibility at each space Surface evenly paved for hard-packed (no cracks) Surface slope less than 1.20, 5% Curbcut to pathway from parking lot at each space if sidewalk (curb) is present. Curbcut is a minimum width of 3 ft, excluding sloped sides, has sloped sides, all slopes not to exceed 1:12, and textured or painted yellow Notes: Ramps Site Access, Path of Travel, Entrances Site Access, Path of Travel, Entrances Surface evenly paved or hard-packed Ponding of water? Disembarking area at accessible entrance Path of Travel Description Path does not require the use of stairs	N/A N/A YES Accessible Si O YES NA NA NA NA NA NA NA NA Ves Yes NA NA Ves Yes Yes Yes Yes Yes Yes Yes	Comments ST, L School lot Comments Comments
Fishing Facilities Community Gardens Parking Total Spaces 55 Description Parking Amenities (Li-lot, ST-street) Accessible space located dosest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft Minimum width of 13 ft includes at Space plus ST access aisle Minimum of 1 van space for every accessible space, 8' wide + 8' aisle. Sign with international symbol of accessibility at each space Surface evenly paved or hard-packed (no cracks) Surface slope less than 1:20,5% Curbout to pathway from parking lot at each space if sidewalk (curb) is present. Curbout is a minimum width of 3 ft, excluding sloped sides, has sloped sides, all slopes not to exceed 1:12, and textured or painted yellow Notes: Ramps Site Access, Path of Travel, Entrances Site Access, Path of Travel, Entrances Site Access and Entrance and parking area and parking area to accessible entrance Surface evenly paved or hard-packed Ponding of water? Disembarking area at accessible entrance Path of Tavel Description Description Description Description	N/A N/A YES Accessible Si O YES NA NA NA NA NA NA NA NA NA Ves Yes Yes Ves Ves Yes Yes Yes Yes Yes	Comments ST, L School lot Comments Comments
Fishing Facilities Community Gardens Parking Total Spaces 55 Description Parking Amenities (I-lot, 5T-street) Accessible space located closest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, Where spaces cannot be located within 200 ft of accessible entrance, Minimum of 1 van space for every accessible space, 8' wide + 8' abile. Sign with international symbol of accessibility at each space Surface evenly paved or hard-packed (no cracks) Surface slope less than 1:20, 5% Curbcut to pathway from parking lot at each space if sidewalk (curb) is present. Curbcut is a minimum width of 3 ft, excluding sloped sides, has sloped sides, all slopes not to exceed 1:12, and textured or painted yellow Notes: Ramps Site Access, Path of Travel, Entrances Site Access, Path of Travel, Entrances Site Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed Ponding of water? Disembarking area at accessible entrance Path of Travel Path of Travel Path of Travel Path of Travel Path so the use of stalies Path does not require the use of stalies Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50).	N/A	Comments ST, L School lot Comments Comments
Fishing Facilities Community Gardens Parking Total Spaces 55 55 55 56 Description Parking Amenities (L-iot, ST-street) Accessible space located diosest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft Minimum width of 13 ft includes 8 ft space plus 5 ft access asisle Minimum of 1 van space for every accessible space, 8' wide + 8' asisle. Sign with international symbol of accessibility at each space Surface evenly paved or hard-packed (no cracks) Surface slope less than 1:20,5% Curbcut to pathway from parking lot at each space if sidewalk (curb) is present. Curbcut to an inimum width of 3 ft, excluding sloped sides, has sloped sides, all slopes not to exceed 1:12, and textured or painted yellow Notes: Ramps Site Access, Path of Travel, Entrances Site Access Description Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed Ponding of water? Disembarking area at accessible entrance Path of Travel Description Path does not require the use of stairs Path does not require the use of otherelation and parking in level greater than 8' inch	N/A N/A N/A YES Accessible Si O YES NA NA NA NA NA NA NA NA Ves Yes Yes Yes Yes Yes Yes Yes Yes Yes Y	Comments ST, L School lot Comments Comments
Fishing Facilities Community Gardens Parking Total Spaces 55 Description Parking Amenities (Li-lot, 5T-street) Accessible space located closest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, Where spaces cannot be located within 200 ft of accessible entrance, Minimum with of 3.8 includes 8 ft space plus 5 ft access sible Minimum of 1 van space for every accessible space, 8' wide + 8' able. Sign with international symbol of accessibility at each space Surface evenly paved or hard-packed (no cracks) Surface slope less than 1:20, 5% Curbcut to pathway from parking lot at each space if sidewalk (curb) is present. Curbcut is a minimum width of 3 ft, excluding sloped sides, has sloped sides, all slopes not to exceed 1:12, and textured or painted yellow Notes: Ramps Site Access, Path of Travel, Entrances Site Access, Path of Travel, Entrances Site Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed Ponding of water? Disembarking area at accessible entrance Path of Travel Path of Travel Path of Travel Path of travel from ad silp resistant Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50).	N/A	Comments ST, L School lot Comments Comments
Fishing Facilities Community Gardens Parking Total Spaces 55 55 55 Description Parking Amenities (L-lot, ST-street) Accessible space located closes to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, drop off area is provided within 100 ft Minimum width of 13 ft includes 8 ft space plus 5 ft access aisle Minimum of 1 van space for every accessible space, 8' wide + 8' aisle. Sign with international symbol of accessibility at each space Surface evenly paved or hard-packed (no cracks) Surface slope less than 1:20, 5% Curbcut to pathway from parking lot at each space if sidewalk (curb) is present. Curbcut is a minimum width of 3 ft, excluding sloped sides, has sloped sides, all slopes not to exceed 1:12, and textured or painted yellow Notes: Ramps Site Access, Path of Travel, Entrances Star Access Description Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed Ponding of water? Disembarking area at accessible entrance Path of Travel Path does not require the use of wheelchair ramp Path does not require the use of wheelchair ramp Path does not require the use of wheelchair ramp Path does not require the use of wheelchair ramp Path does not require the use of wheelchair ramp Path does not require the use of wheelchair ramp Path does not require the use of wheelchair ramp Path does not require the use of wheelchair ramp Path does not require the use of wheelchair ramp Path does not require the use of wheelchair ramp Path does not require the use of wheelchair ramp Path of stable, firm and slip resistant Slope maximum 120 (5%) and maximum cross pitch is 2% (1:50). Continuous common surface, no changes in level greater than % inch Notes:	N/A	Comments ST, L School lot Comments Comments
Fishing Facilities Community Gardens Parking Total Spaces 55 Description Parking Amenities (Li-lot, ST-street) Accessible space located dosest to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft Minimum withor 13 ft includes it space plus 5 ft access asise Minimum of 1 van space for every accessible space, 8' wide + 8' asiale. Sign with international symbol of accessibility at each space Surface evenly paved or hard-packed (no cracks) Surface slope less than 1:20,5% Curbout to pathway from parking lot at each space if sidewalk (curb) is present. Curbout is a minimum width of 3 ft, excluding sloped sides, has sloped sides, all slopes not to exceed 1:12, and textured or painted yellow Notes: Ramps Site Access, Path of Travel, Entrances Site Access, Path of Travel, Entrances Site Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed Ponding of water? Disembarking area at accessible entrance Path of Travel Path ose not require the use of stairs Path does not require the use of wheelchair ramp Path is stable, firm and slip resistant Slope maximum 1.20 (5%) and maximum cross pitch is 2% (1:50). Continuous common surface, no changes in level greater than ½ inch Notes: Stairs and Doors Restrooms	N/A	Comments ST, L School lot Comments Comments
Fishing Facilities Community Gardens Parking Total Spaces 55 55 55 55 56 57 58 58 58 58 58 59 59 59 60 60 60 60 70 70 70 70 70 70	N/A	Comments ST, L School lot Comments Comments
Fishing Facilities Community Gardens Parking Total Spaces 55 Description Parking Amenities (Lolot, 5Testreet) Accessible space located closes to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft Minimum width of 13 ft includes 8 ft space plus 5 ft access alsie Minimum of 1 van space for every accessible space, 8' wide * 8' asile. Sign with international symbol of accessibility at each space Surface evenly paved or hard-packed (no cracks) Surface slope less than 1:20, 5% Curbout to pathway from parking lot at each space if sidewalk (curb) is present. Curbout to an inimum width of 3 ft, excluding sloped sides, has sloped sides, all slopes not to exceed 1:12, and textured or painted yellow Notes: Ramps Site Access, Path of Travel, Entrances Base Access Description Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed Ponding of water? Disembarking area at accessible entrance Path does not require the use of stairs Path does not require the use of vistairs Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50). Continuous common surface, no changes in level greater than ½ inch Notes: Stairs and Doors Restrooms Floors, Drinking Fountains, Telephones Signs, Signals, and Switches	N/A	Comments ST, L School lot Comments Comments
Fishing Facilities Community Gardens Parking Total Spaces 55 55 55 Description Parking Amenities (Livlot, STiestreet) Accessible space located closes to accessible entrance Where spaces cannot be located within 200 ft of accessible entrance, drop off area is provided within 100 ft Minimum width of 13 ft includes 8 ft space plus 5 ft access asise Minimum of 1 van space for every accessible space, 8 wide + 8² asise. Sign with international symbol of accessibility at each space Surface evenly paved or hard-packed (no cracks) Surface slope less than 1:20, 5% Curbcut to pathway from parking lot at each space if sidewalk (curb) is present. Curbcut is a minimum width of 3 ft, excluding sloped sides, has sloped sides, all slopes not to exceed 1:12, and textured or painted yellow Notes: Ramps Site Access, Path of Travel, Entrances Stra Access Description Accessible path of travel from passenger disembarking area and parking area to accessible entrance Surface evenly paved or hard-packed Pending of water? Disembarking area at accessible entrance Path of Travel Description Path does not require the use of wheelchair ramp Path of travel Path does not require the use of wheelchair ramp Path is stable, firm and slip resistant Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50). Continuous common surface, no changes in level greater than % inch Notes: Stairs and Doors Restrooms Floors, Drinking Fountains, Telephones	N/A	Comments ST, L School lot Comments Comments

Picknicking	N/A
Off Leash Dog Areas (OLA)	N/A

<u> </u>	
Facility Name: Washington Park	
Size (Ac): 1.0 acres	
Address: Washington Park, Newtonville	
Ward: 2	
General Facility Notes: Historic park; large, rectangular traffic island; trees and la	awn only; no pathways; benches are not accessible.
Site Furnishings	N/A
Trails & Paths	N/A
Play Areas	N/A
Game Areas	N/A
Boat Docks	N/A
Fishing Facilities	N/A
Community Gardens	N/A
Parking	N/A
Ramps	N/A
Site Access, Path of Travel, Entrances	N/A
Stairs and Doors	N/A
Restrooms	N/A
Floors, Drinking Fountains, Telephones	N/A
Signs, Signals, and Switches Swimming Pool/ Lake beach	N/A N/A
Shower Rooms	IN/A
Picknicking	N/A
Off Leash Dog Areas (OLA)	N/A

Facility Name: Webster Park		
Size (Ac): 1.0 acres		
Address: End of Warren Street, Newton Centre (adjoins Webster Conservation	Area)	
Ward: 7		
General Facility Notes: Oval level lawn area surrounded by woods; no pathway	ys; little parking with no accessible parking space; adjoins Webster Conservation Area.	
Site Furnishings	N/A	
Trails & Paths	N/A	
Play Areas	N/A	
Game Areas	N/A	
Boat Docks	N/A	
Fishing Facilities	N/A	
Community Gardens	N/A	
Parking	N/A	
Ramps	N/A	
Site Access, Path of Travel, Entrances	N/A	
Stairs and Doors	N/A	
Restrooms	N/A	
Floors, Drinking Fountains, Telephones	N/A	
Signs, Signals, and Switches	N/A	
Swimming Pool/ Lake beach	N/A	
Shower Rooms	N/A	
Picknicking	N/A	
Off Leash Dog Areas (OLA)	N/A	

Facility Name: Weeks Park Size (Ac): 11.1 acres Address: Hereward Rd. or Paul St. or Cedric St., Newton Centre (adjacent to Weeks Housing), Ward: 6 General Facility Notes: Soccer fields, ballfields, and bermed passive area in the middle not accessible; accessible route from parking lot to tot lot constructed in 2020. YES Site Furnishings Comments Yes Tables & Benches Number of Benches YES Number of Tables YES 1 in middle area seats 4 Located adjacent to accessible paths No YES Back and Arm Rests Located adjacent to accessible paths No Trash Cans Located adjacent to accessible paths YES icnic Shelters Located adjacent to accessible paths No Notes: Trails & Paths YES Comments Surface (A=Asphalt, C=Concrete, SD= stone dust, NS= naturally surfaced, B=Boardwalk, BR=Bridge) A to playground area Dimensions (width) 4 ft min Rails No Signage for visually impaired No Benches No Notes: YES Play Areas Comments Facility Type (3-5 Yrs,5-12 Yrs) YES 3-5 yrs Same experience provided to all YES Access Routes Located adjacent to accessible paths YES Enough space between equipment for wheelchair YES Notes: YES Game Areas Comments Facility Type (RF=Rectangular Fields, BF= Ballfields, BK=Basketball, TN=Tennis, BC=Bocce) RF, TN Access Routes Located adjacent to accessible paths Path leads to playground only Berm cuts onto courts No quipment No Spectator Seating Notes: N/A **Boat Docks** N/A N/A YES **Fishing Facilities Community Gardens** Parking Required Accessible Spaces otal Spaces 1 Space Description Comments Parking Amenities (L=lot, ST=street) YES Lot Accessible space located closest to accessible entrance NO NA Where spaces cannot be located within 200 ft of accessible entrance, drop-off area is provided within 100 ft $\,$ Minimum width of 13 ft includes 8 ft space plus 5 ft access aisle Yes $\label{eq:minimum} \mbox{Minimum of 1 van space for every accessible space, 8' wide + 8' aisle.}$ No Sign with international symbol of accessibility at each space No Surface evenly paved or hard-packed (no cracks) Yes Surface slope less than 1:20, 5% Yes Curbcut to pathway from parking lot at each space if sidewalk (curb) is present . Yes Curbcut is a minimum width of 3 ft, excluding sloped sides, has sloped sides, all slopes not to exceed 1:12, and textured or painted yellow Yes Notes: Parking spaces need restriping N/A YES Site Access, Path of Travel, Entrances Comments Description Accessible path of travel from passenger disembarking area and parking area to accessible entrance YES Surface evenly paved or hard-packed YES Ponding of water? No Disembarking area at accessible entrance YES ath of Travel Description Comments Path does not require the use of stairs YES Path does not require the use of wheelchair ramp YES Path is stable, firm and slip resistant YES Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50). YES

Continuous common surface, no changes in level greater than ½ inch	YES	
Any objects protruding onto the pathway must be detected by a person with a visual disability using a cane	No	
Objects protruding more than 4" from the wall must be within 27" of the ground, or higher than 80"	No	
Curb on the pathway must have curb cuts at drives, parking and drop-offs	YES	
Notes:		
Stairs and Doors	N/A	
Restrooms	N/A	
Floors, Drinking Fountains, Telephones	N/A	
Signs, Signals, and Switches	N/A	
Swimming Pool/ Lake beach	N/A	
Shower Rooms	N/A	
Picknicking	N/A	
Off Leash Dog Areas (OLA)	N/A	_

Facility Name: Wellington Playground			
Size (Ac): 1.9 acres			
Address: Kilburn Road, West Newton			
Nard: 3			
General Facility Notes: Accessible pathways connecting two of the three entrances to the taccessible.	ot lot; one entranc	e on Kilburn St. not accessible; play equipment area	
Site Furnishings	YES		
Description		Comments	
Ables & Benches Number of Benches	Yes	6	
Number of Tables	Yes	1	
Located adjacent to accessible paths	Yes	2 benches along accessible route	
Back and Arm Rests	Yes		
Located adjacent to accessible paths	NA NA		
rash Cans			
Located adjacent to accessible paths	Yes		
Located adjacent to accessible paths	NA NA		
Votes:	· ·		
- 1 0 p. il	WEG		
Trails & Paths Description	YES	Comments	
Surface (A=Asphalt, C=Concrete, SD= stone dust, NS= naturally surfaced, B=Boardwalk, BR=Bridge)	Yes	A	
Dimensions (width)	5-ft min		
Rails Signage for visually impaired	No No		
Notes:	110		
Play Areas	YES		
Description Service (1975)	Ver	Comments	
Facility Type (3-5 Yrs,5-12 Yrs) Same experience provided to all	Yes No	3-5yrs	
access Routes	<u>'</u>		
Located adjacent to accessible paths Enough space between equipment for wheelchair	Yes Yes		
lotes:	YES		
Game Areas Description	ILS	Comments	
Facility Type (RF=Rectangular Fields, BF= Ballfields, BK=Basketball, TN=Tennis, BC=Bocce)	Yes	BK, TN, RF	
Located adjacent to accessible paths	Yes	Tennis and Basketball located next to Accessiblew route	
Berm cuts onto courts	NA NA	Terminalia dispersioni federali fical di percensione il fode	
quipment			
Spectator Seating Notes:	No		
	101/4		
Boat Docks Fishing Facilities	N/A N/A		
Community Gardens	N/A		
Parking	N/A		
Ramps Site Access, Path of Travel, Entrances	N/A YES		
ite Access	ILJ		
Description		Comments	
Accessible path of travel from passenger disembarking area and parking area to accessible entrance	NA V	Non-designated on-street parking	
Surface evenly paved or hard-packed Ponding of water?	Yes No		
Disembarking area at accessible entrance	NA		
ath of Trave!		Ia .	
Pestription Path does not require the use of stairs	Yes	Comments	
Path does not require the use of wheelchair ramp	Yes	One entrance requires a ramp. Other 2 park entrances are accessible	
Path is stable, firm and slip resistant	Yes		
Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50). Continuous common surface, no changes in level greater than ¼ inch	Yes Yes		
Notes:			
	B1/A		
Stairs and Doors Restrooms	N/A N/A		
Floors, Drinking Fountains, Telephones	N/A		
Signs, Signals, and Switches	N/A		
Swimming Pool/ Lake beach Shower Rooms	N/A N/A		
Picknicking	N/A N/A		
Off Leash Dog Areas (OLA)	N/A		

Facility Name: West Newton Commons Playground		
Size (Ac): 3.7 acres		
Address: Elm Road and Webster Street, West Newton		
Ward: 3		
General Facility Notes: Circumvented by sidewalks on 3 sides; no internal pathwa	ays; On-street parking; acces	sible route from sidewalk to tot lot constructed in 2020.
	VEC	
Site Furnishings Description	YES	Comments
Tables & Benches	l .	comments
Number of Benches	YES	7 benches
Number of Tables	NO	
Located adjacent to accessible paths	NO	
Back and Arm Rests	YES	all benches have back rests; no arm rests
Trash Cans		T
Located adjacent to accessible paths Notes:		
Trails & Paths	YES	
Description	1.23	Comments
Surface (A=Asphalt, C=Concrete, SD= stone dust, NS= naturally surfaced, B=Boardwalk, BR=Bridge)	YES	A
Dimensions (width)	YES	5 feet wide
Rails	NO	
Signage for visually impaired	NO	
Notes: accessible route from Webster street entrance to the play area.		
Play Areas	YES	In the second se
Description Facility Type (3-5 Yrs,5-12 Yrs)	YES	Comments 3-5 Yrs, renovated in 1995
Same experience provided to all	NO	3 3 113, 141104444 III 2333
Access Routes		
Located adjacent to accessible paths	YES	
Enough space between equipment for wheelchair	YES	
Notes:		
Game Areas	YES	
Description		Comments
Description Facility Type (RF=Rectangular Fields, BF= Ballfields, BK=Basketball, TN=Tennis, BC=Bocce)	YES	Comments 1 RF; 1 BF
Description Facility Type (RF=Rectangular Fields, BF= Ballfields, BK=Basketball, TN=Tennis, BC=Bocce) Access Routes	YES	
Description Facility Type (RF-Rectangular Fields, BF= Ballfields, BK=Basketball, TN=Tennis, BC=Bocce) Access Routes Located adjacent to accessible paths		
Description Facility Type (RF=Rectangular Fields, BF= Ballfields, BK=Basketball, TN=Tennis, BC=Bocce) Access Routes Located adjacent to accessible paths Equipment Spectator Seating	YES	
Description Facility Type (RF=Rectangular Fields, BF= Ballfields, BK=Basketball, TN=Tennis, BC=Bocce) Access Routes Located adjacent to accessible paths Equipment Spectator Seating	YES	
Description Facility Type (RF=Rectangular Fields, BF= Ballfields, BK=Basketball, TN=Tennis, BC=Bocce) Access Routes Located adjacent to accessible paths Equipment Spectator Seating Notes: Boat Docks	YES NO YES	
Description Facility Type (RF-Rectangular Fields, BF- Ballfields, BK-Basketball, TN-Tennis, BC-Bocce) Access Routes Located adjacent to accessible paths Seuloment Spectator Seating Notes: Boat Docks Fishing Facilities	VES NO VES	
Description Facility Type (RF-Rectangular Fields, BF- Ballfields, BK-Basketball, TN=Tennis, BC-Bocce) Access Routes Located adjacent to accessible paths Equipment Spectator Seating Notes: Boat Docks Fishing Facilities Community Gardens	VES NO VES N/A N/A N/A	
Description Facility Type (RF-Rectangular Fields, BF= Ballfields, BK=Basketball, TN=Tennis, BC=Bocce) Access Routes Located adjacent to accessible paths Equipment Spectator Seating Notes: Boat Docks Fishing Facilities Community Gardens Parking Parking	VES NO YES N/A N/A N/A N/A	
Description Facility Type (RF-Rectangular Fields, BF- Ballfields, BK-Basketball, TN-Tennis, BC-Bocce) Access Routes Located adjacent to accessible paths Seuloment Spectator Seating Notes: Boat Docks Fishing Facilities Community Gardens Parking Ramps	YES	
Description Facility Type (RF-Rectangular Fields, BF- Ballfields, BK-Basketball, TN=Tennis, BC-Bocce) Access Routes Located adjacent to accessible paths Sequipment Spectator Seating Notes: Boat Docks Fishing Facilities Community Gardens Parking Ramps Site Access, Path of Travel, Entrances	VES NO YES N/A N/A N/A N/A	
Description Facility Type (RF=Rectangular Fields, BF= Ballfields, BK=Basketball, TN=Tennis, BC=Bocce) Access Routes Located adjacent to accessible paths Equipment Spectator Seating Notes: Boat Docks Fishing Facilities Community Gardens Parking Ramps Site Access, Path of Travel, Entrances	YES	
Description Facility Type (RF-Rectangular Fields, BF- Ballfields, BK-Basketball, TN=Tennis, BC-Bocce) Access Routes Located adjacent to accessible paths Equipment Spectator Seating Notes: Boat Docks Fishing Facilities Community Gardens Parking Ramps Site Access, Path of Travel, Entrances Path of Travel	YES	1 RF; 1 BF
Description Facility Type (RF=Rectangular Fields, BF= Ballfields, BK=Basketball, TN=Tennis, BC=Bocce) Access Routes Located adjacent to accessible paths Equipment Spectator Seating Notes: Boat Docks Fishing Facilities Community Gardens Parkling Ramps Site Access, Path of Travel, Entrances Path of Travel Description Path does not require the use of stairs Path does not require the use of wheelchair ramp	NO NO VES N/A N/A N/A N/A N/A N/A YES VES	1 RF; 1 BF
Description Facility Type (RF-Rectangular Fields, RF- Ballfields, BK-Basketball, TN=Tennis, BC-Bocce) Access Routes Located adjacent to accessible paths Sequipment Spectator Seating Notes: Boat Docks Fishing Facilities Community Gardens Parking Ramps Site Access, Path of Travel, Entrances Path of Travel Description Path does not require the use of stairs Path does not require the use of wheelchair ramp Path is stable, firm and slip resistant	NO NO VES N/A N/A N/A N/A N/A YES VES VES VES VES	1 RF; 1 BF
Description Facility Type (RF-Rectangular Fields, BF- Ballfields, BK-Basketball, TN-Tennis, BC-Bocce) Access Routes Located adjacent to accessible paths Equipment Spectator Seating Notes: Boat Docks Fishing Facilities Community Gardens Parking Ramps Site Access, Path of Travel, Entrances Path of Travel Description Path does not require the use of stairs Path does not require the use of wheelchair ramp Path is 15table, firm and slip resistant Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50).	VES	1 RF; 1 BF
Description Facility Type (RF-Rectangular Fields, BF- Ballfields, BK-Basketball, TN=Tennis, BC-Bocce) Access Routes Located adjacent to accessible paths Equipment Spectator Seating Notes: Boat Docks Fishing Facilities Community Gardens Parking Ramps Site Access, Path of Travel, Entrances Path of Travel Description Path does not require the use of stairs Path does not require the use of wheelchair ramp Path is stable, firm and slip resistant Slope maximum 120 (SS) an ansumum cross pitch is 2% (1:50). Continuous common surface, no changes in level greater than % inch	YES	1 RF; 1 BF
Description Facility Type (RF-Rectangular Fields, RF- Ballfields, BK-Basketball, TN=Tennis, BC-Bocce) Access Routes Located adjacent to accessible paths Equipment Spectator Seating Notes: Boat Docks Fishing Facilities Community Gardens Parking Ramps Site Access, Path of Travel, Entrances Path of Travel Description Path does not require the use of stairs Path does not require the use of wheelchair ramp Path is stable, firm and silp resistant Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50). Continuous common surface, no Anages in level greater than ½ inch Any objects protruding onto the pathway must be detected by a person with a visual disability using a cane	VES	1 RF; 1 BF
Description Facility Type (RF-Rectangular Fields, BF- Ballfields, BK-Basketball, TN=Tennis, BC-Bocce) Access Routes Located adjacent to accessible paths Equipment Spectator Seating Notes: Boat Docks Fishing Facilities Community Gardens Parkling Ramps Site Access, Path of Travel, Entrances Path of Travel Description Path does not require the use of stairs Path does not require the use of wheelchair ramp Path does not require the use of wheelchair ramp Path does not require the use of wheelchair ramp Path is stable, firm and silp resistant Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50). Continuous common surface, no changes in level greater than ½ inch Any objects protruding onto the pathway must be detected by a person with a visual disability using a cane Notes:	YES	1 RF; 1 BF
Pescription Facility Type (RF-Rectangular Fields, BF= Balffields, BK=Basketball, TN=Tennis, BC=Bocce) Access Routes Located adjacent to accessible paths Sequipment Spectator Seating Notes: Boat Docks Fishing Facilities Community Gardens Parking Ramps Site Access, Path of Travel, Entrances Path of Travel Description Path oes not require the use of stairs Path does not require the use of whelchair ramp Path is stable, firm and slip resistant Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50). Continuous common surface, no changes in level greater than 5/inch Any objects protruding onto the pathway must be detected by a person with a visual disability using a cane Notes: Stairs and Doors Stairs and Doors	YES	1 RF; 1 BF
Description Facility Type (RF-Rectangular Fields, BF- Ballfields, BK-Basketball, TN=Tennis, BC-Bocce) Access Routes Located adjacent to accessible paths Equipment Spectator Seating Notes: Boat Docks Fishing Facilities Community Gardens Parking Ramps Site Access, Path of Travel, Entrances Path of Travel Description Path does not require the use of stairs Path does not require the use of wheelchair ramp Path is stable, firm and silp resistant Slope maximum 120 (SN) anaximum cross pitch is 2% (1:50). Continuous common surface, no changes in level greater than N inch Any objects protruding onto the pathway must be detected by a person with a visual disability using a cane Notes: Stairs and Doors Restrooms Floors, Drinking Fountains, Telephones	NO	1 RF; 1 BF
Description Facility Type (RF-Rectangular Fields, BF- Baltifields, BK-Basketball, TN=Tennis, BC-Bocce) Access Routes Located adjacent to accessible paths Sequipment Spectator Seating Notes: Boat Docks Fishing Facilities Community Gardens Parking Ramps Site Access, Path of Travel, Entrances Path of Travel Description Path does not require the use of stairs Path does not require the use of wheelchair ramp Path is stable, firm and silp resistant Slope maximum 220 (SN) anaximum cross pitch is 2% (1:50). Continuous common surface, no changes in level greater than N inch Any objects protruding onto the pathway must be detected by a person with a visual disability using a cane Notes: Stairs and Doors Restrooms Floors, Drinking Fountains, Telephones Floors, Drinking Fountains, Telephones	NO	1 RF; 1 BF
Pescription Facility Type (RF-Rectangular Fields, BF- Balffields, BK-Basketball, TN-Tennis, BC-Bocce) Access Routes Located adjacent to accessible paths Sequipment Spectator Seating Notes: Boat Docks Fishing Facilities Community Gardens Parking Ramps Site Access, Path of Travel, Entrances Path of Travel Description Path does not require the use of stairs Path does not require the use of stairs Siope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50). Continuous common surface, no changes in level greater than % inch Any objects protruding onto the pathway must be detected by a person with a visual disability using a cane Notes: Stairs and Doors Restrooms Floors, Drinking Fountains, Telephones Signs, Signals, and Switches Swimming Pool/ Lake beach	VES	1 RF; 1 BF
Description Facility Type (RF-Rectangular Fields, BF- Balffields, BK-Basketball, TN-Tennis, BC-Bocce) Accesse Routes Located adjacent to accessible paths Susiement Spectator Seating Notes: Boat Docks Fishing Facilities Community Gardens Parking Ramps Site Access, Path of Travel, Entrances Path of Travel Description Path does not require the use of stairs Path does not require the use of wheelchair ramp Path is stable, firm and slip resistant Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50). Continuous common surface, no changes in level greater than 1% inch Any objects protruding onto the pathway must be detected by a person with a visual disability using a cane Notes: Stairs and Doors Restrooms Floors, Drinking Fountains, Telephones Signs, Signals, and Switches Swimming Pool/ Lake beach Shower Rooms	NO NO N/A N/A	1 RF; 1 BF
Description Facility Type (RF-Rectangular Fields, BF- Balffields, BK-Basketball, TN-Tennis, BC-Bocce) Access Routes Located adjacent to accessible paths Spectator Seating Notes: Boat Docks Fishing Facilities Community Gardens Parking Ramps Site Access, Path of Travel, Entrances Path of Travel Description Path does not require the use of wheelchair ramp Path is stable, firm and slip resistant Slope maximum 1:20 (5%) and maximum cross pitch is 2% (1:50). Continuous common surface, no changes in level greater than % inch Any objects protruding onto the pathway must be detected by a person with a visual disability using a cane Notes: Stairs and Doors Restrooms Floors, Drinking Fountains, Telephones Signs, Signals, and Switches Swimming Pool/ Lake beach	VES	1 RF; 1 BF